

STORM SEWER PIPE SCHEDULE

FROM STRUCTURE	INVERT ELEVATION	TO STRUCTURE	INVERT ELEVATION	PIPE SLOPE %	550A0340 STORM SEWERS, CLASS A, TYPE 2, 12" (FT.)	550A0360 STORM SEWERS, CLASS A, TYPE 2, 15" (FT.)	550A0380 STORM SEWERS, CLASS A, TYPE 2, 18" (FT.)	550A0470 STORM SEWERS, CLASS A, TYPE 2, 42" (FT.)	550A0050 STORM SEWERS, CLASS A, TYPE 1, 12" (FT.)	550A0070 STORM SEWERS, CLASS A, TYPE 1, 15" (FT.)	550A0090 STORM SEWERS, CLASS A, TYPE 1, 18" (FT.)	Z0056604 STORM SEWER, (WATER MAIN REQUIREMENTS) 8"	Z0056802 STORM SEWER, (WATER MAIN REQUIREMENTS) 4"	20800150 TRENCH BACKFILL (C.Y.)
1	759.30	2	759.50	2.00				4						3
2	761.75	3	762.05	6.00		5		23						16
2	759.60	4	759.83	1.00										2
4	761.75	5	762.05	6.00		5		14						12
4	759.93	6	760.07	1.00			342							50
6	761.25	7	766.38	1.50							34			9
7	766.48	8	767.16	2.00					5					1
8	767.79	9	767.89	2.00					47					9
8	767.79	10	768.50	1.50							144			5
8	767.26	11	770.14	2.00							6			0
11	770.24	12	770.66	3.50					28					7
11	770.74	13	771.02	1.00						75				0
14	769.74	15	770.12	0.50					176					16
15	770.22	16	773.65	1.95					24					4
16	773.75	17	773.99	1.00									19	2
17	774.09	18	VERIFY	EX. STRUCT.					79					11
17	773.75	19	776.12	3.00							6			0
18	776.20	20	VERIFY	3.50										20
6	761.50	21	764.12	1.60		164			41					12
21	764.37	22	765.60	3.00										54
21	764.22	23	766.50	1.00		228			17					5
23	766.60	24	766.77	1.00					23					4
24	766.87	25	767.10	1.00							18			5
26	767.00	27	757.24	1.00										54
27	757.34	28	760.60	1.33			245				21			6
28	759.65	28A	759.78	1.00	13					18				4
28	760.70	29	760.91	1.00						184				35
29	761.44	30	763.84	10.00					18					3
29	761.16	31	764.07	1.50					6					0
31	764.17	32	764.35	1.00										16
33	751.35	34	751.47	1.00										16
34	751.57	35	752.33	2.00										16
TOTAL					51	402	587	41	464	287	223	6	19	394

STORM SEWER STRUCTURE SCHEDULE

STRUCTURE NUMBER	STATION	60218300 MANHOLES, TY. A, 4'-DIA., TYPE 1 FRAME, OPEN LID	MANHOLES TY. A, 4'-DIA., TYPE 8 GRATE W/ 12" RING	60223800 MANHOLES, TY. A, 6'-DIA., TYPE 1 FRAME, CLOSED LID	XX185100 INLET MANHOLE, TY G-1, 4' DIA.	XX008379 INLET MANHOLE, TY G-1, 6' DIA.	INLETS, TYPE G-1	60236200 INLET, TYPE A, TYPE 8 GRATE	60240301 INLET, TYPE B, TYPE 8 GRATE	54213657 PRECAST REINFORCED CONCRETE FLARED END SECTION, 12"	54213660 PRECAST REINFORCED CONCRETE FLARED END SECTION, 15"	54213663 PRECAST REINFORCED CONCRETE FLARED END SECTION, 18"	54213687 PRECAST REINFORCED CONCRETE FLARED END SECTION, 42"
	DALLAS ROAD												X
1	25.84' RT. STA. 71+14.43												
2	13.58' RT. STA. 71+14.43												
3	12.33' RT. STA. 71+21.43												
4	13.58' LT. STA. 71+14.43												
5	12.33' LT. STA. 71+21.43												
6	31.60' LT. STA. 71+16.03												
7	31.58' LT. STA. 67+69.03												
8	31.27' LT. STA. 67+31.24												
9	38.15' LT. STA. 67+33.19												
10	12.76' RT. STA. 67+08.32												
11	30.70' LT. STA. 65+82.31	X											
12	43.70' LT. STA. 65+82.31												
13	30.58' LT. STA. 65+51.58												
14	25.20' RT. STA. 67+00.06												
15	20.56' RT. STA. 66+21.80												
16	13.00' RT. STA. 64+41.59												
17	13.72' LT. STA. 64+41.58												
18	28.71' LT. STA. 64+54.22												
	STRUCT. #18 EX. YARD INLET FIELD VERIFY INVERT ELEVATION												
19	19.90' RT. STA. 63+59.40												
20	VERIFY EXISTING B" PIPE												
21	31.60' LT. STA. 72+84.22												
22	12.33' RT. STA. 72+84.22												
23	31.58' LT. STA. 75+15.46												
24	12.33' LT. STA. 75+15.46												
25	12.33' RT. STA. 75+15.46												
26	25.00' RT. STA. 84+53.76												
27	12.33' RT. STA. 84+30.48												
28	12.33' RT. STA. 81+80.76												
28A	28.58' RT. STA. 81+80.76												
29	12.33' LT. STA. 81+80.76												
30	38.33' LT. STA. 81+76.88												
31	12.33' LT. STA. 79+84.96												
32	31.80' LT. STA. 79+88.83												
33	40.40' RT. STA. 85+66.80												
34	29.00' RT. STA. 85+59.00												
35	12.33' LT. STA. 85+52.71	X											
TOTAL		2	1	1	7	3	8	3	4	1	2	1	1