

SCHEDULE OF PARTIAL DEPTH PATCHING (CONT'D)

STATION	DIRECTION	LENGTH (FOOT)	WIDTH (FOOT)	PARTIAL DEPTH REMOVAL 8 1/2" 44022051 (SQ YD)	PARTIAL DEPTH PATCHING X4421000 (TONS)
296+12.00	WB	6	12	8.0	3.8
296+43.00	EB	10	12	13.3	6.3
296+79.00	EB	20	12	26.7	12.7
298+53.00	EB	50	12	66.7	31.7
298+53.00	WB	50	12	66.7	31.7
299+06.00	EB	20	12	26.7	12.7
299+06.00	WB	20	12	26.7	12.7
299+50.00	EB	20	12	26.7	12.7
299+77.00	WB	30	12	40.0	19.0
300+86.00	WB	30	12	40.0	19.0
301+36.00	WB	50	12	66.7	31.7
302+42.00	WB	12	12	16.0	7.6
302+96.00	WB	15	12	20.0	9.5
305+87.00	WB	6	12	8.0	3.8
308+35.00	WB	60	12	80.0	38.1
312+15.00	WB	20	12	26.7	12.7
313+93.00	WB	6	12	8.0	3.8
315+49.00	WB	10	12	13.3	6.3
315+94.00	WB	12	12	16.0	7.6
318+78.00	WB	15	12	20.0	9.5
322+47.00	WB	15	12	20.0	9.5
325+67.00	EB	15	12	20.0	9.5
325+67.00	WB	30	12	40.0	19.0
326+03.00	EB	20	12	26.7	12.7
326+03.00	WB	20	12	26.7	12.7
338+98.00	EB	60	12	80.0	38.1
338+98.00	WB	60	12	80.0	38.1
339+79.00	WB	30	12	40.0	19.0
340+35.00	EB	10	12	13.3	6.3
340+35.00	WB	10	12	13.3	6.3
SUB-TOTAL =				976.0	464.6