February 20, 2014

SUBJECT: Various Routes

Section 13-00904-01-PP

Fulton County

Contract No. 89633

Item 044

February 28, 2014 Letting

Addendum (A)

NOTICE TO PROSPECTIVE BIDDERS:

Due to clarify information necessary to revise the following:

1. Revised page 2 of the Special Provisions.

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

John Baranzelli, P.E.

Acting Engineer of Design and Environment

By: Ted B. Walschleger, P.E.

Tet Delselye A.E.

Engineer of Project Management

BITUMINOUS SURFACE TREATMENT (A-1)

MATERIALS

WASHED GRAVEL OR WASHED CRUSHED GRAVEL of the Gradation No. CA 16 shall be used for Bituminous Surface Treatment Aggregate

PG46-28 and HFRS-2 shall be used for BITUMINOUS MATERIALS (COVER AND SEAL COATS) as indicated in plans.

EQUIPMENT

In the last line of the first paragraph of Article 1102.04, change "...widths varying up to lane width." to "...widths varying up to the maximum roadway width of 24 foot."

CONSTRUCTION REQUIREMENTS

SEQUENCE OF WORK

Replace Article 403.07 with the following:

- (a) Repair of the existing surface. (Done by others)
- (b) Preparation of existing surface as according to 358.05(b).
- (c) Alternate Application of bituminous material and aggregate (according to 403.10-403.12).

Repair and Preparation of Base or Existing Surface

Article 403.08 does not apply. Preparation of surface is as stated in Sequence of Work.

TRAFFIC CONTROL

Standard BLR 18-5 shall be used while brooming.

Standard BLR 22-7 shall be used while applying bituminous surface treatment materials.

Standard 701311-03 shall be used during the pavement striping operation.