

INDEX OF SHEETS

SHEET NO.	DESCRIPTION
1	COVER SHEET
2	GENERAL NOTES
3	SUMMARY OF QUANTITIES
4-5	SCHEDULES
6	LOCATION MAP
7	DRIVEWAY DETAILS - DISTANCE BETWEEN R.O.W. AND CURB OR EDGE GRATER THAN OR EQUAL TO 15' (4.5 m) (BD01)
8	CONCRETE MEDIAN TYPE SB (DOWELLED) AND CORRUGATED MEDIAN (MODIFIED) (BD05)
9	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT (BD22)
10	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT (BD24)
11	TRAFFIC CONTROL AND PROTECTION FOR SIDEROADS, INTERSECTION AND DRIVEWAYS (TC10)
12	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC) (TC14)
13	ARTERIAL ROAD INFORMATION SIGN (TC22)
14	DRIVEWAY ENTRANCE SIGNING (TC26)

HIGHWAY STANDARDS

STD. NO.	TITLE
424001-05	CURB RAMPS FOR SIDEWALKS
442201-03	CLASS C AND D PATCHES
483001-04	PCC SHOULDER
542301-02	PRECAST REINFORCED CONCRETE FLARED END SECTION
542311-01	GRATING FOR CONCRETE FLARED END SECTION (FOR 600 mm (24") THRU 1300 mm (54") PIPE
604036-02	GRATE, TYPE 8
604056-03	FRAME AND GRATE, TYPE 11V
604091-02	FRAME AND GRATE, TYPE 24
606001-04	CONCRETE CURB AND COMBINATION CONCRETE CURB AND GUTTER
606301-04	PORTLAND CEMENT CONCRETE ISLANDS AND MEDIANS
606306-03	CORRUGATED PORTLAND CEMENT CONCRETE MEDIANS
606401-01	PAVED DITCH
701501-05	URBAN LANE CLOSURE, 2L, 2W - UNDIVIDED
701601-06	URBAN LANE CLOSURE, MULTILANE, 1W OR 2W WITH NON TRAVERSABLE MEDIAN
701602-04	URBAN LANE CLOSURE, MULTILANE, 2W WITH BIDIRECTIONAL LEFT TURN LANE
701606-06	URBAN LANE CLOSURE, MULTILANE, 2W WITH MOUNTABLE MEDIAN
701701-06	URBAN LANE CLOSURE, MULTILANE INTERSECTION
701901-01	TRAFFIC CONTROL DEVICES

GENERAL NOTES

- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "J.U.L.I.E." AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED).
- THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES.
- THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.
- WHEN ARTIFICIAL LIGHTING IS USED IN NIGHT OPERATIONS THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.
- THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM 72 HOURS PRIOR TO THE PLACEMENT OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.

HOT-MIX ASPHALT MIXTURE REQUIREMENTS

MIXTURE TYPE	AIR VOIDS
PAVEMENT PATCHING, TYPE I, II & III	
CLASS D PATCHES (HMA BINDER, IL 19.0), THICKNESS VARIES	4% @ 70 GYR
HMA SHOULDERS	
HOT MIX ASPHALT SHOULDER, (HMA BINDER IL 19.0mm) 6"	2% @ 30 GYR
STABILIZED MEDIAN SURFACE, 12"	
HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50 (IL 9.5mm) - 2"	4% @ 50 GYR
HOT-MIX ASPHALT BASE COURSE (HMA BINDER IL 19.0mm), 10"	4% @ 50 GYR
STABILIZED DRIVEWAYS, 8"	
HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50 (IL 9.5mm) - 2"	4% @ 50GYR
HOT-MIX ASPHALT BASE COURSE (HMA BINDER IL 19.0mm), 8"	4% @ 50 GYR

THE UNIT WEIGHT USED TO CALCULATE ALL HOT-MIX ASPHALT SURFACE MIXTURE A IS 112 LBS/SQ YD/IN.

THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 70-22" AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALL BE "PG 64-22" UNLESS MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS.

FOR "PERCENT OF RAP" SEE DISTRICT ONE SPECIAL PROVISIONS.

FILE NAME *	USER NAME * _USER_	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	DRAINAGE IMPROVEMENTS & CURB AND GUTTER REPAIRS INDEX OF SHEETS, HIGHWAY STANDARDS AND GENERAL NOTES	F.A.P. RTE. *	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
FILEL		DRAWN - EF	REVISED -			•	2009-072 I	LAKE	14	2
	PLOT SCALE = 48.8888" / IN.	CHECKED - RS	REVISED -			• VARIOUS				
	PLOT DATE = 1/11/2010	DATE - 01-11-2010	REVISED -			CONTRACT NO. 60H82		[ILLINOIS] FED. AID PROJECT		
				SCALE: 20	SHEET NO. 1 OF 1 SHEETS	STA.	TO STA.			