INDEX OF SHEETS

DESCRIPTION

SHEET NO.

- 1 COVER SHEET
- 2 INDEX, GENERAL NOTES AND HIGHWAY STANDARDS
- 3 SUMMARY OF QUANTITIES
- 4-5 TYPICAL SECTIONS
- 6-9 ROADWAY AND PAVEMENT MARKING PLANS
- 10-13 DETECTOR LOOP REPLACEMENT
- 14 FRAMES AND LIDS ADJUSTMENT WITH MILLING (BD08)
- 15 PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT (BD22)
- 16 CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT (BD24)
- 17 BUTT JOINTS AND BITUMINOUS TAPER (BD32)
- 18 HMA TAPER AT EDGE OF P.C.C. PAVEMENT (BD33)
- 19 TRAFFIC CONTROL AND PROTECTION FOR SIDEROADS, INTERSECTIONS AND DRIVEWAYS (TC10)
- 20 RAISED REFLECTIVE PAVEMENT MARKERS (SNOW PLOW RESISTANT (TC11)
- 21 DISTRICT ONE TYPICAL PAVEMENT MARKINGS (TC13)
- 22 TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC) (TC14)
- 23 PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING (TC16)
- 24 ARTERIAL ROAD INFORMATION SIGNING (TC22)
- 25 DETECTOR LOOP INSTALLATION DETAIL FOR ROADWAY RESURFACING (TS07)

HOT-MIX ASPHALT MIXTURE REQUIREMENTS							
MIXTURE TYPE	AIR VOIDS @ Nides						
HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70 (IL 9.5mm)	4% @ 70 GYR						
POLYMERIZED LEVELING BINDER (MACHINE METHOD), IL 4.75, N50	4% @ 50 GYR						
CLASS D PATCHES (HMA BINDER IL 19mm)	4% @ 70 GYR						
HOT-MIX ASPHALT REPLACEMENT OVER PATCHES (HMA BINDER IL 19 mm) 4" (IN 2 LIFTS)	4% @ 70 GYR						
PARTIAL DEPTH PATCHING 3"	4% @ 70 GYR						

THE UNIT WEIGHT USED TO CALCULATE ALL HOT-MIX ASPHALT SURFACE MIXTURE A IS 112 LBS/SQ YD/IN.

THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 70-22" AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALE BE "PG 64-22" UNLESS MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS.

FOR "PERCENT OF RAP" SEE DISTRICT ONE SPECIAL PROVISIONS.

HIGHWAY STANDARDS

STD. NO. TITLE

442201-03	CLASS C AND D PATCHES
606001-04	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
606301-04	PC CONCRETE ISLANDS AND MEDIANS
606306-03	CORRUGATED PC CONCRETE MEDIANS
701601-06	URBAN LANE CLOSURE, MULTILANE, 1W OR 2W WITH NONTRAVERSABLE MEDIAN
701602-04	URBAN LANE CLOSURE, MULTILANE, 1W OR 2W WITH BIDIRECTIONAL LEFT TURN LAND
701606-06	URBAN LANE CLOSURE, MULTILANE, 2W WITH MOUNTABLE MEDIAN
701701-06	URBAN LANE CLOSURE, MULTILANE, INTERSECTION
701901-01	TRAFFIC CONTROL DEVICES
780001-02	TYPICAL PAVEMENT MARKINGS
781001-03	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

GENERAL NOTES

- 1. BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "J.U.L.I.E." AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED).
- 2. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES.
- 3. THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.
- 4. WHEN ARTIFICIAL LIGHTING IS USED IN NIGHT OPERATIONS THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILTY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.
- 5. WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 40 MM (1 1/2 INCHES) WHERE THE SPEED LIMIT IS 80 KM/H (45 MPH) OR LESS AND 25 MM (1 INCH) WHERE THE SPEED LIMIT IS GREATER THAN 80 KM/H (45 MPH). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 75 MM (3 INCHES) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).
- 6. BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.
- 7. FOR PAVEMENT MARKING AND RAISED REFLECTIVE PAVEMENT MARKERS. REFER TO DISTRICT ONE TYPICAL MARKINGS FOR DETAILS NOT SHOWN.
- 8. THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM 72 HOURS PRIOR TO THE PLACEMENT OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.
- 9. MATCH EXISTING PAVEMENT MARKINGS AT PROJECT LIMITS.
- 10. THE RESIDENT ENGINEER SHALL CONTACT WALTER CZARNY, AREA TRAFFIC FIELD ENGINEER, AT 847-715-8419 AT LEAST (2) WEEKS PRIOR TO PLACING PERMANENT PAVEMENT MARKINGS.

USER NAME = _USER_	DESIGNED	-	EF	REVISED	=	Γ
	DRAWN	-	EF	REVISED	-	l
PLOT SCALE = 50.0045 '/ IN.	CHECKED	-	RS	REVISED	-	
PLOT DATE = 12/2/2009	DATE	-	12/02/09	REVISED	•	

SCALE:

REENWOOD AVE. – GOLF ROAD (IL 58) TO WEST LAKE AVE.							F.A.U. RTE.	F.A.U. SECTION COUNTY TOTAL SH RTE. SECTION COUNTY SHEETS N				
			•	•			.2743	1316 RS-2	соок	25	2	
INDEX OF SHEETS								-	CONTRACT	NO. E	2548	
	SHEET NO.	OF	SHEETS	STA.		TO STA.		ILLINOIS FED. AID PROJECT				

FILE NAME =