

**COLD IN-PLACE RECYCLING, BITUMINOUS CONCRETE PAVEMENT 8"**

LOCATION	WIDTH	SQ YD
STA 79+77.02 TO STA 97+78.64	32'	6,405.76
STA 121+68.98 TO STA 331+56.17	28'	65,293.48
STA 335+01.66 TO STA 453+40.00	28'	36,830.39
<b>TOTAL</b>		<b>108,529.63</b>

**BITUMINOUS MATERIALS (COLD IN-PLACE RECYCLING)**

LOCATION	WIDTH	GALLON
STA 79+77.02 TO STA 97+78.64	32'	22,420.16
STA 121+68.98 TO STA 331+56.17	28'	228,527.18
STA 335+01.66 TO STA 453+40.00	28'	128,906.37
<b>TOTAL</b>		<b>379,853.71</b>

**BITUMINOUS MATERIALS (PRIME COAT)**

LOCATION	WIDTH	GALLON
STA 79+07.02 TO STA 97+78.64	30.92'	643.01
STA 121+68.98 TO STA 332+26.17	26.92'	6,298.44
STA 334+31.66 TO STA 453+65.00	26.92'	3,569.39
<b>TOTAL</b>		<b>10,510.84</b>

SEE ENTRANCE SCHEDULE FOR ADDITIONAL QUANTITY

**AGGREGATE (PRIME COAT)**

LOCATION	WIDTH	TON
STA 79+07.02 TO STA 97+78.64	30.92'	12.86
STA 121+68.98 TO STA 332+26.17	26.92'	125.97
STA 334+31.66 TO STA 453+65.00	26.92'	71.39
<b>TOTAL</b>		<b>210.22</b>

**HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N70**

LOCATION	THICKNESS	WIDTH	TON
STA 79+24.52 TO STA 79+77.02	1" to 3"	30.92'	20.20
STA 79+77.02 TO STA 97+78.64	3.00"	30.92'	1,039.85
STA 121+68.98 TO STA 331+56.17	3.00"	26.92'	10,546.20
STA 331+56.17 TO STA 332+08.67	1" to 3"	26.92'	17.59
STA 334+49.16 TO STA 335+01.66	1" to 3"	26.92'	17.59
STA 335+01.66 TO STA 453+40.00	3.00"	26.92'	5,948.84
<b>TOTAL</b>			<b>17,590.27</b>

**HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N70**

LOCATION	THICKNESS	WIDTH	TON
STA 79+07.02 TO STA 79+24.52	2.5" to 1.5"	30.25	6.59
STA 79+24.52 TO STA 97+78.64	1.5"	30.25	523.48
STA 121+68.98 TO STA 332+08.67	1.5"	26.25	5,154.72
STA 332+08.67 TO STA 332+26.17	2.5" to 1.5"	26.25	5.72
STA 334+31.66 TO STA 334+49.16	2.5" to 1.5"	26.25	5.72
STA 334+49.16 TO STA 453+65.00	1.5"	26.25	2,919.38
<b>TOTAL</b>			<b>8,615.61</b>

**AGGREGATE SHOULDERS (SPECIAL)**

LOCATION	WIDTH	SQ YD
LT STA 79+77.02 TO STA 97+78.64	6.0'	1,201.08
LT STA 121+68.98 TO STA 332+26.17	3.5'	8,188.91
LT STA 334+31.66 TO STA 453+65.00	3.5'	4,640.74
RT STA 79+77.02 TO STA 97+78.64	6.0'	1,201.08
RT STA 121+68.98 TO STA 332+26.17	3.5'	8,188.91
RT STA 334+31.66 TO STA 453+65.00	3.5'	4,640.74
<b>TOTAL</b>		<b>28,061.46</b>

**HOT-MIX ASPHALT BASE COURSE, 8"**

LOCATION	WIDTH	SQ YD
RT STA 79+07.02 TO STA 79+77.02	9.5'	73.89
LT STA 79+07.02 TO STA 79+77.02	9.5'	73.89
<b>TOTAL</b>		<b>147.78</b>

EXCAVATION REQUIRED TO CONSTRUCT HOT-MIX ASPHALT BASE COURSE 8" SHALL BE PAID FOR AS EARTH EXCAVATION (WIDENING) AS SPECIFIED IN SECTION 202 OF THE STANDARD SPECIFICATIONS

**HOT-MIX ASPHALT SHOULDERS**

LOCATION	THICKNESS	WIDTH	TON
RT STA 79+07.02 TO STA 79+77.02	4.50"	6.0'	11.76
LT STA 79+07.02 TO STA 79+77.02	4.50"	6.0'	11.76
<b>TOTAL</b>			<b>23.52</b>

**HOT-MIX ASPHALT SURFACE REMOVAL, 1 3/4"**

LOCATION	WIDTH	SQ YD
STA 79+07.02 TO STA 97+78.64	24'	4,990.99
STA 121+68.98 TO STA 332+26.17	22'	51,473.13
STA 334+31.66 TO STA 453+40.00	22'	29,109.28
<b>TOTAL</b>		<b>85,573.40</b>

**TEMPORARY RAMP**

LOCATION	THICKNESS	WIDTH	SQ YD
STA 79+07.02	1.5"	24'	13.33
STA 332+26.17	1.5"	22'	12.22
STA 334+31.66	1.5"	22'	12.22
STA 453+40.00	4"	23'	34.07
STA 453+65.00	1.5"	22'	12.22
<b>TOTAL</b>			<b>84.06</b>

**HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT**

LOCATION	WIDTH	SQ YD
STA 453+40.00 TO STA 453+65.00	26'	72.22



JOB = 2233	DESIGNED - NAK	REVISED -
FILE NAME = 2233 SQD.dgn	DRAWN - AJH	REVISED -
PLOT SCALE = 100.0000' / IN.	CHECKED - NAK	REVISED -
PLOT DATE = 11/20/2009	DATE - 9/15/2009	REVISED -

**CHRISTIAN COUNTY  
CH 1 IMPROVEMENTS**

**SCHEDULE OF QUANTITIES**

SCALE:	SHEET NO.	OF	SHEETS	STA.	TO STA.
--------	-----------	----	--------	------	---------

F.A.S. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
645	05-00071-05-RS	CHRISTIAN	28	6
CONTRACT NO.				
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		

93517