



# Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

February 17, 2021

SUBJECT: FAP Route 322 (US 51)  
Project NHPP-J3TP(142)  
Section 20 RS-4 (21,22) RS-2  
Fayette County  
Contract No. 74944  
Item No. 111, March 5, 2021 Letting  
Addendum A

## NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

1. Revised page i of the Table of Contents to the Special Provisions.
2. Revised pages 4-5 of the Special Provisions.

Prime contractors must utilize the enclosed material when preparing their bid and must include any changes to the Schedule of Prices in their bid.

Very truly yours,

A handwritten signature in black ink, appearing to read 'Jack A. Elston'.

Jack A. Elston, P.E.  
Bureau Chief, Design and Environment

TABLE OF CONTENTS

LOCATION OF PROJECT ..... 1  
DESCRIPTION OF PROJECT ..... 1  
TRAFFIC CONTROL PLAN ..... 1  
BORROW AREAS, USE AREAS, AND/OR WASTE AREAS ..... 2  
CHANGEABLE MESSAGE SIGNS ..... 2  
HMA SURFACE REMOVAL..... 2  
INCIDENTAL HOT-MIX ASPHALT SURFACING ..... 3  
PAVEMENT PATCHING STANDARD 442201 ..... 3  
PROTECTING OR RESETTING SURVEY MARKERS ..... 3  
SURFACE REMOVAL, VARIABLE DEPTH (SPECIAL) ..... 4  
AUTOMATED FLAGGER ASSISTANCE DEVICES (BDE) ..... 5  
BITUMINOUS MATERIALS COST ADJUSTMENTS (BDE) ..... 6  
COMPENSABLE DELAY COSTS (BDE) ..... 8  
DISADVANTAGED BUSINESS ENTERPRISE PARTICIPATION (BDE) ..... 11  
DISPOSAL FEES (BDE) ..... 19  
EMULSIFIED ASPHALTS (BDE) ..... 20  
ENGINEER’S FIELD OFFICE AND LABORATORY (BDE) ..... 23  
FUEL COST ADJUSTMENT (BDE) ..... 25  
HOT-MIX ASPHALT – BINDER AND SURFACE COURSE (BDE) ..... 28  
HOT-MIX ASPHALT – LONGITUDINAL JOINT SEALANT (BDE) ..... 34  
HOT-MIX ASPHALT – MIXTURE DESIGN VERIFICATION AND PRODUCTION (MODIFIED FOR I-FIT) (BDE) ..... 37  
HOT MIX ASPHALT - PAY FOR PERFORMANCE USING PERCENT WITHIN LIMITS - JOBSITE SAMPLING (BDE) ..... 40  
MOBILIZATION (BDE) ..... 45  
RECLAIMED ASPHALT PAVEMENT AND RECLAIMED ASPHALT SHINGLES (BDE) ..... 45  
REMOVAL AND DISPOSAL OF REGULATED SUBSTANCES (BDE) ..... 55  
SUBCONTRACTOR AND DBE PAYMENT REPORTING (BDE) ..... 64  
SUBCONTRACTOR MOBILIZATION PAYMENTS (BDE) ..... 65  
SURFACE TESTING OF PAVEMENTS – IRI (BDE) ..... 65  
TEMPORARY PAVEMENT MARKING (BDE) ..... 70  
TRAFFIC CONTROL DEVICES - CONES (BDE) ..... 73

The work for furnishing and installing new survey marker vaults will be paid for according to the survey marker vault special provision.

**SURFACE REMOVAL, VARIABLE DEPTH (SPECIAL)**

This work shall consist of the removal of the oil and chip, hot-mix asphalt or Portland cement concrete surfaces of the entrances in preparation for subsequent resurfacing. The material types of the entrances and the length of the milling will be indicated on the plans. The milling depth shall vary as shown on the plans.

This work will be paid for at the contract unit price per square yard for SURFACE REMOVAL, VARIABLE DEPTH (SPECIAL).

The remainder of this page left blank intentionally.

Revised February 17, 2021

## **AUTOMATED FLAGGER ASSISTANCE DEVICES (BDE)**

Effective: January 1, 2008

**Description.** This work shall consist of furnishing and operating automated flagger assistance devices (AFADs) as part of the work zone traffic control and protection for two-lane highways where two-way traffic is maintained over one lane of pavement. Use of these devices shall be at the option of the Contractor.

**Equipment.** AFADs shall be according to the FHWA memorandum, "MUTCD - Revised Interim Approval for the use of Automated Flagger Assistance Devices in Temporary Traffic Control Zones (IA-4R)", dated January 28, 2005. The devices shall be mounted on a trailer or a moveable cart and shall meet the requirements of NCHRP 350, Category 4.

The AFAD shall be the Stop/Slow type. This device uses remotely controlled "STOP" and "SLOW" signs to alternately control right-of-way.

Signs for the AFAD shall be according to Article 701.03 of the Standard Specifications and the MUTCD. The signs shall be 24 x 24 in. (600 x 600 mm) having an octagon shaped "STOP" sign on one side and a diamond shaped "SLOW" sign on the opposite side. The letters on the signs shall be 8 in. (200 mm) high. If the "STOP" sign has louvers, the full sign face shall be visible at a distance of 50 ft (15 m) and greater.

The signs shall be supplemented with one of the following types of lights.

- (a) Flashing Lights. When flashing lights are used, white or red flashing lights shall be mounted within the "STOP" sign face and white or yellow flashing lights within the "SLOW" sign face.
- (b) Stop and Warning Beacons. When beacons are used, a stop beacon shall be mounted 24 in. (600 mm) or less above the "STOP" sign face and a warning beacon mounted 24 in. (600 mm) or less above, below, or to the side of the "SLOW" sign face. As an option, a Type B warning light may be used in lieu of the warning beacon.

A "WAIT ON STOP" sign shall be placed on the right hand side of the roadway at a point where drivers are expected to stop. The sign shall be 24 x 30 in. (600 x 750 mm) with a black legend and border on a white background. The letters shall be at least 6 in. (150 mm) high.

This device may include a gate arm or mast arm that descends to a horizontal position when the "STOP" sign is displayed and rises to a vertical position when the "SLOW" sign is displayed. When included, the end of the arm shall reach at least to the center of the lane being controlled. The arm shall have alternating red and white retroreflective stripes, on both sides, sloping downward at 45 degrees toward the side on which traffic will pass. The stripes shall be 6 in. (150 mm) in width and at least 2 in. (50 mm) in height.

Revised February 17, 2021