

DATE: _____
 SURVEYED: _____
 PLAN: _____
 NOTE BOOK: _____
 NO. _____

DATE: _____
 SURVEYED: _____
 PROFILE: _____
 NOTE BOOK: _____
 NO. _____

BY: _____
 CHECKED: _____
 DATE: _____


DATE: _____
 SURVEYED: _____
 PLAN: _____
 NOTE BOOK: _____
 NO. _____

DATE: _____
 SURVEYED: _____
 PROFILE: _____
 NOTE BOOK: _____
 NO. _____

CHRISTOPHER B. BURKE ENGINEERING LTD.
 3575 West Higgins Road, Suite 600
 Chicago, IL 60649
 (847) 823-0500

THE FOLLOWING ITEMS SHALL BE REMOVED BY THE CONTRACTOR AND SHALL BE DISPOSED OF BY THEM OUTSIDE THE RIGHT-OF-WAY AT THEIR EXPENSE. THE SALVAGE VALUE OF THE REMOVED EQUIPMENT SHALL BE REFLECTED IN THE CONTRACT BID PRICE.

- 9 EACH SIGNAL HEAD, 1-FACE, 3-SECTION
- 1 EACH SIGNAL HEAD, 2-FACE, 3-SECTION
- 3 EACH ALUMINUM MAST ARM AND POLE
- 3 EACH SIGNAL POST




R10-5
 24" x 30"
 1 REQUIRED
 (INCIDENTAL TO TEMPORARY TRAFFIC SIGNAL INSTALLATION)

- EXISTING EQUIPMENT TO BE REMOVED LEGEND**
- "E" △ EXISTING SIGNAL HEAD TO BE REMOVED
 - "E" ■ EXISTING SERVICE INSTALLATION TO BE REMOVED
 - "E" ○ EXISTING SIGNAL POST AND FOUNDATION TO BE REMOVED
 - "E" □ EXISTING ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED
 - "E" ⊠ EXISTING CONTROLLER AND FOUNDATION TO BE REMOVED
 - "E" ⊞ EXISTING HANDHOLE TO BE REMOVED
 - "E" ⊚ EXISTING PEDESTRIAN SIGNAL HEAD TO BE REMOVED
 - "E" ⊛ EXISTING PEDESTRIAN PUSHBUTTON TO BE REMOVED
 - "E" ⊜ EXISTING EMERGENCY VEHICLE LIGHT DETECTOR TO BE REMOVED
 - "E" ⊝ EXISTING CONFIRMATION BEACON TO BE REMOVED
 - "E" ⊞ EXISTING HEAVY-DUTY HANDHOLE TO BE REMOVED
 - "E" ⊚ EXISTING STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED
 - "A" ABANDON

- TEMPORARY TRAFFIC SIGNAL LEGEND**
- ▲ TEMPORARY TRAFFIC SIGNAL HEAD SPAN WIRE MOUNTED ORIGINAL LOCATION
 - △ TEMPORARY TRAFFIC SIGNAL HEAD SPAN WIRE MOUNTED SECONDARY LOCATION
 - ⊙ TEMPORARY WOOD POLE (CLASS 5 OR BETTER) 45 FOOT (13.7m) MINIMUM DOWN GUY
 - ⊠ TEMPORARY CONTROLLER CABINET
 - ⊞ TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE
 - ⊚ TEMPORARY SERVICE INSTALLATION
 - ⊛ TEMPORARY PEDESTRIAN SIGNAL HEAD, BRACKET MOUNTED
 - ⊜ VIDEO DETECTION CAMERA
 - ⊝ PEDESTRIAN PUSHBUTTON DETECTOR
 - ⊞ EMERGENCY VEHICLE LIGHT DETECTOR
 - ⊚ CONFIRMATION BEACON
 - VEHICLE DETECTOR, INDUCTION LOOP
 - UD UNIT DUCT
 - CI COMMON TRENCH
 - G.S. CONDUIT IN TRENCH (T) OR PUSHED (P)
 - HANDHOLE
 - ⊞ HEAVY DUTY HANDHOLE

- NOTES FOR TEMPORARY TRAFFIC SIGNALS**
- ALL CONTROL EQUIPMENT INCLUDING EMERGENCY PRE-EMPTION AND COMMUNICATION DEVICES FOR THE TEMPORARY TRAFFIC SIGNAL(S) SHALL BE FURNISHED BY THE CONTRACTOR.
 - ONLY CONTROLLERS SUPPLIED BY ONE OF THE DISTRICT APPROVED CLOSED LOOP EQUIPMENT MANUFACTURERS WILL BE APPROVED FOR USE AT TEMPORARY SIGNAL LOCATIONS. ALL CONTROLLERS USED FOR TEMPORARY TRAFFIC SIGNALS SHALL BE FULLY ACTUATED NEMA MICROPROCESSOR BASED WITH RS232 DATA ENTRY PORTS COMPATIBLE WITH EXISTING MONITORING SOFTWARE APPROVED BY IDOT DISTRICT 1, INSTALLED IN A NEMA TS1 OR TS2 CABINET. ONLY ONE BRAND OF CONTROLLER WILL BE ACCEPTED FOR ANY ONE CONTRACT.
 - ALL TRAFFIC SIGNAL SECTIONS AND PEDESTRIAN SIGNAL SECTIONS SHALL BE 12" (300mm). HEADS SHALL BE PLACED AS INDICATED ON THE TEMPORARY TRAFFIC SIGNAL PLAN OR AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHALL FURNISH ENOUGH CABLE SLACK TO RELOCATE HEADS TO ANY POSITION ON THE SPAN WIRE OR AT LOCATIONS ILLUSTRATED ON THE PLANS FOR CONSTRUCTION STAGING. THE TEMPORARY TRAFFIC SIGNAL SHALL REMAIN IN OPERATION DURING ALL SIGNAL HEAD RELOCATIONS. EACH TEMPORARY TRAFFIC SIGNAL HEAD SHALL HAVE ITS OWN CABLE FROM THE CONTROLLER CABINET TO THE SIGNAL HEAD.
 - ALL EXISTING STREET NAME AND INTERSECTION REGULATORY SIGNS SHALL BE REMOVED FROM EXISTING POLES, RELOCATED AND SECURELY FASTENED TO THE SIGNAL SPAN WIRE OR WOOD POLE AS DIRECTED BY THE ENGINEER.
 - ANY TEMPORARY SIGNAL WITHIN AN EXISTING CLOSED LOOP TRAFFIC SIGNAL SYSTEM SHALL BE INTERCONNECTED TO THAT SYSTEM USING SIMILAR BRAND CONTROL EQUIPMENT.
 - THE TEMPORARY TRAFFIC SIGNAL SHALL HAVE THE SIGNAL HEAD DISPLAYS, SIGNAL HEAD PLACEMENTS AND CONTROLLER PHASING MATCH THE EXISTING TRAFFIC SIGNAL, AT THE TIME OF THE TURN ON, IF NO TRAFFIC STAGING IS IN PLACE OR WILL NOT BE STAGED ON THE DAY OF THE TURN ON.

SIDEWALK REMOVAL = 25 SQ. FT.
 P.C. CONC. SIDEWALK, 5" = 25 SQ. FT.



RESTORATION OF WORK AREA. RESTORATION OF THE TRAFFIC SIGNAL WORK AREA SHALL BE INCIDENTAL TO THE RELATED PAY ITEM SUCH AS FOUNDATION, CONDUIT, HANDHOLE, TRENCH AND BACKFILL, ETC., AND NO EXTRA COMPENSATION SHALL BE ALLOWED. ALL ROADWAY SURFACES SUCH AS SHOULDERS, MEDIANS, SIDEWALKS, PAVEMENT, ETC. SHALL BE REPLACED IN KIND. ALL DAMAGE TO MOWED LAWNS SHALL BE REPLACED WITH AN APPROVED SOD, AND ALL DAMAGE TO UNMOWED FIELDS SHALL BE SEED IN ACCORDANCE WITH STANDARD SPECIFICATIONS 252 AND 250 RESPECTIVELY.

FILE NAME =	USER NAME = FPAIONE	DESIGNED = ABR	REVISED =
\\dot\080804\TASK 0 - IL 83\Traffic\TMP	I-57Ramp.dgn	DRAWN = FPB	REVISED =
	PLOT SCALE = 20'	CHECKED = MJT	REVISED =
	PLOT DATE = 11/24/2008	DATE =	REVISED =

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

**TEMPORARY TRAFFIC SIGNAL INSTALLATION AND REMOVE EXISTING TRAFFIC SIGNAL EQUIPMENT PLAN
 IL ROUTE 83 (147th ST.) AND F.A. I-57 RAMPS "A" AND "B"
 POSEN, ILLINOIS**

SCALE: 1"= 20' SHEET NO. OF SHEETS STA. TO STA.

F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
1602	2008-054 TS	COOK	40	24
FED. ROAD DIST. NO.	ILLINOIS FED. AID PROJECT			
	CONTRACT NO. 60F06			