



- (A) STA. 19+61.79, 42.0FT LT
RELOCATE EXIST POLE W/NEW 44' MAST ARM
USE EXST. LUMINAIRE, SV HORI MT PC 400W, 8' M.A., 35' MTG HT
CONCRETE FOUNDATION, TY-E, 30" DIA, 17FT
VIDEO DETECTOR CAMERA, 1 EA
- (B) STA. 19+61.52, 38.6 FT RT
RELOCATE EXIST. STEEL COMB. MAST ARM ASSEMBLY AND POLE, 44' M.A.
USE EXST. LUMINAIRE, SV HORI MT PC 400W, 8' M.A., 35' MTG HT
CONCRETE FOUNDATION, TY-E, 30" DIA, 17FT
VIDEO DETECTOR CAMERA, 1 EA
- (C) STA. 20+39.87, 39.1FT RT
RELOCATE EXIST POLE W/NEW 44' MAST ARM
USE EXST. LUMINAIRE, SV HORI MT PC 400W, 8' M.A., 35' MTG HT
CONCRETE FOUNDATION, TY-E, 30" DIA, 17FT
VIDEO DETECTOR CAMERA, 1 EA
EMERG DOUBLE OPTICLE DETECTOR W/ DOUBLE CONF. BEACON, 1 EA
- (D) STA. 20+41.51, 42.5FT LT
RELOCATE EXIST POLE W/NEW 44' MAST ARM
USE EXST. LUMINAIRE, SV HORI MT PC 400W, 8' M.A., 35' MTG HT
CONCRETE FOUNDATION, TY-E, 30" DIA, 17FT
VIDEO DETECTOR CAMERA, 1 EA
EMERG DOUBLE OPTICLE DETECTOR W/ DOUBLE CONF. BEACON, 1 EA

TRAFFIC SIGNAL LEGEND

	EXISTING	PROPOSED
CONTROLLER		
SERVICE INSTALLATION		
SIGNAL HEAD		
SIGNAL HEAD WITH BACKPLATE		
SIGNAL HEAD, PEDESTRIAN		
PEDESTRIAN PUSHBUTTON DETECTOR		
SIGNAL POST		
MAST ARM ASSEMBLY AND POLE		
HANDHOLE		
HEAVY DUTY HANDHOLE		
DOUBLE HANDHOLE		
EMERGENCY VEHICLE SYSTEM DETECTOR		
CONFIRMATION BEACON		
WOOD POLE		
CONDUIT IN TRENCH OR PUSHED		
COMMON TRENCH		
DETECTOR LOOP		
LUMINAIRE W/MAST ARM		
VIDEO DETECTOR CAMERA		

SCALE
HORIZ. 1"=20' (FULL SIZE)
HORIZ. 1"=40' (1/4 SIZE)