



- SYMBOLS**
- Work area
  - Drum, with steady burn monodirectional light
  - Temporary concrete barrier
  - Monodirectional barrier wall/guardrail marker
  - Impact attenuator

**GENERAL NOTES**

This standard is used where at any time any vehicle, equipment, workers or their activities will encroach on the pavement or on the shoulder within 24 (600) of the edge of pavement for day light operation exceeding one day and where temporary concrete barrier is utilized.

This Standard must always be used in combination with Standard 701402.

When work is being performed in the left lane, the set up would be a mirror image to what is shown.

FILE NAME =	USER NAME = woodshankr1	DESIGNED - RW	REVISED -
c:\pwork\pvidot\woodshankr1\0314761\066C56.sht-details.dgn	066C56.sht-details.dgn	DRAWN - RW	REVISED -
#MOBLNAME#	PLOT SCALE = 1/80.0000 / in.	CHECKED -	REVISED -
	PLOT DATE = 11/15/2012	DATE -	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**STAGING DETAILS - STAGE II  
FOR STRUCTURE NO. 078-0001**

SCALE: SHEET 1 OF 1 SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
180	106-3,78-11PM	BUREAU	10	6
CONTRACT NO. 66C56			ILLINOIS FED. AID PROJECT	