



**LEGEND**

① EXIST. 4" SUB-BASE GRANULAR MATERIAL	⑩ PROP. COMBINATION CURB AND GUTTER REMOVAL	⑬ PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8"	⑲ PROP. HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70 1 1/2"
② EXIST. 8" P.C.C. PAVEMENT	⑪ PROP. CONCRETE MEDIAN SURFACE REMOVAL	⑭ PROP. HMA BASE COURSE 11" ***	⑳ PROP. COMBINATION CONCRETE CURB AND GUTTER, TYPE M-4.24
③ EXIST. 8" H.M.A. SHOULDER	⑫ PROP. SUBBASE GRANULAR MATERIAL, TYPE B 4"	⑮ PROP. PCC BASE COURSE WIDENING 9"	㉑ PROP. CONCRETE MEDIAN SURFACE, 4"
④ EXIST. 4" OVERLAY	⑬ PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8"		㉒ PROP. CONCRETE MEDIAN, TYPE SM-4.24
⑤ EXIST. COMBINATION CURB AND GUTTER, TYPE B-6.06	⑭ PROP. HMA BASE COURSE 11" ***		㉓ PROP. AGGREGATE WEDGE SHOULDER, TYPE B
⑥ PROP. PAVEMENT REMOVAL	⑮ PROP. PCC BASE COURSE WIDENING 9"		㉔ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 5"
⑦ PROP. PAVED SHOULDER REMOVAL			㉕ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 8"
⑧ PROP. HOT-MIX ASPHALT SURFACE REMOVAL (VARIABLE DEPTH) *			㉖ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B TYPE B - LINE 5"
⑨ PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"			㉗ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B TYPE B - LINE 6"

- \*\* NOTES:**
- (A) PROP. CONCRETE MEDIAN ENDS AT STA. 302+98.85 LT.
  - (B) PROP. CONCRETE MEDIAN ENDS AT STA. 303+62.00 RT.
  - (C) PROP. HMA SHOULDERS 6 1/2" ARE LOCATED FR. STA. 303+71.30 TO 304+10.11 LT AND STA. 302+64.58 TO 302+92.75 RT.
  - (D) PAVEMENT STRIPING 6" WHITE (2'DASH/6'SKIP) FR. STA. 302+74.00 TO 304+51.56 LT AND STA. 303+75.94 TO 304+93.00 RT (EB PAVT).

\* NOMINAL MILLING DEPTH 1/2" @ CL OR pgl  
 \*\*\* WHERE WIDENING IS GREATER THAN 6' OR UNDER NEW TURN LANE