



LEGEND

① EXIST. 4" SUB-BASE GRANULAR MATERIAL	⑩ PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"
② EXIST. 8" P.C.C. PAVEMENT	⑪ PROP. CONCRETE MEDIAN SURFACE REMOVAL
③ EXIST. 8" H.M.A. SHOULDER	⑫ PROP. SUBBASE GRANULAR MATERIAL, TYPE B 4"
④ EXIST. 4" OVERLAY	⑬ PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8"
⑤ EXIST. COMBINATION CURB AND GUTTER, TYPE B-6.06	⑭ PROP. HMA BASE COURSE 11" ***
⑥ PROP. PAVEMENT REMOVAL	⑮ PROP. PCC BASE COURSE WIDENING 9"
⑦ PROP. PAVED SHOULDER REMOVAL	⑯ PROP. STRIP REFLECTIVE CRACK CONTROL TREATMENT
⑧ PROP. HOT-MIX ASPHALT SURFACE REMOVAL (VARIABLE DEPTH) *	⑰ PROP. HOT-MIX ASPHALT SHOULDERS 6 1/2"
⑨ PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"	⑱ PROP. LEVELING BINDER (MACHINE METHOD), N70 1"
⑩ PROP. COMBINATION CURB AND GUTTER REMOVAL	⑳ PROP. HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70 1 1/2"
⑪ PROP. CONCRETE MEDIAN SURFACE REMOVAL	㉑ PROP. COMBINATION CONCRETE CURB AND GUTTER, TYPE M-4.24
⑫ PROP. SUBBASE GRANULAR MATERIAL, TYPE B 4"	㉒ PROP. CONCRETE MEDIAN SURFACE, 4"
⑬ PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8"	㉓ PROP. CONCRETE MEDIAN, TYPE SM-4.24
⑭ PROP. HMA BASE COURSE 11" ***	㉔ PROP. AGGREGATE WEDGE SHOULDER, TYPE B
⑮ PROP. PCC BASE COURSE WIDENING 9"	㉕ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 5"
	㉖ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 8"
	㉗ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B TYPE B - LINE 5"
	㉘ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B TYPE B - LINE 6"

- ** NOTES:**
- (A) PAINTED MEDIAN WIDTH VAR. FR. 6'-3" TO 0' FR. STA. 341+28.98 TO 342+40.67 LT.
 - (B) PAVEMENT STRIPING 6" WHITE (2'DASH/6'SKIP) FR. STA. 342+40.67 TO 344+62.20 LT (SB PAVT).
 - (C) LT TURN LANE WIDTH IS 13'-0" FR. STA. 341+28.98 TO 342+40.67 LT AND VAR. FR. 13'-0" TO 1'-0" FR. STA. 342+40.67 TO 344+62.20 LT (SB PAVT).
 - (D) PROP. AGG. SHOULDER WIDTH TAPERS FR. 0 TO 3'-0" FR. STA. 343+51.27 TO 344+62.20 LT.

* NOMINAL MILLING DEPTH 1/2" @ CL OR PGL
 *** WHERE WIDENING IS GREATER THAN 6' OR UNDER NEW TURN LANE