

DS-11

11-1-06

TOTAL SHEET NO. SHEET NO. 17 FAI 72 SANGAMON 559 270 44 SHEETS

\*(84-9-4)A.HBK,BY,BY-1

Contract No 72541

All cast iron parts shall be gray iron conforming to the requirements of AASHTO M 105, Class 35B.

Balts, anchor studs, washers and nuts shall conform to the requirements of ASTM A 307 and shall be galvanized according to AASHTO M 232.

Downspouts located on the exterior side of a painted steel fascia beam shall be painted with the finish coat specified for the exterior side of the fascia beam.


As an alternate, bolts, anchor studs, washers and nuts may stainless steel according to Article 1006.29(d) of the Standard Specifications.

Structural steel weldments of equal sections and of the sai configuration may be substituted for the cast iron scupper frame. Fillet or full penetration welds shall be used for the weldments. Details shall be submitted to the Engineer for approval. Structural steel weldments shall not be substituted for the cast iron scupper grate. Structural steel frames and downspouts shall be galvanized according to AASHTO MIII.

The Contractor shall take appropriate measures to assure that Protective Coat is not applied to the scupper.

Cost of the Grate, Frame, Downspout, Anchor Studs, Bolts. Washers and Nuts including complete installation of the scuppe shall be paid for at the contract unit price each for Drainage Scupper, DS-11.

Alternate fiberglass downspout conforming to ASTM D 2996 with a short-time rupture strength hoop tensile stress of 30,000 psi min. may be used in lieu of the cast iron or steel equivalent.



ANCHOR STUD DETAIL

BILL OF MATERIAL

ITEM	UNIT	QUANTIT
Drainage Scupper, DS-11	Each	4

Corporate License Number 184-001-084

DRAINAGE SCUPPERS, DS-11 F.A.I. 72 OVER UNION PACIFIC RAILROAD SECTION (84-9-4)A,HBK,BY,BY-1 SANGAMON COUNTY STATION 608+51.98 STR NO. 084-0074 EB - 084-0075 WB

**HANSON** 

9652002B 01/12/06