



- ⑨ MANHOLE, TYPE A, 4' DIA., WITH TYPE 1 FRAME, CLOSED LID
28.00' LT. STA. 102+93.50
TOP CASTING 784.91 INV. 780.47 (12"E)
INV. 780.57 (12"W) INV. 780.57 (12"S)
- ⑩ INLET, TYPE G-1
19.33' LT. STA. 102+93.50
TOP/CURB 784.67 EDGE/PAVT 784.29
INV. 780.65 (12"N) INV. 780.75 (12"S)
- ⑪ INLET, TYPE G-1
19.33' RT. STA. 102+93.50
TOP/CURB 784.67 EDGE/PAVT 784.29
INV. 781.13 (12"N)
- ⑫ MANHOLE, TYPE A, 4' DIA., WITH TYPE 1 FRAME, CLOSED LID
28.00' LT. STA. 100+55.50
TOP CASTING 790.09
INV. 785.69 (12"E) INV. 785.79 (12"S)
- ⑬ INLET, TYPE G-1
19.33' LT. STA. 100+55.50
TOP/CURB 789.85 EDGE/PAVT 789.47
INV. 785.87 (12"N) INV. 785.97 (12"S)
- ⑭ INLET, TYPE G-1
19.33' RT. STA. 100+55.50
TOP/CURB 789.85 EDGE/PAVT 789.47
INV. 786.35 (12"N)
- ⑥-⑨ STORM SEWER, TYPE 2, RCCP, CLASS 3, 12"
238 FT. @ 2.15%
- ⑨-⑩ STORM SEWER, TYPE 2, RCCP, CLASS 3, 12"
8 FT. @ 1.00% TRENCH BACKFILL = 2 C.Y.
- ⑩-⑪ STORM SEWER, TYPE 2, RCCP, CLASS 3, 12"
38 FT. @ 1.00% TRENCH BACKFILL = 7 C.Y.
- ⑨-⑫ STORM SEWER, TYPE 2, RCCP, CLASS 3, 12"
238 FT. @ 2.15%
- ⑫-⑬ STORM SEWER, TYPE 2, RCCP, CLASS 3, 12"
8 FT. @ 1.00% TRENCH BACKFILL = 2 C.Y.
- ⑬-⑭ STORM SEWER, TYPE 2, RCCP, CLASS 3, 12"
38 FT. @ 1.00% TRENCH BACKFILL = 7 C.Y.

NOTE: EXISTING CRUGER ROAD TO BE REMOVED - SEE GENERAL NOTE 5 (SHEET 2 OF 47)

NOTE: ALL EXIST. UTILITIES ARE APPROXIMATE AND SHOWN FOR INFORMATION ONLY AND ARE TO BE VERIFIED IN THE FIELD BY THE CONTRACTOR.

STORM SEWER QUANTITIES ARE MEASURED FROM CENTERLINE OF STRUCTURE TO CENTERLINE OF STRUCTURE.

SCALES:
1" = 20' HOR
1" = 5' VER

