

February 27, 2006

SUBJECT: Various Routes Section D5 Crack & Joint Seal 2006-1 Champaign, Edgar & Vermilion Counties Contract No. 70492 Item No. 73, March 10, 2006 Letting Addendum A

NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

- 1. Revised sheets 4, 5 & 6 of the Plans.
- 2. Revised page i of the Table of Contents to the Special Provisions.
- 3. Revised page 12 of the Special Provisions.

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

Michael L. Hine Engineer of Design and Environment

Jerger Jake hayen BE.

By: Ted B. Walschleger, P. E. Engineer of Project Management

cc: J. E. Crowe, Region 3, District 5; Roger Driskell; Estimates; Design & Environment File

TBW:MS:jc

TABLE OF CONTENTS

INTENT OF PROJECT1
DESCRIPTION OF PROJECT1
TRAFFIC CONTROL PLAN
CHANGEABLE MESSAGE SIGN
PAVEMENT MARKINGS
ROUTING DEBRIS CLEAN UP
STATUS OF UTILITIES
FLAGGER VESTS (BDE)
PARTIAL PAYMENTS (BDE)
PAYMENTS TO SUBCONTRACTORS (BDE)
PAYROLLS AND PAYROLL RECORDS (BDE)
PERSONAL PROTECTIVE EQUIPMENT (BDE)
SUBCONTRACTOR MOBILIZATION PAYMENTS (BDE)9
TRAFFIC CONTROL DEFICIENCY DEDUCTION (BDE)9
WORK ZONE SPEED LIMIT SIGNS (BDE)10
WORK ZONE TRAFFIC CONTROL DEVICES (BDE)10
WORKING DAYS (BDE)
MINIMUM LANE WIDTH WITH LANE CLOSURE (BDE)12
Revised 02/27/2006

Revise the sixth paragraph of Article 702.05(a) of the Standard Specifications to read:

"When the work operations exceed four days, all signs shall be post mounted unless the signs are located on the pavement or define a moving or intermittent operation. When approved by the Engineer, a temporary sign stand may be used to support a sign at 1.2 m (5 ft) minimum where posts are impractical. Longitudinal dimensions shown on the plans for the placement of signs may be increased up to 30 m (100 ft) to avoid obstacles, hazards or to improve sight distance, when approved by the Engineer. "ROAD CONSTRUCTION AHEAD" signs will also be required on side roads located within the limits of the mainline "ROAD CONSTRUCTION AHEAD" signs."

Delete all references to "Type 1A barricades" and "wing barricades" throughout Section 702 of the Standard Specifications.

WORKING DAYS (BDE)

Effective: January 1, 2002

The Contractor shall complete the work within 45 working days.

MINIMUM LANE WIDTH WITH LANE CLOSURE (BDE)

Effective: January 1, 2005

Add the following paragraph after the eighth paragraph of Article 701.04(a) of the Standard Specifications.

"The minimum lane width adjacent to a closed lane during paving, patching, and other moving operations on freeways and expressways shall be a minimum of 3 m (10 ft). The 3 m (10 ft) shall be clear, unobstructed, and free of channelizing devices or other obstacles."

Revised 02/27/2006