

SECTION COUNTY TOTAL SHEET HO 288-2-RS-1 McHenry 53 48 TED, NOAD SIST, NO. ILLINGIS FEG. ASS PROJECT CONTRACT No. 60756 PROP. BIT. OR P.C.C.
SURFACE REMOVAL - BUTT JOINT
9.0 m (30ft.) (NOTE "A")
4.5 m (15ft.) (NOTE "B") SAW CUT (INCLUDED IN THE COST OF BITUMINOUS SURFACE REMOVAL - BUTT JOINT) (NOTE "D") 45 (1 3/4) FOR E AND F MIX F 40 (1 1/2) FOR C AND D MIX * * EXIST. PAVEMENT BUTT JOINT DETAIL TAPER LENGTH * * * VARIES PROP. BIT. SURF. CRSE. -45 (1 3/4) FOR E AND F MIX [40 (1 1/2) FOR C AND D MIX PROP. BIT. BINDER CRSE. -* * EXIST. PAVEMENT BITUMINOUS TAPER DETAIL TYPICAL BUTT JOINT AND BITUMINOUS TAPER FOR RESURFACING ONLY * * PC CONCRETE, BITUMINOUS OR BITUMINOUS RESURFACED PAVEMENT. A: MAINLINE ROADWAYS AND MAJOR SIDE ROADS. B: MINOR SIDE ROADS. C: THE TEMP, RAMP SHALL BE CONSTRUCTED IMMEDIATELY UPON REMOVAL OF THE EXISTING BITUMINOUS SURFACE. D: THE BUTT JOINT SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO PLACING THE PROPOSED BITUMINOUS COURSES. E: TAPER THE TEMP. RAMP AT A RATE OF 900 (3 ff.) PER INCH OF MILLING THICKNESS. F: INSTALLATION AND REMOVAL OF THE 1.35 m (4.5') TEMP. BIT. RAMP WILL BE PAID AS "BITUMINOUS SURFACE REMOVAL - BUTT JOINT". G: SEE ARTICLE 406.18 AND 406.24 OF THE STANDARD SPECIFICATIONS FOR "BITUMINOUS AND PCC SURFACE REMOVAL, BUTT JOINT". * SEE TYPICAL SECTIONS FOR MILLING THICKNESS. # # # 6.1 m (20") PER 25 (1) RESURFACING (NOTE "A") 3.0 m (10") PER 25 (1) RESURFACING (NOTE "B") ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE SHOWN. ILLINOIS DEPARTMENT OF TRANSPORTATION BASIS OF PAYMENT: BUTT JOINT AND THE BUTT JOINT WILL BE PAID FOR PER SQUARE METER (SQUARE YARD.) AS "BITUMINOUS SURFACE REMOVAL - BUTT JOINT" OR AS "PORTLAND CEMENT CONCRETE SURFACE REMOVAL- BUTT JOINT". BITUMINOUS TAPER DETAILS DRAWN BY CHECKED BY BD400-05 (VI=BD32) REVISION DATE: 04/06/01