

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
S.B.I. F.A. 5	19B-2-D	STEPHENSON	57	39
FED. ROAD DIST. NO. 7		ILLINOIS	FED. AID PROJECT	

SHEET NO. 23
23 SHEETS

B - 4

B - 4



Illinois Department of Transportation
Division of Highways
Illinois Department of Transportation

SOIL BORING LOG

Page 1 of 2
Date 4/6/00

ROUTE FA 5 (US 20 BR) DESCRIPTION P-92-046-99 US 20 over Yellow Creek LOGGED BY W. Garza
SECTION 19 BR-2 LOCATION Silver Creek Twp, SE, SEC. 4, TWP. 26N, RNG. 8E
COUNTY Stephenson DRILLING METHOD Hollow Stem Auger HAMMER TYPE Mobile Safe-T-Driver

STRUCT. NO.	D	B	U	M	Surface Water Elev.	D	B	U	M
Station 56 + 25	E	L	C	O	Stream Bed Elev.	E	L	C	O
BORING NO. B-4	P	O	S	I	Groundwater Elev.:	P	O	S	I
Station 55 + 83	H	S	Qu	T	First Encounter 78.0 ft	H	S	Qu	T
Offset 32.00ft Lt CL					Upon Completion Wash ft				
Ground Surface Elev. 99.0 ft	(ft)	(/6")	(tsf)	(%)	After Hrs.	(ft)	(/6")	(tsf)	(%)

Air									
					SOFT Same as above, bottom 3" dirty SAND & GRAVEL 8% ORGANICS	2			
						3	0.29	53	
						10	B		
					VERY STIFF gray SILT with CLAY lens	5			
						8	2.47	25	
						10	B		
					VERY STIFF gray SILTY CLAY lens	5			
						7	2.06	22	
						10	B		
					VERY STIFF Same as above	8			
						8	2.47	23	
						10	B		
					VERY STIFF Same as above	8			
						10	2.06	21	
						13	B		
Ground					VERY STIFF Same as above	7			
MEDIUM brown SILTY LOAM		4				10	2.27	21	
		5	0.75	40		11	S		
		5	P						
					SOFT brown SILTY LOAM	3			
		3	0.41	39		9	1.75	22	
		3	B		STIFF gray SILT with CLAY lens	9			
		5				12	P		
					SOFT dark gray with SAND lens SILTY LOAM 8% ORGANICS	2			
		2	0.33	48		17	0.75	20	
		2	B		MEDIUM gray SILT CLAY	20			
		2				22	P		

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T208)

BBS, from 137 (Rev. 8-98)



Illinois Department of Transportation
Division of Highways
Illinois Department of Transportation

SOIL BORING LOG

Page 2 of 2
Date 4/6/00

ROUTE FA 5 (US 20 BR) DESCRIPTION P-92-046-99 US 20 over Yellow Creek LOGGED BY W. Garza
SECTION 19 BR-2 LOCATION Silver Creek Twp, SE, SEC. 4, TWP. 26N, RNG. 8E
COUNTY Stephenson DRILLING METHOD Hollow Stem Auger HAMMER TYPE Mobile Safe-T-Driver

STRUCT. NO.	D	B	U	M	Surface Water Elev.	D	B	U	M
Station 56 + 25	E	L	C	O	Stream Bed Elev.	E	L	C	O
BORING NO. B-4	P	O	S	I	Groundwater Elev.:	P	O	S	I
Station 55 + 83	H	S	Qu	T	First Encounter 78.0 ft	H	S	Qu	T
Offset 32.00ft Lt CL					Upon Completion Wash ft				
Ground Surface Elev. 99.0 ft	(ft)	(/6")	(tsf)	(%)	After Hrs.	(ft)	(/6")	(tsf)	(%)

					Wash	3			
					STIFF gray SILT with TILL lens	11	1.81	22	
						12	B		
					VERY STIFF gray SILT CLAY TILL with SILT lens	11			
						13	3.03	21	
						16	S		
					Wash	30			
					VERY STIFF gray SILT TILL with DOLOMITE lens	28	3.09	18	
						28	S		
					VERY DENSE gray well cemented fine SAND	10			
						83			
						41			
					Wash	24			
					VERY DENSE Same as above	29			
						34			
					VERY DENSE Same as above	23			
						30			
						36			
					End of Boring				

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T208)

BBS, from 137 (Rev. 8-98)

Notes: For location of borings, see General Plan & Elevation sheet No. 1.
Offsets are given from Q F.A. Route 301 U.S. 20.

DESIGNED	L.C.M.
CHECKED	S.D.K.
DRAWN	T.L.N.
CHECKED	S.D.K.

EXAMINED	20
PASSED	ENGINEER OF BRIDGE DESIGN
	ENGINEER OF BRIDGES AND STRUCTURES

LEGEND

- N Standard Penetration Test-Blows per foot to drive 2" O.D. Split Spoon Sampler 12" with 140# hammer falling 30".
- Qu Unconfined Compressive Strength - t/sf.
- W% Water Content - percentage of dry weight - %.

- Type Failure
- B Bulge Failure
- S Shear Failure
- E Estimated Value
- P Penetrometer

SOIL BORING
U.S. 20 B.R. OVER YELLOW CREEK
F.A. RT. 5 SEC. 19B-2-D
STEPHENSON COUNTY
STATION 56+25.00
STRUCTURE NUMBER 089-0008

