

PAVEMENT MARKING SCHEDULE			
STATION	TYPE	PAINT PVT MK LINE 5"	
		WHITE	YELLOW
LT & RT 702+75 TO 784+25	EDGE LINE	16,300 FT	
702+75 TO 784+25	SKIP DASH		2,038 FT
DEDUCT FOR SIDEROADS	EDGE LINE	(108 FT)	
TOTALS		16,192 FT	2,038 FT

ENTRANCE & SIDEROAD SCHEDULE			
STATION	TYPE	INC BIT SURFACING	SECTION
RT 727+78	AGG. P.E.	2.5 TON	A-A
RT 742+44	AGG. P.E.	2.5 TON	A-A
RT 758+61	OIL & CHIP SR (MONTGOMERY RD.)	60.5 TON	B-B
RT 771+66	AGG. P.E.	2.5 TON	A-A

NOTES:
1. STATIONS ARE APPROXIMATE.

MIXTURE REQUIREMENTS			
THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT			
MIXTURE USE(S):	BC SC SUPER "C" N50	LEV BIND (MM) SUP, N50	INCIDENTAL BIT SURF
AC/PG	PG 64-22	PG 64-22	PG 64-22
RAP %: (MAX)	15%	20%	15%
DESIGN AIR VOIDS:	4.0% @ N DESIGN = 50	4.0% @ N DESIGN = 50	4.0% @ N DESIGN = 50
MIXTURE COMP:	IL 9.5 OR 12.5	IL 9.5 OR 12.5	IL 9.5 OR 12.5
FRICITION AGG:	MIX "C"	N/A	MIX "C"

MIXTURE TABLES & SCHEDULES
FAS 1769 (F.R. I-55 WEST)
SEC 111RS-5, (84-5-2)RS-3
MONTGOMERY/SANGAMON COUNTY