

GENERAL NOTES

1. All elevations refer to N.G.V.D. (National Geodetic Vertical Datum) 1929. All coordinates are NAD 1983 with 1986 Adjustment.
2. The Contractor shall furnish, erect, and when directed by the Engineer, completely remove two construction signs (see Standard Sheet). The location of the signs shall be determined by the Engineer in the field.
3. All lateral drainage that exists prior to construction shall be restored as shown on the plans and as directed by the Engineer. Unless otherwise specified all costs of restoration shall be considered included in the Contract and no additional compensation will be allowed.
4. Prior to the beginning of work in the vicinity of utilities, the Contractor shall contact the respective owners as shown on the plans and schedule work so as not to interfere with required adjustments.
5. With the exception of those utilities designated on the plans to be adjusted by the Contractor, all existing utilities affected by the construction operations shall be adjusted by others. Utilities which do not require adjustments shall be protected and not disturbed. All cost of protection shall be incidental to the Contract, and no additional compensation will be allowed.
6. All construction operations shall be contained within the easement area or work limits as indicated on the plans. It shall be the full responsibility of the Contractor to secure all rights of ingress and egress to said Right - of - Way including the satisfactory protection and restoration of property as required in Art. 107.20 and 107.23 of the Standard Specifications.
7. The Contractor shall call J.U.L.I.E. (800-892-0123) for the location of existing utilities 48 hours prior to beginning construction.
8. Field welding of construction accessories will not be permitted to the bottom flange at floor beams or the bottom truss chords. Field welding in other areas will be permitted only when approved by the Engineer.
9. The main load carrying members subject to tensile stress shall conform to the Supplemental Requirements for Notch Toughness Zone 2. These components are the truss bottom chords and diagonals and the floor beam tension flanges and webs and all splice plate material except fill plates.
10. Reinforcement bars shall conform to the requirements of AASHTO M 31 or M 322 Grade 60.
11. Plan dimensions and details relative to existing structures have been taken from existing plans and are subject to nominal construction variations. It shall be the Contractor's responsibility to verify such dimensions and details in the field and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in the scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.
12. Bridge Seat Sealer shall be applied to the seat area of the south abutment and the corbel of the north abutment.
13. All timber members shall meet the requirements of Section 1007 of the Standard Specifications.
14. The Contractor shall coordinate work activities with the Contractor who is onsite completing the previous phase of construction.

UTILITY REFERENCE TABLE

J.U.L.I.E.	Call 48 hours prior to construction	(800) 892-0123
City of Yorkville Water & Sewer	Eric Dhuse, Director of Public Works 800 Game Farm Road Yorkville, IL 60560	(630) 553-4370
Electricity	Commonwealth Edison	(800) 334-7661
Telephone/SBC	John Evers, Plan Engineer 40 S. Mitchell Court Addison, IL 60101	(630) 620-3897
Gas	Monty Johns Nicor Gas	(815) 433-3850 Ext.244

SUMMARY OF QUANTITIES			
CODE NO.	PAY ITEM	UNIT	QUANTITY
28000400	PERIMETER EROSION BARRIER	FOOT	85
42400300	PORTLAND CEMENT CONCRETE SIDEWALK 6 INCH	SQ FT	48
50200100	STRUCTURE EXCAVATION	CU YD	30
50300225	CONCRETE STRUCTURES	CU YD	17
50500405	FURNISHING AND ERECTING STRUCTURAL STEEL	POUND	100
50800205	REINFORCEMENT BARS, EPOXY COATED	POUND	4,300
*50900805	PEDESTRIAN RAILING	FOOT	40
51500100	NAME PLATES	EACH	1
51602000	PERMANENT CASING	FOOT	34
51603000	DRILLED SHAFT IN SOIL	CU YD	3.1
51604000	DRILLED SHAFT IN ROCK	CU YD	1.2
58700200	BRIDGE SEAT SEALER	SQ FT	21
*67000500	ENGINEER'S FIELD OFFICE, TYPE B	CAL MO	6
67100100	MOBILIZATION	L SUM	1
*X0322508	PEDESTRIAN TRUSS SUPERSTRUCTURE	SQ FT	1,294
*XX003949	CONSTRUCTION STAKING	L SUM	1
*	SEEDING, MULCHING AND FERTILIZING	ACRE	0.01
*	STONE FACE FINISH	SQ FT	199
*	RAILING REMOVAL	FOOT	16
*	REMOVE AND RELOCATE EXISTING RAILING	FOOT	23
*	GAGE STATION WALKWAY	L SUM	1
*	WOOD INFORMATION SIGNS	EACH	2
*	BRIDGE LIGHTING	L SUM	1
*	DEBRIS DEFLECTOR	L SUM	1

* INDICATES NON-STANDARD ITEM COVERED BY SPECIAL PROVISION

C:\Dwt\Proj\p\Projects\Yorkville Dam Phase 3\Plans DGN\Summary of Quantities and General Notes.dgn

5:12:41 PM

2/14/2011

Designed By TMM Checked By JUF
Drawn By JUF Checked By TMM