



④ Collar I.D. shall be manufactured to correspond to O.D. of actual galvanized post and stainless steel sleeve plus 1/8" (+1/16"). Maximum gap between post and collar at any location equals 1/8" before tightening bolts.


SECTION B-B
Bolts, washers (including contoured washers), and locknuts shall be stainless steel.



DETAIL A
(Two locations)
3/8" - 45° chamfer on inside of collar to facilitate field assembly




DETAIL B
Two locations
(For details not shown, see Detail C)




CONTOURED WASHERS


Bolt Size	Contoured Washers Hole Dia.	B
7/8"	1"	2 1/2"
1"	1 1/8"	3"
1 1/4"	1 3/8"	3 1/4"




DETAIL OF STAINLESS STEEL SLEEVE
Weld to post after galvanizing.
(Prepare post surface to insure tight, uniform fit and allow welding.)
Welds to be 1 1/2" long at 6" cts. along top edge and at 1/4" opening.




DETAIL D



PLAN VIEW - TOP OF COLUMN
⑤ Optional full penetration weld in collar. (Two locations maximum....180° apart)....X-ray or UT 100%



SECTION THRU POST ABOVE LOWER CHORDS



DETAIL C

Truss Type	Post Size	Upper & Lower Connection Bolt Diameter ③	Lower Juncture Bolt Spacing Dimension "c" ③	Opening in Cap Plate "HH"	Collar Thickness (t)	Side Ribs
						x y
I-C-A	16" φ (83#1/1)	7/8"	3 1/4"	8"	5/8"	1 3/4" 2 1/4"
II-C-A	24" φ (125#1/1)	1"	3 1/2"	12"	7/8"	2" 1 1/4"
III-C-A (35' max.)	24" φ (125#1/1)	1 1/4"	3 1/2"	12"	7/8"	2" 1"
III-C-A (>35' to 40')	24" φ (171#1/1)	1 1/4"	3 1/2"	12"	7/8"	2" 1"

- ① Grind top if required to fully seat aluminum plate and stainless steel sheet.
- ② After tightening lower connection bolts, fill gap with non-hardening, silicone caulk suitable for exterior exposure and acceptable to the Engineer. Cost is included in Overhead Sign Structure Cantilever.
- ③ Upper and lower connection bolts in collar and bolts at lower chord connection shall be high strength with matching locknuts. Connection bolts shall have 2 stainless steel flat washers each.

This Sheet For Information Only