



### PPC I-BEAMS AND BULB-T's



STEEL BEAMS



SECTION A-A

#### TIMBER SPACING

	Timber Sizes (in.)			
Beam Spacing (ft.)	4" x 4" with min. Fb=775 psi Fv=135 psi	4" x 6" with min. Fb=775 psi Fv=135 psi m Timber Spac	6" x 6" with min. Fb=575 psi Fv=125 psi	
4.5	16	16	16	
4.75	16	16	16	
5.0	<i>1</i> 6	16	16	
5.25	16	16	16	
5.5	16	<i>1</i> 6	<i>1</i> 6	
5.75	16	16	16	
6.0	16	16	16	
6.25	12	<i>1</i> 6	16	
6.5	12	16	16	
6.75	12	16	16	
7.0	8	16	16	
7.25	8	16	16	
7.5	8	16	16	
7.75	8	16	16	
8.0	8	12	16	
8.25	8	12	16	
8.5	6	12	12	
8.75	6	12	12	
9.0	6	8	12	

## PPC I-BEAMS AND BULB-T's

BEAM	"A"
36" I-Beam	1/-"
42" I-Beam	1/2//
48" I-Beam	12 12"
54" I-Beam	12
	330"
63" Bulb-T	338
72'' Bulb-T	338"

#### Notes:

: See special provision for Permanent Protective Shield System.

Timber sizes shown are nominal sizes. Rough sawn timber of the dimensions shown will also be considered acceptable.

The minimum Fb and Fv values shown are the tabulated design values given in the National Design Specification for Wood Construction for No. 2 Spruce-Pine-Fir without adjustment factors applied. Better grades or other species with equal or higher allowable stresses will also be considered acceptable.

The timber spacings shown have been determined using allowable stresses with all adjustment factors necessary for the anticipated service conditions.

All timber shall be treated.

Plywood shall be 58" rated Exterior type plywood by APA.

Plywood shall be placed such that the face grain is perpendicular to the timber supports. When less than a full sheet (4' width) of plywood is used, the width of the strip used shall not be less than 2'.

Transverse plywood joints shall be supported by timbers.

When 4" x 6" timbers are used, they shall be placed such that the wide face is horizontal and the narrow face is vertical.

Design load = 200 psf.

# BILL OF MATERIAL

Item	Unit	Total	
Protective Shield (Permanent)	Sq. Yd.	3665	

PPS-1

01-22-09

·				
FILE NAME =	USER NAME = \$USER\$	DESIGNED -	REVISED -	
*FILEL*		DRAWN ~	REVISED -	
	PLOT SCALE : \$SCALE\$	CHECKED -	REVISED -	
	PLOT DATE = \$DATE\$	DATE -	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION