

LOCATION	SUB-BASE GRANULAR MATERIAL, TYPE C	
	Variable Depths	
	TON	
RAMP H/MAIN ST.		
MAIN ST. STA. 32+00 TO 32+36.8		5.0
MAIN ST. STA. 32+36.08 TO RAMP H STA. 24+60		205.0
RAMP H STA. 10+70.97 TO 18+15		61.2
EASTBOUND		
SN. 048-0058		
RT. STA. 371+29 TO 378+08		210.0
LT. STA. 370+88 TO 378+51		107.7
SN. 048-0048		
RT. STA. 425+09 TO 432+81		489.2
LT. STA. 424+82 TO 433+06		246.8
WESTBOUND		
SN 048-0058		
RT. STA. 371+42 TO 398+12		121.8
LT. STA. 371+81 TO 378+73		273.6
SN. 048-0048		
RT. STA. 424+39 TO 429+00		178.2
LT. STA. 424+64 TO 428+35		277.7
RURAL TOTAL		1191.9
URBAN TOTAL		984.3

PAVEMENT REMOVAL	
LOCATION	SQ. YD.
I-74 EASTBOUND	
STA. 372+03 TO 377+45	1490.4
STA. 425+98 TO 430+12	1157.9
I-74 WESTBOUND	
STA. 371+81 TO 378+73	1486.3
STA. 425+29 TO 427+77	662.1
RAMP H	
STA. 1+03 TO 16+74	2933.5
URBAN TOTAL	5910
RURAL TOTAL	1820

PAVEMENT REMOVAL	
LOCATION	SQ. YD.
I-74 EASTBOUND	
STA. 372+03 TO 377+45	1490.4
STA. 425+98 TO 430+12	1157.9
I-74 WESTBOUND	
STA. 371+81 TO 378+73	1486.3
STA. 425+29 TO 427+77	662.1
RAMP H	
STA. 1+03 TO 16+74	2933.5
URBAN TOTAL	5910
RURAL TOTAL	1820

COMBINATION CURB & GUTTER REMOVAL	
LOCATION	FOOT
RAMP H	
STA. 1+23 TO 1+37	26.6
MAIN ST.	
STA. 31+71 TO 32+77	119.2
URBAN TOTAL	146

PAVED SHOULDER REMOVAL	
LOCATION	SQ. YD.
I-74 EASTBOUND	
RT. STA. 371+29 TO 378+08	742.1
LT. STA. 370+88 TO 378+51	281
TEMPORARY SHOULDER (LT. STA. 370+88 TO 378+51)	341.8
RT. STA. 425+09 TO 432+81	860.3
LT. STA. 424+82 TO 433+06	279.9
TEMPORARY SHOULDER (LT. STA. 424+82 TO 433+06)	365.7
RT. STA. 495+72 TO 497+15	158.89
LT. STA. 495+72 TO 497+15	47.67
I-74 WESTBOUND	
RT. STA. 371+42 TO 379+12	297.3
LT. STA. 371+81 TO 378+73	736.7
TEMPORARY SHOULDER (RT. STA. 371+42 TO 379+12)	339.6
RT. STA. 424+39 TO 429+00	202.4
LT. STA. 424+64 TO 428+35	411.7
TEMPORARY SHOULDER (RT. STA. 424+39 TO 429+00)	204.9
RT. STA. 493+61.4 TO 495+04.4	47.67
LT. STA. 493+61.4 TO 495+04.4	158.89
RAMP H	
RT. SIDE FROM MAIN ST. TO STA. 365+31	2031.6
LT. SIDE & GORE AREA	616.3
URBAN TOTAL	5386
RURAL TOTAL	2738

LOCATION	SUB-BASE GRANULAR MATERIAL TYPE A 12"		GEOTECHNICAL FABRIC FOR GROUND STABILIZATION	
	SQ. YD.		SQ. YD.	
RAMPS				
RAMP H Sta. 10+37.41 to 30+02.35 & THE GORE AREA*		3846		
AREA OF PROPOSED 8" SHOULDER				
EASTBOUND				
STA. 372+03 TO 377+45		2436.9		2436.9
STA. 425+98 TO 430+12		1842.8		1842.8
WESTBOUND				
STA. 372+87 TO 378+33		2364.2		2364.2
STA. 425+29 TO 427+77		1074.7		1074.7
RURAL TOTAL		2918		2918
URBAN TOTAL		8647		4801

PAVED DITCH REMOVAL	
LOCATION	FOOT
STA. 358+98 TO 366+04	706
URBAN TOTAL	706

*6" BEYOND THE PROPOSED PAVEMENT AREA. AREA'S MEASURED IN CADD