

BEAM 1

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Back South Abut.	240+40.10	-17.01	427.92	427.92
⊕ Brg. South Abut.	240+41.46	-17.03	427.93	427.93
A	240+51.51	-17.19	427.95	427.96
B	240+61.56	-17.31	427.98	427.99
C	240+71.62	-17.41	427.99	427.99
⊕ Brg. Pier 1	240+77.97	-17.45	428.00	428.00
D	240+88.03	-17.49	428.01	428.03
E	240+98.08	-17.50	428.02	428.05
F	241+08.14	-17.48	428.02	428.04
G	241+18.19	-17.42	428.01	428.02
⊕ Brg. Pier 2	241+28.25	-17.34	428.00	428.00
H	241+38.30	-17.22	427.98	427.99
I	241+48.35	-17.07	427.96	427.98
J	241+58.41	-16.89	427.94	427.95
⊕ Brg. North Abut.	241+64.76	-16.76	427.92	427.92
Back North Abut.	241+66.11	-16.73	427.91	427.91

BEAM 2

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Back South Abut.	240+37.45	-10.13	428.15	428.15
⊕ Brg. South Abut.	240+38.81	-10.15	428.15	428.15
A	240+48.84	-10.32	428.18	428.19
B	240+58.87	-10.45	428.20	428.21
C	240+68.90	-10.55	428.22	428.22
⊕ Brg. Pier 1	240+75.24	-10.60	428.23	428.23
D	240+85.27	-10.65	428.24	428.26
E	240+95.31	-10.67	428.25	428.28
F	241+05.34	-10.65	428.25	428.28
G	241+15.37	-10.61	428.24	428.26
⊕ Brg. Pier 2	241+25.41 241+35.44	-10.53	428.23	428.23
H	241+32.59	-10.42	428.22	428.23
I	241+42.60	-10.28	428.20	428.21
J	241+52.61	-10.11	428.18	428.19
⊕ Brg. North Abut.	241+61.84	-9.99	428.16	428.16
Back North Abut.	241+63.19	-9.96	428.16	428.16

BEAM 3

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Back South Abut.	240+34.82	-3.25	428.37	428.37
⊕ Brg. South Abut.	240+36.17	-3.27	428.37	428.37
A	240+46.17	-3.44	428.40	428.41
B	240+56.18	-3.58	428.43	428.44
C	240+66.20	-3.69	428.45	428.45
⊕ Brg. Pier 1	240+72.52	-3.75	428.46	428.46
D	240+82.53	-3.80	428.47	428.49
E	240+92.55	-3.83	428.48	428.51
F	241+02.56	-3.83	428.48	428.51
G	241+12.57	-3.79	428.48	428.49
⊕ Brg. Pier 2	241+22.58	-3.72	428.47	428.47
H	241+32.59	-3.62	428.46	428.46
I	241+42.60	-3.49	428.44	428.45
J	241+52.61	-3.33	428.42	428.43
⊕ Brg. North Abut.	241+58.93	-3.21	428.40	428.40
Back North Abut.	241+60.28	-3.18	428.40	428.40



FILE NAME =	USER NAME =	DESIGNED - MJP	REVISOR -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	TOP OF SLAB ELEVATIONS STRUCTURE NO. 039-0073	F.A.S. RTE. 1908	SECTION (13B)I-2	COUNTY JACKSON	TOTAL SHEETS 71	SHEET NO. 44	
	PLOT SCALE =	CHECKED - RLM	REVISOR -			CONTRACT NO. 98898					
	PLOT DATE = 12/02/2010	DRAWN - PRC	REVISOR -			ILLINOIS FED. AID PROJECT					
		CHECKED - MJP	REVISOR -			SHEET NO. 5 OF 32 SHEETS					