

BEAM 1

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. Abut. A	10+79.18	-31.25	592.81	592.81
Ⓞ Brg. Abut. A	10+81.68	-31.25	592.86	592.86
A	10+95.37	-31.25	593.15	593.24
B	11+05.37	-31.25	593.38	593.53
C	11+15.37	-31.25	593.60	593.77
D	11+25.37	-31.25	593.80	593.96
E	11+35.37	-31.25	593.97	594.11
F	11+45.37	-31.25	594.12	594.22
G	11+55.37	-31.25	594.24	594.29
Ⓞ Brg. Pier 1	11+65.37	-31.25	594.35	594.35
H	11+71.78	-31.25	594.40	594.38
I	11+81.78	-31.25	594.47	594.44
J	11+91.78	-31.25	594.51	594.49
Ⓞ Brg. Pier 2	11+98.18	-31.25	594.53	594.53
K	12+08.18	-31.25	594.54	594.59
L	12+18.18	-31.25	594.52	594.63
M	12+28.18	-31.25	594.49	594.64
N	12+38.18	-31.25	594.43	594.61
O	12+48.18	-31.25	594.34	594.53
P	12+58.18	-31.25	594.24	594.40
Q	12+68.18	-31.25	594.11	594.22
Ⓞ Brg. Abut. B	12+84.11	-31.25	593.86	593.86
Bk. Abut. B	12+86.64	-31.25	593.82	593.82

BEAM 2

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. Abut. A	10+79.37	-25.00	592.65	592.65
Ⓞ Brg. Abut. A	10+81.87	-25.00	592.70	592.70
A	10+95.24	-25.00	592.98	593.08
B	11+05.24	-25.00	593.22	593.36
C	11+15.24	-25.00	593.44	593.60
D	11+25.24	-25.00	593.63	593.80
E	11+35.24	-25.00	593.80	593.95
F	11+45.24	-25.00	593.95	594.05
G	11+55.24	-25.00	594.08	594.13
Ⓞ Brg. Pier 1	11+65.24	-25.00	594.18	594.18
H	11+71.64	-25.00	594.24	594.22
I	11+81.64	-25.00	594.31	594.28
J	11+91.64	-25.00	594.35	594.33
Ⓞ Brg. Pier 2	11+98.05	-25.00	594.37	594.37
K	12+08.05	-25.00	594.38	594.42
L	12+18.05	-25.00	594.36	594.47
M	12+28.05	-25.00	594.32	594.48
N	12+38.05	-25.00	594.27	594.44
O	12+48.05	-25.00	594.18	594.37
P	12+58.05	-25.00	594.08	594.24
Q	12+68.05	-25.00	593.95	594.06
Ⓞ Brg. Abut. B	12+83.18	-25.00	593.72	593.72
Bk. Abut. B	12+85.71	-25.00	593.67	593.67

BEAM 3

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. Abut. A	10+79.57	-18.75	592.74	592.74
Ⓞ Brg. Abut. A	10+82.07	-18.75	592.79	592.79
A	10+95.10	-18.75	593.06	593.15
B	11+05.10	-18.75	593.29	593.44
C	11+15.10	-18.75	593.51	593.68
D	11+25.10	-18.75	593.71	593.88
E	11+35.10	-18.75	593.88	594.02
F	11+45.10	-18.75	594.03	594.13
G	11+55.10	-18.75	594.16	594.20
Ⓞ Brg. Pier 1	11+65.10	-18.75	594.26	594.26
H	11+71.51	-18.75	594.32	594.30
I	11+81.51	-18.75	594.38	594.35
J	11+91.51	-18.75	594.43	594.41
Ⓞ Brg. Pier 2	11+97.91	-18.75	594.45	594.45
K	12+07.91	-18.75	594.45	594.50
L	12+17.91	-18.75	594.44	594.55
M	12+27.91	-18.75	594.40	594.56
N	12+37.91	-18.75	594.35	594.52
O	12+47.91	-18.75	594.26	594.45
P	12+57.91	-18.75	594.16	594.32
Q	12+67.91	-18.75	594.03	594.14
Ⓞ Brg. Abut. B	12+82.26	-18.75	593.81	593.81
Bk. Abut. B	12+84.79	-18.75	593.77	593.77

BEAM 4

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. Abut. A	10+79.76	-12.50	592.87	592.87
Ⓞ Brg. Abut. A	10+82.26	-12.50	592.91	592.91
A	10+94.96	-12.50	593.18	593.26
B	11+04.96	-12.50	593.42	593.54
C	11+14.96	-12.50	593.63	593.79
D	11+24.96	-12.50	593.83	593.99
E	11+34.96	-12.50	594.00	594.14
F	11+44.96	-12.50	594.15	594.25
G	11+54.96	-12.50	594.28	594.32
Ⓞ Brg. Pier 1	11+64.96	-12.50	594.38	594.38
H	11+71.37	-12.50	594.44	594.42
I	11+81.37	-12.50	594.51	594.48
J	11+91.37	-12.50	594.55	594.54
Ⓞ Brg. Pier 2	11+97.77	-12.50	594.57	594.57
K	12+07.77	-12.50	594.58	594.62
L	12+17.77	-12.50	594.57	594.66
M	12+27.77	-12.50	594.53	594.67
N	12+37.77	-12.50	594.47	594.63
O	12+47.77	-12.50	594.39	594.55
P	12+57.77	-12.50	594.29	594.41
Q	12+67.77	-12.50	594.16	594.24
Ⓞ Brg. Abut. B	12+81.33	-12.50	593.95	593.95
Bk. Abut. B	12+83.86	-12.50	593.91	593.91

BEAM 5

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. Abut. A	10+79.96	6.25	592.99	592.99
Ⓞ Brg. Abut. A	10+82.46	-6.25	593.04	593.04
A	10+94.83	-6.25	593.30	593.38
B	11+04.83	-6.25	593.54	593.67
C	11+14.83	-6.25	593.76	593.91
D	11+24.83	-6.25	593.95	594.11
E	11+34.83	-6.25	594.12	594.26
F	11+44.83	-6.25	594.27	594.37
G	11+54.83	-6.25	594.40	594.45
Ⓞ Brg. Pier 1	11+64.83	-6.25	594.51	594.51
H	11+71.23	-6.25	594.56	594.55
I	11+81.23	-6.25	594.63	594.60
J	11+91.23	-6.25	594.68	594.66
Ⓞ Brg. Pier 2	11+97.64	-6.25	594.70	594.70
K	12+07.64	-6.25	594.70	594.75
L	12+17.64	-6.25	594.69	594.79
M	12+27.64	-6.25	594.66	594.79
N	12+37.64	-6.25	594.60	594.76
O	12+47.64	-6.25	594.52	594.67
P	12+57.64	-6.25	594.41	594.54
Q	12+67.64	-6.25	594.29	594.36
Ⓞ Brg. Abut. B	12+80.41	-6.25	594.09	594.09
Bk. Abut. B	12+82.94	-6.25	594.05	594.05

BEAM 6 & P.G.L.

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. Abut. A	10+80.15	0.00	593.12	593.12
Ⓞ Brg. Abut. A	10+82.65	0.00	593.17	593.17
A	10+94.69	0.00	593.43	593.50
B	11+04.69	0.00	593.66	593.79
C	11+14.69	0.00	593.88	594.03
D	11+24.69	0.00	594.07	594.23
E	11+34.69	0.00	594.25	594.38
F	11+44.69	0.00	594.40	594.49
G	11+54.69	0.00	594.53	594.57
Ⓞ Brg. Pier 1	11+64.69	0.00	594.63	594.63
H	11+71.10	0.00	594.69	594.67
I	11+81.10	0.00	594.76	594.73
J	11+91.10	0.00	594.80	594.79
Ⓞ Brg. Pier 2	11+97.50	0.00	594.82	594.82
K	12+07.50	0.00	594.83	594.87
L	12+17.50	0.00	594.82	594.91
M	12+27.50	0.00	594.78	594.92
N	12+37.50	0.00	594.72	594.88
O	12+47.50	0.00	594.64	594.80
P	12+57.50	0.00	594.54	594.67
Q	12+67.50	0.00	594.41	594.49
Ⓞ Brg. Abut. B	12+79.48	0.00	594.23	594.23
Bk. Abut. B	12+82.01	0.00	594.19	594.19