

GIRDER G1

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. Abutment C	83+99.91	-12.125	593.08	593.08
⊕ Brg. Abutment C	84+05.10	-12.125	593.16	593.16
A	84+16.90	-12.125	593.32	593.40
B	84+26.90	-12.125	593.45	593.59
C	84+36.90	-12.125	593.57	593.76
D	84+46.90	-12.125	593.68	593.89
E	84+56.90	-12.125	593.77	593.99
F	84+66.90	-12.125	593.86	594.07
G	84+76.90	-12.125	593.94	594.13
H	84+86.90	-12.125	594.01	594.16
I	84+96.90	-12.125	594.07	594.17
J	85+06.90	-12.125	594.11	594.16
⊕ Brg. Pier 3	85+16.89	-12.125	594.15	594.15
K	85+26.89	-12.125	594.18	594.15
L	85+36.89	-12.125	594.20	594.16
M	85+46.89	-12.125	594.21	594.17
N	85+56.89	-12.125	594.21	594.18
⊕ Brg. Pier 4	85+71.66	-12.125	594.18	594.18
O	85+81.66	-12.125	594.16	594.20
P	85+91.66	-12.125	594.12	594.20
Q	86+01.66	-12.125	594.07	594.19
R	86+11.66	-12.125	594.02	594.16
S	86+21.66	-12.125	593.95	594.11
T	86+31.66	-12.125	593.87	594.03
U	86+41.66	-12.125	593.79	593.93
V	86+51.66	-12.125	593.69	593.80
W	86+61.66	-12.125	593.58	593.64
⊕ Brg. Abutment D	86+73.31	-12.233	593.45	593.45
Bk. Abutment D	86+77.78	-12.469	593.40	593.40

GIRDER G2

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. Abutment C	84+08.77	-4.042	593.05	593.05
⊕ Brg. Abutment C	84+13.96	-4.042	593.12	593.12
A	84+24.56	-4.042	593.26	593.33
B	84+34.56	-4.042	593.38	593.51
C	84+44.56	-4.042	593.49	593.67
D	84+54.56	-4.042	593.59	593.79
E	84+64.56	-4.042	593.68	593.90
F	84+74.56	-4.042	593.76	593.97
G	84+84.56	-4.042	593.83	594.01
H	84+94.56	-4.042	593.89	594.03
I	85+04.56	-4.042	593.94	594.03
J	85+14.56	-4.042	593.98	594.02
⊕ Brg. Pier 3	85+24.55	-4.042	594.01	594.01
K	85+34.55	-4.042	594.03	594.00
L	85+44.55	-4.042	594.04	594.00
M	85+54.55	-4.042	594.04	594.00
N	85+64.55	-4.042	594.04	594.01
⊕ Brg. Pier 4	85+79.32	-4.042	594.00	594.00
O	85+89.32	-4.042	593.97	594.01
P	85+99.32	-4.042	593.92	594.00
Q	86+09.32	-4.042	593.87	593.99
R	86+19.32	-4.042	593.81	593.95
S	86+29.32	-4.042	593.73	593.89
T	86+39.32	-4.042	593.65	593.81
U	86+49.32	-4.042	593.55	593.69
V	86+59.32	-4.042	593.45	593.56
W	86+69.28	-4.050	593.33	593.39
⊕ Brg. Abutment D	86+81.03	-4.614	593.20	593.20
Bk. Abutment D	86+85.69	-5.083	593.15	593.15

PROFILE GRADE LINE

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. Abutment C	84+13.20	0.00	593.03	593.03
⊕ Brg. Abutment C	84+18.39	0.00	593.10	593.10
A	84+28.39	0.00	593.23	593.29
B	84+38.39	0.00	593.34	593.47
C	84+48.39	0.00	593.45	593.63
D	84+58.39	0.00	593.55	593.74
E	84+68.39	0.00	593.63	593.85
F	84+78.39	0.00	593.71	593.91
G	84+88.39	0.00	593.78	593.96
H	84+98.39	0.00	593.83	593.97
I	85+08.39	0.00	593.88	593.97
J	85+18.39	0.00	593.92	593.96
⊕ Brg. Pier 3	85+28.38	0.00	593.94	593.94
K	85+38.38	0.00	593.96	593.93
L	85+48.38	0.00	593.96	593.92
M	85+58.38	0.00	593.96	593.92
N	85+68.38	0.00	593.95	593.92
⊕ Brg. Pier 4	85+83.15	0.00	593.91	593.91
O	85+93.15	0.00	593.87	593.91
P	86+03.15	0.00	593.82	593.90
Q	86+13.15	0.00	593.77	593.89
R	86+23.15	0.00	593.70	593.84
S	86+33.15	0.00	593.62	593.78
T	86+43.15	0.00	593.53	593.69
U	86+53.15	0.00	593.43	593.57
V	86+63.15	0.00	593.32	593.44
W	86+73.15	-0.095	593.21	593.27
⊕ Brg. Abutment D	86+85.16	-0.957	593.07	593.07
Bk. Abutment D	86+89.91	-1.549	593.02	593.02

GIRDER G3

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. Abutment C	84+17.63	4.042	593.01	593.01
⊕ Brg. Abutment C	84+22.82	4.042	593.08	593.08
A	84+32.22	4.042	593.19	593.25
B	84+42.22	4.042	593.30	593.42
C	84+52.22	4.042	593.41	593.58
D	84+62.22	4.042	593.50	593.69
E	84+72.22	4.042	593.58	593.79
F	84+82.22	4.042	593.65	593.85
G	84+92.22	4.042	593.72	593.90
H	85+02.22	4.042	593.77	593.91
I	85+12.22	4.042	593.81	593.90
J	85+22.22	4.042	593.85	593.89
⊕ Brg. Pier 3	85+32.21	4.042	593.87	593.87
K	85+42.21	4.042	593.88	593.85
L	85+52.21	4.042	593.88	593.84
M	85+62.21	4.042	593.88	593.84
N	85+72.21	4.042	593.86	593.83
⊕ Brg. Pier 4	85+86.98	4.042	593.82	593.82
O	85+96.98	4.042	593.77	593.81
P	86+06.98	4.042	593.72	593.80
Q	86+16.98	4.042	593.66	593.78
R	86+26.98	4.042	593.59	593.73
S	86+36.98	4.042	593.51	593.67
T	86+46.98	4.042	593.41	593.57
U	86+56.98	4.042	593.31	593.45
V	86+66.98	4.042	593.20	593.31
W	86+77.21	3.764	593.08	593.14
⊕ Brg. Abutment D	86+89.48	2.590	592.94	592.94
Bk. Abutment D	86+94.31	1.868	592.89	592.89

GIRDER G4

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. Abutment C	84+26.49	12.125	592.96	592.96
⊕ Brg. Abutment C	84+31.68	12.125	593.02	593.02
A	84+39.88	12.125	593.12	593.17
B	84+49.88	12.125	593.22	593.33
C	84+59.88	12.125	593.32	593.48
D	84+69.88	12.125	593.40	593.58
E	84+79.88	12.125	593.48	593.68
F	84+89.88	12.125	593.54	593.73
G	84+99.88	12.125	593.59	593.76
H	85+09.88	12.125	593.64	593.77
I	85+19.88	12.125	593.68	593.77
J	85+29.88	12.125	593.70	593.74
⊕ Brg. Pier 3	85+39.87	12.125	593.72	593.72
K	85+49.87	12.125	593.72	593.69
L	85+59.87	12.125	593.72	593.68
M	85+69.87	12.125	593.70	593.66
N	85+79.87	12.125	593.68	593.65
⊕ Brg. Pier 4	85+94.64	12.125	593.62	593.62
O	86+04.64	12.125	593.57	593.61
P	86+14.64	12.125	593.51	593.59
Q	86+24.64	12.125	593.44	593.56
R	86+34.64	12.125	593.36	593.50
S	86+44.64	12.125	593.27	593.43
T	86+54.64	12.125	593.18	593.34
U	86+64.64	12.125	593.07	593.21
V	86+75.21	11.960	592.94	593.05
W	86+85.94	11.159	592.82	592.88
⊕ Brg. Abutment D	86+98.69	9.319	592.67	592.67
Bk. Abutment D	87+03.68	8.325	592.62	592.62

GIRDER G5

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
W	86+85.91	11.13	592.82	592.82
⊕ Brg. Abutment D	87+03.77	12.59	592.53	592.53
Bk. Abutment D	87+10.96	12.65	592.43	592.43