

**EARTH EXCAVATION (WIDENING) (20200500)**

STATION	TO	STATION	OFFSET	LENGTH (FT)	WIDTH (FT)	DEPTH (IN)	CU YDS
1239+50.00		1242+38.83	11.0' LT	288.83	3.0	9.0	24.1
1243+85.17		1246+10.00	11.0' LT	224.83	3.0	9.0	18.7
1239+80.00		1242+38.83	11.0' RT	258.83	3.0	9.0	21.6
1243+85.17		1246+40.00	11.0' RT	254.83	3.0	9.0	21.2
TOTAL =							86.0

**FURNISHED EXCAVATION (20400800)**

STATION	TO	STATION	OFFSET	LENGTH (FT)	WIDTH (FT)	DEPTH (IN)	CU YDS
1239+50.00		1242+38.83	11.0' LT	288.83	1.75	7.0	5.5
1239+80.00		1242+38.83	11.0' RT	258.83	1.75	7.0	4.9
1243+85.17		1246+10.00	11.0' LT	224.83	1.75	7.0	4.3
1243+85.17		1246+40.00	11.0' RT	254.83	1.75	7.0	4.8
TOTAL =							20.0

**HOT-MIX ASPHALT BASE COURSE WIDENING, 9" (35800712)**

STATION	TO	STATION	OFFSET	LENGTH (FT)	WIDTH (FT)	SQ YDS
1239+50.00		1242+38.83	11.0' LT	288.83	4.0	128.4
1243+85.17		1246+10.00	11.0' LT	224.83	4.0	99.9
1239+80.00		1242+38.83	11.0' RT	258.83	4.0	115.0
1243+85.17		1246+40.00	11.0' RT	254.83	4.0	113.3
TOTAL =						457.0

**HOT-MIX ASPHALT SURFACE REMOVAL (DECK) (44000915)**

LOCATION	LENGTH (FT)	WIDTH (FT)	SQ YDS
S.N. 092-0048	144.08	30.17	483.0

**PAVED SHOULDER REMOVAL (44004250)**

STATION	TO	STATION	OFFSET	LENGTH (FT)	WIDTH (FT)	SQ YDS
1239+50.00		1242+38.83	12.0' LT	288.83	1.0	32.1
1243+85.17		1246+10.00	12.0' LT	224.83	1.0	25.0
1239+80.00		1242+38.83	12.0' RT	258.83	1.0	28.8
1243+85.17		1246+40.00	12.0' RT	254.83	1.0	28.3
TOTAL =						115.0

**CONCRETE REMOVAL (50102400)**

LOCATION	SQ YDS	
S.N. 092-0048 (W. ABUTMENT JOINT)	4.5	
S.N. 092-0048 (E. ABUTMENT JOINT)	4.2	
TOTAL =		8.7

**CONCRETE SUPERSTRUCTURE (50300255)**

LOCATION	CU YDS	
S.N. 092-0048 (W. ABUTMENT JOINT)	4.62	
S.N. 092-0048 (E. ABUTMENT JOINT)	4.62	
TOTAL =		9.3

**FURNISHING AND ERECTING STRUCTURAL STEEL (50500405)**

LOCATION	LBS	
S.N. 092-0048 (W. ABUTMENT)	740.0	
S.N. 092-0048 (E. ABUTMENT)	660.0	
TOTAL =		1400.0

**JACK AND REMOVE EXISTING BEARINGS (50500715)**

LOCATION	EACH	
S.N. 092-0048 (W. ABUTMENT)	6.0	
S.N. 092-0048 (E. ABUTMENT)	6.0	
TOTAL =		12.0

**REINFORCEMENT BARS, EPOXY COATED (50800205)**

LOCATION	LBS	
S.N. 092-0048 (W. ABUTMENT)	490.0	
S.N. 092-0048 (E. ABUTMENT)	490.0	
TOTAL =		980.0

**BAR SPLICERS (50800515)**

LOCATION	EACH	
S.N. 092-0048 (W. ABUTMENT)	11.0	
S.N. 092-0048 (E. ABUTMENT)	11.0	
TOTAL =		22.0

**PERFORMED JOINT STRIP SEAL (52000110)**

LOCATION	FEET	
S.N. 092-0048 (W. ABUTMENT)	36.0	
S.N. 092-0048 (E. ABUTMENT)	36.0	
TOTAL =		72.0

**ANCHOR BOLTS, 1" (52100520)**

LOCATION	EACH	
S.N. 092-0048 (W. ABUTMENT)	12.0	
S.N. 092-0048 (E. ABUTMENT)	12.0	
TOTAL =		24.0

**WATERPROOFING MEMBRANE SYSTEM (58100200)**

LOCATION	LENGTH (FT)	WIDTH (FT)	SQ YDS
S.N. 092-0048	141.08	30.17	473.0

**REMOVE AND RE-ERECT STEEL PLATE BEAM GUARDRAIL (63301000)**

STATION	TO	STATION	OFFSET	LENGTH (FT)
1242+26.33		1242+38.83	LT	12.5
1242+26.33		1242+38.83	RT	12.5
1243+85.17		1243+97.67	LT	12.5
1243+85.17		1243+97.67	RT	12.5
TOTAL =				50.0

**REMOVE AND RE-ERECT STEEL PLATE BEAM GUARDRAIL, ATTACHED TO STRUCTURES (63301235)**

STATION	TO	STATION	OFFSET	LENGTH (FT)
1242+38.83		1242+53.83	LT	15.0
1242+38.83		1242+53.83	RT	15.0
1243+70.17		1243+85.17	LT	15.0
1243+70.17		1243+85.17	RT	15.0
TOTAL =				60.0