



**SECTION
OF
POST**

**DETAIL OF GROOVE
FORMING
LETTERS AND FIGURES**

GENERAL NOTES

Rubbing will not be required except to remove fins and other irregularities.

Markers shall be placed on the North or East side of the road at the beginning and end of each section. They shall be placed so that the face will be turned toward the improvement and shall be clearly visible from the road. The markers shall be set in a vertical position in compacted soil and the bottom of the holes shall be rammed to provide a stable foundation. The holes shall be backfilled with approved materials in layers, rammed in such a manner that the bottom of the marker will not be moved from its correct position.

Before markers are made the Contractor shall be instructed by the Engineer what figures and letters are to be used.

Markers shall be constructed of Class SI concrete.

The contract unit price for SECTION MARKERS shall be payment in full for furnishing all materials and erecting the markers complete in place.

All dimensions are in millimeters (inches) unless otherwise shown.

Illinois Department of Transportation

APPROVED January 1, 2003
Daniel W. McDermott
 ENGINEER OF LOCAL ROADS AND STREETS

APPROVED January 1, 2003
Michael L. Hine
 ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED 1-1-97

DATE	REVISIONS
1-1-03	Deleted size B aggregate in 4th general note.
1-1-97	Renum. Standard B.L.R. 6-3.

SECTION MARKERS

STANDARD B.L.R. 6-5