

If you plan to submit a bid directly to the Department of Transportation

PREQUALIFICATION

Any contractor who desires to become pre-qualified to bid on work advertised by IDOT must submit the properly completed pre-qualification forms to the Bureau of Construction no later than 4:30 p.m. prevailing time twenty-one days prior to the letting of interest. This pre-qualification requirement applies to first time contractors, contractors renewing expired ratings, contractors maintaining continuous pre-qualification or contractors requesting revised ratings. To be eligible to bid, existing pre-qualification ratings must be effective through the date of letting.

REQUESTS FOR AUTHORIZATION TO BID

Contractors wanting to bid on items included in a particular letting must submit the properly completed "Request for Authorization to Bid/or Not For Bid Status" (BDE 124INT) and the ORIGINAL "Affidavit of Availability" (BC 57) to the proper office no later than 4:30 p.m. prevailing time, three (3) days prior to the letting date.

WHO CAN BID ?

Bids will be accepted from only those companies that request and receive written **Authorization to Bid** from IDOT's Central Bureau of Construction.

WHAT CONSTITUTES WRITTEN AUTHORIZATION TO BID?: When a prospective prime bidder submits a "Request for Authorization to Bid/or Not For Bid Status" (BDE 124INT) he/she must indicate at that time which items are being requested For Bidding purposes. Only those items requested For Bidding will be analyzed. After the request has been analyzed, the bidder will be issued an **Authorization to Bid or Not for Bid Report**, approved by the Central Bureau of Construction that indicates which items have been approved For Bidding. If **Authorization to Bid** cannot be approved, the **Authorization to Bid or Not for Bid Report** will indicate the reason for denial.

ABOUT AUTHORIZATION TO BID: Firms that have not received an authorization form within a reasonable time of complete and correct original document submittal should contact the department as to status. This is critical in the week before the letting. These documents must be received three days before the letting date. Firms unsure as to authorization status should call the Prequalification Section of the Bureau of Construction at the number listed at the end of these instructions.

ADDENDA AND REVISIONS: It is the contractor's responsibility to determine which, if any, addenda or revisions pertain to any project they may be bidding. Failure to incorporate all relevant addenda or revisions may cause the bid to be declared unacceptable.

Each addendum will be placed with the contract number. Addenda and revisions will also be placed on the Addendum/Revision Checklist and each subscription service subscriber will be notified by e-mail of each addendum and revision issued.

The Internet is the Department's primary way of doing business. The subscription server e-mails are an added courtesy the Department provides. It is suggested that bidders check IDOT's website at <http://www.dot.il.gov/desenv/delett.html> before submitting final bid information.

IDOT IS NOT RESPONSIBLE FOR ANY E-MAIL FAILURES.

Addenda Questions may be directed to the Contracts Office at (217)782-7806 or D&Econtracts@dot.il.gov

Technical Questions about downloading these files may be directed to Tim Garman (217)524-1642 or Timothy.Garman@illinois.gov.

WHAT MUST BE INCLUDED WHEN BIDS ARE SUBMITTED?: Bidders need not return the entire proposal when bids are submitted. That portion of the proposal that must be returned includes the following:

1. All documents from the Proposal Cover Sheet through the Proposal Bid Bond
2. Other special documentation and/or information that may be required by the contract special provisions

All proposal documents, including Proposal Guaranty Checks or Proposal Bid Bonds, should be stapled together to prevent loss when bids are processed by IDOT personnel.

ABOUT SUBMITTING BIDS: It is recommended that bidders deliver bids in person to insure they arrive at the proper location prior to the time specified for the receipt of bids. Any bid received at the place of letting after the time specified will not be accepted.

WHO SHOULD BE CALLED IF ASSISTANCE IS NEEDED?

Questions Regarding	Call
Prequalification and/or Authorization to Bid	217/782-3413
Preparation and submittal of bids	217/782-7806
Mailing of plans and proposals	217/782-7806

ADDENDUMS AND REVISIONS TO THE PROPOSAL FORMS

Planholders should verify that they have received and incorporated any addendum and/or revision prior to submitting their bid. Failure by the bidder to include an addendum or revision could result in a bid being rejected as irregular.

78

RETURN WITH BID

Proposal Submitted By
Name
Address
City

Letting April 23, 2010

BIDDERS NEED NOT RETURN THE ENTIRE PROPOSAL
(See instructions inside front cover)

NOTICE TO PROSPECTIVE BIDDERS
 This proposal can be used for bidding purposes by only those companies that request and receive written AUTHORIZATION TO BID from IDOT's Central Bureau of Construction.
 (SEE INSTRUCTIONS ON THE INSIDE OF COVER)

Notice To Bidders, Specifications, Proposal, Contract and Contract Bond



**Illinois Department
of Transportation**

Springfield, Illinois 62764

**Contract No. 64G07
WINNEBAGO County
Section (2,3)RS-3
District 2 Construction Funds
Route FAP 303**

PLEASE MARK THE APPROPRIATE BOX BELOW:

A Bid Bond is included.

A Cashier's Check or a Certified Check is included.

Plans Included
Herein

Prepared by	
Checked by	S

(Printed by authority of the State of Illinois)

INSTRUCTIONS

ABOUT IDOT PROPOSALS: All proposals issued by IDOT are potential bidding proposals. Each proposal contains all Certifications and Affidavits, a Proposal Signature Sheet and a Proposal Bid Bond required for Prime Contractors to submit a bid after written **Authorization to Bid** has been issued by IDOT's Central Bureau of Construction.

WHO CAN BID?: Bids will be accepted from only those companies that request and receive written **Authorization to Bid** from IDOT's Central Bureau of Construction. To request authorization, a potential bidder must complete and submit Part B of the Request for Authorization to Bid/or Not For Bid Status form (BDE 124 INT) and submit an original Affidavit of Availability (BC 57).

WHAT CONSTITUTES WRITTEN AUTHORIZATION TO BID?: When a prospective prime bidder submits a **"Authorization to Bid or Not for Bid"** form, he/she must indicate at that time which items are being requested For Bidding purposes. Only those items requested For Bidding will be analyzed. After the request has been analyzed, the bidder will be issued a **Authorization to Bid or Not for Bid Report**, approved by the Central Bureau of Construction, that indicates which items have been approved For Bidding. If **Authorization to Bid** cannot be approved, the **Authorization to Bid or Not for Bid Report** will indicate the reason for denial. If a contractor has requested to bid but has not received a **Authorization to Bid or Not for Bid Report**, they should contact the Central Bureau of Construction in advance of the letting date.

WHAT MUST BE INCLUDED WHEN BIDS ARE SUBMITTED?: Bidders need not return the entire proposal when bids are submitted. That portion of the proposal that must be returned includes the following:

1. All documents from the Proposal Cover Sheet through the Proposal Bid Bond
2. Other special documentation and/or information that may be required by the contract special provisions

All proposal documents, including Proposal Guaranty Checks or Proposal Bid Bonds, should be stapled together to prevent loss when bids are processed by IDOT personnel.

ABOUT SUBMITTING BIDS: It is recommended that bidders deliver bids in person to insure they arrive at the proper location prior to the time specified for the receipt of bids. Any bid received at the place of letting after the time specified will not be accepted.

WHO SHOULD BE CALLED IF ASSISTANCE IS NEEDED?

Questions Regarding	Call
Prequalification and/or Authorization to Bid	217/782-3413
Preparation and submittal of bids	217/782-7806

RETURN WITH BID



PROPOSAL

TO THE DEPARTMENT OF TRANSPORTATION

1. Proposal of _____

Taxpayer Identification Number (Mandatory) _____ a

for the improvement identified and advertised for bids in the Invitation for Bids as:

**Contract No. 64G07
WINNEBAGO County
Section (2,3)RS-3
Route FAP 303
District 2 Construction Funds**

1.79 miles of milling, patching and resurfacing on IL Rte. 251 from Snow Avenue to Windsor Road in Loves Park.

2. The undersigned bidder will furnish all labor, material and equipment to complete the above described project in a good and workmanlike manner as provided in the contract documents provided by the Department of Transportation. This proposal will become part of the contract and the terms and conditions contained in the contract documents shall govern performance and payments.

RETURN WITH BID

3. **ASSURANCE OF EXAMINATION AND INSPECTION/WAIVER.** The undersigned further declares that he/she has carefully examined the proposal, plans, specifications, form of contract and contract bond, and special provisions, and that he/she has inspected in detail the site of the proposed work, and that he/she has familiarized themselves with all of the local conditions affecting the contract and the detailed requirements of construction, and understands that in making this proposal he/she waives all right to plead any misunderstanding regarding the same.
4. **EXECUTION OF CONTRACT AND CONTRACT BOND.** The undersigned further agrees to execute a contract for this work and present the same to the department within fifteen (15) days after the contract has been mailed to him/her. The undersigned further agrees that he/she and his/her surety will execute and present within fifteen (15) days after the contract has been mailed to him/her contract bond satisfactory to and in the form prescribed by the Department of Transportation, in the penal sum of the full amount of the contract, guaranteeing the faithful performance of the work in accordance with the terms of the contract.
5. **PROPOSAL GUARANTY.** Accompanying this proposal is either a bid bond on the department form, executed by a corporate surety company satisfactory to the department, or a proposal guaranty check consisting of a bank cashier's check or a properly certified check for not less than 5 per cent of the amount bid or for the amount specified in the following schedule:

<u>Amount of Bid</u>		<u>Proposal Guaranty</u>	<u>Amount of Bid</u>		<u>Proposal Guaranty</u>	
Up to	\$5,000	\$150	\$2,000,000	to	\$3,000,000	\$100,000
\$5,000	to \$10,000	\$300	\$3,000,000	to	\$5,000,000	\$150,000
\$10,000	to \$50,000	\$1,000	\$5,000,000	to	\$7,500,000	\$250,000
\$50,000	to \$100,000	\$3,000	\$7,500,000	to	\$10,000,000	\$400,000
\$100,000	to \$150,000	\$5,000	\$10,000,000	to	\$15,000,000	\$500,000
\$150,000	to \$250,000	\$7,500	\$15,000,000	to	\$20,000,000	\$600,000
\$250,000	to \$500,000	\$12,500	\$20,000,000	to	\$25,000,000	\$700,000
\$500,000	to \$1,000,000	\$25,000	\$25,000,000	to	\$30,000,000	\$800,000
\$1,000,000	to \$1,500,000	\$50,000	\$30,000,000	to	\$35,000,000	\$900,000
\$1,500,000	to \$2,000,000	\$75,000	over		\$35,000,000	\$1,000,000

Bank cashier's checks or properly certified checks accompanying proposals shall be made payable to the Treasurer, State of Illinois, when the state is awarding authority; the county treasurer, when a county is the awarding authority; or the city, village, or town treasurer, when a city, village, or town is the awarding authority.

If a combination bid is submitted, the proposal guaranties which accompany the individual proposals making up the combination will be considered as also covering the combination bid.

The amount of the proposal guaranty check is _____ \$(_____). If this proposal is accepted and the undersigned shall fail to execute a contract bond as required herein, it is hereby agreed that the amount of the proposal guaranty shall become the property of the State of Illinois, and shall be considered as payment of damages due to delay and other causes suffered by the State because of the failure to execute said contract and contract bond; otherwise, the bid bond shall become void or the proposal guaranty check shall be returned to the undersigned.

Attach Cashier's Check or Certified Check Here

In the event that one proposal guaranty check is intended to cover two or more proposals, the amount must be equal to the sum of the proposal guaranties which would be required for each individual proposal. If the guaranty check is placed in another proposal, state below where it may be found.

The proposal guaranty check will be found in the proposal for:

Item _____

Section No. _____

County _____

Mark the proposal cover sheet as to the type of proposal guaranty submitted.

RETURN WITH BID

6. **COMBINATION BIDS.** The undersigned further agrees that if awarded the contract for the sections contained in the following combination, he/she will perform the work in accordance with the requirements of each individual proposal comprising the combination bid specified in the schedule below, and that the combination bid shall be prorated against each section in proportion to the bid submitted for the same. If an error is found to exist in the gross sum bid for one or more of the individual sections included in a combination, the combination bid shall be corrected as provided in the specifications.

When a combination bid is submitted, the schedule below must be completed in each proposal comprising the combination.

If alternate bids are submitted for one or more of the sections comprising the combination, a combination bid must be submitted for each alternate.

Schedule of Combination Bids

Combination No.	Sections Included in Combination	Combination Bid	
		Dollars	Cents

7. **SCHEDULE OF PRICES.** The undersigned bidder submits herewith, in accordance with the rules and instructions, a schedule of prices for the items of work for which bids are sought. The unit prices bid are in U.S. dollars and cents, and all extensions and summations have been made. The bidder understands that the quantities appearing in the bid schedule are approximate and are provided for the purpose of obtaining a gross sum for the comparison of bids. If there is an error in the extension of the unit prices, the unit prices shall govern. Payment to the contractor awarded the contract will be made only for actual quantities of work performed and accepted or materials furnished according to the contract. The scheduled quantities of work to be done and materials to be furnished may be increased, decreased or omitted as provided elsewhere in the contract.

8. **CERTIFICATE OF AUTHORITY.** The undersigned bidder, if a business organized under the laws of another State, assures the Department that it will furnish a copy of its certificate of authority to do business in the State of Illinois with the return of the executed contract and bond. Failure to furnish the certificate within the time provided for execution of an awarded contract may be cause for cancellation of the award and forfeiture of the proposal guaranty to the State.

ILLINOIS DEPARTMENT OF TRANSPORTATION
 SCHEDULE OF PRICES
 CONTRACT
 NUMBER - 64G07

State Job # - C-92-093-10
 PPS NBR - 2-29696-0100
 County Name - WINNEBAGO- -
 Code - 201 - -
 District - 2 - -
 Section Number - (2,3)RS-3

Project Number

Route
 FAP 303

Item Number	Pay Item Description	Unit of Measure	Quantity	x	Unit Price	=	Total Price
Z0013798	CONSTRUCTION LAYOUT	L SUM	1.000				
Z0028415	GEOTECHNICAL REINF	SQ YD	76.000				
Z0028700	GRAN SUBGRADE REPL	CU YD	13.000				
35101400	AGG BASE CSE B	TON	546.000				
40600200	BIT MATLS PR CT	TON	47.800				
40600300	AGG PR CT	TON	105.000				
40600535	LEV BIND HM N70	TON	28.000				
40600837	P LEV BIND MM N70	TON	3,676.000				
40600895	CONSTRUC TEST STRIP	EACH	1.000				
40600990	TEMPORARY RAMP	SQ YD	495.000				
40601005	HMA REPL OVER PATCH	TON	156.000				
40603310	HMA SC "C" N50	TON	2,002.000				
40603565	P HMA SC "E" N70	TON	5,514.000				
40800050	INCIDENTAL HMA SURF	TON	628.000				
44000158	HMA SURF REM 2 1/4	SQ YD	90,364.000				

ILLINOIS DEPARTMENT OF TRANSPORTATION
 SCHEDULE OF PRICES
 CONTRACT
 NUMBER -

64G07

State Job # - C-92-093-10
 PPS NBR - 2-29696-0100
 County Name - WINNEBAGO- -
 Code - 201 - -
 District - 2 - -
 Section Number - (2,3)RS-3

Project Number

Route
 FAP 303

Item Number	Pay Item Description	Unit of Measure	Quantity	x	Unit Price	=	Total Price
44002216	HMA RM OV PATCH 4	SQ YD	695.000				
44003100	MEDIAN REMOVAL	SQ FT	21,595.000				
44200144	PAVT PATCH T2 12	SQ YD	26.000				
44200148	PAVT PATCH T3 12	SQ YD	16.000				
44200150	PAVT PATCH T4 12	SQ YD	34.000				
44300200	STRIP REF CR CON TR	FOOT	34,774.000				
60255500	MAN ADJUST	EACH	70.000				
60255800	MAN ADJ NEW T1F CL	EACH	3.000				
60262510	INLET ADJ NEW F&G SPL	EACH	22.000				
60265700	VV ADJUST	EACH	43.000				
60265800	VV ADJUST SPL	EACH	2.000				
60603800	COMB CC&G TB6.12	FOOT	48.000				
60605000	COMB CC&G TB6.24	FOOT	672.000				
60618300	CONC MEDIAN SURF 4	SQ FT	4,121.000				
60619123	CONC MED TSB-6 MOD	SQ FT	7,556.000				

ILLINOIS DEPARTMENT OF TRANSPORTATION
 SCHEDULE OF PRICES
 CONTRACT
 NUMBER -

64G07

State Job # - C-92-093-10
 PPS NBR - 2-29696-0100
 County Name - WINNEBAGO- -
 Code - 201 - -
 District - 2 - -
 Section Number - (2,3)RS-3

Project Number

Route
 FAP 303

Item Number	Pay Item Description	Unit of Measure	Quantity	x	Unit Price	=	Total Price
60620000	CONC MED TSB6.24	SQ FT	8,292.000				
67000400	ENGR FIELD OFFICE A	CAL MO	4.000				
67100100	MOBILIZATION	L SUM	1.000				
70102625	TR CONT & PROT 701606	L SUM	1.000				
70102630	TR CONT & PROT 701601	L SUM	1.000				
70102635	TR CONT & PROT 701701	L SUM	1.000				
70103815	TR CONT SURVEILLANCE	CAL DA	16.000				
70300100	SHORT-TERM PAVT MKING	FOOT	7,864.000				
70301000	WORK ZONE PAVT MK REM	SQ FT	874.000				
78000100	THPL PVT MK LTR & SYM	SQ FT	1,726.000				
78000200	THPL PVT MK LINE 4	FOOT	42,682.000				
78000400	THPL PVT MK LINE 6	FOOT	3,926.000				
78000500	THPL PVT MK LINE 8	FOOT	5,955.000				
78000600	THPL PVT MK LINE 12	FOOT	184.000				
78000650	THPL PVT MK LINE 24	FOOT	1,135.000				

CONTRACT NUMBER

64G07

THIS IS THE TOTAL BID

\$ _____

NOTES:

- 1. Each PAY ITEM should have a UNIT PRICE and a TOTAL PRICE.**
- 2. The UNIT PRICE shall govern if no TOTAL PRICE is shown or if there is a discrepancy between the product of the UNIT PRICE multiplied by the QUANTITY.**
- 3. If a UNIT PRICE is omitted, the TOTAL PRICE will be divided by the QUANTITY in order to establish a UNIT PRICE.**
- 4. A bid may be declared UNACCEPTABLE if neither a unit price nor a total price is shown.**

RETURN WITH BID

STATE REQUIRED ETHICAL STANDARDS GOVERNING CONTRACT PROCUREMENT: ASSURANCES, CERTIFICATIONS AND DISCLOSURES

I. GENERAL

A. Article 50 of the Illinois Procurement Code establishes the duty of all State chief procurement officers, State purchasing officers, and their designees to maximize the value of the expenditure of public moneys in procuring goods, services, and contracts for the State of Illinois and to act in a manner that maintains the integrity and public trust of State government. In discharging this duty, they are charged by law to use all available information, reasonable efforts, and reasonable actions to protect, safeguard, and maintain the procurement process of the State of Illinois.

B. In order to comply with the provisions of Article 50 and to carry out the duty established therein, all bidders are to adhere to ethical standards established for the procurement process, and to make such assurances, disclosures and certifications required by law. By execution of the Proposal Signature Sheet, the bidder indicates that each of the mandated assurances has been read and understood, that each certification is made and understood, and that each disclosure requirement has been understood and completed.

C. In addition to all other remedies provided by law, failure to comply with any assurance, failure to make any disclosure or the making of a false certification shall be grounds for termination of the contract and the suspension or debarment of the bidder.

II. ASSURANCES

A. The assurances hereinafter made by the bidder are each a material representation of fact upon which reliance is placed should the Department enter into the contract with the bidder. The Department may terminate the contract if it is later determined that the bidder rendered a false or erroneous assurance, and the surety providing the performance bond shall be responsible for the completion of the contract.

B. Felons

1. The Illinois Procurement Code provides:

Section 50-10. Felons. Unless otherwise provided, no person or business convicted of a felony shall do business with the State of Illinois or any state agency from the date of conviction until 5 years after the date of completion of the sentence for that felony, unless no person held responsible by a prosecutorial office for the facts upon which the conviction was based continues to have any involvement with the business.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-10.

C. Conflicts of Interest

1. The Illinois Procurement Code provides in pertinent part:

Section 50-13. Conflicts of Interest.

(a) Prohibition. It is unlawful for any person holding an elective office in this State, holding a seat in the General Assembly, or appointed to or employed in any of the offices or agencies of state government and who receives compensation for such employment in excess of 60% of the salary of the Governor of the State of Illinois, or who is an officer or employee of the Capital Development Board or the Illinois Toll Highway Authority, or who is the spouse or minor child of any such person to have or acquire any contract, or any direct pecuniary interest in any contract therein, whether for stationery, printing, paper, or any services, materials, or supplies, that will be wholly or partially satisfied by the payment of funds appropriated by the General Assembly of the State of Illinois or in any contract of the Capital Development Board or the Illinois Toll Highway authority.

(b) Interests. It is unlawful for any firm, partnership, association or corporation, in which any person listed in subsection (a) is entitled to receive (i) more than 7 1/2% of the total distributable income or (ii) an amount in excess of the salary of the Governor, to have or acquire any such contract or direct pecuniary interest therein.

(c) Combined interests. It is unlawful for any firm, partnership, association, or corporation, in which any person listed in subsection (a) together with his or her spouse or minor children is entitled to receive (i) more than 15%, in the aggregate, of the total distributable income or (ii) an amount in excess of 2 times the salary of the Governor, to have or acquire any such contract or direct pecuniary interest therein.

(d) Securities. Nothing in this Section invalidates the provisions of any bond or other security previously offered or to be offered for sale or sold by or for the State of Illinois.

(e) Prior interests. This Section does not affect the validity of any contract made between the State and an officer or employee of the State or member of the General Assembly, his or her spouse, minor child or any combination of those persons if that contract was in existence before his or her election or employment as an officer, member, or employee. The contract is voidable, however, if it cannot be completed within 365 days after the officer, member, or employee takes office or is employed.

The current salary of the Governor is \$177,412.00. Sixty percent of the salary is \$106,447.20.

RETURN WITH BID

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-13, or that an effective exemption has been issued by the Board of Ethics to any individual subject to the Section 50-13 prohibitions pursuant to the provisions of Section 50-20 of the Code and Executive Order Number 3 (1998). Information concerning the exemption process is available from the Department upon request.

D. Negotiations

1. The Illinois Procurement Code provides in pertinent part:

Section 50-15. Negotiations.

(a) It is unlawful for any person employed in or on a continual contractual relationship with any of the offices or agencies of State government to participate in contract negotiations on behalf of that office or agency with any firm, partnership, association, or corporation with whom that person has a contract for future employment or is negotiating concerning possible future employment.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-15, and that the bidder has no knowledge of any facts relevant to the kinds of acts prohibited therein.

E. Inducements

1. The Illinois Procurement Code provides:

Section 50-25. Inducement. Any person who offers or pays any money or other valuable thing to any person to induce him or her not to bid for a State contract or as recompense for not having bid on a State contract is guilty of a Class 4 felony. Any person who accepts any money or other valuable thing for not bidding for a State contract or who withholds a bid in consideration of the promise for the payment of money or other valuable thing is guilty of a Class 4 felony.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-25, and that the bidder has no knowledge of any facts relevant to the kinds of acts prohibited therein.

F. Revolving Door Prohibition

1. The Illinois Procurement Code provides:

Section 50-30. Revolving door prohibition. Chief procurement officers, associate procurement officers, State purchasing officers, their designees whose principal duties are directly related to State procurement, and executive officers confirmed by the Senate are expressly prohibited for a period of 2 years after terminating an affected position from engaging in any procurement activity relating to the State agency most recently employing them in an affected position for a period of at least 6 months. The prohibition includes, but is not limited to: lobbying the procurement process; specifying; bidding; proposing bid, proposal, or contract documents; on their own behalf or on behalf of any firm, partnership, association, or corporation. This Section applies only to persons who terminate an affected position on or after January 15, 1999.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-30, and that the bidder has no knowledge of any facts relevant to the kinds of acts prohibited therein.

G. Reporting Anticompetitive Practices

1. The Illinois Procurement Code provides:

Section 50-40. Reporting anticompetitive practices. When, for any reason, any vendor, bidder, contractor, chief procurement officer, State purchasing officer, designee, elected official, or State employee suspects collusion or other anticompetitive practice among any bidders, offerors, contractors, proposers, or employees of the State, a notice of the relevant facts shall be transmitted to the Attorney General and the chief procurement officer.

2. The bidder assures the Department that it has not failed to report any relevant facts concerning the practices addressed in Section 50-40 which may involve the contract for which the bid is submitted.

H. Confidentiality

1. The Illinois Procurement Code provides:

Section 50-45. Confidentiality. Any chief procurement officer, State purchasing officer, designee, or executive officer who willfully uses or allows the use of specifications, competitive bid documents, proprietary competitive information, proposals, contracts, or selection information to compromise the fairness or integrity of the procurement, bidding, or contract process shall be subject to immediate dismissal, regardless of the Personnel code, any contract, or any collective bargaining agreement, and may in addition be subject to criminal prosecution.

2. The bidder assures the Department that it has no knowledge of any fact relevant to the practices addressed in Section 50-45 which may involve the contract for which the bid is submitted.

RETURN WITH BID

I. Insider Information

1. The Illinois Procurement Act provides:

Section 50-50. Insider information. It is unlawful for any current or former elected or appointed State official or State employee to knowingly use confidential information available only by virtue of that office or employment for actual or anticipated gain for themselves or another person.

2. The bidder assures the Department that it has no knowledge of any facts relevant to the practices addressed in Section 50-50 which may involve the contract for which the bid is submitted.

III. CERTIFICATIONS

A. The certifications hereinafter made by the bidder are each a material representation of fact upon which reliance is placed should the Department enter into the contract with the bidder. The Department may terminate the contract if it is later determined that the bidder rendered a false or erroneous certification, and the surety providing the performance bond shall be responsible for completion of the contract.

B. Bribery

1. The Illinois Procurement Code provides:

Section 50-5. Bribery.

(a) Prohibition. No person or business shall be awarded a contract or subcontract under this Code who:

(1) has been convicted under the laws of Illinois or any other state of bribery or attempting to bribe an officer or employee of the State of Illinois or any other state in that officer's or employee's official capacity; or

(2) has made an admission of guilt of that conduct that is a matter of record but has not been prosecuted for that conduct.

(b) Businesses. No business shall be barred from contracting with any unit of State or local government as a result of a conviction under this Section of any employee or agent of the business if the employee or agent is no longer employed by the business and:

(1) the business has been finally adjudicated not guilty; or

(2) the business demonstrates to the governmental entity with which it seeks to contract, and that entity finds that the commission of the offense was not authorized, requested, commanded, or performed by a director, officer, or high managerial agent on behalf of the business as provided in paragraph (2) of subsection (a) of Section 5-4 of the Criminal Code of 1961.

(c) Conduct on behalf of business. For purposes of this Section, when an official, agent, or employee of a business committed the bribery or attempted bribery on behalf of the business and in accordance with the direction or authorization of a responsible official of the business, the business shall be chargeable with the conduct.

(d) Certification. Every bid submitted to and contract executed by the State shall contain a certification by the contractor that the contractor is not barred from being awarded a contract or subcontract under this Section. A contractor who makes a false statement, material to the certification, commits a Class 3 felony.

2. The bidder certifies that it is not barred from being awarded a contract under Section 50.5.

C. Educational Loan

1. Section 3 of the Educational Loan Default Act provides:

§ 3. No State agency shall contract with an individual for goods or services if that individual is in default, as defined in Section 2 of this Act, on an educational loan. Any contract used by any State agency shall include a statement certifying that the individual is not in default on an educational loan as provided in this Section.

2. The bidder, if an individual as opposed to a corporation, partnership or other form of business organization, certifies that the bidder is not in default on an educational loan as provided in Section 3 of the Act.

D. Bid-Rigging/Bid Rotating

1. Section 33E-11 of the Criminal Code of 1961 provides:

§ 33E-11. (a) Every bid submitted to and public contract executed pursuant to such bid by the State or a unit of local government shall contain a certification by the prime contractor that the prime contractor is not barred from contracting with any unit of State or local government as a result of a violation of either Section 33E-3 or 33E-4 of this Article. The State and units of local government shall provide the appropriate forms for such certification.

RETURN WITH BID

(b) A contractor who makes a false statement, material to the certification, commits a Class 3 felony.

A violation of Section 33E-3 would be represented by a conviction of the crime of bid-rigging which, in addition to Class 3 felony sentencing, provides that any person convicted of this offense or any similar offense of any state or the United States which contains the same elements as this offense shall be barred for 5 years from the date of conviction from contracting with any unit of State or local government. No corporation shall be barred from contracting with any unit of State or local government as a result of a conviction under this Section of any employee or agent of such corporation if the employee so convicted is no longer employed by the corporation and: (1) it has been finally adjudicated not guilty or (2) if it demonstrates to the governmental entity with which it seeks to contract and that entity finds that the commission of the offense was neither authorized, requested, commanded, nor performed by a director, officer or a high managerial agent in behalf of the corporation.

A violation of Section 33E-4 would be represented by a conviction of the crime of bid-rotating which, in addition to Class 2 felony sentencing, provides that any person convicted of this offense or any similar offense of any state or the United States which contains the same elements as this offense shall be permanently barred from contracting with any unit of State or local government. No corporation shall be barred from contracting with any unit of State or local government as a result of a conviction under this Section of any employee or agent of such corporation if the employee so convicted is no longer employed by the corporation and: (1) it has been finally adjudicated not guilty or (2) if it demonstrates to the governmental entity with which it seeks to contract and that entity finds that the commission of the offense was neither authorized, requested, commanded, nor performed by a director, officer or a high managerial agent in behalf of the corporation.

2. The bidder certifies that it is not barred from contracting with the Department by reason of a violation of either Section 33E-3 or Section 33E-4.

E. International Anti-Boycott

1. Section 5 of the International Anti-Boycott Certification Act provides:

§ 5. State contracts. Every contract entered into by the State of Illinois for the manufacture, furnishing, or purchasing of supplies, material, or equipment or for the furnishing of work, labor, or services, in an amount exceeding the threshold for small purchases according to the purchasing laws of this State or \$10,000.00, whichever is less, shall contain certification, as a material condition of the contract, by which the contractor agrees that neither the contractor nor any substantially-owned affiliated company is participating or shall participate in an international boycott in violation of the provisions of the U.S. Export Administration Act of 1979 or the regulations of the U.S. Department of Commerce promulgated under that Act.

2. The bidder makes the certification set forth in Section 5 of the Act.

F. Drug Free Workplace

1. The Illinois "Drug Free Workplace Act" applies to this contract and it is necessary to comply with the provisions of the "Act" if the contractor is a corporation, partnership, or other entity (including a sole proprietorship) which has 25 or more employees.

2. The bidder certifies that if awarded a contract in excess of \$5,000 it will provide a drug free workplace by:

(a) Publishing a statement notifying employees that the unlawful manufacture, distribution, dispensation, possession or use of a controlled substance, including cannabis, is prohibited in the contractor's workplace; specifying the actions that will be taken against employees for violations of such prohibition; and notifying the employee that, as a condition of employment on such contract, the employee shall abide by the terms of the statement, and notify the employer of any criminal drug statute conviction for a violation occurring in the workplace no later than five (5) days after such conviction.

(b) Establishing a drug free awareness program to inform employees about the dangers of drug abuse in the workplace; the contractor's policy of maintaining a drug free workplace; any available drug counseling, rehabilitation, and employee assistance programs; and the penalties that may be imposed upon employees for drug violations.

(c) Providing a copy of the statement required by subparagraph (1) to each employee engaged in the performance of the contract and to post the statement in a prominent place in the workplace.

(d) Notifying the Department within ten (10) days after receiving notice from an employee or otherwise receiving actual notice of the conviction of an employee for a violation of any criminal drug statute occurring in the workplace.

(e) Imposing or requiring, within 30 days after receiving notice from an employee of a conviction or actual notice of such a conviction, an appropriate personnel action, up to and including termination, or the satisfactory participation in a drug abuse assistance or rehabilitation program approved by a federal, state or local health, law enforcement or other appropriate agency.

(f) Assisting employees in selecting a course of action in the event drug counseling, treatment, and rehabilitation is required and indicating that a trained referral team is in place.

(g) Making a good faith effort to continue to maintain a drug free workplace through implementation of the actions and efforts stated in this certification.

RETURN WITH BID

G. Debt Delinquency

1. The Illinois Procurement Code provides:

Section 50-11 and 50-12. Debt Delinquency.

The contractor or bidder certifies that it, or any affiliate, is not barred from being awarded a contract under 30 ILCS 500. Section 50-11 prohibits a person from entering into a contract with a State agency if it knows or should know that it, or any affiliate, is delinquent in the payment of any debt to the State as defined by the Debt Collection Board. Section 50-12 prohibits a person from entering into a contract with a State agency if it, or any affiliate, has failed to collect and remit Illinois Use Tax on all sales of tangible personal property into the State of Illinois in accordance with the provisions of the Illinois Use Tax Act. The contractor further acknowledges that the contracting State agency may declare the contract void if this certification is false or if the contractor, or any affiliate, is determined to be delinquent in the payment of any debt to the State during the term of the contract.

H. Sarbanes-Oxley Act of 2002

1. The Illinois Procurement Code provides:

Section 50-60(c).

The contractor certifies in accordance with 30 ILCS 500/50-10.5 that no officer, director, partner or other managerial agent of the contracting business has been convicted of a felony under the Sarbanes-Oxley Act of 2002 or a Class 3 or Class 2 felony under the Illinois Securities Law of 1953 for a period of five years prior to the date of the bid or contract. The contractor acknowledges that the contracting agency shall declare the contract void if this certification is false.

I. Addenda

The contractor or bidder certifies that all relevant addenda have been incorporated in to this contract. Failure to do so may cause the bid to be declared unacceptable.

J. Section 42 of the Environmental Protection Act

The contractor certifies in accordance with 30 ILCS 500/50-12 that the bidder or contractor is not barred from being awarded a contract under this Section which prohibits the bidding on or entering into contracts with the State of Illinois or a State agency by a person or business found by a court or the Pollution Control Board to have committed a willful or knowing violation of Section 42 of the Environmental Protection Act for a period of five years from the date of the order. The contractor acknowledges that the contracting agency may declare the contract void if this certification is false.

K. Apprenticeship and Training Certification (Does not apply to federal aid projects)

In accordance with the provisions of Section 30-22 (6) of the Illinois Procurement Code, the bidder certifies that it is a participant, either as an individual or as part of a group program, in the approved apprenticeship and training programs applicable to each type of work or craft that the bidder will perform with its own forces. The bidder further certifies for work that will be performed by subcontract that each of its subcontractors submitted for approval either (a) is, at the time of such bid, participating in an approved, applicable apprenticeship and training program; or (b) will, prior to commencement of performance of work pursuant to this contract, begin participation in an approved apprenticeship and training program applicable to the work of the subcontract. The Department, at any time before or after award, may require the production of a copy of each applicable Certificate of Registration issued by the United States Department of Labor evidencing such participation by the contractor and any or all of its subcontractors. Applicable apprenticeship and training programs are those that have been approved and registered with the United States Department of Labor. The bidder shall list in the space below, the official name of the program sponsor holding the Certificate of Registration for all of the types of work or crafts in which the bidder is a participant and that will be performed with the bidder's forces. Types of work or craft work that will be subcontracted shall be included and listed as subcontract work. The list shall also indicate any type of work or craft job category that does not have an applicable apprenticeship or training program. **The bidder is responsible for making a complete report and shall make certain that each type of work or craft job category that will be utilized on the project as reported on the Construction Employee Workforce Projection (Form BC-1256) and returned with the bid is accounted for and listed.**

The requirements of this certification and disclosure are a material part of the contract, and the contractor shall require this certification provision to be included in all approved subcontracts. In order to fulfill this requirement, it shall not be necessary that an applicable program sponsor be currently taking or that it will take applications for apprenticeship, training or employment during the performance of the work of this contract.

L. Executive Order Number 1 (2007) Regarding Lobbying on Government Procurements

The bidder hereby warrants and certifies that they have complied and will comply with the requirements set forth in this Order. The requirements of this warrant and certification are a material part of the contract, and the contractor shall require this warrant and certification provision to be included in all approved subcontracts.

RETURN WITH BID

M. Disclosure of Business Operations in Iran

Section 50-36 of the Illinois Procurement Code, 30ILCS 500/50-36 provides that each bid, offer, or proposal submitted for a State contract shall include a disclosure of whether or not the Company acting as the bidder, offeror, or proposing entity, or any of its corporate parents or subsidiaries, within the 24 months before submission of the bid, offer, or proposal had business operations that involved contracts with or provision of supplies or services to the Government of Iran, companies in which the Government of Iran has any direct or indirect equity share, consortiums or projects commissioned by the Government of Iran, or companies involved in consortiums or projects commissioned by the Government of Iran and either of the following conditions apply:

- (1) More than 10% of the Company's revenues produced in or assets located in Iran involve oil-related activities or mineral-extraction activities; less than 75% of the Company's revenues produced in or assets located in Iran involve contracts with or provision of oil-related or mineral-extraction products or services to the Government of Iran or a project or consortium created exclusively by that government; and the Company has failed to take substantial action.
- (2) The Company has, on or after August 5, 1996, made an investment of \$20 million or more, or any combination of investments of at least \$10 million each that in the aggregate equals or exceeds \$20 million in any 12-month period, which directly or significantly contributes to the enhancement of Iran's ability to develop petroleum resources of Iran.

The terms "Business operations", "Company", "Mineral-extraction activities", "Oil-related activities", "Petroleum resources", and "Substantial action" are all defined in the Code.

Failure to make the disclosure required by the Code shall cause the bid, offer or proposal to be considered not responsive. The disclosure will be considered when evaluating the bid, offer, or proposal or awarding the contract. The name of each Company disclosed as doing business or having done business in Iran will be provided to the State Comptroller.

Check the appropriate statement:

Company has no business operations in Iran to disclose.

Company has business operations in Iran as disclosed the attached document.

N. Political Contributions and Registration with the State Board of Elections

Sections 20-160 and 50-37 of the Illinois Procurement Code regulate political contributions from business entities and any affiliated entities or affiliated persons bidding on or contracting with the state. Generally under Section 50-37, any business entity, and any affiliated entity or affiliated person of the business entity, whose current year contracts with all state agencies exceed an awarded value of \$50,000, are prohibited from making any contributions to any political committees established to promote the candidacy of the officeholder responsible for the awarding of the contracts or any other declared candidate for that office for the duration of the term of office of the incumbent officeholder or a period 2 years after the termination of the contract, whichever is longer. Any business entity and affiliated entities or affiliated persons whose state contracts in the current year do not exceed an awarded value of \$50,000, but whose aggregate pending bids and proposals on state contracts exceed \$50,000, either alone or in combination with contracts not exceeding \$50,000, are prohibited from making any political contributions to any political committee established to promote the candidacy of the officeholder responsible for awarding the pending contract during the period beginning on the date the invitation for bids or request for proposals is issued and ending on the day after the date of award or selection if the entity was not awarded or selected. Section 20-160 requires certification of registration of affected business entities in accordance with procedures found in Section 9-35 of The Election Code.

By submission of a bid, the contractor business entity acknowledges and agrees that it has read and understands Sections 20-160 and 50-37 of the Illinois Procurement Code, and that it makes the following certification:

The undersigned business entity certifies that it has registered as a business with the State Board of Elections and acknowledges a continuing duty to update the registration in accordance with the above referenced statutes. A copy of the certificate of registration shall be submitted with the bid. The bidder is cautioned that the Department will not award a contract without submission of the certificate of registration.

These requirements and compliance with the above referenced statutory sections are a material part of the contract, and any breach thereof shall be cause to void the contract under Section 50-60 of the Illinois Procurement Code. This provision does not apply to Federal-aid contracts.

TO BE RETURNED WITH BID

IV. DISCLOSURES

A. The disclosures hereinafter made by the bidder are each a material representation of fact upon which reliance is placed should the Department enter into the contract with the bidder. The Department may terminate the contract if it is later determined that the bidder rendered a false or erroneous disclosure, and the surety providing the performance bond shall be responsible for completion of the contract.

B. Financial Interests and Conflicts of Interest

1. Section 50-35 of the Illinois Procurement Code provides that all bids of more than \$10,000 shall be accompanied by disclosure of the financial interests of the bidder. This disclosed information for the successful bidder, will be maintained as public information subject to release by request pursuant to the Freedom of Information Act.

The financial interests to be disclosed shall include ownership or distributive income share that is in excess of 5%, or an amount greater than 60% of the annual salary of the Governor, of the bidding entity or its parent entity, whichever is less, unless the contractor or bidder is a publicly traded entity subject to Federal 10K reporting, in which case it may submit its 10K disclosure in place of the prescribed disclosure. If a bidder is a privately held entity that is exempt from Federal 10K reporting, but has more than 400 shareholders, it may submit the information that Federal 10K companies are required to report, and list the names of any person or entity holding any ownership share that is in excess of 5%. The disclosure shall include the names, addresses, and dollar or proportionate share of ownership of each person making the disclosure, their instrument of ownership or beneficial relationship, and notice of any potential conflict of interest resulting from the current ownership or beneficial interest of each person making the disclosure having any of the relationships identified in Section 50-35 and on the disclosure form.

In addition, all disclosures shall indicate any other current or pending contracts, proposals, leases, or other ongoing procurement relationships the bidding entity has with any other unit of state government and shall clearly identify the unit and the contract, proposal, lease, or other relationship.

2. Disclosure Forms. Disclosure Form A is attached for use concerning the individuals meeting the above ownership or distributive share requirements. Subject individuals should be covered each by one form. In addition, a second form (Disclosure Form B) provides for the disclosure of current or pending procurement relationships with other (non-IDOT) state agencies. **The forms must be included with each bid or incorporated by reference.**

C. Disclosure Form Instructions

Form A: For bidders that have previously submitted the information requested in Form A

The Department has retained the Form A disclosures submitted by all bidders responding to these requirements for the April 24, 1998 or any subsequent letting conducted by the Department. The bidder has the option of submitting the information again or the bidder may check the following certification statement indicating that the information previously submitted by the bidder is, as of the date of submission, current and accurate. Before checking this certification, the bidder should carefully review its prior submissions to ensure the Certification is correct. If the Bidder checks the Certification, the Bidder should proceed to Form B instructions.

CERTIFICATION STATEMENT

I have determined that the Form A disclosure information previously submitted is current and accurate, and all forms are hereby incorporated by reference in this bid. Any necessary additional forms or amendments to previously submitted forms are attached to this bid.

(Bidding Company)



Signature of Authorized Representative

Date

Form A: For bidders who have NOT previously submitted the information requested in Form A

If the bidder is a publicly traded entity subject to Federal 10K reporting, the 10K Report may be submitted to meet the requirements of Form A. If a bidder is a privately held entity that is exempt from Federal 10K reporting, but has more than 400 shareholders, it may submit the information that Federal 10K companies are required to report, and list the names of any person or entity holding any ownership share that is in excess of 5%. If a bidder is not subject to Federal 10K reporting, the bidder must determine if any individuals are required by law to complete a financial disclosure form. To do this, the bidder should answer each of the following questions. A "YES" answer indicates Form A must be completed. If the answer to each of the following questions is "NO", then the NOT APPLICABLE STATEMENT on the second page of Form A must be signed and dated by a person that is authorized to execute contracts for the bidding company. Note: These questions are for assistance only and are not required to be completed.

1. Does anyone in your organization have a direct or beneficial ownership share of greater than 5% of the bidding entity or parent entity? YES ___ NO ___
2. Does anyone in your organization have a direct or beneficial ownership share of less than 5%, but which has a value greater than \$106,447.20? YES ___ NO ___
3. Does anyone in your organization receive more than \$106,447.20 of the bidding entity's or parent entity's distributive income? (Note: Distributive income is, for these purposes, any type of distribution of profits. An annual salary is not distributive income.) YES ___ NO ___
4. Does anyone in your organization receive greater than 5% of the bidding entity's or parent entity's total distributive income, but which is less than \$106,447.20? YES ___ NO ___

(Note: Only one set of forms needs to be completed per person per bid even if a specific individual would require a yes answer to more than one question.)

A "YES" answer to any of these questions requires the completion of Form A. The bidder must determine each individual in the bidding entity or the bidding entity's parent company that would cause the questions to be answered "Yes". Each form must be signed and dated by a person that is authorized to execute contracts for your organization. **Photocopied or stamped signatures are not acceptable.** The person signing can be, but does not have to be, the person for which the form is being completed. The bidder is responsible for the accuracy of any information provided.

If the answer to each of the above questions is "NO", then the NOT APPLICABLE STATEMENT on page 2 of Form A must be signed and dated by a person that is authorized to execute contracts for your company.

Form B: Identifying Other Contracts & Procurement Related Information Disclosure Form B must be completed for each bid submitted by the bidding entity. Note: *Checking the NOT APPLICABLE STATEMENT on Form A does not allow the bidder to ignore Form B. Form B must be completed, checked, and dated or the bidder may be considered nonresponsive and the bid will not be accepted.*

The Bidder shall identify, by checking Yes or No on Form B, whether it has any pending contracts (including leases), bids, proposals, or other ongoing procurement relationship with any other (non-IDOT) State of Illinois agency. If "No" is checked, the bidder only needs to complete the check box on the bottom of Form B. If "Yes" is checked, the bidder must do one of the following:

Option I: If the bidder did not submit an Affidavit of Availability to obtain authorization to bid, the bidder must list all non-IDOT State of Illinois agency pending contracts, leases, bids, proposals, and other ongoing procurement relationships. These items may be listed on Form B or on an attached sheet(s). Do not include IDOT contracts. Contracts with cities, counties, villages, etc. are not considered State of Illinois agency contracts and are not to be included. Contracts with other State of Illinois agencies such as the Department of Natural Resources or the Capital Development Board must be included. Bidders who submit Affidavits of Availability are suggested to use Option II.

Option II: If the bidder is required and has submitted an Affidavit of Availability in order to obtain authorization to bid, the bidder may write or type "See Affidavit of Availability" which indicates that the Affidavit of Availability is incorporated by reference and includes all non-IDOT State of Illinois agency pending contracts, leases, bids, proposals, and other ongoing procurement relationships. For any contracts that are not covered by the Affidavit of Availability, the bidder must identify them on Form B or on an attached sheet(s). These might be such things as leases.

D. Bidders Submitting More Than One Bid

Bidders submitting multiple bids may submit one set of forms consisting of all required Form A disclosures and one Form B for use with all bids. Please indicate in the space provided below the bid item that contains the original disclosure forms and the bid items which incorporate the forms by reference.

- The bid submitted for letting item _____ contains the Form A disclosures or Certification Statement and the Form B disclosures. The following letting items incorporate the said forms by reference:

**ILLINOIS DEPARTMENT
OF TRANSPORTATION**

**Form A
Financial Information &
Potential Conflicts of Interest
Disclosure**

Contractor Name		
Legal Address		
City, State, Zip		
Telephone Number	Email Address	Fax Number (if available)

Disclosure of the information contained in this Form is required by the Section 50-35 of the Illinois Procurement Code (30 ILCS 500). Vendors desiring to enter into a contract with the State of Illinois must disclose the financial information and potential conflict of interest information as specified in this Disclosure Form. This information shall become part of the publicly available contract file. This Form A must be completed for bids in excess of \$10,000, and for all open-ended contracts. **A publicly traded company may submit a 10K disclosure (or equivalent if applicable) in satisfaction of the requirements set forth in Form A. See Disclosure Form Instructions.**

DISCLOSURE OF FINANCIAL INFORMATION

1. Disclosure of Financial Information. The individual named below has an interest in the BIDDER (or its parent) in terms of ownership or distributive income share in excess of 5%, or an interest which has a value of more than \$106,447.20 (60% of the Governor's salary as of 7/1/07). **(Make copies of this form as necessary and attach a separate Disclosure Form A for each individual meeting these requirements)**

FOR INDIVIDUAL (type or print information)

NAME: _____

ADDRESS _____

Type of ownership/distributable income share:

stock _____ sole proprietorship _____ Partnership _____ other: (explain on separate sheet):
% or \$ value of ownership/distributable income share: _____

2. Disclosure of Potential Conflicts of Interest. Check "Yes" or "No" to indicate which, if any, of the following potential conflict of interest relationships apply. If the answer to any question is "Yes", please attach additional pages and describe.

(a) State employment, currently or in the previous 3 years, including contractual employment of services. Yes ___ No ___

If your answer is yes, please answer each of the following questions.

1. Are you currently an officer or employee of either the Capitol Development Board or the Illinois Toll Highway Authority? Yes ___ No ___
2. Are you currently appointed to or employed by any agency of the State of Illinois? If you are currently appointed to or employed by any agency of the State of Illinois, and your annual salary exceeds \$106,447.20, (60% of the Governor's salary as of 7/1/07) provide the name the State agency for which you are employed and your annual salary. _____

RETURN WITH BID/OFFER

- 3. If you are currently appointed to or employed by any agency of the State of Illinois, and your annual salary exceeds \$106,447.20, (60% of the Governor's salary as of 7/1/07) are you entitled to receive (i) more than 7 1/2% of the total distributable income of your firm, partnership, association or corporation, or (ii) an amount in excess of the salary of the Governor? Yes ___ No ___

- 4. If you are currently appointed to or employed by any agency of the State of Illinois, and your annual salary exceeds \$106,447.20, (60% of the Governor's salary as of 7/1/07) are you and your spouse or minor children entitled to receive (i) more than 15 % in the aggregate of the total distributable income of your firm, partnership, association or corporation, or (ii) an amount in excess of 2 times the salary of the Governor? Yes ___ No ___

(b) State employment of spouse, father, mother, son, or daughter, including contractual employment services in the previous 2 years.

Yes ___ No ___

If your answer is yes, please answer each of the following questions.

- 1. Is your spouse or any minor children currently an officer or employee of the Capitol Development Board or the Illinois Toll Highway Authority? Yes ___ No ___

- 2. Is your spouse or any minor children currently appointed to or employed by any agency of the State of Illinois? If your spouse or minor children is/are currently appointed to or employed by any agency of the State of Illinois, and his/her annual salary exceeds \$106,447.20, (60 % of the Governor's salary as of 7/1/07) provide the name of your spouse and/or minor children, the name of the State agency for which he/she is employed and his/her annual salary. _____

- 3. If your spouse or any minor children is/are currently appointed to or employed by any agency of the State of Illinois, and his/her annual salary exceeds \$106,447.20, (60% of the salary of the Governor as of 7/1/07) are you entitled to receive (i) more then 71/2% of the total distributable income of your firm, partnership, association or corporation, or (ii) an amount in excess of the salary of the Governor? Yes ___ No ___

- 4. If your spouse or any minor children are currently appointed to or employed by any agency of the State of Illinois, and his/her annual salary exceeds \$106,447.20, (60% of the Governor's salary as of 7/1/07) are you and your spouse or minor children entitled to receive (i) more than 15 % in the aggregate of the total distributable income of your firm, partnership, association or corporation, or (ii) an amount in excess of 2 times the salary of the Governor? Yes ___ No ___

(c) Elective status; the holding of elective office of the State of Illinois, the government of the United States, any unit of local government authorized by the Constitution of the State of Illinois or the statutes of the State of Illinois currently or in the previous 3 years. Yes ___ No ___

(d) Relationship to anyone holding elective office currently or in the previous 2 years; spouse, father, mother, son, or daughter. Yes ___ No ___

(e) Appointive office; the holding of any appointive government office of the State of Illinois, the United States of America, or any unit of local government authorized by the Constitution of the State of Illinois or the statutes of the State of Illinois, which office entitles the holder to compensation in excess of the expenses incurred in the discharge of that office currently or in the previous 3 years. Yes ___ No ___

(f) Relationship to anyone holding appointive office currently or in the previous 2 years; spouse, father, mother, son, or daughter. Yes ___ No ___

(g) Employment, currently or in the previous 3 years, as or by any registered lobbyist of the State government. Yes ___ No ___

RETURN WITH BID/OFFER

(h) Relationship to anyone who is or was a registered lobbyist in the previous 2 years; spouse, father, mother, son, or daughter. Yes ___ No ___

(i) Compensated employment, currently or in the previous 3 years, by any registered election or reelection committee registered with the Secretary of State or any county clerk of the State of Illinois, or any political action committee registered with either the Secretary of State or the Federal Board of Elections. Yes ___ No ___

(j) Relationship to anyone; spouse, father, mother, son, or daughter; who was a compensated employee in the last 2 years by any registered election or re-election committee registered with the Secretary of State or any county clerk of the State of Illinois, or any political action committee registered with either the Secretary of State or the Federal Board of Elections. Yes ___ No ___

APPLICABLE STATEMENT

This Disclosure Form A is submitted on behalf of the INDIVIDUAL named on previous page.

Completed by: _____
Signature of Individual or Authorized Representative Date

NOT APPLICABLE STATEMENT

I have determined that no individuals associated with this organization meet the criteria that would require the completion of this Form A.

This Disclosure Form A is submitted on behalf of the CONTRACTOR listed on the previous page.

Signature of Authorized Representative Date

RETURN WITH BID/OFFER

ILLINOIS DEPARTMENT OF TRANSPORTATION

Form B Other Contracts & Procurement Related Information Disclosure

Contractor Name		
Legal Address		
City, State, Zip		
Telephone Number	Email Address	Fax Number (if available)

Disclosure of the information contained in this Form is required by the Section 50-35 of the Illinois Procurement Act (30 ILCS 500). This information shall become part of the publicly available contract file. This Form B must be completed for bids in excess of \$10,000, and for all open-ended contracts.

DISCLOSURE OF OTHER CONTRACTS AND PROCUREMENT RELATED INFORMATION

1. Identifying Other Contracts & Procurement Related Information. The BIDDER shall identify whether it has any pending contracts (including leases), bids, proposals, or other ongoing procurement relationship with any other State of Illinois agency: Yes ___ No ___

If "No" is checked, the bidder only needs to complete the signature box on the bottom of this page.

2. If "Yes" is checked. Identify each such relationship by showing State of Illinois agency name and other descriptive information such as bid or project number (attach additional pages as necessary). SEE DISCLOSURE FORM INSTRUCTIONS:

THE FOLLOWING STATEMENT MUST BE CHECKED

<input type="checkbox"/>	<hr style="border: none; border-top: 1px solid black;"/> Signature of Authorized Representative	<hr style="border: none; border-top: 1px solid black;"/> Date
--------------------------	---	---

RETURN WITH BID

SPECIAL NOTICE TO CONTRACTORS

The following requirements of the Illinois Department of Human Rights' Rules and Regulations are applicable to bidders on all construction contracts advertised by the Illinois Department of Transportation:

CONSTRUCTION EMPLOYEE UTILIZATION PROJECTION

- (a) All bidders on construction contracts shall complete and submit, along with and as part of their bids, a Bidder's Employee Utilization Form (Form BC-1256) setting forth a projection and breakdown of the total workforce intended to be hired and/or allocated to such contract work by the bidder including a projection of minority and female employee utilization in all job classifications on the contract project.
- (b) The Department of Transportation shall review the Employee Utilization Form, and workforce projections contained therein, of the contract awardee to determine if such projections reflect an underutilization of minority persons and/or women in any job classification in accordance with the Equal Employment Opportunity Clause and Section 7.2 of the Illinois Department of Human Rights' Rules and Regulations for Public Contracts adopted as amended on September 17, 1980. If it is determined that the contract awardee's projections reflect an underutilization of minority persons and/or women in any job classification, it shall be advised in writing of the manner in which it is underutilizing and such awardee shall be considered to be in breach of the contract unless, prior to commencement of work on the contract project, it submits revised satisfactory projections or an acceptable written affirmative action plan to correct such underutilization including a specific timetable geared to the completion stages of the contract.
- (c) The Department of Transportation shall provide to the Department of Human Rights a copy of the contract awardee's Employee Utilization Form, a copy of any required written affirmative action plan, and any written correspondence related thereto. The Department of Human Rights may review and revise any action taken by the Department of Transportation with respect to these requirements.

RETURN WITH BID

**Contract No. 64G07
WINNEBAGO County
Section (2,3)RS-3
Route FAP 303
District 2 Construction Funds**

PART II. WORKFORCE PROJECTION - continued

- B. Included in "Total Employees" under Table A is the total number of **new hires** that would be employed in the event the undersigned bidder is awarded this contract.

The undersigned bidder projects that: (number) _____ new hires would be recruited from the area in which the contract project is located; and/or (number) _____ new hires would be recruited from the area in which the bidder's principal office or base of operation is located.

- C. Included in "Total Employees" under Table A is a projection of numbers of persons to be employed directly by the undersigned bidder as well as a projection of numbers of persons to be employed by subcontractors.

The undersigned bidder estimates that (number) _____ persons will be directly employed by the prime contractor and that (number) _____ persons will be employed by subcontractors.

PART III. AFFIRMATIVE ACTION PLAN

- A. The undersigned bidder understands and agrees that in the event the foregoing minority and female employee utilization projection included under **PART II** is determined to be an underutilization of minority persons or women in any job category, and in the event that the undersigned bidder is awarded this contract, he/she will, prior to commencement of work, develop and submit a written Affirmative Action Plan including a specific timetable (geared to the completion stages of the contract) whereby deficiencies in minority and/or female employee utilization are corrected. Such Affirmative Action Plan will be subject to approval by the contracting agency and the **Department of Human Rights**.
- B. The undersigned bidder understands and agrees that the minority and female employee utilization projection submitted herein, and the goals and timetable included under an Affirmative Action Plan if required, are deemed to be part of the contract specifications.

Company _____ Telephone Number _____

Address _____

NOTICE REGARDING SIGNATURE

The Bidder's signature on the Proposal Signature Sheet will constitute the signing of this form. The following signature block needs to be completed if revisions are required.

Signature: _____ Title: _____ Date: _____

Instructions: All tables must include subcontractor personnel in addition to prime contractor personnel.

Table A - Include both the number of employees that would be hired to perform the contract work and the total number currently employed (Table B) that will be allocated to contract work, and include all apprentices and on-the-job trainees. The "Total Employees" column should include all employees including all minorities, apprentices and on-the-job trainees to be employed on the contract work.

Table B - Include all employees currently employed that will be allocated to the contract work including any apprentices and on-the-job trainees currently employed.

Table C - Indicate the racial breakdown of the total apprentices and on-the-job trainees shown in Table A.

RETURN WITH BID

**Contract No. 64G07
WINNEBAGO County
Section (2,3)RS-3
Route FAP 303
District 2 Construction Funds**

PROPOSAL SIGNATURE SHEET

The undersigned bidder hereby makes and submits this bid on the subject Proposal, thereby assuring the Department that all requirements of the Invitation for Bids and rules of the Department have been met, that there is no misunderstanding of the requirements of paragraph 3 of this Proposal, and that the contract will be executed in accordance with the rules of the Department if an award is made on this bid.

(IF AN INDIVIDUAL)

Firm Name _____

Signature of Owner _____

Business Address _____

(IF A CO-PARTNERSHIP)

Firm Name _____

By _____

Business Address _____

Name and Address of All Members of the Firm:

(IF A CORPORATION)

Corporate Name _____

By _____

Signature of Authorized Representative _____

Typed or printed name and title of Authorized Representative _____

Attest _____

Signature _____

(IF A JOINT VENTURE, USE THIS SECTION FOR THE MANAGING PARTY AND THE SECOND PARTY SHOULD SIGN BELOW)

Business Address _____

(IF A JOINT VENTURE)

Corporate Name _____

By _____

Signature of Authorized Representative _____

Typed or printed name and title of Authorized Representative _____

Attest _____

Signature _____

Business Address _____

If more than two parties are in the joint venture, please attach an additional signature sheet.



Return with Bid

Division of Highways
Proposal Bid Bond
(Effective November 1, 1992)

Item No. _____

Letting Date _____

KNOW ALL MEN BY THESE PRESENTS, That We _____

as PRINCIPAL, and _____

_____ as SURETY, are held jointly, severally and firmly bound unto the STATE OF ILLINOIS in the penal sum of 5 percent of the total bid price, or for the amount specified in Article 102.09 of the "Standard Specifications for Road and Bridge Construction" in effect on the date of invitation for bids, whichever is the lesser sum, well and truly to be paid unto said STATE OF ILLINOIS, for the payment of which we bind ourselves, our heirs, executors, administrators, successors and assigns.

THE CONDITION OF THE FOREGOING OBLIGATION IS SUCH, that whereas, the PRINCIPAL has submitted a bid proposal to the STATE OF ILLINOIS, acting through the Department of Transportation, for the improvement designated by the Transportation Bulletin Item Number and Letting Date indicated above.

NOW, THEREFORE, if the Department shall accept the bid proposal of the PRINCIPAL; and if the PRINCIPAL shall, within the time and as specified in the bidding and contract documents, submit a DBE Utilization Plan that is accepted and approved by the Department; and if, after award by the Department, the PRINCIPAL shall enter into a contract in accordance with the terms of the bidding and contract documents including evidence of the required insurance coverages and providing such bond as specified with good and sufficient surety for the faithful performance of such contract and for the prompt payment of labor and material furnished in the prosecution thereof; or if, in the event of the failure of the PRINCIPAL to make the required DBE submission or to enter into such contract and to give the specified bond, the PRINCIPAL pays to the Department the difference not to exceed the penalty hereof between the amount specified in the bid proposal and such larger amount for which the Department may contract with another party to perform the work covered by said bid proposal, then this obligation shall be null and void, otherwise, it shall remain in full force and effect.

IN THE EVENT the Department determines the PRINCIPAL has failed to comply with any requirement as set forth in the preceding paragraph, then Surety shall pay the penal sum to the Department within fifteen (15) days of written demand therefor. If Surety does not make full payment within such period of time, the Department may bring an action to collect the amount owed. Surety is liable to the Department for all its expenses, including attorney's fees, incurred in any litigation in which it prevails either in whole or in part.

In TESTIMONY WHEREOF, the said PRINCIPAL and the said SURETY have caused this instrument to be signed by

their respective officers this _____ day of _____ A.D., _____ .

PRINCIPAL

SURETY

(Company Name)

(Company Name)

By _____
(Signature & Title)

By: _____
(Signature of Attorney-in-Fact)

Notary Certification for Principal and Surety

STATE OF ILLINOIS,
County of _____

I, _____, a Notary Public in and for said County, do hereby certify that

_____ and _____
(Insert names of individuals signing on behalf of PRINCIPAL & SURETY)

who are each personally known to me to be the same persons whose names are subscribed to the foregoing instrument on behalf of PRINCIPAL and SURETY, appeared before me this day in person and acknowledged respectively, that they signed and delivered said instrument as their free and voluntary act for the uses and purposes therein set forth.

Given under my hand and notarial seal this _____ day of _____ A.D. _____

My commission expires _____

Notary Public

In lieu of completing the above section of the Proposal Bid Form, the Principal may file an Electronic Bid Bond. By signing the proposal and marking the check box next to the Signature and Title line below, the Principal is ensuring the identified electronic bid bond has been executed and the Principal and Surety are firmly bound unto the State of Illinois under the conditions of the bid bond as shown above.

Electronic Bid Bond ID#

Company / Bidder Name



Signature and Title

PROPOSAL ENVELOPE



PROPOSALS

for construction work advertised for bids by the
Illinois Department of Transportation

Item No.	Item No.	Item No.

Submitted By:

Name:
Address:
Phone No.

Bidders should use an IDOT proposal envelope or affix this form to the front of a 10" x 13" envelope for the submittal of bids. If proposals are mailed, they should be enclosed in a second or outer envelope addressed to:

Engineer of Design and Environment - Room 326
Illinois Department of Transportation
2300 South Dirksen Parkway
Springfield, Illinois 62764

NOTICE

Individual bids, including Bid Bond and/or supplemental information if required, should be securely stapled.

CONTRACTOR OFFICE COPY OF CONTRACT SPECIFICATIONS

NOTICE

None of the following material needs to be returned with the bid package unless the special provisions require documentation and/or other information to be submitted.

**Contract No. 64G07
WINNEBAGO County
Section (2,3)RS-3
Route FAP 303
District 2 Construction Funds**



Illinois Department of Transportation



NOTICE TO BIDDERS

- 1. TIME AND PLACE OF OPENING BIDS.** Sealed proposals for the improvement described herein will be received by the Department of Transportation at the Harry R. Hanley Building, 2300 South Dirksen Parkway, in Springfield, Illinois until 10:00 o'clock a.m., April 23, 2010. All bids will be gathered, sorted, publicly opened and read in the auditorium at the Department of Transportation's Harry R. Hanley Building shortly after the 10:00 a.m. cut off time.
- 2. DESCRIPTION OF WORK.** The proposed improvement is identified and advertised for bids in the Invitation for Bids as:

**Contract No. 64G07
WINNEBAGO County
Section (2,3)RS-3
Route FAP 303
District 2 Construction Funds**

1.79 miles of milling, patching and resurfacing on IL Rte. 251 from Snow Avenue to Windsor Road in Loves Park.

- 3. INSTRUCTIONS TO BIDDERS.** (a) This Notice, the invitation for bids, proposal and letter of award shall, together with all other documents in accordance with Article 101.09 of the Standard Specifications for Road and Bridge Construction, become part of the contract. Bidders are cautioned to read and examine carefully all documents, to make all required inspections, and to inquire or seek explanation of the same prior to submission of a bid.

(b) State law, and, if the work is to be paid wholly or in part with Federal-aid funds, Federal law requires the bidder to make various certifications as a part of the proposal and contract. By execution and submission of the proposal, the bidder makes the certification contained therein. A false or fraudulent certification shall, in addition to all other remedies provided by law, be a breach of contract and may result in termination of the contract.
- 4. AWARD CRITERIA AND REJECTION OF BIDS.** This contract will be awarded to the lowest responsive and responsible bidder considering conformity with the terms and conditions established by the Department in the rules, Invitation for Bids and contract documents. The issuance of plans and proposal forms for bidding based upon a prequalification rating shall not be the sole determinant of responsibility. The Department reserves the right to determine responsibility at the time of award, to reject any or all proposals, to readvertise the proposed improvement, and to waive technicalities.

By Order of the
Illinois Department of Transportation

Gary Hannig,
Secretary

INDEX
FOR
SUPPLEMENTAL SPECIFICATIONS
AND RECURRING SPECIAL PROVISIONS

Adopted January 1, 2010

This index contains a listing of SUPPLEMENTAL SPECIFICATIONS and frequently used RECURRING SPECIAL PROVISIONS.

ERRATA Standard Specifications for Road and Bridge Construction (Adopted 1-1-07) (Revised 1-1-10)

SUPPLEMENTAL SPECIFICATIONS

<u>Std. Spec. Sec.</u>		<u>Page No.</u>
201	Clearing, Tree Removal and Protection	1
205	Embankment	2
251	Mulch	3
253	Planting Woody Plants	4
280	Temporary Erosion Control	6
406	Hot-Mix Asphalt Binder and Surface Course	7
443	Reflective Crack Control Treatment	12
502	Excavation for Structures	15
503	Concrete Structures	16
504	Precast Concrete Structures	17
505	Steel Structures	18
540	Box Culverts	19
581	Waterproofing Membrane System	20
630	Steel Plate Beam Guardrail	21
633	Removing and Reerecting Guardrail and Terminals	22
637	Concrete Barrier	23
669	Removal and Disposal of Regulated Substances	24
672	Sealing Abandoned Water Wells	25
701	Work Zone Traffic Control and Protection	26
720	Sign Panels and Appurtenances	27
721	Sign Panel Overlay	28
722	Demountable Sign Legend Characters and Arrows	29
726	Mile Post Marker Assembly	30
733	Overhead Sign Structures	31
783	Pavement Marking and Marker Removal	32
801	Electrical Requirements	33
805	Electrical Service Installation – Traffic Signals	34
836	Pole Foundation	35
838	Breakaway Devices	36
862	Uninterruptable Power Supply	37
873	Electric Cable	39
878	Traffic Signal Concrete Foundation	41
1003	Fine Aggregates	42
1004	Coarse Aggregates	43
1005	Stone and Broken Concrete	44
1006	Metals	45
1008	Structural Steel Coatings	47
1010	Finely Divided Materials	48
1020	Portland Cement Concrete	49
1022	Concrete Curing Materials	58
1024	Nonshrink Grout	59
1030	Hot-Mix Asphalt	60
1032	Bituminous Materials	65

1042	Precast Concrete Products	68
1062	Reflective Crack Control System	70
1069	Pole and Tower	72
1074	Control Equipment	75
1076	Wire and Cable	80
1080	Fabric Materials	81
1081	Materials for Planting	82
1083	Elastomeric Bearings	84
1090	Sign Base	85
1091	Sign Face	87
1092	Sign Legend and Supplemental Panels	95
1093	Sign Supports	96
1094	Overhead Sign Structures	98
1095	Pavement Markings	104
1101	General Equipment	106
1102	Hot-Mix Asphalt Equipment	107
1103	Portland Cement Concrete Equipment	109
1106	Work Zone Traffic Control Devices	110

RECURRING SPECIAL PROVISIONS

The following RECURRING SPECIAL PROVISIONS indicated by an "X" are applicable to this contract and are included by reference:

<u>CHECK SHEET #</u>	<u>PAGE NO.</u>
1	111
2	114
3 X	115
4 X	125
5 X	130
6	135
7	136
8	137
9	138
10 X	141
11	144
12	146
13	150
14 X	152
15	153
16 X	155
17	156
18	158
19	159
20	160
21	164
22	166
23	168
24	170
25	171
26	172
27	173
28	174
29	175
30	176
31	184
32	196
33	197

TABLE OF CONTENTS

LOCATION OF PROJECT	1
DESCRIPTION OF PROJECT	1
TRAFFIC CONTROL PLAN	1
START DATE	4
COMPACTION OF POLYMERIZED HOT-MIX ASPHALT CONCRETE	4
DETECTOR LOOP, SPECIAL	4
GEOTECHNICAL REINFORCEMENT	5
ENGINEER'S FIELD OFFICE TYPE A	7
CONCRETE MEDIAN, TYPE SB-6 (MODIFIED)	9
VALVE VAULTS TO BE ADJUSTED (SPECIAL)	9
MEDIAN REMOVAL	10
DELAYED START OF MULTIPLE CONTRACTS	10
INLETS TO BE ADJUSTED WITH NEW FRAME AND GRATE (SPECIAL)	10
APPROVAL OF PROPOSED BORROW AREAS, USE AREAS, AND/OR WASTE AREAS INSIDE ILLINOIS STATE BORDERS (BDE)	11
CEMENT (BDE)	11
CONCRETE ADMIXTURES (BDE)	13
CONSTRUCTION AIR QUALITY - DIESEL VEHICLE EMISSIONS CONTROL (BDE)	16
CONSTRUCTION AIR QUALITY - IDLING RESTRICTIONS (BDE)	17
DISADVANTAGED BUSINESS ENTERPRISE PARTICIPATION (BDE)	18
EQUIPMENT RENTAL RATES (BDE)	26
HOT-MIX ASPHALT – ANTI-STRIPPING ADDITIVE (BDE)	27
HOT-MIX ASPHALT - DENSITY TESTING OF LONGITUDINAL JOINTS (BDE)	27
HOT-MIX ASPHALT – DROP-OFFS (BDE)	28
HOT-MIX ASPHALT - FINE AGGREGATE (BDE)	28
HOT-MIX ASPHALT – PLANT TEST FREQUENCY (BDE)	29
HOT-MIX ASPHALT – QC/QA ACCEPTANCE CRITERIA (BDE)	30
HOT-MIX ASPHALT – TRANSPORTATION (BDE)	31
LIQUIDATED DAMAGES (BDE)	31
MULTILANE PAVEMENT PATCHING (BDE)	32
NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM / EROSION AND SEDIMENT CONTROL DEFICIENCY DEDUCTION (BDE)	32
PAVEMENT PATCHING (BDE)	33
PAYMENTS TO SUBCONTRACTORS (BDE)	33
PERSONAL PROTECTIVE EQUIPMENT (BDE)	34
RAISED REFLECTIVE PAVEMENT MARKERS (BDE)	35
RECLAIMED ASPHALT PAVEMENT (RAP) (BDE)	35
REFLECTIVE SHEETING ON CHANNELIZING DEVICES (BDE)	42

SUBCONTRACTOR MOBILIZATION PAYMENTS (BDE) 42
THERMOPLASTIC PAVEMENT MARKINGS (BDE) 43
TRUCK MOUNTED/TRAILER MOUNTED ATTENUATORS (BDE) 44
WORKING DAYS (BDE) 44
BITUMINOUS MATERIALS COST ADJUSTMENTS (BDE) (RETURN FORM WITH BID) 44
MONTHLY EMPLOYMENT REPORT (BDE) 47

STATE OF ILLINOIS

SPECIAL PROVISIONS

The following Special Provisions supplement the "Standard Specifications for Road and Bridge Construction," adopted January 1, 2007, the latest edition of the "Manual on Uniform Traffic Control Devices for Streets and Highways," and the "Manual of Test Procedures for Materials" in effect on the date of invitation for bids, and the Supplemental Specifications and Recurring Special Provisions indicated on the Check Sheet included herein which apply to and govern the construction of FAP Route 303 (IL 251), Section (2, 3)RS-3, Winnebago County, Contract 64G07, and in case of conflict with any part or parts of said Specifications, the said Special Provisions shall take precedence and shall govern.

LOCATION OF PROJECT

IL 251 between Snow Avenue and Windsor Road in Loves Park.

DESCRIPTION OF PROJECT

This project consists of milling, patching, hot-mix asphalt resurfacing, and removing and replacing concrete median.

TRAFFIC CONTROL PLAN

Effective January 14, 1999

Traffic Control shall be according to the applicable sections of the Standard Specifications for Road and Bridge Construction, the applicable guidelines contained in the National Manual on Uniform Traffic Control Devices for Streets and Highways, Illinois Supplement to the National Manual on Uniform Traffic Control Devices, these special provisions, and any special details and Highway Standards contained herein and in the plans.

Special attention is called to Articles 107.09 and 107.14 of the Standard Specifications for Road and Bridge Construction and the following Highway Standards relating to traffic control.

Standards:

701101 701421 701426 701601 701606 701701 701901

Details:

Traffic Control & Protection at Turn Bays (To Remain Open to Traffic) (DS 94.2)
Rough Grooved Surface Sign (DS 91.2)

Signs:

No bracing shall be allowed on post-mounted signs.

Post-mounted signs shall be installed using standard 720011, 728001, 729001, on 4"x4" wood posts, or on any other "break away" connection if accepted by the FHWA and corresponding letter is provided to the resident.

All signs are required on both sides of the road when the median is greater than 10 feet and on one way roadways.

The "WORKERS" (W21-1a(O)-48) signs shall be replaced with symbol "Right or Left Lane Closed Ahead" (W4-2R or L(O)-48) signs on multilane roadways.

"BUMP" (W8-1(O)48) signs shall be installed as directed by the Engineer.

"UNEVEN LANES" W8-11(O)48 signs shall be installed at 1 mile intervals or as directed by the Engineer on roadways where the posted speed limit is greater than 40 mph.

"LOW SHOULDER" W8-9(O)48 signs shall be installed at 1 mile intervals or as directed by the Engineer.

When covering existing Department signs, no tape shall be used on the reflective portion of the sign. Contact the District sign shop for covering techniques.

All regulatory signs shall be maintained at a 5 foot minimum bottom (rural), 7 foot minimum (urban).

Devices:

A minimum of 3 drums spaced at 1.2 meters (4 feet) shall be placed at each return when the sideroad is open.

Direction Indicator Barricades shall exclusively be used in lane closure tapers. They shall be used only when traffic is being merged with an adjacent through lane or shifted onto a median crossover.

Flaggers:

Flagger at Sideroads and Commercial Entrances:

Effective: April 9, 2009

Revise the second paragraph of Article 701.13(a) of the Standard Specifications to read:

"The Engineer will determine when a sideroad or commercial entrance shall be closed to traffic. A flagger will be required at each sideroad and any commercial entrance deemed necessary by the Engineer remaining open to traffic within the operation where one lane of traffic is maintained in either direction. The flagger shall be positioned as shown on the plans or as directed by the Engineer."

Revise the first and second paragraph of Article 701.20(i) of the Standard Specifications to read:

"Signs, barricades, or other traffic control devices required by the Engineer over and above those specified will be paid for according to Article 109.04.

All flaggers required at side roads and entrances remaining open to traffic including those that are shown on the Highway Standards and/or additional barricades required by the Engineer to close side roads and entrances will be paid for according to Article 109.04.”

Flaggers shall comply with all requirements contained in the Department’s “Flagger Handbook” with the following exception: The ANSI Class 2 vest will not be supplied by the Department.

Pavement Marking: All short term or temporary pavement marking placed on a milled surface shall be paint.

Highway Standards Application.

Traffic Control and Protection Standards 701601: This work shall be done according to Standard 701601 and Section 701 of the Standard Specifications. The Contractor shall be required to install the 701601 two (2) calendar days in advance of the areas to be patched for the protection of the State personnel laying out the locations for pavement patching.

The barricades as shown in Standard 701601 shall not encroach on the lane open to traffic at any time. The only exception to this will be in the immediate work area when workers are present, then the barricades may be moved out to permit the construction operation.

This work shall be included in the contract unit price per Lump Sum for TRAFFIC CONTROL AND PROTECTION STANDARD 701601.

Traffic Control and Protection Standards 701421: Northbound traffic shall have its traffic control set up according to Standard 701421 and Section 701 of the Standard Specifications. The speed limit signing in this Standard shall be omitted.

This work shall be included in the contract unit price per Lump Sum for TRAFFIC CONTROL AND PROTECTION STANDARD 701601.

Traffic Control and Protection Standards 701701: This work shall be done according to Section 701 of the Standard Specifications and the Typical Application of Traffic Control Devices for Highway Construction, Standard 701701, and as specified herein.

The left leg of the intersection shown on this standard also applies when the right turn lane is closed. When the right turn lane is closed, “RIGHT TURN LANE CLOSED AHEAD” sign shall be substituted for the “LEFT TURN LANE CLOSED AHEAD” sign and the set up would be a mirror image to what is shown.

This work shall be included in the contract unit price per Lump Sum for TRAFFIC CONTROL AND PROTECTION STANDARD 701701.

Maintenance of Traffic: The mainline shall be kept open to one lane of traffic in each direction at all times during working hours, and two lanes of traffic in each direction during non-working hours.

The Contractor shall be required to notify the Winnebago County Highway Department, the City of Loves Park, and/or corresponding Township Commissioner for any sideroad closure or opening.

The sawing of patches, milling, and resurfacing shall be completed using Traffic Control and Protection Standard 701601.

The pavement patch removal and replacement shall be completed using Traffic Control and Protection Standard 701601.

Placing and removing pavement marking shall be completed using Traffic Control and Protection Standard 701701.

The Contractor shall have all lanes open by 3:00 p.m. on Fridays unless prior approval is obtained from the Resident Engineer. All lanes shall remain open until 7:00 a.m. on Mondays.

Lane closures shall only be allowed while work operations are in progress. Overnight lane closures will only be allowed for the median work.

In areas scheduled for milling and resurfacing with leveling binder and surface course, the leveling binder shall be placed the same day as the milling operation. Milled areas scheduled for all other bituminous surfacing shall be paved within ten calendar days.

START DATE

No work shall be started on this project until June 1, 2010.

COMPACTION OF POLYMERIZED HOT-MIX ASPHALT CONCRETE

Effective January 16, 2002

This work shall consist of furnishing a pneumatic tired roller as specified in Article 406, in addition to all other rollers specified in the Standard Specifications. The spray system shall be in good working order. The tires shall be in good condition and be constructed heavy enough to withstand 90 to 110 psi inflation pressures on a continual basis. An approved water based release agent shall be utilized on the tires similar to, but not limited to, Tech Shield that effectively prevents mix adhesion. The dilution rate shall be as per manufacturer's recommendations. The mixture compaction temperature will be the maximum possible without experiencing surface damage to the mix caused by adhesion to the tires. The recommended range is from 200° to 260° Fahrenheit. This work shall be included in the cost of the polymerized Hot-Mix Asphalt concrete of the type and size specified.

DETECTOR LOOP, SPECIAL

This item shall consist of replacing detector loops, furnishing, installing, and testing in accordance with Section 886 of the current "Standards Specifications for Road Bridge Construction".

This item shall include replacing any conduit stubs damaged during the surface grinding process. This shall also include any wire in conduit required to connect the loops.

Any 6'x20' Detector Loops shall have a minimum of three turns of wire, any 6'x6' Detector Loops shall have a minimum of four turns of wire.

Detector Loops are measured along the sawed slot in the pavement containing the loop and lead-in rather than the actual length of the wire. The cables, from the end of the saw cut for the loop to the splice in the handhole, shall not be measured for payment since it is considered to be included in the cost of the Detector Loop.

For appropriate layout of Detector Loops, Scott Kullerstrand (815/284-5468) of the Illinois Department of Transportation, Bureau of Operations, shall be contacted prior to reinstallation to mark the Detector Loop locations.

This work will be paid for at the contract unit price per Foot for DETECTOR LOOP, SPECIAL, which price shall include furnishing, installing all required components, and testing inductance to assure satisfactory operation.

GEOTECHNICAL REINFORCEMENT

Revised September 1, 2004

Biaxial Geogrid Flat Installation

This work consists of furnishing and installing an integrally-formed polypropylene geotechnical grid reinforcement material. The grid shall have an aperture, rib and junction cross section sufficient to permit significant mechanical interlock with the material being reinforced. There shall be a high continuity of tensile strength through all ribs and junctions of the grid material to reinforce the embankment or subgrade as shown on the plans and specifications.

Materials: Each layer of geogrid shall conform to the property requirements listed below. Multilayer geogrid and multiple layers of lesser strength geogrids will not be accepted.

Reinforcement and Interlock

<u>Property</u>	<u>Test Method</u>	<u>Value</u>
<u>Tensile Modulus:</u>		
▪ True Tensile Modulus	ASTMD 6637	17,000 lb./ft. (Min.)
▪ True Tensile Strength @ 2% Strain		280 lb./ft. (Min.)
▪ True Tensile Strength @5% Strain		580 lb./ft. (Min.)
<u>Apertures:</u>		
▪ Aperture Stability	USACE*	2.7 in. – lb./deg. (min.)
▪ Open Area	COE Method Modified**	70% (Nom.)

* Resistance to in-plane rotational movement measured by applying a 20 kg-cm moment to the central junction of a 9 inch x 9 inch specimen restrained at its perimeter (U.S. Army Corps of Engineers Methodology for measurement of Torsional Rigidity).

** Percent open area measured without magnification by Corps of Engineers method as specified in CW 02215 Civil Works Construction Guide, November, 1977.

Structural Integrity:

- Flexural Stiffness ASTM D-5732-95 *** 0.2 in.-lb. (Min.)
- Junction Efficiency GRI GG2-87**** 90% (Min.)

*** Resistance to bending force measured via ASTM D-5732-95, using specimens of width two ribs wide, with transverse ribs cut flush with exterior edges of longitudinal ribs (as a “ladder), and of length sufficiently long to enable measurement of the overhang dimension. The overall Flexural Stiffness is calculated as the square root of the product of machine-and cross-machine-direction Flexural Stiffness values.

**** Load transfer capability measured via GRI-GG2-87. Expressed as a percentage of ultimate tensile strength.

Material

- | | | |
|---------------|--|-------------|
| Polypropylene | ASTM D 1401
Group I/Class 1/Grade 2 | 98% (Min.) |
| Carbon Black | ASTM 4218 | 0.5% (Min.) |

The supplier should provide a certification that their product meets the above requirements.

The geotechnical reinforcement shall be placed as described herein or as shown on the cross sections.

Geogrid shall be delivered to the jobsite in such a manner as to facilitate handling and incorporation into the work without damage. Material shall be stored in such a manner as to prevent exposure to direct sunlight and damage by other construction activities.

Prior to the installation of the geogrid, the application surface shall be cleared of debris, sharp objects and trees. Tree stumps shall be cut to the level of the ground surface. If the stumps cannot be cut to the ground level, they shall be completely removed. In the case of subgrades, all wheel tracks or ruts in excess of 75 mm (3 inches) in depth shall be graded smooth or otherwise filled with soil to provide a reasonably smooth surface.

The geotechnical reinforcement shall be placed with the “roll length” parallel to the pavement. Fabric of insufficient width or length to fully cover the specified area shall be lapped a minimum of 600 mm (24 inches).

Installation:

The granular blanket shall be constructed to the width and depth required on the plans. Unless otherwise specified, the material shall be back-dumped on the Geogrid in a sequence of operations beginning at the outer edges of the treatment area with subsequent placement towards the middle.

Placement of material on the Geogrid shall be accomplished by spreading dumped material off of previously placed material with a bulldozer blade or endloader, in such a manner as to prevent tearing or shoving of the Geogrid. Dumping of material directly on the Geogrid will only be permitted to establish an initial working platform. No construction equipment shall be allowed on the Geogrid prior to placement of the granular blanket.

Unless otherwise specified in the plans or Special Provisions, the granular material, shall be placed to the full required thickness and compacted.

Geogrid which is damaged during installation or subsequent placement of granular material, due to failure of the Contractor to comply with these provisions, shall be repaired or replaced at his expense, including costs of removal and replacement of the granular material.

Torn Geogrid may be patched in-place by cutting and placing a piece of the same Geogrid over the tear. The dimensions of the patch shall be at least 600 mm (2 feet) larger than the largest dimension of the tear and it shall be weighted or otherwise secured to prevent the granular material from causing lap separation.

Method of Measurement: Geotechnical Reinforcement will be measured in square meters (square yards) for the surface area placed. The excavation, replacement and compaction of the granular layer shall be paid for separately. Each layer of geogrid will be paid for separately.

Basis of Payment: This work will be measured in place and the area computed in square yards. The work will be paid for at the contract unit price per Square Meter (Square Yard) for GEOTECHNICAL REINFORCEMENT.

ENGINEER'S FIELD OFFICE TYPE A

Effective: June 1, 2009

Revise Article 670.02 of the Standard Specifications to read:

"670.02 Engineer's Field Office Type A. Type A field offices shall have a minimum ceiling height of 7 ft (2 m) and a minimum floor space 450 sq ft (42 sq m). The office shall be provided with sufficient heat, natural and artificial light, and air conditioning.

The office shall have an electronic security system that will respond to any breach of exterior doors and windows. Doors and windows shall be equipped with locks. Doors shall also be equipped with dead bolt locks or other secondary locking device.

Windows shall be equipped with exterior screens to allow adequate ventilation. All windows shall be equipped with interior shades, curtains, or blinds. Adequate all-weather parking space shall be available to accommodate a minimum of ten vehicles.

Suitable on-site sanitary facilities meeting Federal, State, and local health department requirements shall be provided, maintained clean and in good working condition, and shall be stocked with lavatory and sanitary supplies at all times.

Sanitary facilities shall include hot and cold potable running water, lavatory and toilet as an integral part of the office where available. Solid waste disposal consisting of two waste baskets and an outside trash container of sufficient size to accommodate a weekly provided pick-up service.

In addition, the following furniture and equipment shall be furnished.

- (a) Four desks with minimum working surface 42 x 30 in. (1.1 m x 750 mm) each and five non-folding chairs with upholstered seats and backs.
- (b) One desk with minimum working surface 48 x 72 in. (1.2 x 1.8 m) with height adjustment of 23 to 30 in. (585 to 750 mm).
- (c) One four-post drafting table with minimum top size of 37 1/2 x 48 in. (950 mm x 1.2 m). The top shall be basswood or equivalent and capable of being tilted through an angle of 50 degrees. An adjustable height drafting stool with upholstered seat and back shall also be provided.
- (d) Two free standing four drawer legal size file cabinet with lock and an underwriters' laboratories insulated file device 350 degrees one hour rating.
- (e) One 6 ft (1.8 m) folding table with six folding chairs.
- (f) One equipment cabinet of minimum inside dimension of 44 in. (1100 mm) high x 24 in. (600 mm) wide x 30 in. (750 mm) deep with lock. The walls shall be of steel with a 3/32 in. (2 mm) minimum thickness with concealed hinges and enclosed lock constructed in such a manner as to prevent entry by force. The cabinet assembly shall be permanently attached to a structural element of the field office in a manner to prevent theft of the entire cabinet.
- (g) One refrigerator with a minimum size of 16 cu ft (0.45 cu m) with a freezer unit.
- (h) Two electric desk type tape printing calculator.
- (i) A minimum of two communication paths. The configuration shall include:
 - (1) Internet Connection. An internet service connection using telephone DSL, cable broadband, or CDMA wireless technology. Additionally, an 802.11g/N wireless router shall be provided, which will allow connection by the Engineer and up to four Department staff.
 - (2) Telephone Lines. Two separate telephone lines, one to be set up for the exclusive use of the State supplied fax machine.
- (j) One plain paper copy machine capable of reproducing prints up to 11 x 17 in. (280 x 432 mm) with an automatic feed tray capable of storing 30 sheets of paper. Letter size and 11 x 17 in. (280 x 432 mm) paper shall be provided.
- (k) One telephone, with touch tone, where available, and a digital telephone answering machine, for exclusive use by the Engineer.

- (l) Cellular phone with a minimum of 500 anytime calling minutes per month for use by the site resident engineer/technician.
- (m) One electric water cooler dispenser.
- (n) One first-aid cabinet fully equipped.
- (o) One post mounted rain gauge, located on the project site for each 5 miles (8 km) of project length.”

Revise the last sentence of the first paragraph of Article 670.07 of the Standard Specifications to read:

“This price shall include all utility costs and shall reflect the salvage value of the building or buildings, equipment, and furniture which become the property of the Contractor after release by the Engineer, except that the Department will pay that portion of the monthly long distance telephone bills that, when combined, exceed \$150.”

CONCRETE MEDIAN, TYPE SB-6 (MODIFIED)

Effective January 11, 2010

This work shall be done in accordance with Section 606 of the Standard Specifications and as specified herein.

This concrete median shall have Type SB-6.12 Median adjacent to the left turn lane and the taper to the left turn lane. This median shall also have Type SB-6.24 Median adjacent to the through lanes.

This work shall be paid for at the contract unit price per Square Foot for CONCRETE MEDIAN, TYPE SB-6 (MODIFIED).

VALVE VAULTS TO BE ADJUSTED (SPECIAL)

Effective: February 18, 2008

This work shall consist of removing and replacing the upper slide or screw box and lid of cast iron water valve boxes to the finished pavement grade. Prior to replacement and during the construction operation, the Contractor shall be responsible for protecting the existing valve box from damage or from being filled with debris. Should the box be filled, it shall be cleaned by the Contractor and no additional compensation shall be made for this work.

Final replacement of the upper section of the box shall be made after the binder course has been installed and prior to the installation of the surface course. Any excavation around the box necessary to free the upper slide or screw box for replacement shall be backfilled with sand and thoroughly tamped. After adjusting to final grade, the space around the box for the full depth of base and binder course thickness shall be filled with a full mortar bed.

This work will be paid for at the contract unit price per Each for VALVE VAULTS TO BE ADJUSTED (SPECIAL), which price shall include all items as described above.

MEDIAN REMOVAL

Effective: February 2, 2009

This work shall be done in accordance with Section 440 of the Standard Specifications and as specified herein.

This work shall consist of complete removal and disposal of the center median at locations specified in the plans. Work shall include the removal of the adjacent combination curb and gutter.

Measurement for median removal shall be from the front of the gutter flag.

This work shall be paid for at the contract unit price per Square Foot for MEDIAN REMOVAL.

DELAYED START OF MULTIPLE CONTRACTS

Effective: January 7, 2010

Add the following after the first paragraph of Article 108.03 of the Standard Specifications:

“Contractors who are the apparent low bidders on multiple District 2 contracts in one letting may submit a written request for waiver, within 10 days after bid opening, to each of the Regional Engineers in whose district the affected contract is located. The request shall include specific reasons for the delay in a contract prosecution coordination plan and a proposed progress schedule for each contract. Each Regional Engineer will schedule a meeting with the Contractor within 5 working days after receipt of the request for waiver. Schedules for the prosecution of each contract and exact starting dates, as well as dates for preconstruction conferences, for each contract shall be established. Consideration of waivers will not affect award decisions or the procedures followed to execute awarded contracts.

By submission of a delayed start plan, the Contractor understands and agrees that the granting of a delayed start shall not be reason for an extension of time to complete the contract, and that the decision to approve a waiver for any or all contracts will reside with the Department, whose decision will be final.

All delayed working day contracts shall be scheduled for completion, except for non-pavement and/or cleanup work, by October 1, 2010. However, upon starting a working day contract, working days will be charged according to Article 108.04 of the Standard Specifications until the contract is complete.

Completion date contracts will not be extended beyond the date included in the plans due to the granting of a request for delayed start.

INLETS TO BE ADJUSTED WITH NEW FRAME AND GRATE (SPECIAL)

Effective: January 11, 2010

This work shall be done according to Section 602 of the Standard Specifications and as specified herein.

The new frame and grate shall be as shown in the District Standard 13.2c, “FRAME AND GRATE FOR INLET SPECIAL”.

This work shall be paid for at the contract unit price per Each for INLETS TO BE ADJUSTED WITH NEW FRAME AND GRATE (SPECIAL).

APPROVAL OF PROPOSED BORROW AREAS, USE AREAS, AND/OR WASTE AREAS INSIDE ILLINOIS STATE BORDERS (BDE)

Effective: November 1, 2008

Revise the title of Article 107.22 of the Standard Specifications to read:

“107.22 Approval of Proposed Borrow Areas, Use Areas, and/or Waste Areas Inside Illinois State Borders.”

Add the following sentence to the end of the first paragraph of Article 107.22 of the Standard Specifications:

“Proposed borrow areas, use areas, and/or waste areas outside of Illinois shall comply with Article 107.01.”

CEMENT (BDE)

Effective: January 1, 2007

Revised: April 1, 2009

Revise Section 1001 of the Standard Specifications to read:

“SECTION 1001. CEMENT

1001.01 Cement Types. Cement shall be according to the following.

- (a) Portland Cement. Acceptance of portland cement shall be according to the current Bureau of Materials and Physical Research’s Policy Memorandum, “Portland or Blended Cement Acceptance Procedure for Qualified and Non-Qualified Plants”.

Portland cement shall be according to ASTM C 150, and shall meet the standard physical and chemical requirements. Type I or Type II may be used for cast-in-place, precast, and precast prestressed concrete. Type III may be used according to Article 1020.04, or when approved by the Engineer. All other cements referenced in ASTM C 150 may be used when approved by the Engineer.

The total of all organic processing additions shall be a maximum of 1.0 percent by weight (mass) of the cement. The total of all inorganic processing additions shall be a maximum of 4.0 percent by weight (mass) of the cement. However, a cement kiln dust inorganic processing addition shall be limited to a maximum of 1.0 percent. Organic processing additions shall be limited to grinding aids that improve the flowability of cement, reduce pack set, and improve grinding efficiency. Inorganic processing additions shall be limited to granulated blast-furnace slag according to the chemical requirements of AASHTO M 302, Class C fly ash according to the chemical requirements of AASHTO M 295, and cement kiln dust.

- (b) Portland-Pozzolan Cement. Acceptance of portland-pozzolan cement shall be according to the current Bureau of Materials and Physical Research's Policy Memorandum, "Portland or Blended Cement Acceptance Procedure for Qualified and Non-Qualified Plants".

Portland-pozzolan cement shall be according to ASTM C 595 and shall meet the standard physical and chemical requirements. Type IP may be used for cast-in-place, precast, and precast prestressed concrete, except when Class PP concrete is used. The pozzolan constituent for Type IP shall be a maximum of 21 percent of the weight (mass) of the portland-pozzolan cement.

For cast-in-place construction, portland-pozzolan cement shall not be used in concrete mixtures when the air temperature is below 40 °F (4 °C) without permission of the Engineer. If permission is given, the mix design strength requirement may require the Contractor to increase the cement or eliminate the cement factor reduction for a water-reducing or high range water-reducing admixture which is permitted according to Article 1020.05(b).

The total of all organic processing additions shall be a maximum of 1.0 percent by weight (mass) of the cement. Organic processing additions shall be limited to grinding aids as defined in (a) above. Inorganic processing additions shall be limited to cement kiln dust at a maximum of 1.0 percent.

- (c) Portland Blast-Furnace Slag Cement. Acceptance of portland blast-furnace slag cement shall be according to the current Bureau of Materials and Physical Research's Policy Memorandum, "Portland or Blended Cement Acceptance Procedure for Qualified and Non-Qualified Plants".

Portland blast-furnace slag cement shall be according to ASTM C 595 and shall meet the standard physical and chemical requirements. Type IS portland blast-furnace slag cement may be used for cast-in-place, precast, and precast prestressed concrete, except when Class PP concrete is used. The blast-furnace slag constituent for Type IS shall be a maximum of 25 percent of the weight (mass) of the portland blast-furnace slag cement.

For cast-in-place construction, portland blast-furnace slag cement shall not be used in concrete mixtures when the air temperature is below 40 °F (4 °C) without permission of the Engineer. If permission is given, the mix design strength requirement may require the Contractor to increase the cement or eliminate the cement factor reduction for a water-reducing or high range water-reducing admixture which is permitted according to Article 1020.05(b).

The total of all organic processing additions shall be a maximum of 1.0 percent by weight (mass) of the cement. Organic processing additions shall be limited to grinding aids as defined in (a) above. Inorganic processing additions shall be limited to cement kiln dust at a maximum of 1.0 percent.

- (d) Rapid Hardening Cement. Rapid hardening cement shall be used according to Article 1020.04 or when approved by the Engineer.

The cement shall be on the Department's current "Approved List of Packaged, Dry, Rapid Hardening Cementitious Materials for Concrete Repairs", and shall be according to the following.

- (1) The cement shall have a maximum final set of 25 minutes, according to Illinois Modified ASTM C 191.
 - (2) The cement shall have a minimum compressive strength of 2000 psi (13,800 kPa) at 3.0 hours, 3200 psi (22,100 kPa) at 6.0 hours, and 4000 psi (27,600 kPa) at 24.0 hours, according to Illinois Modified ASTM C 109.
 - (3) The cement shall have a maximum drying shrinkage of 0.050 percent at seven days, according to Illinois Modified ASTM C 596.
 - (4) The cement shall have a maximum expansion of 0.020 percent at 14 days, according to Illinois Modified ASTM C 1038.
 - (5) The cement shall have a minimum 80 percent relative dynamic modulus of elasticity; and shall not have a weight (mass) gain in excess of 0.15 percent or a weight (mass) loss in excess of 1.0 percent, after 100 cycles, according to AASHTO T 161, Procedure B.
- (e) Calcium Aluminate Cement. Calcium aluminate cement shall be used only where specified by the Engineer. The cement shall meet the standard physical requirements for Type I cement according to ASTM C 150, except the time of setting shall not apply. The chemical requirements shall be determined according to ASTM C 114 and shall be as follows: minimum 38 percent aluminum oxide (Al_2O_3), maximum 42 percent calcium oxide (CaO), maximum 1 percent magnesium oxide (MgO), maximum 0.4 percent sulfur trioxide (SO_3), maximum 1 percent loss on ignition, and maximum 3.5 percent insoluble residue.

1001.02 Uniformity of Color. Cement contained in single loads or in shipments of several loads to the same project shall not have visible differences in color.

1001.03 Mixing Brands and Types. Different brands or different types of cement from the same manufacturing plant, or the same brand or type from different plants shall not be mixed or used alternately in the same item of construction unless approved by the Engineer.

1001.04 Storage. Cement shall be stored and protected against damage, such as dampness which may cause partial set or hardened lumps. Different brands or different types of cement from the same manufacturing plant, or the same brand or type from different plants shall be kept separate."

CONCRETE ADMIXTURES (BDE)

Effective: January 1, 2003

Revised: April 1, 2009

Replace the first paragraph of Article 1020.05(b) of the Standard Specifications to read:

“(b) Admixtures. The use of admixtures to increase the workability or to accelerate the hardening of the concrete will be permitted when approved by the Engineer. Admixture dosages shall result in the mixture meeting the specified plastic and hardened properties. The Department will maintain an Approved List of Corrosion Inhibitors. Corrosion inhibitor dosage rates shall be according to Article 1020.05(b)(12). The Department will also maintain an Approved List of Concrete Admixtures, and an admixture technical representative shall be consulted when determining an admixture dosage from this list. The dosage shall be within the range indicated on the approved list unless the influence by other admixtures, jobsite conditions (such as a very short haul time), or other circumstances warrant a dosage outside the range. The Engineer shall be notified when a dosage is proposed outside the range. To determine an admixture dosage, air temperature, concrete temperature, cement source and quantity, finely divided mineral sources(s) and quantity, influence of other admixtures, haul time, placement conditions, and other factors as appropriate shall be considered. The Engineer may request the Contractor to have a batch of concrete mixed in the lab or field to verify the admixture dosage is correct. An admixture dosage or combination of admixture dosages shall not delay the initial set of concrete by more than one hour. When a retarding admixture is required or appropriate for a bridge deck or bridge deck overlayer pour, the initial set time shall be delayed until the deflections due to the concrete dead load are no longer a concern for inducing cracks in the completed work. However, a retarding admixture shall not be used to further extend the pour time and justify the alteration of a bridge deck pour sequence.

When determining water in admixtures for water/cement ratio, the Contractor shall calculate 70 percent of the admixture dosage as water, except a value of 50 percent shall be used for a latex admixture used in bridge deck latex concrete overlays.”

Revise Section 1021 of the Standard Specifications to read:

“SECTION 1021. CONCRETE ADMIXTURES

1021.01 General. Admixtures shall be furnished in liquid form ready for use. The admixtures shall be delivered in the manufacturer's original containers, bulk tank trucks or such containers or tanks as are acceptable to the Engineer. Delivery shall be accompanied by a ticket which clearly identifies the manufacturer and trade name of the material. Containers shall be readily identifiable as to manufacturer and trade name of the material they contain.

Corrosion inhibitors will be maintained on the Department's Approved List of Corrosion Inhibitors. All other concrete admixture products will be maintained on the Department's Approved List of Concrete Admixtures. For the admixture submittal, a report prepared by an independent laboratory accredited by the AASHTO Materials Reference Laboratory (AMRL) for Portland Cement Concrete shall be provided. The report shall show the results of physical tests conducted no more than five years prior to the time of submittal, according to applicable specifications. However, for corrosion inhibitors the ASTM G 109 test information specified in ASTM C 1582 is not required to be from and independent lab. All other information in ASTM C 1582 shall be from and independent lab.

Tests shall be conducted using materials and methods specified on a "test" concrete and a "reference" concrete, together with a certification that no changes have been made in the formulation of the material since the performance of the tests.

Per the manufacturer's option, the cement content for all required tests shall either be according to applicable specifications or 5.65 cwt/cu yd (335 kg/cu m). Compressive strength test results for six months and one year will not be required.

Prior to the approval of an admixture, the Engineer reserves the right to request a sample for testing. The test and reference concrete mixtures tested by the Engineer will contain a cement content of 5.65 cwt/cu yd (335 kg/cu m). For freeze-thaw testing, the Department will perform the test according to AASHTO T 161, Procedure B. The flexural strength test will be performed according to AASHTO T 177. If the Engineer decides to test the admixture, the manufacturer shall submit AASHTO T 197 water content and set time test results on the standard cement used by the Department. The test and reference concrete mixture shall contain a cement content of 5.65 cwt/cu yd (335 kg/cu m). The manufacturer may select their lab or an independent lab to perform this testing. The laboratory is not required to be accredited by AASHTO.

The manufacturer shall include in the submittal the following admixture information: the manufacturing range for specific gravity, the midpoint and manufacturing range for residue by oven drying, and the manufacturing range for pH. The submittal shall also include an infrared spectrophotometer trace no more than five years old.

For air-entraining admixtures according to Article 1021.02, the specific gravity allowable manufacturing range shall be established by the manufacturer and the test method shall be according to ASTM C 494. For residue by oven drying and pH, the allowable manufacturing range and test methods shall be according to ASTM C 260.

For admixtures according to Articles 1021.03, 1021.04, 1021.05, 1021.06, and 1021.07, the pH allowable manufacturing range shall be established by the manufacturer and the test method shall be according to ASTM E 70. For specific gravity and residue by oven drying, the allowable manufacturing range and test methods shall be according to ASTM C 494.

When test results are more than seven years old, the manufacturer shall re-submit the infrared spectrophotometer trace and the report prepared by an independent laboratory accredited by AASHTO.

All admixtures, except chloride-based accelerators, shall contain a maximum of 0.3 percent chloride by weight (mass).

Random field samples may be taken by the Department to verify an admixture meets specification. A split sample will be provided to the manufacturer if requested. Admixtures that do not meet specification requirements or an allowable manufacturing range established by the manufacturer shall be replaced with new material.

1021.02 Air-Entraining Admixtures. Air-entraining admixtures shall be according to AASHTO M 154.

1021.03 Retarding and Water-Reducing Admixtures. The admixture shall be according to the following.

- (a) The retarding admixture shall be according to AASHTO M 194, Type B (retarding) or Type D (water-reducing and retarding).

- (b) The water-reducing admixture shall be according to AASHTO M 194, Type A.
- (c) The high range water-reducing admixture shall be according to AASHTO M 194, Type F (high range water-reducing) or Type G (high range water-reducing and retarding).

1021.04 Accelerating Admixtures. The admixture shall be according to AASHTO M 194, Type C (accelerating) or Type E (water reducing and accelerating).

1021.05 Self-Consolidating Admixtures. The self-consolidating admixture system shall consist of either a high range water-reducing admixture only or a high range water-reducing admixture combined with a separate viscosity modifying admixture. The one or two component admixture system shall be capable of producing a concrete mixture that can flow around reinforcement and consolidate under its own weight without additional effort and without segregation.

The high range water-reducing admixture shall be according to AASHTO M 194, Type F.

The viscosity modifying admixture shall be according to ASTM C 494, Type S (specific performance).

1021.06 Rheology-Controlling Admixture. The rheology-controlling admixture shall be capable of producing a concrete mixture with a lower yield stress that will consolidate easier for slipform applications used by the Contractor. The rheology-controlling admixture shall be according to ASTM C 494, Type S (specific performance).

1021.07 Corrosion Inhibitor. The corrosion inhibitor shall be according to one of the following.

- (a) Calcium Nitrite. The corrosion inhibitor shall contain a minimum 30 percent calcium nitrite by weight (mass) of solution, and shall comply with the requirements of AASHTO M 194, Type C (accelerating).
- (b) Other Materials. The corrosion inhibitor shall be according to ASTM C 1582.”

CONSTRUCTION AIR QUALITY - DIESEL VEHICLE EMISSIONS CONTROL (BDE)

Effective: April 1, 2009

Revised: July 1, 2009

Diesel Vehicle Emissions Control. The reduction of construction air emissions shall be accomplished by using cleaner burning diesel fuel. The term “equipment” refers to any and all diesel fuel powered devices rated at 50 hp and above, to be used on the project site in excess of seven calendar days over the course of the construction period on the project site (including any “rental” equipment).

All equipment on the jobsite, with engine ratings of 50 hp and above, shall be required to: use Ultra Low Sulfur Diesel fuel (ULSD) exclusively (15 ppm sulfur content or less).

Diesel powered equipment in non-compliance will not be allowed to be used on the project site, and is also subject to a notice of non-compliance as outlined below.

The Contractor shall submit copies of monthly summary reports and include certified copies of the ULSD diesel fuel delivery slips for diesel fuel delivered to the jobsite for the reporting time period, noting the quantity of diesel fuel used.

If any diesel powered equipment is found to be in non-compliance with any portion of this specification, the Engineer will issue the Contractor a notice of non-compliance and identify an appropriate period of time, as outlined below under environmental deficiency deduction, in which to bring the equipment into compliance or remove it from the project site.

Any costs associated with bringing any diesel powered equipment into compliance with these diesel vehicle emissions controls shall be considered as included in the contract unit prices bid for the various items of work involved and no additional compensation will be allowed. The Contractor's compliance with this notice and any associated regulations shall also not be grounds for a claim.

Environmental Deficiency Deduction. When the Engineer is notified, or determines that an environmental control deficiency exists, he/she will notify the Contractor in writing, and direct the Contractor to correct the deficiency within a specified time period. The specified time-period, which begins upon Contractor notification, will be from 1/2 hour to 24 hours long, based on the urgency of the situation and the nature of the deficiency. The Engineer shall be the sole judge regarding the time period.

The deficiency will be based on lack of repair, maintenance and diesel vehicle emissions control.

If the Contractor fails to correct the deficiency within the specified time frame, a daily monetary deduction will be imposed for each calendar day or fraction thereof the deficiency continues to exist. The calendar day(s) will begin when the time period for correction is exceeded and end with the Engineer's written acceptance of the correction. The daily monetary deduction will be \$1,000.00 for each deficiency identified.

If a Contractor or subcontractor accumulates three environmental deficiency deductions in a contract period, the Contractor will be shutdown until the deficiency is corrected. Such a shutdown will not be grounds for any extension of contract time, waiver of penalties, or be grounds for any claim.

CONSTRUCTION AIR QUALITY - IDLING RESTRICTIONS (BDE)

Effective: April 1, 2009

Idling Restrictions. The Contractor shall establish truck-staging areas for all diesel powered vehicles that are waiting to load or unload material at the jobsite. Staging areas shall be located where the diesel emissions from the equipment will have a minimum impact on adjacent sensitive receptors. The Department will review the selection of staging areas, whether within or outside the existing highway right-of-way, to avoid locations near sensitive areas or populations to the extent possible. Sensitive receptors include, but are not limited to, hospitals, schools, residences, motels, hotels, daycare facilities, elderly housing and convalescent facilities. Diesel powered engines shall also be located as far away as possible from fresh air intakes, air conditioners, and windows.

The Engineer will approve staging areas before implementation.

Diesel powered vehicle operators may not cause or allow the motor vehicle, when it is not in motion, to idle for more than a total of 10 minutes within any 60 minute period, except under any of the following circumstances:

- 1) The motor vehicle has a gross vehicle weight rating of less than 8000 lb (3630 kg).
- 2) The motor vehicle idles while forced to remain motionless because of on-highway traffic, an official traffic control device or signal, or at the direction of a law enforcement official.
- 3) The motor vehicle idles when operating defrosters, heaters, air conditioners, or other equipment solely to prevent a safety or health emergency.
- 4) A police, fire, ambulance, public safety, other emergency or law enforcement motor vehicle, or any motor vehicle used in an emergency capacity, idles while in an emergency or training mode and not for the convenience of the vehicle operator.
- 5) The primary propulsion engine idles for maintenance, servicing, repairing, or diagnostic purposes if idling is necessary for such activity.
- 6) A motor vehicle idles as part of a government inspection to verify that all equipment is in good working order, provided idling is required as part of the inspection.
- 7) When idling of the motor vehicle is required to operate auxiliary equipment to accomplish the intended use of the vehicle (such as loading, unloading, mixing, or processing cargo; controlling cargo temperature; construction operations, lumbering operations; oil or gas well servicing; or farming operations), provided that this exemption does not apply when the vehicle is idling solely for cabin comfort or to operate non-essential equipment such as air conditioning, heating, microwave ovens, or televisions.
- 8) When the motor vehicle idles due to mechanical difficulties over which the operator has no control.
- 9) The outdoor temperature is less than 32 °F (0 °C) or greater than 80 °F (26 °C).

When the outdoor temperature is greater than or equal to 32 °F (0 °C) or less than or equal to 80 °F (26 °C), a person who operates a motor vehicle operating on diesel fuel shall not cause or allow the motor vehicle to idle for a period greater than 30 minutes in any 60 minute period while waiting to weigh, load, or unload cargo or freight, unless the vehicle is in a line of vehicles that regularly and periodically moves forward.

The above requirements do not prohibit the operation of an auxiliary power unit or generator set as an alternative to idling the main engine of a motor vehicle operating on diesel fuel.

Environmental Deficiency Deduction. When the Engineer is notified, or determines that an environmental control deficiency exists based on non-compliance with the idling restrictions, he/she will notify the Contractor, and direct the Contractor to correct the deficiency.

If the Contractor fails to correct the deficiency a monetary deduction will be imposed. The monetary deduction will be \$1,000.00 for each deficiency identified.

DISADVANTAGED BUSINESS ENTERPRISE PARTICIPATION (BDE)

Effective: September 1, 2000

Revised: January 1, 2010

FEDERAL OBLIGATION. The Department of Transportation, as a recipient of federal financial assistance, is required to take all necessary and reasonable steps to ensure nondiscrimination in the award and administration of contracts.

Consequently, the federal regulatory provisions of 49 CFR part 26 apply to this contract concerning the utilization of disadvantaged business enterprises. For the purposes of this Special Provision, a disadvantaged business enterprise (DBE) means a business certified by the Department in accordance with the requirements of 49 CFR part 26 and listed in the Illinois Unified Certification Program (IL UCP) DBE Directory.

STATE OBLIGATION. This Special Provision will also be used by the Department to satisfy the requirements of the Business Enterprise for Minorities, Females, and Persons with Disabilities Act, 30 ILCS 575. When this Special Provision is used to satisfy state law requirements on 100 percent state-funded contracts, the federal government has no involvement in such contracts (not a federal-aid contract) and no responsibility to oversee the implementation of this Special Provision by the Department on those contracts. DBE participation on 100 percent state-funded contracts will not be credited toward fulfilling the Department's annual overall DBE goal required by the US Department of Transportation to comply with the federal DBE program requirements.

CONTRACTOR ASSURANCE. The Contractor makes the following assurance and agrees to include the assurance in each subcontract that the Contractor signs with a subcontractor:

The Contractor, subrecipient, or subcontractor shall not discriminate on the basis of race, color, national origin, or sex in the performance of this contract. The Contractor shall carry out applicable requirements of 49 CFR part 26 in the award and administration of contracts funded in whole or in part with federal or state funds. Failure by the Contractor to carry out these requirements is a material breach of this contract, which may result in the termination of this contract or such other remedy as the recipient deems appropriate.

OVERALL GOAL SET FOR THE DEPARTMENT. As a requirement of compliance with 49 CFR part 26, the Department has set an overall goal for DBE participation in its federally assisted contracts. That goal applies to all federal-aid funds the Department will expend in its federally assisted contracts for the subject reporting fiscal year. The Department is required to make a good faith effort to achieve the overall goal. The dollar amount paid to all approved DBE companies performing work called for in this contract is eligible to be credited toward fulfillment of the Department's overall goal.

CONTRACT GOAL TO BE ACHIEVED BY THE CONTRACTOR. This contract includes a specific DBE utilization goal established by the Department. The goal has been included because the Department has determined that the work of this contract has subcontracting opportunities that may be suitable for performance by DBE companies. This determination is based on an assessment of the type of work, the location of the work, and the availability of DBE companies to do a part of the work. The assessment indicates that, in the absence of unlawful discrimination, and in an arena of fair and open competition, DBE companies can be expected to perform **8.0%** of the work. This percentage is set as the DBE participation goal for this contract. Consequently, in addition to the other award criteria established for this contract, the Department will only award this contract to a bidder who makes a good faith effort to meet this goal of DBE participation in the performance of the work. A bidder makes a good faith effort for award consideration if either of the following is done in accordance with the procedures set forth in this Special Provision:

(a) The bidder documents that enough DBE participation has been obtained to meet the goal; or

(b) The bidder documents that a good faith effort has been made to meet the goal, even though the effort did not succeed in obtaining enough DBE participation to meet the goal.

DBE LOCATOR REFERENCES. Bidders may consult the IL UCP DBE Directory as a reference source for DBE-certified companies. In addition, the Department maintains a letting and item specific DBE locator information system whereby DBE companies can register their interest in providing quotes on particular bid items advertised for letting. Information concerning DBE companies willing to quote work for particular contracts may be obtained by contacting the Department's Bureau of Small Business Enterprises at telephone number (217)785-4611, or by visiting the Department's web site at www.dot.il.gov.

BIDDING PROCEDURES. Compliance with this Special Provision is a material bidding requirement. The failure of the bidder to comply will render the bid not responsive.

(a) The bidder shall submit a Disadvantaged Business Utilization Plan on Department forms SBE 2025 and 2026 with the bid.

(b) The Utilization Plan shall indicate that the bidder either has obtained sufficient DBE participation commitments to meet the contract goal or has not obtained enough DBE participation commitments in spite of a good faith effort to meet the goal. The Utilization Plan shall further provide the name, telephone number, and telefax number of a responsible official of the bidder designated for purposes of notification of plan approval or disapproval under the procedures of this Special Provision.

(c) The Utilization Plan shall include a DBE Participation Commitment Statement, Department form SBE 2025, for each DBE proposed for the performance of work to achieve the contract goal. For bidding purposes, submission of the completed SBE 2025 forms, signed by the DBEs and faxed to the bidder will be acceptable as long as the original is available and provided upon request. All elements of information indicated on the said form shall be provided, including but not limited to the following:

(1)The names and addresses of DBE firms that will participate in the contract;

(2)A description, including pay item numbers, of the work each DBE will perform;

(3)The dollar amount of the participation of each DBE firm participating. The dollar amount of participation for identified work shall specifically state the quantity, unit price, and total subcontract price for the work to be completed by the DBE. If partial pay items are to be performed by the DBE, indicate the portion of each item, a unit price where appropriate and the subcontract price amount;

(4)DBE Participation Commitment Statements, form SBE 2025, signed by the bidder and each participating DBE firm documenting the commitment to use the DBE subcontractors whose participation is submitted to meet the contract goal;

(5)If the bidder is a joint venture comprised of DBE companies and non-DBE companies, the plan must also include a clear identification of the portion of the work to be performed by the DBE partner(s); and,

(6) If the contract goal is not met, evidence of good faith efforts.

GOOD FAITH EFFORT PROCEDURES. The contract will not be awarded until the Utilization Plan submitted by the apparent successful bidder is approved. All information submitted by the bidder must be complete, accurate and adequately document the good faith efforts of the bidder before the Department will commit to the performance of the contract by the bidder. The Utilization Plan will be approved by the Department if the Utilization Plan commits sufficient commercially useful DBE work performance to meet the contract goal or the bidder submits sufficient documentation of a good faith effort to meet the contract goal pursuant to 49 CFR part 26, Appendix A. The Utilization Plan will not be approved by the Department if the Utilization Plan does not commit sufficient DBE participation to meet the contract goal unless the apparent successful bidder documented in the Utilization Plan that it made a good faith effort to meet the goal. This means that the bidder must show that all necessary and reasonable steps were taken to achieve the contract goal. Necessary and reasonable steps are those which, by their scope, intensity and appropriateness to the objective, could reasonably be expected to obtain sufficient DBE participation, even if they were not successful. The Department will consider the quality, quantity, and intensity of the kinds of efforts that the bidder has made. Mere *pro forma* efforts, in other words, efforts done as a matter of form, are not good faith efforts; rather, the bidder is expected to have taken genuine efforts that would be reasonably expected of a bidder actively and aggressively trying to obtain DBE participation sufficient to meet the contract goal.

(a) The following is a list of types of action that the Department will consider as part of the evaluation of the bidder's good faith efforts to obtain participation. These listed factors are not intended to be a mandatory checklist and are not intended to be exhaustive. Other factors or efforts brought to the attention of the Department may be relevant in appropriate cases, and will be considered by the Department.

(1) Soliciting through all reasonable and available means (e.g. attendance at pre-bid meetings, advertising and/or written notices) the interest of all certified DBE companies that have the capability to perform the work of the contract. The bidder must solicit this interest within sufficient time to allow the DBE companies to respond to the solicitation. The bidder must determine with certainty if the DBE companies are interested by taking appropriate steps to follow up initial solicitations.

(2) Selecting portions of the work to be performed by DBE companies in order to increase the likelihood that the DBE goals will be achieved. This includes, where appropriate, breaking out contract work items into economically feasible units to facilitate DBE participation, even when the prime Contractor might otherwise prefer to perform these work items with its own forces.

(3) Providing interested DBE companies with adequate information about the plans, specifications, and requirements of the contract in a timely manner to assist them in responding to a solicitation.

(4) a. Negotiating in good faith with interested DBE companies. It is the bidder's responsibility to make a portion of the work available to DBE subcontractors and suppliers and to select those portions of the work or material needs consistent with the available DBE subcontractors and suppliers, so as to facilitate DBE participation.

Evidence of such negotiation includes the names, addresses, and telephone numbers of DBE companies that were considered; a description of the information provided regarding the plans and specifications for the work selected for subcontracting; and evidence as to why additional agreements could not be reached for DBE companies to perform the work.

b. A bidder using good business judgment would consider a number of factors in negotiating with subcontractors, including DBE subcontractors, and would take a firm's price and capabilities as well as contract goals into consideration. However, the fact that there may be some additional costs involved in finding and using DBE companies is not in itself sufficient reason for a bidder's failure to meet the contract DBE goal, as long as such costs are reasonable. Also, the ability or desire of a bidder to perform the work of a contract with its own organization does not relieve the bidder of the responsibility to make good faith efforts. Bidders are not, however, required to accept higher quotes from DBE companies if the price difference is excessive or unreasonable.

(5) Not rejecting DBE companies as being unqualified without sound reasons based on a thorough investigation of their capabilities. The bidder's standing within its industry, membership in specific groups, organizations, or associations and political or social affiliations (for example union vs. non-union employee status) are not legitimate causes for the rejection or non-solicitation of bids in the bidder's efforts to meet the project goal.

(6) Making efforts to assist interested DBE companies in obtaining bonding, lines of credit, or insurance as required by the recipient or Contractor.

(7) Making efforts to assist interested DBE companies in obtaining necessary equipment, supplies, materials, or related assistance or services.

(8) Effectively using the services of available minority/women community organizations; minority/women contractors' groups; local, state, and federal minority/women business assistance offices; and other organizations as allowed on a case-by-case basis to provide assistance in the recruitment and placement of DBE companies.

(b) If the Department determines that the apparent successful bidder has made a good faith effort to secure the work commitment of DBE companies to meet the contract goal, the Department will award the contract provided that it is otherwise eligible for award. If the Department determines that the bidder has failed to meet the requirements of this Special Provision and that a good faith effort has not been made, the Department will notify the responsible company official designated in the Utilization Plan that the bid is not responsive. The notification shall include a statement of reasons why good faith efforts have not been found.

(c) The bidder may request administrative reconsideration of a determination adverse to the bidder within the five working days after receipt of the notification date of the determination by delivering the request to the Department of Transportation, Bureau of Small Business Enterprises, Contract Compliance Section, 2300 South Dirksen Parkway, Room 319, Springfield, Illinois 62764 (Telefax: (217)785-1524). Deposit of the request in the United States mail on or before the fifth business day shall not be deemed delivery. The determination shall become final if a request is not made and delivered. A request may provide additional written documentation and/or argument concerning the issue of whether an adequate good faith effort was made to meet the contract goal.

The request will be forwarded to the Department's Reconsideration Officer. The Reconsideration Officer will extend an opportunity to the bidder to meet in person in order to consider all issues of whether the bidder made a good faith effort to meet the goal. After the review by the Reconsideration Officer, the bidder will be sent a written decision within ten working days after receipt of the request for reconsideration, explaining the basis for finding that the bidder did or did not meet the goal or make adequate good faith efforts to do so. A final decision by the Reconsideration Officer that a good faith effort was made shall approve the Utilization Plan submitted by the bidder and shall clear the contract for award. A final decision that a good faith effort was not made shall render the bid not responsive.

CALCULATING DBE PARTICIPATION. The Utilization Plan values represent work anticipated to be performed and paid for upon satisfactory completion. The Department is only able to count toward the achievement of the overall goal and the contract goal the value of payments made for the work actually performed by DBE companies. In addition, a DBE must perform a commercially useful function on the contract to be counted. A commercially useful function is generally performed when the DBE is responsible for the work and is carrying out its responsibilities by actually performing, managing, and supervising the work involved. The Department and Contractor are governed by the provisions of 49 CFR part 26.55(c) on questions of commercially useful functions as it affects the work. Specific counting guidelines are provided in 49 CFR part 26.55, the provisions of which govern over the summary contained herein.

(a) DBE as the Contractor: 100 percent goal credit for that portion of the work performed by the DBE's own forces, including the cost of materials and supplies. Work that a DBE subcontracts to a non-DBE does not count toward the DBE goals.

(b) DBE as a joint venture Contractor: 100 percent goal credit for that portion of the total dollar value of the contract equal to the distinct, clearly defined portion of the work performed by the DBE's own forces.

(c) DBE as a subcontractor: 100 percent goal credit for the work of the subcontract performed by the DBE's own forces, including the cost of materials and supplies, excluding the purchase of materials and supplies or the lease of equipment by the DBE subcontractor from the prime Contractor or its affiliates. Work that a DBE subcontractor in turn subcontracts to a non-DBE does not count toward the DBE goal.

(d) DBE as a trucker: 100 percent goal credit for trucking participation provided the DBE is responsible for the management and supervision of the entire trucking operation for which it is responsible. At least one truck owned, operated, licensed, and insured by the DBE must be used on the contract. Credit will be given for the following:

(1) The DBE may lease trucks from another DBE firm, including an owner-operator who is certified as a DBE. The DBE who leases trucks from another DBE receives credit for the total value of the transportation services the lessee DBE provides on the contract.

(2) The DBE may also lease trucks from a non-DBE firm, including from an owner-operator. The DBE who leases trucks from a non-DBE is entitled to credit only for the fee or commission it receives as a result of the lease arrangement.

(e) DBE as a material supplier:

- (1) 60 percent goal credit for the cost of the materials or supplies purchased from a DBE regular dealer.
- (2) 100 percent goal credit for the cost of materials or supplies obtained from a DBE manufacturer.
- (3) 100 percent credit for the value of reasonable fees and commissions for the procurement of materials and supplies if not a regular dealer or manufacturer.

CONTRACT COMPLIANCE. Compliance with this Special Provision is an essential part of the contract. The Department is prohibited by federal regulations from crediting the participation of a DBE included in the Utilization Plan toward either the contract goal or the Department's overall goal until the amount to be applied toward the goals has been paid to the DBE. The following administrative procedures and remedies govern the compliance by the Contractor with the contractual obligations established by the Utilization Plan. After approval of the Utilization Plan and award of the contract, the Utilization Plan and individual DBE Participation Statements become part of the contract. If the Contractor did not succeed in obtaining enough DBE participation to achieve the advertised contract goal, and the Utilization Plan was approved and contract awarded based upon a determination of good faith, the total dollar value of DBE work calculated in the approved Utilization Plan as a percentage of the awarded contract value shall become the amended contract goal.

(a) No amendment to the Utilization Plan may be made without prior written approval from the Department's Bureau of Small Business Enterprises. All requests for amendment to the Utilization Plan shall be submitted to the Department of Transportation, Bureau of Small Business Enterprises, Contract Compliance Section, 2300 South Dirksen Parkway, Room 319, Springfield, Illinois 62764. Telephone number (217) 785-4611. Telefax number (217) 785-1524.

(b) The Contractor must notify and obtain written approval from the Department's Bureau of Small Business Enterprises prior to replacing a DBE or making any change in the participation of a DBE. Approval for replacement will be granted only if it is demonstrated that the DBE is unable or unwilling to perform. The Contractor must make every good faith effort to find another certified DBE subcontractor to substitute for the original DBE. The good faith efforts shall be directed at finding another DBE to perform at least the same amount of work under the contract as the original DBE, to the extent needed to meet the contract goal.

(c) Any deviation from the DBE condition-of-award or contract specifications must be approved, in writing, by the Department. The Contractor shall notify affected DBEs in writing of any changes in the scope of work which result in a reduction in the dollar amount condition-of-award to the contract.

(d) In addition to the above requirements for reductions in the condition of award, additional requirements apply to the two cases of Contractor-initiated work substitution proposals. Where the contract allows alternate work methods which serve to delete or create underruns in condition of award DBE work, and the Contractor selects that alternate method or, where the Contractor proposes a substitute work method or material that serves to diminish or delete work committed to a DBE and replace it with other work, then the Contractor must demonstrate one of the following:

- (1) That the replacement work will be performed by the same DBE (as long as the DBE is certified in the respective item of work) in a modification of the condition of award; or
- (2) That the DBE is aware that its work will be deleted or will experience underruns and has agreed in writing to the change. If this occurs, the Contractor shall substitute other work of equivalent value to a certified DBE or provide documentation of good faith efforts to do so; or
- (3) That the DBE is not capable of performing the replacement work or has declined to perform the work at a reasonably competitive price. If this occurs, the Contractor shall substitute other work of equivalent value to a certified DBE or provide documentation of good faith efforts to do so.

(e) Where the revision includes work committed to a new DBE subcontractor, not previously involved in the project, then a Request for Approval of Subcontractor, Department form BC 260A, must be signed and submitted.

(f) If the commitment of work is in the form of additional tasks assigned to an existing subcontract, then a new Request for Approval of Subcontractor shall not be required. However, the Contractor must document efforts to assure that the existing DBE subcontractor is capable of performing the additional work and has agreed in writing to the change.

(g) All work indicated for performance by an approved DBE shall be performed, managed, and supervised by the DBE executing the Participation Statement. The Contractor shall not terminate for convenience a DBE listed in the Utilization Plan and then perform the work of the terminated DBE with its own forces, those of an affiliate or those of another subcontractor, whether DBE or not, without first obtaining the written consent of the Bureau of Small Business Enterprises to amend the Utilization Plan. The Contractor shall notify the Bureau of Small Business Enterprises of any termination for reasons other than convenience, and shall obtain approval for inclusion of the substitute DBE in the Utilization Plan. If good faith efforts following a termination of a DBE for cause are not successful, the Contractor shall contact the Bureau of Small Business Enterprises and provide a full accounting of the efforts undertaken to obtain substitute DBE participation. The Bureau of Small Business Enterprises will evaluate the good faith efforts in light of all circumstances surrounding the performance status of the contract, and determine whether the contract goal should be amended.

(h) The Contractor shall maintain a record of payments for work performed to the DBE participants. The records shall be made available to the Department for inspection upon request. After the performance of the final item of work or delivery of material by a DBE and final payment therefore to the DBE by the Contractor, but not later than thirty calendar days after payment has been made by the Department to the Contractor for such work or material, the Contractor shall submit a DBE Payment Agreement on Department form SBE 2115 to the Regional Engineer. If full and final payment has not been made to the DBE, the DBE Payment Agreement shall indicate whether a disagreement as to the payment required exists between the Contractor and the DBE or if the Contractor believes that the work has not been satisfactorily completed. If the Contractor does not have the full amount of work indicated in the Utilization Plan performed by the DBE companies indicated in the Utilization Plan and after good faith efforts are reviewed, the Department may deduct from contract payments to the Contractor the amount of the goal not achieved as liquidated and ascertained damages. The Contractor may request an administrative reconsideration of any amount deducted as damages pursuant to subsection (j) of this part.

(i) The Department reserves the right to withhold payment to the Contractor to enforce the provisions of this Special Provision. Final payment shall not be made on the contract until such time as the Contractor submits sufficient documentation demonstrating achievement of the goal in accordance with this Special Provision or after liquidated damages have been determined and collected.

(j) Notwithstanding any other provision of the contract, including but not limited to Article 109.09 of the Standard Specifications, the Contractor may request administrative reconsideration of a decision to deduct the amount of the goal not achieved as liquidated damages. A request to reconsider shall be delivered to the Contract Compliance Section and shall be handled and considered in the same manner as set forth in paragraph (c) of "Good Faith Effort Procedures" of this Special Provision, except a final decision that a good faith effort was not made during contract performance to achieve the goal agreed to in the Utilization Plan shall be the final administrative decision of the Department.

EQUIPMENT RENTAL RATES (BDE)

Effective: August 2, 2007

Revised: January 2, 2008

Replace the second and third paragraphs of Article 105.07(b)(4)a. of the Standard Specifications with the following:

"Equipment idled which cannot be used on other work, and which is authorized to standby on the project site by the Engineer, will be paid for according to Article 109.04(b)(4)."

Replace Article 109.04(b)(4) of the Standard Specifications with the following:

"(4) Equipment. Equipment used for extra work shall be authorized by the Engineer. The equipment shall be specifically described, be of suitable size and capacity for the work to be performed, and be in good operating condition. For such equipment, the Contractor will be paid as follows.

- a. Contractor Owned Equipment. Contractor owned equipment will be paid for by the hour using the applicable FHWA hourly rate from the "Equipment Watch Rental Rate Blue Book" (Blue Book) in effect when the force account work begins. The FHWA hourly rate is calculated as follows.

$$\text{FHWA hourly rate} = (\text{monthly rate}/176) \times (\text{model year adj.}) \times (\text{Illinois adj.}) + \text{EOC}$$

Where: EOC = Estimated Operating Costs per hour (from the Blue Book)

The time allowed will be the actual time the equipment is operating on the extra work. For the time required to move the equipment to and from the site of the extra work and any authorized idle (standby) time, payment will be made at the following hourly rate: $0.5 \times (\text{FHWA hourly rate} - \text{EOC})$.

All time allowed shall fall within the working hours authorized for the extra work.

The rates above include the cost of fuel, oil, lubrication, supplies, small tools, necessary attachments, repairs, overhaul and maintenance of any kind, depreciation, storage, overhead, profits, insurance, and all incidentals. The rates do not include labor.

The Contractor shall submit to the Engineer sufficient information for each piece of equipment and its attachments to enable the Engineer to determine the proper equipment category. If a rate is not established in the Blue Book for a particular piece of equipment, the Engineer will establish a rate for that piece of equipment that is consistent with its cost and use in the industry.

- b. Rented Equipment. Whenever it is necessary for the Contractor to rent equipment to perform extra work, the rental and transportation costs of the equipment plus five percent for overhead will be paid. In no case shall the rental rates exceed those of established distributors or equipment rental agencies.

All prices shall be agreed to in writing before the equipment is used.”

HOT-MIX ASPHALT – ANTI-STRIPPING ADDITIVE (BDE)

Effective: November 1, 2009

Revise the first and second paragraphs of Article 1030.04(c) of the Standard Specifications to read:

“(c) Determination of Need for Anti-Stripping Additive. The mixture designer shall determine if an additive is needed in the mix to prevent stripping. The determination will be made on the basis of tests performed according to Illinois Modified AASHTO T 283. To be considered acceptable by the Department as a mixture not susceptible to stripping, the conditioned to unconditioned split tensile strength ratio (TSR) shall be equal to or greater than 0.85 for 6 in. (150 mm) specimens. Mixtures, either with or without an additive, with TSRs less than 0.85 for 6 in. (150 mm) specimens will be considered unacceptable. Also, the conditioned tensile strength for mixtures containing an anti-strip additive shall not be lower than the original conditioned tensile strength determined for the same mixture without the anti-strip additive.

If it is determined that an additive is required, the additive may be hydrated lime, slaked quicklime, or a liquid additive, at the Contractor's option.”

HOT-MIX ASPHALT - DENSITY TESTING OF LONGITUDINAL JOINTS (BDE)

Effective: January 1, 2010

Description. This work shall consist of testing the density of longitudinal joints as part of the quality control/quality assurance (QC/QA) of hot-mix asphalt (HMA). Work shall be according to Section 1030 of the Standard Specifications except as follows.

Quality Control/Quality Assurance (QC/QA). Delete the second and third sentence of the third paragraph of Article 1030.05(d)(3) of the Standard Specifications.

Add the following paragraphs to the end of Article 1030.05(d)(3) of the Standard Specifications:

“Longitudinal joint density testing shall be performed at each random density test location. Longitudinal joint testing shall be located at a distance equal to the lift thickness or a minimum of 2 in. (50 mm), from each pavement edge. (i.e. for a 4 in. (100 mm) lift the near edge of the density gauge or core barrel shall be within 4 in. (100 mm) from the edge of pavement.) Longitudinal joint density testing shall be performed using either a correlated nuclear gauge or cores.

- a. Confined Edge. Each confined edge density shall be represented by a one-minute nuclear density reading or a core density and shall be included in the average of density readings or core densities taken across the mat which represents the Individual Test.
- b. Unconfined Edge. Each unconfined edge joint density shall be represented by an average of three one-minute density readings or a single core density at the given density test location and shall meet the density requirements specified herein. The three one-minute readings shall be spaced ten feet apart longitudinally along the unconfined pavement edge and centered at the random density test location.”

Revise the Density Control Limits table in Article 1030.05(d)(4) of the Standard Specifications to read:

“Mixture Composition	Parameter	Individual Test (includes confined edges)	Unconfined Edge Joint Density Minimum
IL-9.5, IL-12.5	Ndesign ≥ 90	92.0 – 96.0%	90.0%
IL-9.5,IL-9.5L, IL-12.5	Ndesign < 90	92.5 – 97.4%	90.0%
IL-19.0, IL-25.0	Ndesign ≥ 90	93.0 – 96.0%	90.0%
IL-19.0, IL-19.0L, IL-25.0	Ndesign < 90	93.0 – 97.4%	90.0%
SMA	Ndesign = 50 & 80	93.5 – 97.4%	91.0%
All Other	Ndesign = 30	93.0 - 97.4%	90.0%”

HOT-MIX ASPHALT – DROP-OFFS (BDE)

Effective: January 1, 2010

Revise the third paragraph of Article 701.07 of the Standard Specifications to read:

“At locations where construction operations result in a differential in elevation exceeding 3 in. (75 mm) between the edge of pavement or edge of shoulder within 3 ft (900 mm) of the edge of the pavement and the earth or aggregate shoulders, Type I or II barricades or vertical panels shall be placed at 100 ft (30 m) centers on roadways where the posted speed limit is 45 mph or greater and at 50 ft (15 m) centers on roadways where the posted speed limit is less than 45 mph.”

HOT-MIX ASPHALT - FINE AGGREGATE (BDE)

Effective: April 1, 2010

Add the following to the gradation tables of Article 1003.01(c) of the Standard Specifications:

"FINE AGGREGATE GRADATIONS					
Grad No.	Sieve Size and Percent Passing				
	3/8	No. 4	No. 8	No. 16	No. 200
FA 22	100	6/	6/	8±8	2±2

FINE AGGREGATE GRADATIONS (Metric)					
Grad No.	Sieve Size and Percent Passing				
	9.5 mm	4.75 mm	2.36 mm	1.18 mm	75 µm
FA 22	100	6/	6/	8±8	2±2

6/ For the fine aggregate gradation FA 22, the aggregate producer shall set the midpoint percent passing, and the Department will apply a range of ± ten percent. The midpoint shall not be changed without Department approval."

Revise Article 1003.03(a) of the Standard Specifications to read:

"(a) Description. Fine aggregate for HMA shall consist of sand, stone sand, chats, slag sand, or steel slag sand. For gradation FA 22, uncrushed material will not be permitted."

Revise Article 1003.03(c) of the Standard Specifications to read:

"(c) Gradation. The fine aggregate gradation for all HMA shall be FA 1, FA 2, FA 20, FA 21, or FA 22.

Gradation FA 1, FA 2, or FA 3 shall be used when required for prime coat aggregate application for HMA."

HOT-MIX ASPHALT – PLANT TEST FREQUENCY (BDE)

Effective: April 1, 2008

Revised: January 1, 2010

Revise the table in Article 1030.05(d)(2)a. of the Standard Specifications to read:

"Parameter	Frequency of Tests		Frequency of Tests All Other Mixtures	Test Method See Manual of Test Procedures for Materials
	High ESAL Mixture	Low ESAL Mixture		
Aggregate Gradation % passing sieves: 1/2 in. (12.5 mm), No. 4 (4.75 mm), No. 8 (2.36 mm), No. 30 (600 µm) No. 200 (75 µm) Note 1.	1 washed ignition oven test on the mix per half day of production Note 4.	1 washed ignition oven test on the mix per day of production Note 4.	Illinois Procedure	

Asphalt Binder Content by Ignition Oven Note 2.	1 per half day of production	1 per day	Illinois-Modified AASHTO T 308
VMA Note 3.	Day's production \geq 1200 tons: 1 per half day of production	N/A	Illinois Modified AASHTO R 35
	Day's production < 1200 tons: 1 per half day of production for first 2 days and 1 per day thereafter (first sample of the day)		
Air Voids Bulk Specific Gravity of Gyratory Sample	Day's production \geq 1200 tons: 1 per half day of production	1 per day	Illinois-Modified AASHTO T 312
	Day's production < 1200 tons: 1 per half day of production for first 2 days and 1 per day thereafter (first sample of the day)		
Maximum Specific Gravity of Mixture	Day's production \geq 1200 tons: 1 per half day of production	1 per day	Illinois-Modified AASHTO T 209
	Day's production < 1200 tons: 1 per half day of production for first 2 days and 1 per day thereafter (first sample of the day)		

Note 1. The No. 8 (2.36 mm) and No. 30 (600 μ m) sieves are not required for All Other Mixtures.

Note 2. The Engineer may waive the ignition oven requirement for asphalt binder content if the aggregates to be used are known to have ignition asphalt binder content calibration factors which exceed 1.5 percent. If the ignition oven requirement is waived, other Department approved methods shall be used to determine the asphalt binder content.

Note 3. The G_{sb} used in the voids in the mineral aggregate (VMA) calculation shall be the same average G_{sb} value listed in the mix design.

Note 4. The Engineer reserves the right to require additional hot bin gradations for batch plants if control problems are evident.”

HOT-MIX ASPHALT – QC/QA ACCEPTANCE CRITERIA (BDE)

Effective: January 1, 2010

Revise Article 1030.05(f)(3) of the Standard Specifications to read:

“(3) Department assurance tests for voids, field VMA, and density.”

HOT-MIX ASPHALT – TRANSPORTATION (BDE)

Effective: April 1, 2008

Revise Article 1030.08 of the Standard Specifications to read:

“1030.08 Transportation. Vehicles used in transporting HMA shall have clean and tight beds. The beds shall be sprayed with asphalt release agents from the Department’s approved list. In lieu of a release agent, the Contractor may use a light spray of water with a light scatter of manufactured sand (FA 20 or FA 21) evenly distributed over the bed of the vehicle. After spraying, the bed of the vehicle shall be in a completely raised position and it shall remain in this position until all excess asphalt release agent or water has been drained.

When the air temperature is below 60 °F (15 °C), the bed, including the end, endgate, sides and bottom shall be insulated with fiberboard, plywood or other approved insulating material and shall have a thickness of not less than 3/4 in (20 mm). When the insulation is placed inside the bed, the insulation shall be covered with sheet steel approved by the Engineer. Each vehicle shall be equipped with a cover of canvas or other suitable material meeting the approval of the Engineer which shall be used if any one of the following conditions is present.

- (a) Ambient air temperature is below 60 °F (15 °C).
- (b) The weather is inclement.
- (c) The temperature of the HMA immediately behind the paver screed is below 250 °F (120 °C).

The cover shall extend down over the sides and ends of the bed for a distance of approximately 12 in. (300 mm) and shall be fastened securely. The covering shall be rolled back before the load is dumped into the finishing machine.”

LIQUIDATED DAMAGES (BDE)

Effective: April 1, 2009

Revise the table in Article 108.09 of the Standard Specifications to read:

“Schedule of Deductions for Each Day of Overrun in Contract Time			
Original Contract Amount		Daily Charges	
From More Than	To and Including	Calendar Day	Work Day
\$ 0	\$ 100,000	\$ 375	\$ 500
100,000	500,000	625	875
500,000	1,000,000	1,025	1,425
1,000,000	3,000,000	1,125	1,550
3,000,000	5,000,000	1,425	1,950
5,000,000	10,000,000	1,700	2,350
10,000,000	And over	3,325	4,650”

MULTILANE PAVEMENT PATCHING (BDE)

Effective: November 1, 2002

Pavement broken and holes opened for patching shall be completed prior to weekend or holiday periods. Should delays of any type or for any reason prevent the completion of the work, temporary patches shall be constructed. Material able to support the average daily traffic and meeting the approval of the Engineer shall be used for the temporary patches. The cost of furnishing, placing, maintaining, removing and disposing of the temporary work, including traffic control, shall be the responsibility of the Contractor.

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM / EROSION AND SEDIMENT CONTROL DEFICIENCY DEDUCTION (BDE)

Effective: April 1, 2007

Revised: November 1, 2009

Revise Article 105.03(a) of the Standard Specifications to read:

“(a) National Pollutant Discharge Elimination System (NPDES) / Erosion and Sediment Control Deficiency Deduction When the Engineer is notified or determines an erosion and/or sediment control deficiency(s) exists, or the Contractor’s activities represents a violation of the Department’s NPDES permits, the Engineer will notify and direct the Contractor to correct the deficiency within a specified time. The specified time, which begins upon notification to the Contractor, will be from 1/2 hour to 1 week based on the urgency of the situation and the nature of the work effort required. The Engineer will be the sole judge.

A deficiency may be any lack of repair, maintenance, or implementation of erosion and/or sediment control devices included in the contract, or any failure to comply with the conditions of the Department’s NPDES permits. A deficiency may also be applied to situations where corrective action is not an option such as the failure to participate in a jobsite inspection of the project, failure to install required measures prior to initiating earth moving operations, disregard of concrete washout requirements, or other disregard of the NPDES permit.

If the Contractor fails to correct a deficiency within the specified time, a daily monetary deduction will be imposed for each calendar day or portion of a calendar day until the deficiency is corrected to the satisfaction of the Engineer. The calendar day(s) will begin with notification to the Contractor and end with the Engineer’s acceptance of the correction. The base value of the daily monetary deduction is \$1000.00 and will be applied to each location for which a deficiency exists. The value of the deficiency deduction assessed for each infraction will be determined by multiplying the base value by a Gravity Adjustment Factor provided in Table A. Except for failure to participate in a required jobsite inspection of the project prior to initiating earthmoving operations which will be based on the total acreage of planned disturbance at the following multipliers: <5 Acres: 1; 5-10 Acres: 2; >10-25 Acres: 3; >25 Acres: 5. For those deficiencies where corrective action was not an option, the monetary deduction will be immediate and will be valued at one calendar day multiplied by a Gravity Adjustment Factor.

Table A Deficiency Deduction Gravity Adjustment Factors				
Types of Violations	Soil Disturbed and Not Permanently Stabilized At Time of Violation			
	< 5 Acres	5 - 10 Acres	>10 - 25 Acres	> 25 Acres
Failure to Install or Properly Maintain BMP	0.1 - 0.5	0.2 - 1.0	0.5 - 2.5	1.0 - 5
Careless Destruction of BMP	0.2 - 1	0.5 - 2.5	1.0 - 5.	1.0 - 5
Intrusion into Protected Resource	1.0 - 5	1.0 - 5	2.0 - 10	2.0 - 10
Failure to properly manage Chemicals, Concrete Washouts or Residuals, Litter or other Wastes	0.2 - 1	0.2 - 1	0.5 - 2.5	1.0 - 5
Improper Vehicle and Equipment Maintenance, Fueling or Cleaning	0.1 - 0.5	0.2 - 1	0.2 - 1	0.5 - 2.5
Failure to Provide or Update Written or Graphic Plans Required by SWPPP	0.2 - 1	0.5 - 2.5	1.0 - 5	1.0 - 5
Failure to comply with Other Provisions of the NPDES Permit	0.1 - 0.5	0.2 - 1	0.2 - 1	0.5 - 2.5"

PAVEMENT PATCHING (BDE)

Effective: January 1, 2010

Revise the first sentence of the second paragraph of Article 701.17(e)(1) of the Standard Specifications to read:

“In addition to the traffic control and protection shown elsewhere in the contract for pavement, two devices shall be placed immediately in front of each open patch, open hole, and broken pavement where temporary concrete barriers are not used to separate traffic from the work area.”

PAYMENTS TO SUBCONTRACTORS (BDE)

Effective: June 1, 2000

Revised: January 1, 2006

Federal regulations found at 49 CFR §26.29 mandate the Department to establish a contract clause to require Contractors to pay subcontractors for satisfactory performance of their subcontracts and to set the time for such payments.

State law also addresses the timing of payments to be made to subcontractors and material suppliers. Section 7 of the Prompt Payment Act, 30 ILCS 540/7, requires that when a Contractor receives any payment from the Department, the Contractor shall make corresponding, proportional payments to each subcontractor and material supplier performing work or supplying material within 15 calendar days after receipt of the Department payment. Section 7 of the Act further provides that interest in the amount of two percent per month, in addition to the payment due, shall be paid to any subcontractor or material supplier by the Contractor if the payment required by the Act is withheld or delayed without reasonable cause.

The Act also provides that the time for payment required and the calculation of any interest due applies to transactions between subcontractors and lower-tier subcontractors and material suppliers throughout the contracting chain.

This Special Provision establishes the required federal contract clause, and adopts the 15 calendar day requirement of the State Prompt Payment Act for purposes of compliance with the federal regulation regarding payments to subcontractors. This contract is subject to the following payment obligations.

When progress payments are made to the Contractor according to Article 109.07 of the Standard Specifications, the Contractor shall make a corresponding payment to each subcontractor and material supplier in proportion to the work satisfactorily completed by each subcontractor and for the material supplied to perform any work of the contract. The proportionate amount of partial payment due to each subcontractor and material supplier throughout the contracting chain shall be determined by the quantities measured or otherwise determined as eligible for payment by the Department and included in the progress payment to the Contractor. Subcontractors and material suppliers shall be paid by the Contractor within 15 calendar days after the receipt of payment from the Department. The Contractor shall not hold retainage from the subcontractors. These obligations shall also apply to any payments made by subcontractors and material suppliers to their subcontractors and material suppliers; and to all payments made to lower tier subcontractors and material suppliers throughout the contracting chain. Any payment or portion of a payment subject to this provision may only be withheld from the subcontractor or material supplier to whom it is due for reasonable cause.

This Special Provision does not create any rights in favor of any subcontractor or material supplier against the State or authorize any cause of action against the State on account of any payment, nonpayment, delayed payment, or interest claimed by application of the State Prompt Payment Act. The Department will not approve any delay or postponement of the 15 day requirement except for reasonable cause shown after notice and hearing pursuant to Section 7(b) of the State Prompt Payment Act. State law creates other and additional remedies available to any subcontractor or material supplier, regardless of tier, who has not been paid for work properly performed or material furnished. These remedies are a lien against public funds set forth in Section 23(c) of the Mechanics Lien Act, 770 ILCS 60/23(c), and a recovery on the Contractor's payment bond according to the Public Construction Bond Act, 30 ILCS 550.

PERSONAL PROTECTIVE EQUIPMENT (BDE)

Effective: November 1, 2008

Revise the first sentence of Article 701.12 of the Standard Specifications to read:

“All personnel on foot, excluding flaggers, within the highway right-of-way shall wear a fluorescent orange, fluorescent yellow/green, or a combination of fluorescent orange and fluorescent yellow/green vest meeting the requirements of ANSI/ISEA 107-2004 for Conspicuity Class 2 garments.”

RAISED REFLECTIVE PAVEMENT MARKERS (BDE)

Effective: November 1, 2009

Revised: April 1, 2010

Revise the first sentence of the second paragraph of Article 781.03(a) of the Standard Specifications to read:

“The pavement shall be cut to match the bottom contour of the marker using a concrete saw fitted with 18 and 20 in. (450 and 500 mm) diameter blades.”

RECLAIMED ASPHALT PAVEMENT (RAP) (BDE)

Effective: January 1, 2007

Revised: January 1, 2010

In Article 1030.02(g), delete the last sentence of the first paragraph in (Note 2).

Revise Section 1031 of the Standard Specifications to read:

“SECTION 1031. RECLAIMED ASPHALT PAVEMENT

1031.01 Description. Reclaimed asphalt pavement (RAP) is reclaimed asphalt pavement resulting from cold milling or crushing of an existing dense graded hot-mix asphalt (HMA) pavement. The Contractor shall supply written documentation that the RAP originated from routes or airfields under federal, state, or local agency jurisdiction.

1031.02 Stockpiles. The Contractor shall construct individual, sealed RAP stockpiles meeting one of the following definitions. No additional RAP shall be added to the pile after the pile has been sealed. Stockpiles shall be sufficiently separated to prevent intermingling at the base. Stockpiles shall be identified by signs indicating the type as listed below (i.e. “Homogeneous Surface”).

Prior to milling, the Contractor shall request the District to provide verification of the quality of the RAP to clarify appropriate stockpile.

- (a) Fractionated RAP (FRAP). FRAP shall consist of RAP from Class I, Superpave (High ESAL), HMA (High ESAL), or equivalent mixtures. The coarse aggregate in FRAP shall be crushed aggregate and may represent more than one aggregate type and/or quality but shall be at least C quality. All FRAP shall be fractionated prior to testing by screening into a minimum of two size fractions with the separation occurring on or between the #4 (4.75 mm) and 1/2 in. (12.5 mm) sieves. Agglomerations shall be minimized such that 100 percent of the RAP in the coarse fraction shall pass one sieve size larger than the maximum sieve size specified for the mix the RAP will be used in.
- (b) Homogeneous. Homogeneous RAP stockpiles shall consist of RAP from Class I, Superpave (High ESAL), HMA (High ESAL), or equivalent mixtures and represent:
1) the same aggregate quality, but shall be at least C quality; 2) the same type of crushed aggregate (either crushed natural aggregate, ACBF slag, or steel slag); 3) similar gradation; and 4) similar asphalt binder content. If approved by the Engineer, combined single pass surface/binder millings may be considered “homogenous” with a quality rating dictated by the lowest coarse aggregate quality present in the mixture.

- (c) Conglomerate. Conglomerate RAP stockpiles shall consist of RAP from Class I, Superpave (High ESAL), HMA (High ESAL), or equivalent mixtures. The coarse aggregate in this RAP shall be crushed aggregate and may represent more than one aggregate type and/or quality but shall be at least C quality. This RAP may have an inconsistent gradation and/or asphalt binder content prior to processing. All conglomerate RAP shall be processed prior to testing by crushing to where all RAP shall pass the 5/8 in. (16 mm) or smaller screen. Conglomerate RAP stockpiles shall not contain steel slag or other expansive material as determined by the Department.
- (d) Conglomerate "D" Quality (DQ). Conglomerate DQ RAP stockpiles shall consist of RAP from Class I, Superpave (High or Low ESAL), HMA (High or Low ESAL), or equivalent mixtures. The coarse aggregate in this RAP may be crushed or round but shall be at least D quality. This RAP may have an inconsistent gradation and/or asphalt binder content. Conglomerate DQ RAP stockpiles shall not contain steel slag or other expansive material as determined by the Department.
- (e) Non-Quality. RAP stockpiles that do not meet the requirements of the stockpile categories listed above shall be classified as "Non-Quality".

RAP/FRAP containing contaminants, such as earth, brick, sand, concrete, sheet asphalt, bituminous surface treatment (i.e. chip seal), pavement fabric, joint sealants, etc., will be unacceptable unless the contaminants are removed to the satisfaction of the Engineer. Sheet asphalt shall be stockpiled separately.

1031.03 Testing. When used in HMA, the RAP/FRAP shall be sampled and tested either during or after stockpiling.

For testing during stockpiling, washed extraction samples shall be run at the minimum frequency of one sample per 500 tons (450 metric tons) for the first 2000 tons (1800 metric tons) and one sample per 2000 tons (1800 metric tons) thereafter. A minimum of five tests shall be required for stockpiles less than 4000 tons (3600 metric tons).

For testing after stockpiling, the Contractor shall submit a plan for approval to the District proposing a satisfactory method of sampling and testing the RAP/FRAP pile either in-situ or by restockpiling. The sampling plan shall meet the minimum frequency required above and detail the procedure used to obtain representative samples throughout the pile for testing.

Before extraction, each field sample shall be split to obtain two samples of test sample size. One of the two test samples from the final split shall be labeled and stored for Department use. The Contractor shall extract the other test sample according to Department procedure. The Engineer reserves the right to test any sample (split or Department-taken) to verify Contractor test results.

Evaluation of Test Results. All of the extraction results shall be compiled and averaged for asphalt binder content and gradation and, when applicable G_{mm} . Individual extraction test results, when compared to the averages, will be accepted if within the tolerances listed below.

Parameter	FRAP/Homogeneous /Conglomerate	Conglomerate "D" Quality
1 in. (25 mm)		± 5 %
1/2 in. (12.5 mm)	± 8 %	± 15 %
No. 4 (4.75 mm)	± 6 %	± 13 %
No. 8 (2.36 mm)	± 5 %	
No. 16 (1.18 mm)		± 15 %
No. 30 (600 μm)	± 5 %	
No. 200 (75 μm)	± 2.0 %	± 4.0 %
Asphalt Binder	± 0.4 % ^{1/}	± 0.5 %
G _{mm}	± 0.03	

1/ The tolerance for FRAP shall be ± 0.3 %.

If more than 20 percent of the individual sieves are out of the gradation tolerances, or if more than 20 percent of the asphalt binder content test results fall outside the appropriate tolerances, the RAP/FRAP shall not be used in HMA unless the RAP/FRAP representing the failing tests is removed from the stockpile. All test data and acceptance ranges shall be sent to the District for evaluation.

With the approval of the Engineer, the ignition oven may be substituted for extractions according to the Illinois Test Procedure, "Calibration of the Ignition Oven for the Purpose of Characterizing Reclaimed Asphalt Pavement (RAP)".

1031.04 Quality Designation of Aggregate in RAP/FRAP.

- (a) The aggregate quality of the RAP for homogenous, conglomerate, and conglomerate "D" quality stockpiles shall be set by the lowest quality of coarse aggregate in the RAP stockpile and are designated as follows.
 - (1) RAP from Class I, Superpave (High ESAL)/HMA (High ESAL), or HMA (Low ESAL) IL-9.5L surface mixtures are designated as containing Class B quality coarse aggregate.
 - (2) RAP from Superpave (Low ESAL)/HMA (Low ESAL) IL-19.0L binder mixture is designated as Class D quality coarse aggregate.
 - (3) RAP from Class I, Superpave (High ESAL), or HMA (High ESAL) binder mixtures, bituminous base course mixtures, and bituminous base course widening mixtures are designated as containing Class C quality coarse aggregate.
 - (4) RAP from bituminous stabilized subbase and BAM shoulders are designated as containing Class D quality coarse aggregate.
- (b) The aggregate quality of FRAP shall be determined as follows.

Fractionated stockpiles containing plus #4 (4.75 mm) sieve coarse aggregate shall have a maximum tonnage of 5000 tons (4500 metric tons). The Contractor shall obtain a representative sample witnessed by the Engineer. The sample shall be a minimum of 50 lb (25 kg). The sample shall be extracted according to Illinois Modified AASHTO T 164 by a consultant prequalified by the Department for the specified testing. The consultant shall submit the test results along with the recovered aggregate to the District Office. The cost for this testing shall be paid by the Contractor. The District will forward the sample to the Bmpr Aggregate Lab for MicroDeval Testing, according to Illinois Modified AASHTO T 327. A maximum loss of 15.0 percent will be applied for all HMA applications.”

1031.05 Use of RAP/FRAP in HMA. The use of RAP/FRAP shall be a Contractor’s option when constructing HMA in all contracts. The use of RAP/FRAP in HMA shall be as follows.

- (a) Coarse Aggregate Size. The coarse aggregate in all RAP shall be equal to or less than the nominal maximum size requirement for the HMA mixture to be produced.
- (b) Steel Slag Stockpiles. RAP stockpiles containing steel slag or other expansive material, as determined by the Department, shall be homogeneous and will be approved for use in HMA (High ESAL and Low ESAL) surface mixtures only.
- (c) Use in HMA Surface Mixtures (High and Low ESAL). RAP/FRAP stockpiles for use in HMA surface mixtures (High and Low ESAL) shall be FRAP or homogeneous in which the coarse aggregate is Class B quality or better.
- (d) Use in HMA Binder Mixtures (High and Low ESAL), HMA Base Course, and HMA Base Course Widening. RAP/FRAP stockpiles for use in HMA binder mixtures (High and Low ESAL), HMA base course, and HMA base course widening shall be FRAP, homogeneous, or conglomerate, in which the coarse aggregate is Class C quality or better.
- (e) Use in Shoulders and Subbase. RAP/FRAP stockpiles for use in HMA shoulders and stabilized subbase (HMA) shall be FRAP, homogeneous, conglomerate, or conglomerate DQ.
- (f) When the Contractor chooses the RAP option, the percentage of RAP shall not exceed the amounts indicated in the table below for a given N Design.

Max RAP Percentage

HMA Mixtures ^{1/, 3/}	Maximum % RAP		
	Binder/Leveling Binder	Surface	Polymer Modified
30	30	30	10
50	25	15	10
70	15 / 25 ^{2/}	10 / 15 ^{2/}	10
90	10	10	10
105	10	10	10

- 1/ For HMA shoulder and stabilized subbase (HMA) N-30, the amount of RAP shall not exceed 50% of the mixture.
- 2/ Value of Max % RAP if homogeneous RAP stockpile of IL-9.5 RAP is utilized.
- 3/ When RAP exceeds 20 percent, the high and low virgin asphalt binder grades shall each be reduced by one grade (i.e. 25 percent RAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-28). If warm mix asphalt (WMA) technology is utilized, and production temperatures do not exceed 275°F (135 °C) the grades shall be reduced as follows:

Overlays:

When WMA contains between 20 and 30 percent RAP the high temperature shall be reduced by one grade (i.e. 25 percent RAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-22). When WMA contains 30 percent or more RAP the high and low temperature grades shall each be reduced by one grade (i.e. 35 percent RAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-28).

Full Depth:

When WMA contains between 20 and 30 percent RAP, the low temperature shall be reduced by one grade (i.e. 25 percent RAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG64-28). When the WMA contains 30 percent or more RAP the high and low temperature grades shall each be reduced by one grade (i.e. 35 percent RAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-28).

- (g) When the Contractor chooses the FRAP option, the percentage of FRAP shall not exceed the amounts indicated in the table below for a given N Design.

Max FRAP Percentage

HMA Mixtures ^{1/, 2/}	Maximum % FRAP		
	Ndesign	Binder/Leveling Binder	Surface
30	35	35	10
50	30	25	10
70	25	20	10
90	20	15	10
105	10	10	10

- 1/ For HMA shoulder and stabilized subbase (HMA) N30, the amount of FRAP shall not exceed 50 percent of the mixture.
- 2/ When FRAP exceeds 20 percent, the high and low virgin asphalt binder grades shall each be reduced by one grade (i.e. 25 percent FRAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-28). If warm mix asphalt (WMA) technology is utilized, and production temperatures do not exceed 275°F (135 °C) the grades shall be reduced as follows:

Overlays:

When WMA contains between 20 and 30 percent FRAP the high temperature shall be reduced by one grade (i.e. 25 percent FRAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-22). When WMA contains 30 percent or more FRAP the high and low temperature grades shall each be reduced by one grade (i.e. 35 percent FRAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-28).

Full Depth:

When WMA contains between 20 and 30 percent FRAP, the low temperature shall be reduced by one grade (i.e. 25 percent FRAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG64-28). When the WMA contains 30 percent or more FRAP the high and low temperature grades shall each be reduced by one grade (i.e. 35 percent FRAP would require a virgin asphalt binder grade of PG64-22 to be reduced to a PG58-28).

1031.06 HMA Mix Designs. At the Contractor's option, HMA mixtures may be constructed utilizing RAP/FRAP material meeting the above detailed requirements.

RAP/FRAP designs shall be submitted for volumetric verification. If additional RAP/FRAP stockpiles are tested and found that no more than 20 percent of the results, as defined under "Testing" herein, are outside of the control tolerances set for the original RAP/FRAP stockpile and HMA mix design, and meets all of the requirements herein, the additional RAP/FRAP stockpiles may be used in the original mix design at the percent previously verified.

1031.07 HMA Production. The coarse aggregate in all RAP used shall be equal to or less than the nominal maximum size requirement for the HMA mixture being produced.

To remove or reduce agglomerated material, a scalping screen, gator, crushing unit, or comparable sizing device approved by the Engineer shall be used in the RAP feed system to remove or reduce oversized material. If material passing the sizing device adversely affects the mix production or quality of the mix, the sizing device shall be set at a size specified by the Engineer.

If the RAP/FRAP control tolerances or QC/QA test results require corrective action, the Contractor shall cease production of the mixture containing RAP/FRAP and either switch to the virgin aggregate design or submit a new RAP/FRAP design.

HMA plants utilizing RAP/FRAP shall be capable of automatically recording and printing the following information.

(a) Dryer Drum Plants.

- (1) Date, month, year, and time to the nearest minute for each print.
- (2) HMA mix number assigned by the Department.
- (3) Accumulated weight of dry aggregate (combined or individual) in tons (metric tons) to the nearest 0.1 ton (0.1 metric ton).

- (4) Accumulated dry weight of RAP/FRAP in tons (metric tons) to the nearest 0.1 ton (0.1 metric ton).
- (5) Accumulated mineral filler in revolutions, tons (metric tons), etc. to the nearest 0.1 unit.
- (6) Accumulated asphalt binder in gallons (liters), tons (metric tons), etc. to the nearest 0.1 unit.
- (7) Residual asphalt binder in the RAP/FRAP material as a percent of the total mix to the nearest 0.1 percent.
- (8) Aggregate and RAP/FRAP moisture compensators in percent as set on the control panel. (Required when accumulated or individual aggregate and RAP/FRAP are printed in wet condition.)

(b) Batch Plants.

- (1) Date, month, year, and time to the nearest minute for each print.
- (2) HMA mix number assigned by the Department.
- (3) Individual virgin aggregate hot bin batch weights to the nearest pound (kilogram).
- (4) Mineral filler weight to the nearest pound (kilogram).
- (5) RAP/FRAP weight to the nearest pound (kilogram).
- (6) Virgin asphalt binder weight to the nearest pound (kilogram).
- (7) Residual asphalt binder in the RAP/FRAP material as a percent of the total mix to the nearest 0.1 percent.

The printouts shall be maintained in a file at the plant for a minimum of one year or as directed by the Engineer and shall be made available upon request. The printing system will be inspected by the Engineer prior to production and verified at the beginning of each construction season thereafter.

1031.08 RAP in Aggregate Surface Course and Aggregate Shoulders. The use of RAP in aggregate surface course and aggregate shoulders shall be as follows.

- (a) Stockpiles and Testing. RAP stockpiles may be any of those listed in Article 1031.02, except "Non-Quality" and "FRAP". The testing requirements of Article 1031.03 shall not apply.
- (b) Gradation. One hundred percent of the RAP material shall pass the 1 1/2 in. (37.5 mm) sieve. The RAP material shall be reasonably well graded from coarse to fine. RAP material that is gap-graded or single sized will not be accepted."

REFLECTIVE SHEETING ON CHANNELIZING DEVICES (BDE)

Effective: April 1, 2007

Revised: November 1, 2008

Revise the seventh paragraph of Article 1106.02 of the Standard Specifications to read:

“At the time of manufacturing, the retroreflective prismatic sheeting used on channelizing devices shall meet or exceed the initial minimum coefficient of retroreflection as specified in the following table. Measurements shall be conducted according to ASTM E 810, without averaging. Sheeting used on cones, drums and flexible delineators shall be reboundable as tested according to ASTM D 4956. Prestriped sheeting for rigid substrates on barricades shall be white and orange. **The sheeting shall be uniform in color and devoid of streaks throughout the length of each roll. The color shall conform to the latest appropriate standard color tolerance chart issued by the U.S. Department of Transportation, Federal Highway Administration, and to the daytime and nighttime color requirements of ASTM D 4956.**

Initial Minimum Coefficient of Retroreflection candelas/foot candle/sq ft (candelas/lux/sq m) of material				
Observation Angle (deg.)	Entrance Angle (deg.)	White	Orange	Fluorescent Orange
0.2	-4	365	160	150
0.2	+30	175	80	70
0.5	-4	245	100	95
0.5	+30	100	50	40”

Revise the first sentence of the first paragraph of Article 1106.02(c) of the Standard Specifications to read:

“Barricades and vertical panels shall have alternating white and orange stripes sloping downward at 45 degrees toward the side on which traffic will pass.”

Revise the third sentence of the first paragraph of Article 1106.02(d) of the Standard Specifications to read:

“The bottom panels shall be 8 x 24 in. (200 x 600 mm) with alternating white and orange stripes sloping downward at 45 degrees toward the side on which traffic will pass.”

SUBCONTRACTOR MOBILIZATION PAYMENTS (BDE)

Effective: April 2, 2005

To account for the preparatory work and operations necessary for the movement of subcontractor personnel, equipment, supplies, and incidentals to the project site and for all other work or operations that must be performed or costs incurred when beginning work approved for subcontracting in accordance with Article 108.01 of the Standard Specifications, the Contractor shall make a mobilization payment to each subcontractor.

This mobilization payment shall be made at least 14 days prior to the subcontractor starting work. The amount paid shall be equal to 3 percent of the amount of the subcontract reported on form BC 260A submitted for the approval of the subcontractor’s work.

This provision shall be incorporated directly or by reference into each subcontract approved by the Department.

THERMOPLASTIC PAVEMENT MARKINGS (BDE)

Effective: January 1, 2007

Revise Article 1095.01(a)(2) of the Standard Specifications to read:

“(2) Pigment. The pigment used for the white thermoplastic compound shall be a high-grade pure (minimum 93 percent) titanium dioxide (TiO₂). The white pigment content shall be a minimum of ten percent by weight and shall be uniformly distributed throughout the thermoplastic compound.

The pigments used for the yellow thermoplastic compound shall not contain any hazardous materials listed in the Environmental Protection Agency Code of Federal Regulations (CFR) 40, Section 261.24, Table 1. The combined total of RCRA listed heavy metals shall not exceed 100 ppm when tested by X-ray fluorescence spectroscopy. The pigments shall also be heat resistant, UV stable and color-fast yellows, golds, and oranges, which shall produce a compound which shall match Federal Standard 595 Color No. 33538. The pigment shall be uniformly distributed throughout the thermoplastic compound.”

Revise Article 1095.01(b)(1)e. of the Standard Specifications to read:

“e. Daylight Reflectance and Color. The thermoplastic compound after heating for four hours ± five minutes at 425 ± 3 °F (218.3 ± 2 °C) and cooled at 77 °F (25 °C) shall meet the following requirements for daylight reflectance and color, when tested, using a color spectrophotometer with 45 degree circumferential/zero degree geometry, illuminant C, and two degree observer angle. The color instrument shall measure the visible spectrum from 380 to 720 nm with a wavelength measurement interval and spectral bandpass of 10 nm.

White: Daylight Reflectance75 percent min.

*Yellow: Daylight Reflectance45 percent min.

*Shall meet the coordinates of the following color tolerance chart.

x	0.490	0.475	0.485	0.530
y	0.470	0.438	0.425	0.456”

Revise Article 1095.01(b)(1)k. of the Standard Specifications to read:

“k. Accelerated Weathering. After heating the thermoplastic for four hours ± five minutes at 425 ± 3 °F (218.3 ± 2 °C) the thermoplastic shall be applied to a steel wool abraded aluminum alloy panel (Federal Test Std. No. 141, Method 2013) at a film thickness of 30 mils (0.70 mm) and allowed to cool for 24 hours at room temperature. The coated panel shall be subjected to accelerated weathering using the light and water exposure apparatus (fluorescent UV - condensation type) for 75 hours according to ASTM G 53 (equipped with UVB-313 lamps).

The cycle shall consist of four hours UV exposure at 122 °F (50 °C) followed by four hours of condensation at 104 °F (40 °C). UVB 313 bulbs shall be used. At the end of the exposure period, the panel shall not exceed 10 Hunter Lab Delta E units from the original material.”

TRUCK MOUNTED/TRAILER MOUNTED ATTENUATORS (BDE)

Effective: January 1, 2010

Revise Article 701.03(k) of the Standard Specifications to read:

“(k) Truck Mounted/Trailer Mounted Attenuators 1106.02”

Revise Article 701.15(h) of the Standard Specifications to read:

“(h) Truck Mounted/Trailer Mounted Attenuators (TMA). TMA units shall have a roll ahead distance in the event of an impact. The TMA shall be between 100 and 200 ft (30 and 60 m) behind the vehicle ahead or the workers. This distance may be extended by the Engineer.

TMA host vehicles shall have the parking brake engaged when stationary.

The driver and passengers of the TMA host vehicle should exit the vehicle if the TMA is to remain stationary for 15 minutes or more in duration.”

Revise Article 1106.02(g) of the Standard Specifications to read:

“(g) Truck Mounted/Trailer Mounted Attenuators. The attenuator shall be a NCHRP 350 approved unit for Test Level 3. Test Level 2 may be used as directed by the Engineer for normal posted speeds less than or equal to 45 mph.”

WORKING DAYS (BDE)

Effective: January 1, 2002

The Contractor shall complete the work within **60** working days.

BITUMINOUS MATERIALS COST ADJUSTMENTS (BDE) (RETURN FORM WITH BID)

Effective: November 2, 2006

Revised: April 1, 2009

Description. Bituminous material cost adjustments will be made to provide additional compensation to the Contractor, or credit to the Department, for fluctuations in the cost of bituminous materials when optioned by the Contractor. The adjustments shall apply to permanent and temporary hot-mix asphalt (HMA) mixtures, bituminous surface treatments (cover and seal coats), and pavement preservation type surface treatments. The adjustments shall not apply to bituminous prime coats, tack coats, crack filling/sealing, or joint filling/sealing.

The bidder shall indicate on the attached form whether or not this special provision will be part of the contract and submit the completed form with his/her bid.

Failure to submit the form, or failure to fill out the form completely, shall make this contract exempt of bituminous materials cost adjustments.

Method of Adjustment. Bituminous materials cost adjustments will be computed as follows.

$$CA = (BPI_P - BPI_L) \times (\%AC_V / 100) \times Q$$

- Where: CA = Cost Adjustment, \$.
BPI_P = Bituminous Price Index, as published by the Department for the month the work is performed, \$/ton (\$/metric ton).
BPI_L = Bituminous Price Index, as published by the Department for the month prior to the letting, \$/ton (\$/metric ton).
%AC_V = Percent of virgin Asphalt Cement in the Quantity being adjusted. For HMA mixtures, the % AC_V will be determined from the adjusted job mix formula. For bituminous materials applied, a performance graded or cutback asphalt will be considered to be 100% AC_V and undiluted emulsified asphalt will be considered to be 65% AC_V.
Q = Authorized construction Quantity, tons (metric tons) (see below).

For HMA mixtures measured in square yards: $Q, \text{ tons} = A \times D \times (G_{mb} \times 46.8) / 2000$. For HMA mixtures measured in square meters: $Q, \text{ metric tons} = A \times D \times (G_{mb} \times 24.99) / 1000$. When computing adjustments for full-depth HMA pavement, separate calculations will be made for the binder and surface courses to account for their different G_{mb} and % AC_V.

For bituminous materials measured in gallons: $Q, \text{ tons} = V \times 8.33 \text{ lb/gal} \times SG / 2000$
For bituminous materials measured in liters: $Q, \text{ metric tons} = V \times 1.0 \text{ kg/L} \times SG / 1000$

- Where: A = Area of the HMA mixture, sq yd (sq m).
D = Depth of the HMA mixture, in. (mm).
 G_{mb} = Average bulk specific gravity of the mixture, from the approved mix design.
V = Volume of the bituminous material, gal (L).
SG = Specific Gravity of bituminous material as shown on the bill of lading.

Basis of Payment. Bituminous materials cost adjustments may be positive or negative but will only be made when there is a difference between the BPI_L and BPI_P in excess of five percent, as calculated by:

$$\text{Percent Difference} = \{(BPI_L - BPI_P) \div BPI_L\} \times 100$$

Bituminous materials cost adjustments will be calculated for each calendar month in which applicable bituminous material is placed; and will be paid or deducted when all other contract requirements for the work placed during the month are satisfied. The adjustments shall not apply during contract time subject to liquidated damages for completion of the entire contract.

RETURN WITH BID

ILLINOIS DEPARTMENT OF TRANSPORTATION

OPTION FOR BITUMINOUS MATERIALS COST ADJUSTMENTS

The bidder shall submit this completed form with his/her bid. Failure to submit the form, or failure to fill out the form completely, shall make this contract exempt of bituminous materials cost adjustments. After award, this form, when submitted, shall become part of the contract.

Contract No.: _____

Company Name: _____

Contractor's Option:

Is your company opting to include this special provision as part of the contract?

Yes No

Signature: _____ **Date:** _____

MONTHLY EMPLOYMENT REPORT (BDE)

Effective: April 1, 2009

Revised: January 1, 2010

In addition to any other reporting required by the contract, the Contractor shall provide to the Engineer an employment summary for all employees working on the contract from the contract execution date to the last full pay period each month for the duration of the contract. The report may include but is not limited to:

- a) Total number of employees.
- b) The total hours worked.
- c) Total payroll.

The report shall be completed by the Contractor. The Contractor shall also report for each subcontractor. Employee hours worked from home office or other off-site office hours worked related directly to this contract shall be included. Engineering consulting firms performing construction layout and material testing for the Contractor shall also be included.

Hours worked for material suppliers, services provided by purchase orders, Department employees or consulting firms performing inspection or testing for the Department shall not be included in the report.

The report shall contain all hours worked under the contract from the start of the month to the last full pay period each month and shall be submitted no later than five business days after the end of each month.

The report shall be submitted electronically by accessing the Department's website (<http://www.dot.il.gov/stimulus/index.html>).

Any costs associated with complying with this provision shall be considered as included in the contract unit prices bid for the various items of work involved and no additional compensation will be allowed.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
303	(2,3)RS-3	WINNEBAGO	37	1
		ILLINOIS	CONTRACT NO. 64G07	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

**PROPOSED
HIGHWAY PLANS**

FAP ROUTE 303 (IL 251)
SECTION (2,3)RS-3




RESURFACING PROJECT
WINNEBAGO COUNTY
C-92-093-10

FOR INDEX OF SHEETS, SEE SHEET NO. 2
FOR STATE STANDARDS, SEE SHEET NO. 2

SECTION & IMPROVEMENT ENDS
STA 707+06

NORTHWEST ROCKFORD TOWNSHIP SECTIONS 1 & 12
NORTHEAST ROCKFORD TOWNSHIP SECTIONS 6 & 7

SECTION & IMPROVEMENT BEGINS
STA 612+50



LOCATION OF SECTION INDICATED THERE

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

SUBMITTED Jan. 22, 2010
[Signature]
DEPUTY DIRECTOR OF HIGHWAYS, REGION ENGINEER

ENGINEER OF DESIGN AND ENVIRONMENT
DIRECTOR OF HIGHWAYS, CHIEF ENGINEER

**PRINTED BY THE AUTHORITY
OF THE STATE OF ILLINOIS**

GROSS LENGTH = 9456 FT. = 1.79 MILE
NET LENGTH = 9456 FT. = 1.79 MILE

LITTLE
JOINT UTILITY LOCATOR INFORMATION FOR EXCAVATION
1-800-852-9123
OR 311

PROJECT ENGINEER: MASOOD AHMAD
SENIOR SOUJAD LEADER: SAMEER ABDULLAH (615) 284-5535
STUDIES & PLANS SOUJAD ENGINEER: MAT DOBIE
CONTRACT NO. 64G07

FAP ROUTE 303 (IL 251) SECTION (2,3)RS-3 WINNEBAGO COUNTY

INDEX OF SHEETS

1	COVER SHEET
2	INDEX OF SHEETS AND STATE STANDARDS
3 - 4	SUMMARY OF QUANTITIES
5 - 10	TYPICAL SECTIONS
11 - 13	GENERAL NOTES
14 - 18	SCHEDULE OF QUANTITIES
19 - 26	BITUMINOUS SCHEDULE
27	PATCHING SCHEDULE
28 - 30	TYPICAL PAVEMENT MARKINGS (DIST STD 41.1)
31	FRAME AND GRATE SPECIAL (DIST STD 13.2C)
32	ROUGH GROOVED SURFACE SIGN (DIST STD 91.2)
33	T. C. AND PROTECTION AT TURN BAYS (TO REMAIN OPEN...) (DIST STD 94.2)
34	CATCH BASINS OR INLETS TO BE ADJUSTED... (DIST STD 17.4A)
35	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT (DIST STD 32.4)
36	TYPICAL MARKING FOR PAINTED ISLAND (DIST STD 93.4)
37	SUBGRADE REPLACEMENT (DIST STD 97.4)

STATE STANDARDS

420001 - 07	PAVEMENT JOINTS
442201 - 03	CLASS C & D PATCHES
604001 - 03	FRAMES AND LIDS, TYPE 1
606001 - 04	CONCRETE CURB TY B AND COMBINATION CONCRETE CURB & GUTTER
606301 - 04	PC CONCRETE ISLANDS AND MEDIANS
701101 - 02	OFF-ROAD OPERATIONS, MULTILANE, 15' TO 24" FROM PAVEMENT EDGE
701421 - 02	LANE CLOSURE, MULTILANE, DAY OPERATIONS ONLY, FOR SPEEDS...
701426 - 03	LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPERATIONS...
701601 - 06	URBAN LANE CLOSURE, MULTILANE, 1W OR 2W W/ NONTRANSVERSABLE
701606 - 06	URBAN LANE CLOSURE, MULTILANE, 2W W/ MOUNTABLE MEDIAN
701701 - 06	URBAN LANE CLOSURE, MULTILANE INTERSECTION
701901 - 01	TRAFFIC CONTROL DEVICES
720011 - 01	METAL POSTS FOR SIGNS, MARKERS & DELINEATORS
728001 - 01	TELESCOPING STEEL SIGN SUPPORT
729001 - 01	APPLICATION OF TYPES A & B METAL POSTS
780001 - 02	TYPICAL PAVEMENT MARKINGS
781001 - 03	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS
886001 - 01	DETECTOR LOOPS INSTALLATIONS
886006 - 01	TYPICAL LAYOUT FOR DETECTOR LOOPS

SUMMARY OF QUANTITIES

FAP 303 (IL 251)
SECTION (2,3)RS-3
WINNEBAGO CO.
CONTRACT 64G07
SHEET 3 OF 37

CODE NUMBER	ITEM	UNITS	TOTAL	100% STATE URBAN 0000-2A	50% CITY 50% STATE Y060	100% CITY Y060	100% RRWRD Y060
35101400	AGGREGATE BASE COURSE, TYPE B	TON	546	546			
40600200	BITUMINOUS MATERIALS (PRIME COAT)	TON	47.8	47.80			
40600300	AGGREGATE (PRIME COAT)	TON	105	105			
40600535	LEVELING BINDER (HAND METHOD), N70	TON	28	28			
40600837	POLYMERIZED LEVELING BINDER (MACHINE METHOD), N70	TON	3676	3676			
40600895	CONSTRUCTING TEST STRIP	EACH	1	1			
40600990	TEMPORARY RAMP	SQ YD	495	495			
40601005	HOT-MIX ASPHALT REPLACEMENT OVER PATCHES	TON	156	156			
40603310	HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50	TON	2002		2002		
40603565	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "E", N70	TON	5514	5514			
40800050	INCIDENTAL HOT-MIX SURFACING	TON	628	628			
44000158	HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/4"	SQ YD	90364	74473	15891		
44002216	HOT-MIX ASPHALT REMOVAL OVER PATCHES, 4"	SQ YD	695	695			
44003100	MEDIAN REMOVAL	SQ FT	21595	21595			
44200144	PAVEMENT PATCHING, TYPE II, 12 INCH	SQ YD	26	26			
44200148	PAVEMENT PATCHING, TYPE III, 12 INCH	SQ YD	16	16			
44200150	PAVEMENT PATCHING, TYPE IV, 12 INCH	SQ YD	34	34			
44300200	STRIP REFLECTIVE CRACK CONTROL TREATMENT	FOOT	34774	34774			
60255500	MANHOLES TO BE ADJUSTED	EACH	70	46			24
60255900	MANHOLES TO BE ADJUSTED WITH NEW TYPE 1 FRAME, CLOSED LID	EACH	3	3			
60262510	INLETS TO BE ADJUSTED WITH NEW FRAME AND GRATE (SPECIAL)	EACH	22	19		3	
60265700	VALVE VAULTS TO BE ADJUSTED	EACH	43			43	
60265800	VALVE VAULTS TO BE ADJUSTED (SPECIAL)	EACH	2			2	
60603800	COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12	FOOT	48	48			
60605000	COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.24	FOOT	672	672			

SUMMARY OF QUANTITIES


FAP 303 (IL 251)
SECTION (2,3)RS-3
WINNEBAGO CO.
CONTRACT 64G07
SHEET 4 OF 37

CODE NUMBER	ITEM	UNITS	TOTAL	100% STATE	50% CITY	100 %	100 %
				URBAN 1000-2A	50% STATE Y060	CITY Y060	RRWRD Y060
60618300	CONCRETE MEDIAN SURFACE, 4 INCH	SQ FT	4121	4121			
60619123	CONCRETE MEDIAN, TYPE SB-6 (MODIFIED)	SQ FT	7556	7556			
60620000	CONCRETE MEDIAN, TYPE SB-6.24	SQ FT	8292	8292			
67000400	ENGINEERS FIELD OFFICE, TYPE A	CA MO	4	4			
67100100	MOBILIZATION	L SUM	1	1			
70102625	TRAFFIC CONTROL AND PROTECTION, STANDARD 701606	L SUM	1	1			
70102630	TRAFFIC CONTROL AND PROTECTION, STANDARD 701601	L SUM	1	1			
70102635	TRAFFIC CONTROL AND PROTECTION, STANDARD 701701	L SUM	1	1			
70103815	TRAFFIC CONTROL SURVEILLANCE	CAL DA	16	16			
70300100	SHORT-TERM PAVEMENT MARKING	FOOT	7864	7864			
70301000	WORK ZONE PAVEMENT MARKING REMOVAL	SQ FT	874	874			
* 78000100	THERMOPLASTIC PAVEMENT MARKING - LETTERS AND SYMBOLS	SQ FT	1726	1726			
* 78000200	THERMOPLASTIC PAVEMENT MARKING - LINE 4"	FOOT	42682	42682			
* 78000400	THERMOPLASTIC PAVEMENT MARKING - LINE 6"	FOOT	3926	3926			
* 78000500	THERMOPLASTIC PAVEMENT MARKING - LINE 8"	FOOT	5955	5955			
* 78000600	THERMOPLASTIC PAVEMENT MARKING - LINE 12"	FOOT	184	184			
* 78000650	THERMOPLASTIC PAVEMENT MARKING - LINE 24"	FOOT	1135	1135			
* 78100100	RAISED REFLECTIVE PAVEMENT MARKER	EACH	733	733			
78300200	RAISED REFLECTIVE PAVEMENT MARKER REMOVAL	EACH	707	707			
* 88600400	DETECTOR LOOP, SPECIAL	FOOT	3600	3600			
Z0013798	CONSTRUCTION LAYOUT	L SUM	1	1			
Z0028415	GEOTECHNICAL REINFORCEMENT	SQ YD	76	76			
Z0028700	GRANULAR SUBGRADE REPLACEMENT	CU YD	13	13			


*SPECIALTY ITEMS

TYPICAL SECTION

- STA 612+50 TO 646+64
- STA 648+44 TO 656+12
- STA 659+00 TO 659+36
- STA 661+83 TO 677+09
- STA 678+87 TO 679+45
- STA 681+80 TO 682+46
- STA 684+77 TO 688+57
- STA 690+80 TO 695+20
- STA 698+16 TO 698+90
- STA 701+59 TO 702+37
- STA 704+81 TO 707+06



- STRIP REFLECTIVE CRACK CONTROL
- EXISTING PAVEMENT
- BITUMINOUS SURFACE REMOVAL, 2 1/4"
- 1 1/2" POLYMERIZED HMA SURFACE COURSE, SUPERPAVE, MIX "E", NTO
- 3/4" POLYMERIZED LEVEL BINDER (MACHINE METHOD), SUPERPAVE, NTO
- STRIP REFLECTIVE CRACK CONTROL
- 2 1/4" HMA SURFACE COURSE, SUPERPAVE, MIX "C", N50




• MATCH EXISTING CROSS SLOPE (MIN OF 1/8"/FT)
 112 LBS/SQ YD/IN FOR LEVEL BINDER & SURFACE COURSE

FILE NAME =	USER NAME = josedd	STATE OF ILLINOIS	TYPICAL SECTION	F.A.P. RITE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
ct:\pw-vo-r\K\PM\DOT\005500\017938\1\020530-01-typical.dgn		DEPARTMENT OF TRANSPORTATION		303	(2,3)RS-3	WINNEBAGO	37	5
PLOT DATE = Fri, Jan 15 17:43:47 2010		ILLINOIS FED. AID PROJECT		CONTRACT NO. 64C07				


TYPICAL SECTION

STA 679+45 TO 680+25 STA 698+90 TO 701+59
 STA 688+57 TO 690+80 STA 702+37 TO 702+77
 STA 695+20 TO 698+16
 § IL 251



SEE DETAIL "A"

- BITUMINOUS SURFACE REMOVAL, 2 1/4"
- STRIP REFLECTIVE CRACK CONTROL
- 3/4" POLYMERIZED LEVEL BINDER (MACHINE METHOD), SUPERPAVE, N70
- 1 1/2" POLYMERIZED HMA SURFACE COURSE, SUPERPAVE, MIX "E", N70
- 2 1/4" HMA SURFACE COURSE, SUPERPAVE, MIX "C", N50



• MATCH EXISTING CROSS SLOPE (MIN OF 1/8"/FT)
 112 LBS/SQ YD/IN FOR LEVEL BINDER & SURFACE COURSE



- EXISTING MEDIAN TO BE REMOVED
- 4" AGGREGATE BASE COURSE, TYPE B
- CONCRETE MEDIAN, TYPE SB-6.24 MATCH EXISTING WIDTH

FILE NAME = c:\p\work\p\1001\005500\d8179381\0205310-shit-typical.dgn	USER NAME = dbsadd	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	TYPICAL SECTION	F.A.P. RTE. 303	SECTION (2.3)RS-3	COUNTY WINNEBAGO	TOTAL SHEETS 37	SHEET NO. 6
PLOT DATE = Fri Jan 15 17:43:51 2010				FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT		CONTRACT NO. 64G07		

TYPICAL SECTION

STA 646+64 TO 648+44 STA 677+09 TO 678+87
 STA 656+12 TO 659+00 STA 680+25 TO 681+80
 STA 659+36 TO 661+83 STA 683+70 TO 684+77

CL IL 251





• MATCH EXISTING CROSS SLOPE (MIN OF 1/8"/FT)
 112 LBS/SQ YD/IN FOR LEVEL BINDER & SURFACE COURSE

FILE NAME =	USER NAME =	STATE OF ILLINOIS	TYPICAL SECTION	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
es:\pr-nor-k\FWDDT\DDSSDU\0175381\020530-shr-typrcal.dgn	dossdd	DEPARTMENT OF TRANSPORTATION		(2,3)RS-3	WINNEBAGO	37	7
PLOT DATE = Fri, Jan 15 17:43:55 2010			FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		CONTRACT NO. 64G07

TYPICAL SECTION

STA 682+46 TO 683+70
 STA 702+77 TO 704+81

CL IL 251



REMOVAL
 EXISTING
 * MATCH EXISTING CROSS
 SLOPE (MIN OF 1/8"/FT)
 112 LBS/SQ YD/IN FOR LEVEL
 BINDER & SURFACE COURSE

COMBINATION CURB & GUTTER, TYPE B-6.12
 RT STA 683+22 TO STA 683+70

COMBINATION CURB & GUTTER, TYPE B-6.24
 4" CONCRETE MEDIAN SURFACE 4", MATCH EXISTING WIDTH
 * AGGREGATE BASE COURSE, TYPE B
 & SHALL MEET THE REQUIREMENTS OF ARTICLE 606.09
 AGGREGATE FILL REQUIRED SHALL BE INCLUDED IN THE COST OF THE MEDIAN
 EXISTING MEDIAN TO BE REMOVED

FILE NAME =
 USER NAME = dbeadd
 c:\pw-hor-k\p\iddot\00550p\081753b\022053\0-sh-t-tp\cacl.dgn

PLOT DATE = Fri Jan 15 17:44:00 2010

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
303	12, 31RS-3	WINNEBAGO	37	8
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT			CONTRACT NO. 64C07	


STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

TYPICAL SECTION


TYPICAL SECTION

•• RIGHT TURN LANE STATIONS
 SOUTHBOUND: STA 672+48 TO 674+86
 STA 665+85 TO 668+86
 NORTHBOUND: STA 669+22 TO 673+08
 STA 677+12 TO 679+48
 STA 692+64 TO 693+48

CL IL 251



BITUMINOUS SURFACE REMOVAL, 2 1/4"
 STRIP REFLECTIVE CRACK CONTROL
 3/4" POLYMERIZED LEVEL BINDER
 (MACHINE METHOD), SUPERPAVE, N70
 1 1/2" POLYMERIZED HMA SURFACE
 COURSE, SUPERPAVE, MIX "E", N70
 2 1/4" HMA SURFACE COURSE,
 SUPERPAVE, MIX "C", N50



• MATCH EXISTING CROSS SLOPE (MIN OF 1/8"/FT)
 112 LBS/SQ YD/IN FOR LEVEL BINDER & SURFACE COURSE

FILE NAME = c:\pw\work\p\VIDDT\055500\40175381\020530-sht-typsec1.dgn	USER NAME = dcsddd	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	TYPICAL SECTION	F.A.P. RTE. 303	SECTION (2.3)RS-3	COUNTY WINNEBAGO	TOTAL SHEETS 37	SHEET NO. 9
PLOT DATE = Fri Jan 15 17:44:05 2010				FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT CONTRACT NO. 64C07		



TYPICAL SECTION

SIDE STREETS


SNOW AVENUE
LILLIAN COURT
OLIVE COURT
JUNIUS STREET
BOYLSTON STREET
BEACON STREET
CARMEN AVENUE
MCKINLEY AVENUE
SYDNEY AVENUE
FRANCIS AVENUE
EAST & WEST PEARL AVENUE

LAWN DRIVE
EAST & WEST RIVER LANE
EAST & WEST MERRILL AVENUE
EAST & WEST GRAND AVENUE
EAST & WEST LOVES PARK ROAD
RIVER PARK ROAD
FRONTAGE ROAD ENTRANCES
SHERIDAN DRIVE
PARKWAY AVENUE
GRAND BOULEVARD
EAST & WEST CLIFFORD AVENUE

BELTEBERG ROAD
PENNSYLVANIA AVENUE
HANNA COURT
RENROSE AVENUE
HOSMER STREET
EAST & WEST THEODORE STREET
BURWOOD AVENUE
CORONADO BOULEVARD
WEST GLENDALE ROAD
RIGHT TURN LANE @ WINDSOR ROAD



REMOVAL



EXISTING

• MATCH EXISTING CROSS SLOPE (MIN OF 1/8"/FT)
112 LBS/SQ YD/IN FOR LEVEL BINDER & SURFACE COURSE

FILE NAME = c:\ph-work\PMIDOT\DDSSUD\00179581\028530-sit-typical.dgn	USER NAME = dossdd	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	TYPICAL SECTION	F.A.P. RTE. 303	SECTION (2.3)RS-3	COUNTY WINNEBAGO	TOTAL SHEETS 37	SHEET NO. 10
PLOT DATE = Fri Jan 15 17:44:09 2010		FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT		CONTRACT NO. 64607				

GENERAL NOTES

All Borrow/Waste/Use sites must be approved by the Department prior to removing any material from the project or initiating any earthmoving activities, including temporary stockpiling outside the limits of construction.

When laying out for patching, the minimum distance between new patches (saw cut to saw cut) shall be 4.6 m (15 feet). When patch spacing is less than 4.6 m (15 feet), the pavement between patches shall also be removed and replaced.

The minimum patch dimension for full-depth patches will be 1.2 m (four feet) and half-lane width. Half-lane patches shall be confined to the outside edges of the pavement.

Milling machines on this project shall be capable of removing a layer of bituminous a minimum 6' wide and 1-1/2 inches in depth in a single pass.

The following Mixture Requirements are applicable for this project:

Mixture Uses(s):	Surface	Level Binder (MM)	HMA Replacement Over Patches/ Pavement Patching	Parking Lanes
PG:	SBS PG 70-22	SBS PG 70-22	PG 64-22	PG 64-22
Design Air Voids	4.0 @ N70	4.0 @ N70	4.0 @ N70	4.0 @ N50
Mixture Composition (Gradation Mixture)	IL 9.5 or 12.5	IL 9.5	IL 19.0	IL 9.5 or 12.5
Friction Aggregate	E	N/A	N/A	C
20 Year ESAL	3.9	3.9	3.9	N/A
Mix Unit Weight	112 lbs/sy/in	112 lbs/sy/in	112 lbs/sy/in	112 lbs/sy/in

The Contractor shall place temporary hot-mix asphalt tapers along all sides of the utility structures protruding above the milled surface. The temporary tapers shall extend 2' outside of the castings, except for the approach side to traffic shall have a 4' taper length. Hot-mix asphalt meeting the approval of the Engineer shall be used, no cold millings will be allowed. The cost of the material, placement, maintenance, removal and disposal of said work will be included in the Pay Item for Hot-Mix Asphalt Surface Removal.

The Contractor will be required to furnish 140 mm (5 1/2") high brass stencils as approved by the Engineer and install stationing at 250' intervals. Stationing shall be placed on both lanes of 2-lane highways and on the outside lanes in both directions on 4-lane highways. The stations shall be placed 150 mm (6") inside the pavement marking edge so they can be read from the shoulder. This work will be included in the cost of the final pavement surface.

The area to be primed shall be limited to that which can be covered with HMA the same day, unless otherwise permitted by the Engineer.

Reflective Crack Control shall be placed on the existing surface prior to any resurfacing, unless pavement is milled then it will be placed on the binder course.

The Contractor shall install 450 mm (18") diameter formed openings in the Concrete Median Surface, spaced at intervals no greater than 75 m (250 feet), and/or as directed by the Engineer. All existing pavement surfaces or other existing obstructions beneath these openings shall be removed by the Contractor. After the median is in place, core each opening down 1.2 m (4') and fill with dirt. All costs incurred shall be included in the contract unit price per Square Meter (Square Foot) for P.C. CONCRETE MEDIAN SURFACE, 100 mm (4 INCH).

All frames and grates of drainage structures to be removed or filled shall be carefully salvaged and shall remain the property of the City of Loves Park.

The new manhole lids on this project shall have the word "STORM", "SANITARY", or "WATER" on the lid. The word to be used is noted on the plans. It will be the Contractor's responsibility to determine the word to be used on other lids not noted on the plans. No additional compensation will be allowed for this work.

Pavement Marking shall be done according to Standard 780001, except as follows:

1. All words, such as ONLY, shall be 2.4 m (8 feet) high.
2. All non-freeway arrows shall be the large size.
3. The distance between yellow no-passing lines shall be 200 mm (8"), not 180 mm (7") as shown in the detail of Typical Lane and Edge Lines.

Detector Loop, Special

1. Any Conduit stubs damaged during the surface grinding process shall be replaced in this cost. This shall also include any wire in the conduit required to connect the loops.
2. Any 6'x20' Detector Loop shall have a minimum of three turns of wire and any 6'x6' Detector Loop shall have a minimum of four turns of wire.
3. Detector loops are measured along the sawed slot in the pavement containing the loop and lead-in rather than the actual length of the wire.
4. The cables, from the end of the saw cut for the loop to the splice in the handhole, shall not be measured for payment and shall be considered to be included in the cost of the Detector Loop.
5. Seven (7) days prior to any work that may affect the operation of the Detector Loops, and for signal timing adjustments to be made for the construction period and appropriate layout of Detector Loops for reinstallation. Notice shall be given to Scott Kullerstrand at the Illinois Department of Transportation, District 2 (815/284-5468).

Aggregate Base Course, Type B, is provided in the plan quantities and shall be used only as needed when directed by the Engineer.

The Contractor shall be responsible for protecting utility property during construction operations as outlined in Article 107.31 of the Standard Specifications. A minimum of 48 hours advance notice is required for non-emergency work. The JULIE number is 800-892-0123. The following listed utilities located within the project limits or immediately adjacent to the project construction limits are members of JULIE:

Commonwealth Edison Co.
NICOR Gas Co.
Comcast
US Signal

AT&T
Rock River Water Reclamation Dist.
City of Loves Park

Following are the known utilities located within the project limits or immediately adjacent to the project construction limits which are not members of JULIE and should be notified individually by the contractor:

Mr. Edward Rice
North Park Public Water Dist.
1350 Turret Dr.
Machesney Park, IL 61115
Ph. 815/633-5461

Tie bars shall be installed to tie PCC appurtenance to adjacent existing concrete pavement.

Tie the following
to the existing
concrete pavement

Length, size, and
spacing of Tie Bars

Gutter or Curb & Gutter	Std. 606001	600 mm (24") long No. 20 (No. 6) @ 600 mm (24") centers
PCC Base Course	Std. 353001	600 mm (24") long No. 20 (No. 6) @ 750 mm (30") centers
PCC Pavement	Std. 420101	600 mm (24") long No. 20 (No. 6) @ 750 mm (30") centers

Tie bars to be installed in accordance with the applicable portions of Article 420.05(b) of the Standard Specifications. See Highway Standard 420001 for detail on longitudinal construction joint grouted-in-place tie bar. The cost of the tie bars to be included in the cost of the PCC appurtenance adjacent to the existing pavement.

The Engineer shall determine if any aggregate is required under the Combination Concrete Curb & Gutter, Type B- and the Concrete Median Type SB-6.24 & Type SB-6 (Modified). The aggregate shall be AGGREGATE BASE COURSE, TYPE B. The thickness of this material shall be 4".

The transition from Combination Concrete Curb & Gutter, Type B-6.12 to Type B-6.24 shall be in 12 feet, and shall be paid for at the contract unit price per Foot for COMBINATION CONCRETE CURB & GUTTER, TYPE B-6.24.

The contractor shall be required to document the locations of the striping before any milling is performed. The contractor shall also be required to stake or mark out the locations of the final striping once the HMA items are completed. The cost of this work shall be included in the contract unit price for CONTRACTOR STAKING.

The contractor shall be required to station the road to the satisfaction of the Engineer prior to starting any work. The cost of this work shall be included in the contract unit price for CONTRACTOR STAKING.

It shall be the Contractor's responsibility to contact the municipality to determine approved methods of utility structure adjustment. (Mr. Steve Buelow of the Rock River Water Reclamation District (RRWRD) shall be contacted at 815/387-7592 when utility work involves sanitary manholes.) Utility structures may include, but are not limited to, manholes, water valves, handholes, etc. All materials and work necessary to complete adjustments per municipality requirements shall be included in the cost of the associated adjustment pay item. Several sanitary castings and lids shall be replaced as determined by the RRWRD. The new castings and lids will be provided to the Contractor by the RRWRD. The existing casting and lid shall remain the property of the RRWRD.

SCHEDULE OF QUANTITIES

35101400 AGGREGATE BASE COURSE, TYPE B

<u>TON</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
546.0	646+64	TO 704+81	CL	UNDER NEW MEDIAN, AS DIRECTED BY THE ENGINEER
546.0	TOTAL			

40600535 LEVELING BINDER (HAND METHOD), N70

<u>TON</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
28.0	612+50	TO 707+06		
28.0	TOTAL			

44003100 MEDIAN REMOVAL

<u>SQ FT</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
1240.0	646+64	TO 648+44	CL	
1728.0	656+12	TO 659+00	CL	
1482.0	659+36	TO 651+83	CL	
1256.0	677+09	TO 678+87	CL	
1730.0	679+45	TO 681+80	CL	
2810.0	692+46	TO 684+77	CL	
2007.0	688+57	TO 690+80	CL	
2664.0	695+20	TO 698+16	CL	
2421.0	698+90	TO 701+59	CL	
4257.0	702+37	TO 704+81	CL	
21595.0	TOTAL			

44200144 PAVEMENT PATCHING, TYPE II, 12"

<u>SQ YD</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
25.0	612+50	TO 707+06		TO BE USED AS DIRECTED BY THE ENGINEER
25.0	TOTAL			

44200148 PAVEMENT PATCHING, TYPE III, 12"

<u>SQ YD</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
15.0	612+50	TO 707+06		TO BE USED AS DIRECTED BY THE ENGINEER
15.0	TOTAL			

44200150 PAVEMENT PATCHING, TYPE IV, 12"

<u>SQ YD</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
34.0	612+50	TO 707+06		TO BE USED AS DIRECTED BY THE ENGINEER
34.0	TOTAL			

44300200 STRIP REFLECTIVE CRACK CONTROL TREATMENT

<u>FOOT</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
3700.0	638+00	TO 675+00	RT	NB RT LANE 4' FROM EDGE OF RT LANE (ALONG WIDE, CRACK)
2706.0	680+00	TO 707+06	RT	NB RT LANE 4' FROM EDGE OF RT LANE (ALONG WIDE, CRACK)
9456.0	612+50	TO 707+06	RT	NB LT LANE 4' FROM EDGE OF LT LANE (ALONG WIDE, CRACK)
9456.0	612+50	TO 707+06	LT	NB LT LANE 4' FROM EDGE OF LT LANE (ALONG WIDE, CRACK)
9456.0	612+50	TO 707+06	LT	SB LT LANE 4' FROM EDGE OF LT LANE (ALONG WIDE, CRACK)
9456.0	612+50	TO 707+06	LT	SB RT LANE 6' FROM EDGE OF RT LANE (ALONG WIDE, CRACK)
34774.0	TOTAL			

60255600 MANHOLES TO BE ADJUSTED

<u>EACH</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
18	612+50	TO 707+06	VAR.	SANITARY MANHOLES (100% RRWRD)
1	648+87		32' LT	SANITARY (RRWRD WILL PROVIDE NEW CASTINGS)
1	655+97		32' LT	SANITARY (RRWRD WILL PROVIDE NEW CASTINGS)
1	678+99		34' LT	SANITARY (RRWRD WILL PROVIDE NEW CASTINGS)
1	679+03		34' RT	SANITARY (RRWRD WILL PROVIDE NEW CASTINGS)
1	688+13		34' LT	SANITARY (RRWRD WILL PROVIDE NEW CASTINGS)
1	705+27		40' RT	SANITARY (RRWRD WILL PROVIDE NEW CASTINGS)
46	612+50	TO 707+06	VAR.	STORM MANHOLES
70	TOTAL			

60255800 MANHOLES TO BE ADJUSTED WITH NEW TYPE 1 FRAME, CLOSED LID

<u>EACH</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
3	612+50	TO 707+06	VAR.	STORM, TO BE USED AS DIRECTED BY THE ENGINEER
3	TOTAL			

60262510 INLETS TO BE ADJUSTED WITH NEW FRAME AND GRATE (SPECIAL)

<u>EACH</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
2	612+50	TO 707+06	VAR.	TO BE USED AS DIRECTED BY THE ENGINEER
2	612+50	TO 707+06	VAR.	TO BE USED AS DIRECTED IN PARKING LANE (100% CITY)
1	638+13		RT	NB IN PARKING LANE (100% CITY)
2	656+19		CL	SB AND NB IN MEDIAN
2	659+52		CL	SB AND NB IN MEDIAN
1	661+65		CL	SOUTH BOUND, IN MEDIAN
2	673+12		CL	SB AND NB IN MEDIAN
2	677+32		CL	SB AND NB IN MEDIAN
1	679+53		CL	SOUTH BOUND, IN MEDIAN
1	682+64		CL	SOUTH BOUND, IN MEDIAN
1	686+58		CL	SOUTH BOUND, IN MEDIAN
1	696+24		CL	SOUTH BOUND, IN MEDIAN
1	698+13		CL	SOUTH BOUND, IN MEDIAN
1	699+80		CL	SOUTH BOUND, IN MEDIAN
1	701+58		CL	SOUTH BOUND, IN MEDIAN
1	702+39		CL	SOUTH BOUND, IN MEDIAN
<u>22</u>				

60265700 VALVE VAULTS TO BE ADJUSTED

<u>EACH</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
43	612+50	TO 707+06	VAR	
<u>43</u>	<u>TOTAL</u>			

60265800 VALVE VAULTS TO BE ADJUSTED (SPECIAL)

<u>EACH</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
2	612+50	TO 707+06	VAR	TO BE USED AS DIRECTED BY THE ENGINEER
<u>2</u>	<u>TOTAL</u>			

60603800 COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12

<u>FOOT</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
48.0	683+22	TO 683+70	CL	NB MEDIAN, IN TAPER TO LEFT TURN LANE
<u>48.0</u>				

60605000 COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.24

<u>FOOT</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
54.0	682+68	TO 683+22	CL	NB MEDIAN
154.0	682+46	TO 683+70	CL	SB MEDIAN, INCLUDES QTY FOR RAMPED NOSE
464.0	702+89	TO 704+81	CL	AROUND MEDIAN
<u>672.0</u>	<u>TOTAL</u>			

60618300 CONCRETE MEDIAN SURFACE, 4"

<u>SQ FT</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
1349.0	682+46	TO 683+70	CL	
2772.0	702+77	TO 704+81	CL	
<u>4121.0</u>	<u>TOTAL</u>			

60619123 CONCRETE MEDIAN, TYPE SB-6 (MODIFIED)

<u>SQ FT</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
1240.0	646+64	TO 648+44	CL	
1728.0	656+12	TO 659+00	CL	
1482.0	659+36	TO 661+83	CL	
1266.0	677+09	TO 678+87	CL	
930.0	680+25	TO 681+80	CL	
920.0	683+70	TO 684+77	CL	
<u>7566.0</u>	<u>TOTAL</u>			

60620000 CONCRETE MEDIAN, TYPE SB-6.24

<u>SQ FT</u>	<u>LOCATION</u>		<u>OFFSET</u>	<u>REMARKS</u>
800.0	679+45	TO 680+25	CL	
2007.0	688+57	TO 690+80	CL	
2664.0	695+20	TO 698+16	CL	
2421.0	689+90	TO 701+59	CL	
400.0	702+37	TO 702+77	CL	
<u>8292.0</u>	<u>TOTAL</u>			

78000100 THERMOPLASTIC PAVEMENT MARKING - LETTERS AND SYMBOLS

SO FT	LOCATION	OFFSET	REMARKS
1,497.6	48 LEFT TURN LANES VAR. LOC.	CL	LEFT ARROWS, 2 ARROWS PER LANE
41.6	E RIVER LANE	CL	1 LEFT ARROW & 1 RIGHT / THROUGH COMBO ARROW
46.8	NB RIVERSIDE	RT	3 RIGHT ARROWS
46.8	SB RIVERSIDE	LT	3 RIGHT ARROWS
46.8	NB THEODORE	RT	3 RIGHT ARROWS
46.8	NB WINDSOR	RT	3 RIGHT ARROWS
1,728	TOTAL		

78000200 THERMOPLASTIC PAVEMENT MARKING - LINE 4"

FOOT	LOCATION	OFFSET	REMARKS
2,364	612+50 TO 707+06	LT	SB WHITE SKIP DASH
2,364	612+50 TO 707+06	RT	NB WHITE SKIP DASH
9,456	612+50 TO 707+06	LT	SB WHITE EOP (GAP AT SIDEROADS)
9,456	612+50 TO 707+06	RT	NB WHITE EOP (GAP AT SIDEROADS)
18,912	612+50 TO 707+06	CL	YELLOW EDGE LINE AROUND MEDIANS
30	RIVER LANE		INCLUDES EAST DOUBLE YELLOW & WEST YELLOW SKIP
20	GRAND AVE.		INCLUDES EAST & WEST YELLOW SKIP
30	CLIFFORD AVE.		INCLUDES EAST DOUBLE YELLOW & WEST YELLOW SKIP
30	THEODORE AVE		INCLUDES EAST DOUBLE YELLOW & WEST YELLOW SKIP
20	W. GLENDALE RD.		DOUBLE YELLOW
42,682	TOTAL		

78000400 THERMOPLASTIC PAVEMENT MARKING - LINE 6"

FOOT	LOCATION	OFFSET	REMARKS
60	SNOW AVE		
54	LILLIAN CT		
54	OLIVE CT		
60	JUNIUS AVE		
60	BOYLSTON ST.		
60	BEACON ST.		
60	CARMAN AVE.		
60	McKINLEY AVE.		
60	SYDNEY AVE.		
60	W PEARL AVE		
60	E PEARL AVE.		
60	LAWN DR.		
148	652+54		
60	W. RIVER LN.		
74	E. RIVER LN.		
148	652+97		
60	W. MERRILL		
60	E. MERRILL		
148	658+97		
82	W. GRAND AVE.		
82	E. GRAND AVE.		
148	659+52		
40	W. LOVES CT.		
60	E. LOVES CT.		
64	W. RIVER PARK RD.		
60	W. SHERIDAN DR.		
172	672+74		
152	W. RIVERSIDE BLVD.		
152	E. RIVERSIDE BLVD.		
160	673+08		
60	PARKWAY AVE.		
84	GRAND BLVD / CEL		
72	W. CLIFFORD AVE.		
60	E. CLIFFORD AVE.		
164	679+48		
52	BELTEBERG RD.		
52	W. HANNA CT.		
52	E. PENNSLVANIA AVE		
52	RENROSE AVE.		
52	HOSMER ST.		
52	W. THEODORE ST.		
72	E. THEODORE ST.		
148	685+24		
64	BURRWOOD AVE.		
84	CORONADO BLVD.		
28	705+07		
148	705+07		
72	W. GLENDALE RD.		
3,926	TOTAL		NB RIGHT TURN LANE MAINLINE

78000500 THERMOPLASTIC PAVEMENT MARKING - LINE 8"

FOOT	LOCATION	OFFSET	REMARKS
4,800	48 LEFT TURN LANES VAR. LOC.	CL	MATCH EXISTING LENGTHS
301	665+85 TO 668+86	LT	SB PARKING LANE
314	671+18 TO 672+75	RT	NB RIGHT TURN LANE AT RIVERSIDE
110	673+08 TO 674+18	LT	SB RIGHT TURN LANE AT RIVERSIDE
170	677+10 TO 678+80	RT	NB PARKING LANE
104	693+44 TO 694+48	RT	NB RIGHT TURN LANE AT THEODORE
116	703+57 TO 704+73	RT	NB RIGHT TURN LANE AT WINSOR
10	W. GLENDALE		
15	E. THEODORE		
15	E RIVER LANE		
5,955	TOTAL		

78000600 THERMOPLASTIC PAVEMENT MARKING - LINE 12"

FOOT	LOCATION	OFFSET	REMARKS
55	665+85 TO 668+86	LT	SB PARKING LANE
99	671+18 TO 672+75	RT	NB RIGHT TURN LANE AT RIVERSIDE
30	677+10 TO 678+80	RT	NB PARKING LANE
184	TOTAL		

78000650 THERMOPLASTIC PAVEMENT MARKING - LINE 24"

FOOT	LOCATION	OFFSET	REMARKS
15	SNOW AVE		
13	LILLIAN CT		
13	OLIVE CT		
15	JUNIUS AVE		
15	BOYLSTON ST.		
30	624+44		NB
15	BEACON ST.		
37	625+00		SB
15	CARMAN AVE		
15	McKINLEY AVE.		
15	SYDNEY AVE.		
15	W PEARL AVE		
15	E PEARL AVE.		
15	LAWN DR.		
30	652+54		NB
15	W. RIVER LN.		
18	E. RIVER LN.		
37	652+97		SB
15	W. MERRILL AVE.		
15	E. MERRILL AVE.		
38	658+97		NB
20	W. GRAND AVE.		
20	E. GRAND AVE.		
37	659+52		SB
10	W. LOVES CT.		
15	E. LOVES CT.		
18	W. RIVER PARK RD.		
14	E. FRONTAGE RD. ENT.		
15	W. SHERIDAN DR.		
14	E. FRONTAGE RD. ENT.		
52	672+74		NB
48	673+08		SB
15	PARKWAY AVE.		
21	GRAND BLVD / CEL		
40	678+78		NB
18	W. CLIFFORD AVE.		
16	E. CLIFFORD AVE.		
40	679+48		SB
13	BELTEBERG RD.		
13	W. HANNA CT.		
13	E. PENNSLVANIA AVE		
13	RENROSE AVE.		
13	HOSMER ST.		
34	694+48		NB
13	W. THEODORE ST.		
24	E. THEODORE ST.		
44	695+24		SB
13	BURRWOOD AVE.		
13	CORONADO BLVD.		
34	705+07		NB
14	705+07		NB RIGHT TURN LANE
24	W. GLENDALE R.D.		
36	705+81		SB
1,135	TOTAL		

78100100 RAISED REFLECTIVE PAVEMENT MARKER

<u>EACH</u>	<u>LOCATION</u>			<u>OFFSET</u>	<u>REMARKS</u>
236	612+50	TO	707+06	NB CL	2 ONE-WAY CRYSTAL MARKERS AT 80' SPACING
236	612+50	TO	707+06	SB CL	2 ONE-WAY CRYSTAL MARKERS AT 80' SPACING
250	612+50	TO	707+06	LT & RT	ONE-WAY CRYSTAL MARKERS-TURN LANES 20' SPACING
<u>733</u>	<u>TOTAL</u>				

78300200 RAISED REFLECTIVE PAVEMENT MARKER REMOVAL

<u>EACH</u>	<u>LOCATION</u>			<u>OFFSET</u>	<u>REMARKS</u>
214	612+50	TO	707+06	NB CL	
208	612+50	TO	707+06	SB CL	
285	612+50	TO	707+06	LT & RT	VARIOUS TURN BAYS
<u>707</u>	<u>TOTAL</u>				

88600400 DETECTOR LOOPS, SPECIAL

<u>FOOT</u>	<u>LOCATION</u>			<u>OFFSET</u>	<u>REMARKS</u>
200	CEL				2 - 6X20
200	BEACON ST.				2 - 6X20
100	652+25				1 - 6 X 30 NB LEFT TURN LANE AT RIVER LANE
100	653+30				1 - 6 X 30 SB LEFT TURN LANE AT RIVER LANE
200	W. RIVER LN				1 - 6 X 30 AND 1 - 4 X 30
100	E RIVER LN				2 - 6 X 20
100	W. GRAND AVE				1 - 6 X 20
100	E. GRAND AVE				1 - 6 X 20
200	672+40				2 - 6 X 20 NB LEFT TURN LANE AT RIVERSIDE
200	672+40				1 - 6 X 20 NB EACH THROUGH LANE
200	673+30				2 - 6 X 20 SB LEFT TURN LANE AT RIVERSIDE
200	673+30				1 - 6 X 20 SB EACH THROUGH LANE
200	W CLIFFORD				2 - 6 X 20
100	E CLIFFORD				1 - 6 X 20
200	679+75				2 - 6 X 20 SB LEFT TURN LANE AT CLIFFORD AVE
100	W THEODORE				1 - 6 X 20
200	E THEODORE				2 - 6 X 20
100	695+40				1 - 6 X 20 SB LEFT TURN LANE AT THEODORE
400	W GLENDALE RD				4 - 6 X 20
200	704+70				2 - 6 X 20 NB LEFT TURN LANE AT GLENDALE/WINDSOR
200	706+15				2 - 6 X 20 SB LEFT TURN LANE AT GLENDALE/WINDSOR
<u>3600</u>	<u>TOTAL</u>				

Z0028415 GEOTECHNICAL REINFORCEMENT

<u>SQ YD</u>	<u>LOCATION</u>			<u>OFFSET</u>	<u>REMARKS</u>
76.0	612+50	TO	707+06		TO BE USED AS DIRECTED BY THE ENGINEER
<u>76.0</u>	<u>TOTAL</u>				

Z0028700 GRANULAR SUBGRADE REPLACEMENT

<u>CU YD</u>	<u>LOCATION</u>			<u>OFFSET</u>	<u>REMARKS</u>
13	612+50	TO	707+06		TO BE USED AS DIRECTED BY THE ENGINEER
<u>13</u>	<u>TOTAL</u>				

BITUMINOUS SCHEDULE

LOCATION		PAVT LENGTH	PAVT WIDTH	PAVEMENT AREA	BIT. PRIME 2 APPL	AGG. PRIME	POLYMERIZED LEVELING BINDER (MM), N70	TEMPORARY RAMP
STATIONING	DESCRIPTION	(FT.)	(FT.)	(SQ YD)	(TON)	(TON)	(TON)	(SQ YD)
	NORTH BOUND							
612+50 TO 614+77		227	26	656	0.49	1.0	35.7	11.6
614+77 TO 615+13	LILLIAN CT	36	33	132	0.09	0.2	7.4	
615+13 TO 616+56		143	26	413	0.31	0.6	23.1	
616+56 TO 616+96		40	30	133	0.10	0.2	7.5	
616+96 TO 617+88		92	34	348	0.25	0.5	19.5	
617+88 TO 618+24	OLIVE ST	36	33	132	0.09	0.2	7.4	
618+24 TO 619+93		169	28	526	0.39	0.8	29.4	
619+93 TO 620+29	JUNIUS AVE	36	33	132	0.09	0.2	7.4	
620+29 TO 621+16		87	26	251	0.19	0.4	14.1	
621+16 TO 621+52	BOYLSTON ST	36	33	132	0.09	0.2	7.4	
621+52 TO 624+54		302	26	872	0.65	1.3	48.9	
624+54 TO 624+90	BEACON ST	36	33	132	0.09	0.2	7.4	
624+90 TO 626+43		153	28	476	0.35	0.7	26.7	
626+43 TO 626+79	CARMEN AVE	36	33	132	0.09	0.2	7.4	
626+79 TO 628+07		128	30	427	0.31	0.6	23.9	
628+07 TO 629+38		131	34	455	0.35	0.7	27.7	
629+38 TO 629+74	WOODWARD	36	33	132	0.09	0.2	7.4	
629+74 TO 631+13		139	26	402	0.30	0.6	22.5	
631+13 TO 631+53		40	30	133	0.10	0.2	7.5	
631+53 TO 632+93		140	34	529	0.37	0.8	29.6	
632+93 TO 633+29	McKINLEY AVE	36	33	132	0.09	0.2	7.4	
633+29 TO 633+77		48	30	160	0.12	0.2	9.0	
633+77 TO 634+29		52	34	196	0.14	0.3	11.0	
634+29 TO 634+65	SYDNEY AVE	36	33	132	0.09	0.2	7.4	
634+65 TO 637+74		309	26	853	0.67	1.3	50.0	
637+74 TO 638+10	FRANCES AVE	36	33	132	0.09	0.2	7.4	
638+10 TO 639+45		135	30	450	0.33	0.7	25.2	
639+45 TO 639+83	W PEARL AVE	38	33	139	0.10	0.2	7.8	
639+83 TO 641+37		154	26	445	0.33	0.7	24.9	
641+37 TO 641+73	E PEARL AVE	36	33	132	0.09	0.2	7.4	
641+73 TO 643+16		143	26	413	0.31	0.6	23.1	
643+16 TO 643+93		77	30	257	0.19	0.4	14.4	
643+93 TO 645+03		110	34	416	0.29	0.6	23.3	
645+03 TO 645+48	CEL	45	33	165	0.12	0.2	9.2	
645+48 TO 646+28		80	34	302	0.21	0.5	16.9	
646+28 TO 646+64	LAWN DR	36	33	132	0.09	0.2	7.4	
646+64 TO 649+59		295	26	852	0.64	1.3	47.7	
649+59 TO 651+20		161	30	537	0.39	0.8	30.1	
651+20 TO 652+57		137	34	518	0.37	0.8	29.0	
652+57 TO 652+93	RIVER LN	36	33	132	0.09	0.2	7.4	
652+93 TO 654+12		119	26	344	0.26	0.5	19.3	
654+12 TO 654+52		40	30	133	0.10	0.2	7.5	
654+52 TO 655+71		119	34	450	0.32	0.7	25.2	
655+71 TO 656+12	MERRILL AVE	41	33	150	0.11	0.2	8.4	
656+12 TO 657+35		123	26	355	0.27	0.5	19.9	
657+35 TO 657+75		40	30	133	0.10	0.2	7.5	
657+75 TO 659+00		125	34	472	0.33	0.7	25.4	
659+00 TO 659+35	GRAND AVE	36	33	132	0.09	0.2	7.4	
659+35 TO 660+39		103	26	298	0.22	0.4	18.7	
660+39 TO 660+79		40	30	133	0.10	0.2	7.5	
660+79 TO 661+83		104	34	393	0.28	0.6	22.0	
661+83 TO 662+57	LOVES CT	84	33	308	0.22	0.5	17.2	
662+57 TO 663+88		121	26	350	0.26	0.5	19.6	
663+88 TO 664+28		40	30	133	0.10	0.2	7.5	
664+28 TO 665+49		121	34	457	0.32	0.7	25.6	
665+49 TO 665+85	RIVER PARK RD	36	33	132	0.09	0.2	7.4	
665+85 TO 667+15		130	26	376	0.28	0.6	21.0	

BITUMINOUS SCHEDULE

		40603310	40603565	40600050	44000158	44000158	70300100	70301000
LOCATION		HMA SURF CRSE MIX "C", N50 2-1/4"	POLYMERIZED HMA SURF CRSE, MIX "E" N70, 1-1/2"	INCIDENTAL HOT MIX SURFACING	HMA SURF REM 2 1/4" MAINLINE	HMA SURF REM 2 1/4" PARKING	SHORT TERM PAVEMENT MARKINGS	WORK ZONE PAVE MARK REMOVAL
STATIONING		(TON)	(TON)	(TON)	(SQ YD)	(SQ YD)	(FT.)	(SQ FT)
DESCRIPTION		NORTH BOUND						
612+50	TO 614 + 77	25.4	55.1		655.8	201.8	90.8	10.1
614+77	TO 615 + 13	4.0	11.1		132.0	32.0	14.4	1.6
615+13	TO 616 + 55	16.0	34.7		413.1	127.1	57.2	6.4
616+55	TO 616 + 95	4.5	11.2		133.3	35.6	16.0	1.8
616+95	TO 617 + 88	10.3	29.2		347.6	81.8	36.8	4.1
617+88	TO 618 + 24	4.0	11.1		132.0	32.0	14.4	1.6
618+24	TO 619 + 93	18.9	44.2		525.8	150.2	67.5	7.5
619+93	TO 620 + 29	4.0	11.1		132.0	32.0	14.4	1.6
620+29	TO 621 + 16	9.7	21.1		251.3	77.3	34.8	3.9
621+16	TO 621 + 52	4.0	11.1		132.0	32.0	14.4	1.6
621+52	TO 624 + 54	33.8	73.3		872.4	258.4	120.8	13.4
624+54	TO 624 + 90	4.0	11.1		132.0	32.0	14.4	1.6
624+90	TO 626 + 43	17.1	40.0		475.0	135.0	61.2	6.8
626+43	TO 626 + 79	4.0	11.1		132.0	32.0	14.4	1.6
626+79	TO 628 + 07	14.3	35.8		426.7	113.8	51.2	5.7
628+07	TO 629 + 38	14.7	41.6		494.9	116.4	52.4	5.8
629+38	TO 629 + 74	4.0	11.1		132.0	32.0	14.4	1.6
629+74	TO 631 + 13	15.6	33.7		401.6	123.6	55.6	6.2
631+13	TO 631 + 53	4.5	11.2		133.3	35.6	16.0	1.8
631+53	TO 632 + 93	15.7	44.4		528.9	124.4	56.0	6.2
632+93	TO 633 + 29	4.0	11.1		132.0	32.0	14.4	1.6
633+29	TO 633 + 77	5.4	13.4		150.0	42.7	19.2	2.1
633+77	TO 634 + 29	5.8	16.5		196.4	46.2	20.8	2.3
634+29	TO 634 + 65	4.0	11.1		132.0	32.0	14.4	1.6
634+65	TO 637 + 74	34.6	75.0		892.7	274.7	123.6	13.7
637+74	TO 638 + 10	4.0	11.1		132.0	32.0	14.4	1.6
638+10	TO 639 + 45	15.1	37.8		450.0	120.0	54.0	6.0
639+45	TO 639 + 83	4.3	11.7		139.3	33.8	15.2	1.7
639+83	TO 641 + 37	17.2	37.4		444.9	136.9	61.6	6.8
641+37	TO 641 + 73	4.0	11.1		132.0	32.0	14.4	1.6
641+73	TO 643 + 16	16.0	34.7		413.1	127.1	57.2	6.4
643+16	TO 643 + 93	8.6	21.6		256.7	68.4	30.8	3.4
643+93	TO 645 + 03	12.3	34.9		415.6	97.8	44.0	4.9
645+03	TO 645 + 48	5.0	13.9		165.0	40.0	18.0	2.0
645+48	TO 646 + 28	9.0	25.4		302.2	71.1	32.0	3.6
646+28	TO 646 + 64	4.0	11.1		172.0	32.0	14.4	1.6
646+64	TO 649 + 59	33.0	71.6		852.2	262.2	118.0	13.1
649+59	TO 651 + 20	18.0	45.1		536.7	143.1	64.4	7.2
651+20	TO 652 + 57	15.3	43.5		517.6	121.8	54.8	6.1
652+57	TO 652 + 93	4.0	11.1		132.0	32.0	14.4	1.6
652+93	TO 654 + 12	13.3	28.9		343.8	105.8	47.6	5.3
654+12	TO 654 + 52	4.5	11.2		133.3	35.6	16.0	1.8
654+52	TO 655 + 71	13.3	37.8		449.6	105.8	47.6	5.3
655+71	TO 656 + 12	4.6	12.6		150.3	36.4	16.4	1.8
656+12	TO 657 + 35	13.8	29.8		355.3	109.3	49.2	5.5
657+35	TO 657 + 75	4.5	11.2		177.8	35.6	16.0	1.8
657+75	TO 659 + 00	14.0	39.7		611.1	111.1	50.0	5.6
659+00	TO 659 + 36	4.0	11.1		172.0	32.0	14.4	1.6
659+36	TO 660 + 39	11.5	25.0		412.0	91.6	41.2	4.6
660+39	TO 660 + 79	4.5	11.2		177.8	35.6	16.0	1.8
660+79	TO 661 + 83	11.6	33.0		508.4	92.4	41.6	4.6
661+83	TO 662 + 67	9.4	25.9		401.3	74.7	33.6	3.7
662+67	TO 663 + 88	13.6	29.4		484.0	107.6	48.4	5.4
663+88	TO 664 + 28	4.5	11.2		177.8	35.6	16.0	1.8
664+28	TO 665 + 49	13.6	38.4		591.6	107.6	48.4	5.4
665+49	TO 665 + 85	4.0	11.1		172.0	32.0	14.4	1.6
665+85	TO 667 + 15	14.6	31.5		520.0	115.6	52.0	5.8

BITUMINOUS SCHEDULE

LOCATION		PAVT LENGTH	PAVT WIDTH	PAVEMENT AREA	BIT. PRIME 2 APPL	AGG. PRIME	POLYMERIZED LEVELING BINDER (MM), N70	TEMPORARY RAMP
STATIONING		(FT.)	(FT.)	(SQ YD)	(TON)	(TON)	(TON)	(SQ YD)
667+15	TO 667 + 55	40	30	133	0.10	0.2	7.5	
667+55	TO 668 + 86	131	34	495	0.35	0.7	27.7	
668+86	TO 669 + 22	36	33	132	0.09	0.2	7.4	
669+22	TO 670 + 57	135	40	600	0.34	0.9	33.6	
670+57	TO 672 + 64	207	52	1196	0.69	1.8	67.0	
672+64	TO 673 + 08	44	58	284	0.16	0.4	15.9	19.6
673+08	TO 674 + 46	138	26	399	0.30	0.6	22.3	
674+46	TO 674 + 86	40	30	133	0.10	0.2	7.5	
674+86	TO 676 + 72	186	34	703	0.50	1.1	39.3	
676+72	TO 677 + 12	40	33	147	0.10	0.2	8.2	
677+12	TO 677 + 52	40	38	169	0.10	0.3	9.5	
677+52	TO 678 + 78	126	44	616	0.35	0.9	34.5	
678+78	TO 679 + 48	70	33	257	0.15	0.4	14.4	
679+48	TO 680 + 25	77	26	222	0.18	0.3	12.5	
680+25	TO 681 + 04	79	31	272	0.21	0.4	15.2	
681+04	TO 681 + 80	76	36	304	0.22	0.5	17.0	
681+80	TO 682 + 36	59	32	210	0.16	0.3	11.7	
682+36	TO 683 + 22	83	26	240	0.19	0.4	13.4	
683+22	TO 684 + 02	80	31	276	0.21	0.4	15.4	
684+02	TO 684 + 77	75	36	300	0.22	0.5	16.8	
684+77	TO 685 + 27	50	32	178	0.13	0.3	10.0	
685+27	TO 686 + 07	80	26	231	0.18	0.3	12.9	
686+07	TO 686 + 77	70	31	241	0.18	0.4	13.5	
686+77	TO 687 + 77	100	36	400	0.29	0.6	22.4	
687+77	TO 688 + 53	76	32	270	0.20	0.4	15.1	
688+53	TO 689 + 21	68	26	196	0.16	0.3	11.0	
689+21	TO 690 + 01	80	31	276	0.21	0.4	15.4	
690+01	TO 690 + 80	79	36	316	0.23	0.5	17.7	
690+80	TO 691 + 41	61	32	217	0.16	0.3	12.1	
691+41	TO 692 + 64	123	26	355	0.28	0.5	19.9	
692+64	TO 693 + 44	80	41	364	0.21	0.5	20.4	
693+44	TO 694 + 48	104	46	532	0.30	0.8	29.8	
694+48	TO 694 + 80	32	46	164	0.09	0.2	9.2	
694+80	TO 695 + 44	64	33	235	0.13	0.4	13.1	
695+44	TO 696 + 29	85	28	264	0.15	0.4	14.8	
696+29	TO 697 + 09	80	33	293	0.17	0.4	16.4	
697+09	TO 698 + 14	105	38	443	0.25	0.7	24.8	
698+14	TO 698 + 82	68	33	249	0.14	0.4	14.0	
698+82	TO 699 + 84	102	28	317	0.18	0.5	17.8	
699+84	TO 700 + 64	80	33	293	0.17	0.4	16.4	
700+64	TO 701 + 59	95	38	401	0.23	0.6	22.5	
701+59	TO 702 + 37	76	33	285	0.15	0.4	16.0	
702+37	TO 702 + 87	50	28	156	0.09	0.2	8.7	
702+87	TO 703 + 57	70	38	296	0.17	0.4	16.6	
703+57	TO 704 + 73	116	48	619	0.35	0.9	34.6	
704+73	TO 705 + 73	100	34	378	0.22	0.6	21.2	
705+73	TO 707 + 06	133	28	414	0.24	0.6	23.2	12.4
NORTH BOUND TOTALS					23.0	50.0	1867.0	43.6

BITUMINOUS SCHEDULE

LOCATION		40803310	40603565	40800050	44000158	44000158	70300100	70301000
		HMA SURF CRSE MIX "C", N50 2-1/4"	POLYMERIZED HMA SURF CRSE, MIX "E" N70, 1-1/2"	INCIDENTAL HOT MIX SURFACING	HMA SURF REM 2 1/4" MAINLINE	HMA SURF REM 2 1/4" PARKING	SHORT TERM PAVEMENT MARKINGS	WORK ZONE PAVE MARK REMOVAL
STATIONING	DESCRIPTION	(TON)	(TON)	(TON)	(SQ YD)	(SQ YD)	(FT.)	(SQ FT)
667+15 TO 667 + 55		4.5	11.2		177.8	35.6	16.0	1.8
667+55 TO 668 + 86		14.7	41.6		640.4	116.4	52.4	5.8
668+86 TO 669 + 22	SHERIDAN DR	4.0	11.1		172.0	32.0	14.4	1.6
669+22 TO 670 + 57			50.4		750.0		54.0	6.0
670+57 TO 672 + 64			100.5		1426.0		82.8	9.2
672+64 TO 673 + 08	RIVERSIDE BLVD		23.8		332.4		17.6	2.0
673+08 TO 674 + 46		15.5	33.5		552.0	122.7	55.2	6.1
674+46 TO 674 + 86		4.5	11.2		177.8	35.6	16.0	1.8
674+86 TO 676 + 72		20.8	58.0		909.3	165.3	74.4	8.3
676+72 TO 677 + 12	GRAND BLVD / CEL	4.5	12.3		191.1	35.6	16.0	1.8
677+12 TO 677 + 52			14.2		213.3		15.0	1.8
677+52 TO 678 + 78			51.7		755.0		50.4	5.6
678+78 TO 679 + 48	CLIFFORD AVE		21.6		334.4		28.0	3.1
679+48 TO 680 + 25		10.6	18.7		308.0	85.6	30.8	3.4
680+25 TO 681 + 04		11.1	22.9		359.9	87.8	31.6	3.5
681+04 TO 681 + 80		10.6	25.5		388.4	84.4	30.4	3.4
681+80 TO 682 + 39	BETTEBERG RD	8.3	17.6		275.3	65.6	23.6	2.6
682+39 TO 683 + 22		11.6	20.1		332.0	92.2	33.2	3.7
683+22 TO 684 + 02		11.2	23.1		364.4	88.9	32.0	3.6
684+02 TO 684 + 77		10.5	25.2		383.3	83.3	30.0	3.3
684+77 TO 685 + 27	PENNSYLVANIA AVE	7.0	14.9		177.8	55.6	20.0	2.2
685+27 TO 685 + 07		11.2	19.4		231.1	88.8	32.0	3.6
685+07 TO 685 + 77		9.8	20.3		241.1	77.8	28.0	3.1
685+77 TO 687 + 77		14.0	33.6		400.0	111.1	40.0	4.4
687+77 TO 688 + 53	RENROSE AVE	10.6	22.7		270.2	84.4	30.4	3.4
688+53 TO 689 + 21		9.5	16.5		196.4	75.6	27.2	3.0
689+21 TO 690 + 01		11.2	23.1		275.6	88.9	32.0	3.6
690+01 TO 690 + 80		11.1	26.5		316.0	87.8	31.6	3.5
690+80 TO 691 + 41	HOSMER ST	8.5	18.2		216.9	67.8	24.4	2.7
691+41 TO 692 + 64		17.2	29.8		355.3	136.7	48.2	5.5
692+64 TO 693 + 44			30.6		364.4		32.0	3.6
693+44 TO 694 + 48			44.7		531.6		41.6	4.6
694+48 TO 694 + 80	INCL. QUANT. FOR RT TURN LN		13.7		163.6		12.8	1.4
694+80 TO 695 + 44	THEODORE ST		19.7		234.7		25.6	2.8
695+44 TO 696 + 29			22.2		264.4		34.0	3.8
696+29 TO 697 + 09			24.6		293.3		32.0	3.6
697+09 TO 698 + 14			37.2		443.3		42.0	4.7
698+14 TO 698 + 82	BURRWOOD AVE / CER		20.9		249.3		27.2	3.0
698+82 TO 699 + 84			26.7		317.3		40.8	4.5
699+84 TO 700 + 64			24.6		283.3		32.0	3.6
700+64 TO 701 + 59			33.7		506.7		38.0	4.2
701+59 TO 702 + 37	CORONADO BLVD / CER		24.0		372.7		31.2	3.5
702+37 TO 702 + 87			13.1		211.1		20.0	2.2
702+87 TO 703 + 57			24.8		295.6		28.0	3.1
703+57 TO 704 + 73			52.0		618.7		46.4	5.2
704+73 TO 705 + 73	WINDSOR RD		31.7		377.8		40.0	4.4
705+73 TO 707 + 06			34.8		413.8		53.2	5.9
NORTH BOUND TOTALS		864.8	2800.5		36673.2	6863.1	3782.4	420.3

BITUMINOUS SCHEDULE

LOCATION		PAVT LENGTH	PAVT WIDTH	PAVEMENT AREA	BIT. PRIME 2 APPL	AGG. PRIME	POLYMERIZED LEVELING BINDER (MM), NTD	TEMPORARY RAMP
STATIONING		(FT.)	(FT.)	(SQ YD)	(TON)	(TON)	(TON)	(SQ YD)
707+06	TO 706 + 14	92	40	409	0.23	0.6	22.9	17.8
706+14	TO 704 + 96	118	34	446	0.33	0.7	25.0	
704+96	TO 703 + 53	143	26	413	0.33	0.6	23.1	
703+53	TO 702 + 77	76	31	262	0.20	0.4	14.7	
702+77	TO 701 + 59	118	36	472	0.34	0.7	26.4	
701+59	TO 700 + 64	95	26	274	0.22	0.4	15.4	
700+64	TO 699 + 84	80	31	276	0.21	0.4	15.4	
699+84	TO 698 + 14	170	36	680	0.50	1.0	38.1	
698+14	TO 697 + 09	105	26	303	0.24	0.5	17.0	
697+09	TO 695 + 29	80	31	276	0.21	0.4	15.4	
696+29	TO 694 + 48	181	36	724	0.53	1.1	40.5	
694+48	TO 691 + 41	307	26	887	0.70	1.3	49.7	
691+41	TO 690 + 80	61	34	230	0.17	0.3	12.9	
690+80	TO 690 + 01	79	26	228	0.18	0.3	12.8	
690+01	TO 689 + 21	80	31	276	0.21	0.4	15.4	
689+21	TO 687 + 77	144	36	576	0.42	0.9	32.3	
687+77	TO 685 + 27	250	26	722	0.57	1.1	40.4	
685+27	TO 684 + 77	50	34	189	0.14	0.3	10.6	
684+77	TO 682 + 39	238	26	688	0.54	1.0	38.5	
682+39	TO 681 + 80	59	34	223	0.16	0.3	12.5	
681+80	TO 681 + 04	76	26	220	0.17	0.3	12.3	
681+04	TO 680 + 25	79	30	263	0.20	0.4	14.7	
680+25	TO 678 + 78	147	34	555	0.41	0.8	31.1	
678+78	TO 677 + 12	166	26	480	0.35	0.7	26.9	
677+12	TO 676 + 72	40	34	151	0.11	0.2	8.5	
676+72	TO 674 + 86	186	26	537	0.40	0.8	30.1	
674+86	TO 674 + 46	40	44	196	0.11	0.3	11.0	
674+46	TO 672 + 48	198	48	1056	0.60	1.5	59.1	19.6
672+48	TO 669 + 29	319	26	822	0.69	1.4	51.6	
669+29	TO 668 + 86	43	33	158	0.11	0.2	8.8	
668+86	TO 667 + 55	131	40	582	0.33	0.9	32.6	
667+55	TO 667 + 15	40	45	200	0.11	0.3	11.2	
667+15	TO 665 + 85	130	48	693	0.40	1.0	38.8	
665+85	TO 665 + 49	36	33	132	0.09	0.2	7.4	
665+49	TO 664 + 28	121	26	350	0.26	0.5	19.6	
664+28	TO 663 + 88	40	30	133	0.10	0.2	7.5	
663+88	TO 662 + 67	121	34	457	0.33	0.7	26.6	
662+67	TO 661 + 83	84	33	308	0.22	0.5	17.2	
661+83	TO 660 + 79	104	26	300	0.23	0.5	16.8	
660+79	TO 660 + 39	40	30	133	0.10	0.2	7.5	
660+39	TO 659 + 00	139	34	525	0.38	0.8	29.4	
659+00	TO 657 + 75	125	26	361	0.28	0.5	20.2	
657+75	TO 657 + 35	40	30	133	0.10	0.2	7.5	
657+35	TO 655 + 71	164	34	620	0.45	0.9	34.7	
655+71	TO 654 + 62	119	26	344	0.28	0.5	19.3	
654+62	TO 654 + 12	40	30	133	0.10	0.2	7.5	
654+12	TO 652 + 57	155	34	586	0.42	0.9	32.8	
652+57	TO 648 + 44	413	26	1193	0.92	1.8	65.8	
648+44	TO 648 + 04	40	30	133	0.10	0.2	7.5	
648+04	TO 646 + 28	176	34	656	0.48	1.0	37.2	

BITUMINOUS SCHEDULE

STATIONING		DESCRIPTION	40603310 HMA SURF CRSE MIX "C", N50 2-1/4" (TON)	40603565 POLYMERIZED HMA SURF CRSE, MIX "E" N70, 1-1/2" (TON)	40900050 INCIDENTAL HOT MIX SURFACING (TON)	44000158 HMA SURF REM 2 1/4" MAINLINE (SQ YD)	44000158 HMA SURF REM 2 1/4" PARKING (SQ YD)	70300100 SHORT TERM PAVEMENT MARKINGS (FT.)	70301000 WORK ZONE PAVE MARK REMOVAL (SQ FT)
		SOUTH BOUND							
707+96	TO 706 + 14			34.3		552.0		36.8	4.1
706+14	TO 704 + 96	WINDSOR RD	16.5	37.4		629.3	191.1	47.2	5.2
704+96	TO 703 + 53		20.0	34.7		413.1	159.9	37.2	6.4
703+53	TO 702 + 77		10.6	22.0		261.8	84.4	30.4	3.4
702+77	TO 701 + 59	CORONADO BLVD / CER	16.5	39.6		603.1	131.1	47.2	5.2
701+59	TO 700 + 64		13.3	23.1		380.0	105.6	38.0	4.2
700+64	TO 699 + 84		11.2	23.1		346.7	88.9	32.0	3.6
699+84	TO 698 + 14	BURRWOOD AVE / CER	23.8	57.1		831.1	188.9	68.0	7.6
698+14	TO 697 + 09		14.7	25.5		396.7	116.7	42.0	4.7
697+09	TO 696 + 29		11.2	23.1		346.7	88.9	32.0	3.6
696+29	TO 694 + 48	THEODORE ST	25.3	60.8		724.0	201.1	72.4	8.0
694+48	TO 691 + 41		43.0	74.5		1159.8	341.1	122.8	13.6
691+41	TO 690 + 80	HOSMER ST	8.5	19.4		284.7	67.8	24.4	2.7
690+80	TO 690 + 01		11.1	19.2		298.4	87.8	31.6	3.5
690+01	TO 689 + 21		11.2	23.1		346.7	88.9	32.0	3.6
689+21	TO 687 + 77	RENROSE AVE	20.2	48.4		576.0	160.0	57.6	6.4
687+77	TO 685 + 27		35.0	60.7		722.2	277.9	100.0	11.1
685+27	TO 684 + 77	PENNSYLVANIA AVE	7.0	15.9		188.9	55.6	20.0	2.2
684+77	TO 682 + 39		33.3	57.8		687.6	264.4	95.2	10.6
682+39	TO 681 + 80	BETTEBERG RD	8.3	18.7		222.9	65.6	23.6	2.6
681+80	TO 681 + 04		10.6	18.4		219.6	84.4	30.4	3.4
681+04	TO 680 + 25		11.1	22.1		263.3	87.8	31.6	3.5
680+25	TO 678 + 78	CLIFFORD AVE	20.6	46.6		555.3	163.3	58.8	6.5
678+78	TO 677 + 12		18.6	40.3		479.6	147.6	66.4	7.4
677+12	TO 676 + 72	GRAND BLVD / CEL	4.5	12.7		151.1	35.6	16.0	1.8
676+72	TO 674 + 86		20.8	45.1		537.3	165.3	74.4	8.3
674+86	TO 674 + 46			16.4		195.6		16.0	1.8
674+46	TO 672 + 48	THRU RIVERSIDE BLVD		88.7		1056.0		79.2	8.8
672+48	TO 659 + 29		35.7	77.4		921.6	283.6	127.6	14.2
659+29	TO 658 + 86	SHERIDAN DR	4.8	13.2		157.7	38.2	17.2	1.9
658+86	TO 657 + 55			48.9		582.2		52.4	5.8
657+55	TO 657 + 15			16.8		200.0		16.0	1.8
657+15	TO 655 + 85			58.2		693.3		52.0	5.8
655+85	TO 655 + 49	RIVER PARK RD	4.0	11.1		132.0	32.0	14.4	1.6
655+49	TO 664 + 28		13.6	29.4		349.6	107.6	48.4	5.4
664+28	TO 663 + 88		5.0	11.2		133.3	40.0	16.0	1.8
663+88	TO 662 + 87		15.2	38.4		467.1	121.0	48.4	5.4
662+87	TO 661 + 83	LOVES CT	10.6	25.9		308.0	84.0	33.6	3.7
661+83	TO 660 + 79		13.1	25.2		300.4	104.0	41.6	4.6
660+79	TO 660 + 39		5.0	11.2		133.3	40.0	16.0	1.8
660+39	TO 659 + 00	GRAND AVE	17.5	44.1		525.1	139.0	55.6	6.2
659+00	TO 657 + 75		15.8	30.3		381.1	125.0	50.0	5.6
657+75	TO 657 + 35		5.0	11.2		133.3	40.0	16.0	1.8
657+35	TO 655 + 71	MERRILL AVE	20.7	52.0		519.6	154.0	65.6	7.3
655+71	TO 654 + 52		15.0	28.9		343.8	119.0	47.6	5.3
654+52	TO 654 + 12		5.0	11.2		133.3	40.0	16.0	1.8
654+12	TO 652 + 67	RIVER LN	19.5	49.2		586.6	155.0	62.0	6.9
652+67	TO 648 + 44		52.0	100.2		1183.1	413.0	165.2	18.4
648+44	TO 648 + 04		5.0	11.2		133.3	40.0	16.0	1.8
648+04	TO 645 + 28	LAWN DR	22.2	55.9		664.6	175.0	70.4	7.8

BITUMINOUS SCHEDULE

LOCATION		PAVT LENGTH	PAVT WIDTH	PAVEMENT AREA	BIT. PRIME 2 APPL	ASG. PRIME	POLYMERIZED LEVELING BINDER (MM), N70	TEMPORARY RAMP
STATIONING		(FT.)	(FT.)	(SQ YD)	(TON)	(TON)	(TON)	(SQ YD)
646+28 TO 645+48	CEL	80	26	231	0.18	0.3	12.9	
645+48 TO 645+03	CEL	45	33	165	0.12	0.2	9.2	
645+03 TO 643+93		110	26	318	0.24	0.5	17.8	
643+93 TO 643+16		77	30	257	0.19	0.4	14.4	
643+16 TO 641+37	EAST PEARL AVE	179	34	676	0.49	1.0	37.9	
641+37 TO 639+83		154	26	445	0.34	0.7	24.9	
639+83 TO 639+45	WEST PEARL AVE	38	33	139	0.10	0.2	7.8	
639+45 TO 638+12		133	30	443	0.33	0.7	24.8	
638+12 TO 637+76	FRANCIS AVE	36	33	132	0.10	0.2	7.4	
637+76 TO 636+45		131	26	378	0.29	0.6	21.2	
636+45 TO 636+05		40	30	133	0.10	0.2	7.5	
636+05 TO 634+29	SYDNEY AVE	176	34	665	0.48	1.0	37.2	
634+29 TO 633+29		100	26	289	0.22	0.4	16.2	
633+29 TO 632+93	McKINLEY AVE	36	33	132	0.10	0.2	7.4	
632+93 TO 631+53		140	26	404	0.31	0.6	22.6	
631+53 TO 631+13		40	30	133	0.10	0.2	7.5	
631+13 TO 629+38	WOODWARD	175	34	661	0.48	1.0	37.0	
629+38 TO 626+79		259	26	748	0.58	1.1	41.9	
626+79 TO 626+43	CARMEN AVE	36	33	132	0.10	0.2	7.4	
626+43 TO 624+90		153	32	544	0.40	0.8	30.5	
624+90 TO 624+54	BEACON ST	36	33	132	0.10	0.2	7.4	
624+54 TO 623+35		119	26	344	0.26	0.5	19.3	
623+35 TO 622+85		40	30	133	0.10	0.2	7.5	
622+85 TO 621+16	BOYLSTON ST	179	34	676	0.49	1.0	37.9	
621+16 TO 620+29		87	26	251	0.19	0.4	14.1	
620+29 TO 619+95	JUNIUS AVE	34	33	125	0.09	0.2	7.0	
619+95 TO 618+24		171	32	608	0.45	0.9	34.0	
618+24 TO 617+88	OLIVE ST	36	33	132	0.10	0.2	7.4	
617+88 TO 616+86		92	26	266	0.20	0.4	14.9	
616+86 TO 616+56		40	30	133	0.10	0.2	7.5	
616+56 TO 614+77	LILLIAN CT	179	34	676	0.49	1.0	37.9	
614+77 TO 613+97		80	26	231	0.18	0.3	12.9	
613+97 TO 613+17		80	29	258	0.19	0.4	14.4	
613+17 TO 612+50		67	32	238	0.17	0.4	13.3	14.2
SOUTHBOUND TOTALS					23.6	48.5	1809.0	51.6
SNOW AVE.		17	VAR	78	0.02	0.1		10.0
LILLIAN CT.		12	VAR	44	0.01	0.1		10.0
OLIVE ST.		18	VAR	75	0.02	0.1		10.0
JUNIUS ST.		15	VAR	67	0.02	0.1		10.0
BOYLSTON ST.		17	VAR	82	0.02	0.1		10.0
BEACON ST.		19	VAR	91	0.03	0.1		10.0
CARMEN AVE.		14	VAR	80	0.02	0.1		10.0
McKINLEY AVE.		17	VAR	67	0.02	0.1		10.0
SYDNEY AVE.		33	VAR	232	0.07	0.3		10.0
FRANCIS AVE.		34	VAR	232	0.07	0.3		10.0
WEST PEARL AVE.		19	VAR	86	0.02	0.1		10.0
EAST PEARL AVE		15	VAR	62	0.02	0.1		10.0
LAWN DR.		12	VAR	107	0.03	0.2		10.0
WEST RIVER LANE		17	VAR	84	0.02	0.1		10.0
EAST RIVER LANE		15	VAR	61	0.02	0.1		10.0
WEST MERRILL AVE.		16	VAR	67	0.02	0.1		10.0
EAST MERRILL AVE.		18	VAR	79	0.02	0.1		10.0
WEST GRAND AVE.		20	VAR	93	0.03	0.1		10.0
EAST GRAND AVE.		15	VAR	58	0.02	0.1		10.0
LOVES CT.		13	VAR	27	0.01	0.0		10.0
EAST LOVES PARK RD.		20	VAR	96	0.03	0.1		10.0
RIVER PARK RD.		17	VAR	71	0.02	0.1		10.0
665 + 70	EAST FRONTAGE RD. ENT.	12	VAR	32	0.01	0.0		10.0
669 + 15	EAST FRONTAGE RD. ENT.	12	VAR	32	0.01	0.0		10.0
SHERIDAN DR.		12	VAR	44	0.01	0.1		10.0
EAST & WEST RIVERSIDE DR. MILL & PAVE UPTO HMA PAVEMENT. QUANTITIES ARE INCLUDED IN MAINLINE PAVEMENT.								
PARKWAY AVE.		15	VAR	60	0.02	0.1		10.0
GRAND BLVD / CEL	LT STA. 676+90	20	VAR	99	0.03	0.1		10.0
WEST CLIFFORD AVE.		20	VAR	90	0.03	0.1		10.0
EAST CLIFFORD AVE.		19	VAR	90	0.03	0.1		10.0
BELTEBERG RD.		19	VAR	94	0.03	0.1		10.0
PENNSLVANIA AVE.		13	VAR	51	0.02	0.1		10.0
HANNA CT.		13	VAR	47	0.01	0.1		10.0
RENROSE AVE.		13	VAR	44	0.01	0.1		10.0
HOSMER ST.		15	VAR	71	0.02	0.1		10.0
WEST THEODORE ST.		18	VAR	80	0.02	0.1		10.0
EAST THEODORE ST.		90	VAR	726	0.21	1.1		10.0
BURRWOOD AVE.		14	VAR	69	0.02	0.1		10.0
CORONADO BLVD.		13	VAR	62	0.02	0.1		10.0
WEST GLENDALE RD.		30	VAR	187	0.05	0.3		10.0
WINDSOR ROAD.	NB RIGHT TURN LANE ONLY	255	VAR	255	0.07	0.4		10.0
SIDEROAD TOTALS					1.2	6.1	0.0	400.0
TOTALS					47.8	104.6	3676.0	495.2


BITUMINOUS SCHEDULE

LOCATION		40603310	40603555	40800050	44000158	44000158	70300100	70301000
		HMA SURF CRSE MIX "C", N50 2-1/4"	POLYMERIZED HMA SURF CRSE, MIX "E" N70, 1-1/2"	INCIDENTAL HOT MIX SURFACING	HMA SURF REM 2 1/4" MAINLINE	HMA SURF REM 2 1/4" PARKING	SHORT TERM PAVEMENT MARKINGS	WORK ZONE PAVE MARK REMOVAL
STATIONING	DESCRIPTION	(TON)	(TON)	(TON)	(SQ YD)	(SQ YD)	(F.T.)	(SQ FT)
646+28 TO 645+48	CEL	10.1	19.4		231.1	80.0	32.0	3.6
645+48 TO 643+93		5.7	13.9		165.0	45.0	18.0	2.0
645+03 TO 643+16		13.9	25.7		317.8	110.0	44.0	4.9
643+93 TO 641+37	EAST PEARL AVE	9.7	21.6		256.7	77.0	30.8	3.4
643+16 TO 639+83		22.6	58.8		676.2	179.0	71.6	8.0
641+37 TO 639+45	WEST PEARL AVE	19.4	37.4		444.9	154.0	51.6	6.8
639+83 TO 638+12		4.8	11.7		139.3	38.0	15.2	1.7
639+45 TO 637+76	FRANCIS AVE	16.8	37.2		443.3	133.0	53.2	5.9
638+12 TO 636+45		4.5	11.1		132.0	36.0	14.4	1.6
637+76 TO 636+05		16.5	31.8		378.4	131.0	52.4	5.8
636+45 TO 634+29	SYDNEY AVE	5.0	11.2		133.3	40.0	16.0	1.8
636+05 TO 633+29		22.2	55.9		664.9	176.0	70.4	7.8
634+29 TO 632+93	McKINLEY AVE	12.6	24.3		288.9	100.0	40.0	4.4
633+29 TO 631+53		4.5	11.1		132.0	36.0	14.4	1.6
632+93 TO 631+13		17.6	34.0		404.4	140.0	55.0	6.2
631+53 TO 629+38	WOODWARD	5.0	11.2		133.3	40.0	16.0	1.8
631+13 TO 628+43		22.1	55.5		661.1	175.0	70.0	7.8
629+38 TO 626+43	CARMEN AVE	32.5	62.9		748.2	259.0	103.6	11.5
626+43 TO 624+90		4.5	11.1		132.0	36.0	14.4	1.6
624+90 TO 624+54	BEACON ST	19.3	45.7		544.0	153.0	51.2	6.8
624+54 TO 623+35		4.5	11.1		132.0	36.0	14.4	1.6
623+35 TO 622+95		15.0	28.9		343.6	119.0	47.6	5.3
622+95 TO 621+16	BOYLSTON ST	5.0	11.2		133.3	40.0	16.0	1.8
621+16 TO 620+29		22.6	56.8		676.2	179.0	71.6	8.0
620+29 TO 619+95	JUNIUS AVE	11.0	21.1		251.3	87.0	34.8	3.9
619+95 TO 618+24		4.3	10.5		124.7	34.0	13.6	1.5
618+24 TO 617+88	OLIVE ST	21.5	51.1		608.0	171.0	68.4	7.6
617+88 TO 616+96		4.5	11.1		132.0	36.0	14.4	1.6
616+96 TO 616+55		11.6	22.3		255.8	92.0	35.8	4.1
616+55 TO 614+77	LILLIAN CT	5.0	11.2		133.3	40.0	16.0	1.8
614+77 TO 613+97		22.6	56.8		676.2	179.0	71.6	8.0
613+97 TO 612+50		10.1	19.4		231.1	80.0	32.0	3.6
612+50		10.1	21.7		257.8	80.0	32.0	3.6
		8.4	20.0		238.2	67.0	26.8	3.0
SOUTHBOUND TOTALS		1137.5	2713.5		33721.8	9027.8	3782.4	420.3
SNOW AVE.				12.0	78.1		5.1	0.6
LILLIAN CT.				6.7	43.7		3.6	0.4
OLIVE ST.				11.5	74.6		5.4	0.6
JUNIUS ST.				10.3	66.8		4.5	0.5
BOYLSTON ST.				12.6	82.1		5.1	0.6
BEACON ST.				14.0	90.8		5.7	0.6
CARMEN AVE.				12.3	79.6		4.2	0.5
McKINLEY AVE.				10.3	66.8		5.1	0.6
SYDNEY AVE.				35.7	231.6		9.9	1.1
FRANCIS AVE.				35.7	231.5		10.2	1.1
WEST PEARL AVE.				13.2	85.6		5.7	0.6
EAST PEARL AVE				9.5	61.7		4.8	0.5
LAWN DR.				16.4	105.6		3.6	0.4
WEST RIVER LANE				12.9	83.7		5.1	0.6
EAST RIVER LANE				9.5	61.4		4.5	0.5
WEST MERRILL AVE.				10.3	67.1		4.8	0.5
EAST MERRILL AVE.				12.2	79.0		5.4	0.6
WEST GRAND AVE.				14.3	92.9		6.0	0.7
EAST GRAND AVE.				8.9	57.8		4.5	0.5
LOVES CT.				4.1	26.7		3.9	0.4
EAST LOVES PARK RD.				14.8	95.4		6.0	0.7
RIVER PARK RD.				11.0	71.4		5.1	0.6
665 + 70 EAST FRONTAGE RD. ENT.				4.9	32.0		3.6	0.4
669 + 15 EAST FRONTAGE RD. ENT.				4.9	32.0		3.6	0.4
SHERIDAN DR.				6.7	43.6		3.6	0.4
EAST & WEST RIVERSIDE DR. MILL & PAVE UPTO HMA PAVEMEN								
PARKWAY AVE.				9.2	59.6		4.5	0.5
GRAND BLVD / CEL LT STA. 676+90				15.2	98.5		6.0	0.7
WEST CLIFFORD AVE.				13.9	90.1		6.0	0.7
EAST CLIFFORD AVE.				13.9	90.3		5.7	0.6
BELTEBERG RD.				14.5	94.2		5.7	0.6
PENNSLVANIA AVE.				9.4	61.3		3.9	0.4
HANNA CT.				7.3	47.1		3.9	0.4
RENROSE AVE.				6.8	44.2		3.9	0.4
HOSMER ST.				10.9	70.8		4.5	0.5
WEST THEODORE ST.				12.3	79.7		5.4	0.6
EAST THEODORE ST.				111.7	725.5		27.0	3.0
BURRWOOD AVE.				10.7	69.2		4.2	0.5
CORONADO BLVD.				9.5	61.7		3.9	0.4
WEST GLENDALE RD.				26.9	187.4		9.0	1.0
WINDSOR ROAD. NB RIGHT TURN LANE ONLY				39.3	255.1		76.5	8.5
SIDEROAD TOTALS			0.0	628.0	4078.2		289.1	33.2
		2002.3	5513.9	628.0	74473.2	15890.9	7863.9	873.8

PAVEMENT PATCHING


STATION	REMARKS	LENGTH OF PATCH		AREA OF PATCHES								44200156		44200160		44200162		44002216		40601005				
		INSIDE (feet)	OUTSIDE (feet)	TYPE 1		TYPE 2		TYPE 3		TYPE 4		INSIDE (yd ²)	OUTSIDE (yd ²)	INSIDE (yd ²)	OUTSIDE (yd ²)	INSIDE (tons)	OUTSIDE (tons)	INSIDE (yd ²)	OUTSIDE (yd ²)	INSIDE (tons)	OUTSIDE (tons)			
				INSIDE (yd ²)	OUTSIDE (yd ²)	INSIDE (yd ²)	OUTSIDE (yd ²)	INSIDE (yd ²)	OUTSIDE (yd ²)	INSIDE (yd ²)	OUTSIDE (yd ²)													
612 + 73	NORTH BOUND	6			8.0												9.3			2.08	0.00			
613 + 35		6	6		8.0															9.3	0.00	2.08		
617 + 27		6	6		8.0															9.3	9.3	2.08	2.08	
618 + 76			12					16.0													17.3	0.00	3.88	
620 + 60			30									40.0									41.3	0.00	9.25	
626 + 44			10				13.3														14.6	0.00	3.28	
626 + 79			6				8.0														9.3	0.00	2.08	
627 + 85			6				8.0														9.3	0.00	2.08	
630 + 55			6				8.0														9.3	0.00	2.08	
630 + 95			6				8.0														9.3	0.00	2.08	
685 + 17			30									40.0									41.3	0.00	2.08	
688 + 00			65									86.7									88.0	0.00	19.70	
688 + 43			6				8.0														9.3	0.00	2.08	
681 + 16			30									40.0									41.3	9.25	9.25	
699 + 70			20									26.7									28.0	0.00	6.26	
701 + 17			6				8.0														9.3	0.00	2.08	
706 + 00	NORTH BOUND	6	6				8.0														9.3	2.08	2.08	
704 + 00	SOUTH BOUND	6	6				8.0														9.3	2.08	2.08	
696 + 95		6	6				8.0														9.3	2.08	2.08	
687 + 5		20										26.7									28.0	6.26	0.00	
684 + 00		15										20.0									21.3	4.77	0.00	
678 + 40		6	6				8.0														9.3	2.08	2.08	
662 + 80			6				8.0														9.3	0.00	2.08	
661 + 00			6				8.0														9.3	0.00	2.08	
652 + 70			6				8.0														9.3	2.08	2.08	
650 + 20		6	6				8.0														9.3	2.08	2.08	
639 + 95			6				8.0														9.3	0.00	2.08	
636 + 85			6				8.0														9.3	2.08	2.08	
633 + 95			6				8.0														9.3	0.00	2.08	
633 + 83			6				8.0														9.3	0.00	2.08	
631 + 94			8				10.7														12.0	2.68	0.00	
631 + 37			6				8.0														9.3	2.08	0.00	
629 + 00			6				8.0														9.3	2.08	0.00	
613 + 90	SOUTH BOUND	6	6				8.0														9.3	2.08	2.08	
Total							130.7					106.7									283.3	411.3	63.5	92.1
Expect to replace 10% +/- of total							13.1					10.7									23.3	34.0	6.5	155.6
Grand Total							26.4					16.0									694.6	155.6		

TYPICAL PAVEMENT MARKINGS



* SEE HIGHWAY STANDARD 781001 FOR SPACING DETAILS.
USE DOUBLE MARKERS WHEN ADT ≥ 25,000.


MULTI-LANE / DIVIDED



* REDUCE TO 12.2m (40') O.C. ON CURVES WHERE ADVISORY SPEEDS ARE 15km/h (10MPH) LOWER THAN POSTED SPEEDS.

** USE DOUBLE MARKERS WHEN ADT ≥ 25,000

TYPICAL PAVEMENT MARKING FOR TWO LANE SECTION - NO PASSING ZONES




SYMBOLS


MULTI-LANE / UNDIVIDED

FILE NAME = c:\ppl\work\p\m1001\005500\40179381\026530-ahx-cover.dgn	USER NAME = dossed	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	REGION 201RICT 2 STANDARD	F.A.P. RTE. 303	SECTION 12,3RS-3	COUNTY WINNEBAGO	TOTAL SHEET SHEETS NO. 37	30
PLOT DATE = Fri Jan 15 17:53:33 2010			FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT		CONTRACT NO. 64C07		41.1	


FRAME AND GRATE FOR INLET SPECIAL




PLAN OF FRAME
WITHOUT GRATE AND CURB BOX



TRANSVERSE SECTION



LONGITUDINAL SECTION



PLAN OF GRATE

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE NOTED.

REVISED - 9-25-92

R 3067
APPROXIMATE WEIGHT - 231 Kg. (510 LBS.)

FILE NAME = c:\pk-wor-k\p\1\DOT\DOSSDD\08179381\0205310-ahf-cover.dgn	USER NAME = d0sadd	F.A.P. RTE. 303	SECTION 12.31RS-3	COUNTY WINNEBAGO	TOTAL SHEET SHEETS NO.
	PLOT DATE = Fri Jan 15 17:33:38 2002				37 31
STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION			REGION 3-DISTRICT 2 STANDARD		CONTRACT NO. 64G07
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT					FRAME AND GRATE FOR INLET SPECIAL 13.2c

ROUGH GROOVED SURFACE SIGN

ILLINOIS STANDARD W8-I107
SIGN PANEL TYPE 1



COLOR: LEGEND AND BORDER - BLACK NON-REFLECTIVE
BACKGROUND - ORANGE REFLECTORIZED

SIGN SIZE	DIMENSIONS							
	A	B	C	D	E	F	G	H
1200x1200 (48x48)	1200 (48.0)	600 (24.1)	75 (3.0)	850 (34.0)	825 (33.0)	150 (6.0)	325 (13.0)	88 (3.5)

SIGN SIZE	SERIES			MARGIN	BORDER	BLANK STD.
	LINES					
	1	2	3			
1200x1200 (48x48)	7C	7C	7C	20 (0.8)	30 (1.2)	B4-48D

ALL DIMENSIONS IN INCHES.

REVISED - 1-09-08

GENERAL NOTES

SIGN PANELS AND FACE MATERIALS SHALL BE ACCORDING TO SECTION 720 OF THE STANDARD SPECIFICATIONS


METAL POSTS SHALL BE IN ACCORDANCE WITH STD. 720011.

ALL MOUNTING HARDWARE SHALL BE ALUMINUM, STAINLESS STEEL, ZINC OR CADMIUM PLATED STEEL AND SHALL BE INCLUDED TO THE COST OF THE INSTALLATION.

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE NOTED.

TOTAL SHEET SHEETS NO.		COUNTY		SECTION		F.A.P. RTE.		REGION PROJECT & STANDARD		STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION		USER NAME: = dssdd		PLOT DATE = Fri Jan 15 17:53:43 2010	
37		WINNEBAGO		12.3IRS-3		303		REGION PROJECT & STANDARD		STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION		FILE NAME =		FILE NAME =	
CONTRACT NO. 64G07		ILLINOIS FED. AID PROJECT										c:\pw_wor-k\PM\100T\1055DU\017936\120530-sh-t-cover.dgn			
ROUGH GROOVED SURFACE SIGN 91.2															

TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)



LEGEND

-  WORK AREA
-  LANE OPEN TO TRAFFIC
-  TYPE I OR II BARRICADE OR DRUM WITH FLASHING BURNING LIGHT
-  DRUM OR BARRICADE WITH STEADY BURN LIGHT
-  SIGN (SEE DETAIL)
-  TYPE I OR II CHECK BARRICADE WITH STEADY LIGHT BURN

REVISED - 12-9-09

GENERAL NOTES

- CONES MAY BE SUBSTITUTED FOR BARRICADES OR DRUMS AT HALF THE SPACING DURING DAY OPERATIONS. CONES SHALL BE A MINIMUM OF 110 (28) IN HEIGHT.
- STEADY BURNING LIGHTS WILL NOT BE REQUIRED ON BARRICADES OR DRUMS FOR DAY OPERATIONS. ALL LIGHTS WILL BE MONODIRECTIONAL.
- TEMPORARY PAVEMENT MARKING SHALL BE PLACED THROUGHOUT THE BARRICADED AREA OF EACH BAY WHERE THE CLOSURE TIME IS GREATER THAN FOURTEEN DAYS.
- THIS APPLICATION ALSO APPLIES WHEN WORK IS BEING PERFORMED IN THE RIGHT LANE(S) AND THE RIGHT TURN BAY IS TO REMAIN OPEN. UNDER THIS CONDITION, "RIGHT TURN LANE" R3-100 600 X 600 (24 X 24) AND M6-2R 530 X 380 (21 X 15) SHALL BE USED.
- THESE CONTROLS SHALL SUPPLEMENT MAINLINE TRAFFIC CONTROL FOR LANE CLOSURES. LONGITUDINAL DIMENSIONS MAY BE ADJUSTED TO FIT FIELD CONDITIONS.
- TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC) SHALL BE INCLUDED IN THE COST SPECIFIED TRAFFIC CONTROL STANDARDS OR ITEMS.
- ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE NOTED.

	COUNTY	TOTAL SHEETS	SHEET NO.
	WINNEBAGO	37	33
SECTION	F.A.P. RTE.	CONTRACT NO.	CONTRACT NO.
(2,3)RS-3	303	64G07	64G07
ILLINOIS FED. AID PROJECT			
REGION 2/DISTRICT 2 STANDARD		STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	
R 3-1100L 600 X 600 (24 X 24) M6-2L 530 X 380 (21 X 15)		PLOT DATE = Fri Jan 15 17:33:48 2010	
TEMPORARY SIGN SUPPORT THAT MEETS NCHRP 350 REQUIREMENTS		USER NAME = dssad es\pm-wor-k\p\1100T\DOSSAD\0175381\029538-ahc-cover.dgn	

TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC) 94.2

CATCH BASIN OR INLETS TO BE ADJUSTED OR RECONSTRUCTED

(DETAILS FOR CURB & GUTTER REPLACEMENT)

CONCRETE CURB AND GUTTER SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 606 OF THE STANDARD SPECIFICATIONS, SUPPLEMENTAL SPECIFICATIONS, STANDARD 606001 AND THIS DRAWING.

CLASS SI CONCRETE SHALL BE USED THROUGHOUT. A HOLE 40 (1 1/2) IN DIAMETER AND 225 (9) DEEP SHALL BE DRILLED IN THE EXISTING CONCRETE CURB AS SHOWN. A 32x450 (1 1/4 X 18) SMOOTH DOWEL BAR SHALL BE GROUTED IN THE HOLE LONGITUDINALLY.

JOINTS OF A TYPE SIMILAR TO THAT IN THE UNDERLYING PAVEMENT (EXPANSION OR CONTRACTION) SHALL BE INSTALLED IN THE CONCRETE CURB IN ALIGNMENT WITH THE JOINTS IN THE PAVEMENT.


THE PROPOSED CONFIGURATION OF THE CURB AND GUTTER SHALL MATCH THAT REMOVED.

THE LOCATION OF THE DOWEL BAR SHALL BE DETERMINED BY THE ENGINEER.

ALL EXISTING TIE BARS IN EDGE OF PAVEMENT SLAB THRU REPLACEMENT AREA SHALL BE CUT OFF.

THE WORK SHALL BE DONE IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS AND INCLUDES THE REMOVAL AND REPLACEMENT OF SOD, CONCRETE PAVEMENT AND/OR CURB AND GUTTER ADJACENT TO CATCH BASINS OR INLETS TO BE ADJUSTED OR RECONSTRUCTED AND SHALL BE INCLUDED IN THE PAY ITEM OF CATCH BASINS OR INLETS TO BE ADJUSTED OR RECONSTRUCTED AS SPECIFIED.

REVISED - 5-4-94



WHEN "A" IS GREATER THAN 50 (2), 2 NO. 15 (NO. 4) BARS SHALL BE PLACED AS SHOWN.


SAME REPAIR AS INDICATED ON OTHER SIDE OF FRAME AND GRATE.

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE NOTED.

FILE NAME = c:\p_m\work\PM\DOT\005SOD\0179381\026538-ht-cover.dgn	USER NAME = dssdd	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	REGION 2/DISTRICT 2 STANDARD	F.A.P. RTE. 303	SECTION (2,3)RS-3	COUNTY WINNEBAGO	TOTAL SHEETS 37	SHEET NO. 34
PLOT DATE = Fri, Jan 15 17:33:53 2010		FED. ROAD DIST. NO. ILLINOIS/FED. AID PROJECT		CONTRACT NO. 64C07				

CATCH BASIN OR INLETS TO BE ADJUSTED OR RECONSTRUCTED 17.48

PAVEMENT PATCHING FOR HOT-MIX ASPHALT SURFACED PAVEMENT



SEQUENCE OF CONSTRUCTION:

1. REMOVE THE EXISTING HOT-MIX ASPHALT SURFACE.
2. RESIDENT ENGINEER WILL DETERMINE IF LOCATION IS TO BE PATCHED OR TO ONLY REPLACE HOT-MIX ASPHALT SURFACE.
3. REMOVE AND REPLACE FULL DEPTH PATCHES AT LOCATIONS DIRECTED BY THE ENGINEER.
4. REPLACE HOT-MIX ASPHALT SURFACE OVER FULL DEPTH PATCHES AND AT LOCATIONS OF HOT-MIX ASPHALT SURFACE REMOVAL.


REVISED --5-27-09

GENERAL NOTES:

1. FOR BASIS OF PAYMENT: SEE THE RECURRING SPECIAL PROVISION "PATCHING WITH HOT-MIX ASPHALT OVERLAY REMOVAL".
- ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE NOTED.

FILE NAME = c:\pwwork\pwwork\10065500\10179381\10265318-sht-cover.dgn	USER NAME = dmsadd	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	REGION 2/DISTRICT 2 STANDARD	F.A.P. RTE. 303	SECTION (2-3)RS-3	COUNTY WINNEBAGO	TOTAL SHEETS 37	SHEET NO. 35
PLOT DATE = Fri, Jan 15 17:53:58 2010		FED. ROAD DIST. NO. ILLINOIS/FED. AID PROJECT		CONTRACT NO. 64G07		PAVEMENT PATCHING FOR HOT-MIX ASPHALT SURFACED PAVEMENT 32.4		

TYPICAL MARKING FOR PAINTED ISLANDS




NOTE:
* 45° TO LOCAL TAN.

REVISED - 2-7-05

ALL DIMENSIONS ARE IN MILLIMETERS
(INCHES) UNLESS OTHERWISE NOTED.

FILE NAME = c:\pw_work\p\100T\005500\40179381\022630-sht-cover.dgn	USER NAME = dassdd	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	REGION 4018RICT & STANDARD	F.A.P. RTE. 303	SECTION 12.3IRS-3	COUNTY WINNEBAGO	TOTAL SHEETS 37	SHEET NO. 36
PLOT DATE = Fri Jan 15 17:34:02 2010		FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT		CONTRACT NO. 64G07		TYPICAL MARKING FOR PAINTED ISLANDS 93.4		

SUBGRADE REPLACEMENT



NOTES:

THE CA 6 OR CA 10 SHALL BE COMPACTED IN A MANNER APPROVED BY THE ENGINEER. IF THE MOISTURE CONTENT OF THE MATERIAL IS SUCH THAT COMPACTION SATISFACTORY TO THE ENGINEER CANNOT BE OBTAINED, SUFFICIENT WATER SHALL BE ADDED SO THAT SATISFACTORY COMPACTION CAN BE OBTAINED.

THE CA 6 OR CA 10 WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER CU YD FOR GRANULAR SUBGRADE REPLACEMENT

THE GEOTECHNICAL REINFORCEMENT WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER 50 YD FOR GEOTECHNICAL REINFORCEMENT

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE NOTED.

REVISED - 1-09-08

FILE NAME = c:\pw\work\p\WIDOT\DOSSDD\017538\1205310-ahb-cover.dgn	USER NAME = dossed	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	REGION 201RUCT 2 STANDARD	F.A.P. RTE. 303	SECTION 12,31RS-3	COUNTY WINNEBAGO	TOTAL SHEETS 37	SHEET NO. 37
PLOT DATE = Fri Jan 15 17:34:08 2010		FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT		CONTRACT NO. 64G07		SUBGRADE REPLACEMENT 97.4		

ILLINOIS DEPARTMENT OF LABOR

PREVAILING WAGES FOR WINNEBAGO COUNTY EFFECTIVE APRIL 2010

The Prevailing rates of wages are included in the Contract proposals which are subject to Check Sheet #5 of the Supplemental Specifications and Recurring Special Provisions. The rates have been ascertained and certified by the Illinois Department of Labor for the locality in which the work is to be performed and for each craft or type of work or mechanic needed to execute the work of the Contract. As required by Prevailing Wage Act (820 ILCS 130/0.01, et seq.) and Check Sheet #5 of the Contract, not less than the rates of wages ascertained by the Illinois Department of Labor and as revised during the performance of a Contract shall be paid to all laborers, workers and mechanics performing work under the Contract. Post the scale of wages in a prominent and easily accessible place at the site of work.

If the Illinois Department of Labor revises the prevailing rates of wages to be paid as listed in the specification of rates, the contractor shall post the revised rates of wages and shall pay not less than the revised rates of wages. Current wage rate information shall be obtained by visiting the Illinois Department of Labor web site at <http://www.state.il.us/agency/idol/> or by calling 312-793-2814. It is the responsibility of the contractor to review the rates applicable to the work of the contract at regular intervals in order to insure the timely payment of current rates. Provision of this information to the contractor by means of the Illinois Department of Labor web site satisfies the notification of revisions by the Department to the contractor pursuant to the Act, and the contractor agrees that no additional notice is required. The contractor shall notify each of its subcontractors of the revised rates of wages.

Winnebago County Prevailing Wage for April 2010

Trade Name	RG	TYP	C	Base	FRMAN	*M-F>8	OSA	OSH	H/W	Pensn	Vac	Trng
=====	==	===	=	=====	=====	=====	===	===	=====	=====	=====	=====
ASBESTOS ABT-GEN		BLD		28.810	29.810	1.5	1.5	2.0	7.290	10.41	0.000	0.800
ASBESTOS ABT-MEC		BLD		18.950	0.000	1.5	1.5	2.0	2.700	3.350	0.000	0.000
BOILERMAKER		BLD		43.020	46.890	2.0	2.0	2.0	6.720	9.890	0.000	0.350
BRICK MASON		BLD		34.500	37.250	1.5	1.5	2.0	6.550	10.96	0.000	0.510
CARPENTER		BLD		34.010	37.750	1.5	1.5	2.0	6.550	10.50	0.000	0.600
CARPENTER		HWY		33.170	34.920	1.5	1.5	2.0	6.550	8.800	0.000	0.490
CEMENT MASON		ALL		34.000	36.750	1.5	1.5	2.0	6.550	10.55	0.000	0.150
CERAMIC TILE FNSHER		BLD		29.530	0.000	1.5	1.5	2.0	6.550	4.230	0.000	0.440
COMMUNICATION TECH		BLD		33.000	36.300	1.5	1.5	2.0	9.390	9.550	0.000	0.660
ELECTRIC PWR EQMT OP		ALL		33.140	42.570	1.5	1.5	2.0	4.750	10.27	0.000	0.250
ELECTRIC PWR GRNDMAN		ALL		25.680	42.570	1.5	1.5	2.0	4.750	7.960	0.000	0.190
ELECTRIC PWR LINEMAN		ALL		39.420	42.570	1.5	1.5	2.0	4.750	12.22	0.000	0.300
ELECTRIC PWR TRK DRV		ALL		26.520	42.570	1.5	1.5	2.0	4.750	8.230	0.000	0.200
ELECTRICIAN		BLD		38.520	42.370	1.5	1.5	2.0	9.390	13.96	0.000	0.770
ELEVATOR CONSTRUCTOR		BLD		42.540	47.860	2.0	2.0	2.0	10.03	9.460	2.550	0.000
GLAZIER		BLD		30.330	31.330	1.5	1.5	2.0	7.500	7.250	0.000	0.750
HT/FROST INSULATOR		BLD		32.680	35.130	1.5	1.5	2.0	7.250	12.07	0.000	0.000
IRON WORKER		ALL		35.000	36.750	2.0	2.0	2.0	7.700	18.76	0.000	1.200
LABORER		BLD		28.810	29.810	1.5	1.5	2.0	7.290	10.41	0.000	0.800
LABORER		HWY		27.660	28.410	1.5	1.5	2.0	7.290	10.41	0.000	0.800
LABORER, SKILLED		HWY		29.510	30.260	1.5	1.5	2.0	7.290	10.41	0.000	0.800
LATHER		BLD		34.010	37.750	1.5	1.5	2.0	6.550	10.50	0.000	0.600
MACHINIST		BLD		42.770	44.770	1.5	1.5	2.0	7.750	8.690	0.650	0.000
MARBLE FINISHERS		BLD		29.530	0.000	1.5	1.5	2.0	6.550	4.230	0.000	0.440
MARBLE MASON		BLD		32.020	32.270	1.5	1.5	2.0	6.550	6.730	0.000	0.470
MATERIAL TESTER I		ALL		21.550	0.000	1.5	1.5	2.0	7.460	4.840	0.000	0.170
MATERIALS TESTER II		ALL		26.550	0.000	1.5	1.5	2.0	7.460	4.840	0.000	0.170
MILLWRIGHT		BLD		33.970	37.370	1.5	1.5	2.0	6.550	12.35	0.000	0.500
OPERATING ENGINEER		BLD	1	39.150	43.150	2.0	2.0	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		BLD	2	38.450	43.150	2.0	2.0	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		BLD	3	36.000	43.150	2.0	2.0	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		BLD	4	34.000	43.150	2.0	2.0	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		BLD	5	42.900	43.150	2.0	2.0	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		BLD	6	42.150	43.150	2.0	2.0	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		BLD	7	39.150	43.150	2.0	2.0	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		HWY	1	39.000	43.000	1.5	1.5	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		HWY	2	38.450	43.000	1.5	1.5	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		HWY	3	37.150	43.000	1.5	1.5	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		HWY	4	35.700	43.000	1.5	1.5	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		HWY	5	34.250	43.000	1.5	1.5	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		HWY	6	42.000	43.000	1.5	1.5	2.0	11.70	8.100	2.250	1.150
OPERATING ENGINEER		HWY	7	40.000	43.000	1.5	1.5	2.0	11.70	8.100	2.250	1.150
PAINTER		ALL		34.500	36.500	1.5	1.5	1.5	7.500	7.250	0.000	0.750
PILEDRIVER		BLD		35.010	38.860	1.5	1.5	2.0	6.550	10.50	0.000	0.600
PILEDRIVER		HWY		33.170	34.920	1.5	1.5	2.0	6.550	8.800	0.000	0.490
PIPEFITTER		BLD		37.200	39.800	1.5	1.5	2.0	7.640	9.880	0.000	0.700
PLASTERER		BLD		32.540	35.790	1.5	1.5	2.0	6.550	10.70	0.000	0.150
PLUMBER		BLD		37.200	39.800	1.5	1.5	2.0	7.640	9.880	0.000	0.700
ROOFER		BLD		37.000	40.000	1.5	1.5	2.0	7.500	6.020	0.000	0.330
SHEETMETAL WORKER		BLD		34.160	36.090	1.5	1.5	2.0	5.150	13.51	0.520	0.290
SPRINKLER FITTER		BLD		36.140	38.890	1.5	1.5	2.0	8.200	6.550	0.000	0.250
STONE MASON		BLD		34.500	37.250	1.5	1.5	2.0	6.550	10.96	0.000	0.510
TERRAZZO FINISHER		BLD		29.530	0.000	1.5	1.5	2.0	6.550	4.230	0.000	0.440
TERRAZZO MASON		BLD		32.020	32.270	1.5	1.5	2.0	6.550	6.730	0.000	0.470
TILE LAYER		BLD		34.010	37.750	1.5	1.5	2.0	6.550	10.50	0.000	0.600
TILE MASON		BLD		32.020	32.270	1.5	1.5	2.0	6.550	6.730	0.000	0.470
TRUCK DRIVER		ALL	1	25.880	26.430	1.5	1.5	2.0	5.150	6.500	0.000	0.000
TRUCK DRIVER		ALL	2	26.030	26.430	1.5	1.5	2.0	5.150	6.500	0.000	0.000

TRUCK DRIVER	ALL	3	26.230	26.430	1.5	1.5	2.0	5.150	6.500	0.000	0.000
TRUCK DRIVER	ALL	4	26.430	26.430	1.5	1.5	2.0	5.150	6.500	0.000	0.000
TUCKPOINTER	BLD		34.500	37.250	1.5	1.5	2.0	6.550	10.96	0.000	0.510

Legend:

M-F>8 (Overtime is required for any hour greater than 8 worked each day, Monday through Friday.)

OSA (Overtime is required for every hour worked on Saturday)

OSH (Overtime is required for every hour worked on Sunday and Holidays)

H/W (Health & Welfare Insurance)

Pensn (Pension)

Vac (Vacation)

Trng (Training)

Explanations

WINNEBAGO COUNTY

The following list is considered as those days for which holiday rates of wages for work performed apply: New Years Day, Memorial/Decoration Day, Fourth of July, Labor Day, Veterans Day, Thanksgiving Day, Christmas Day. Generally, any of these holidays which fall on a Sunday is celebrated on the following Monday. This then makes work performed on that Monday payable at the appropriate overtime rate for holiday pay. Common practice in a given local may alter certain days of celebration such as the day after Thanksgiving for Veterans Day. If in doubt, please check with IDOL.

EXPLANATION OF CLASSES

ASBESTOS - GENERAL - removal of asbestos material/mold and hazardous materials from any place in a building, including mechanical systems where those mechanical systems are to be removed. This includes the removal of asbestos materials/mold and hazardous materials from ductwork or pipes in a building when the building is to be demolished at the time or at some close future date.

ASBESTOS - MECHANICAL - removal of asbestos material from mechanical systems, such as pipes, ducts, and boilers, where the mechanical systems are to remain.

CERAMIC TILE FINISHER, MARBLE FINISHER, TERRAZZO FINISHER

Assisting, helping or supporting the tile, marble and terrazzo mechanic by performing their historic and traditional work assignments required to complete the proper installation of the work covered by said crafts. The term "Ceramic" is used for naming the classification only and is in no way a limitation of the product handled. Ceramic takes into consideration most hard tiles.

COMMUNICATIONS TECHNICIAN

Installing, manufacturing, assembling and maintaining sound and

intercom, protection alarm (security), fire alarm, master antenna television, closed circuit television, low voltage control for computers and/or door monitoring, school communications systems, telephones and servicing of nurse and emergency calls, and the installation and maintenance of transmit and receive antennas, transmitters, receivers, and associated apparatus which operates in conjunction with above systems. All work associated with these system installations will be included EXCEPT the installation of protective metallic conduit in new construction projects (excluding less than ten-foot, runs strictly for protection of cable) and 120 volt AC (or higher) power wiring and associated hardware.

LABORER, SKILLED - HIGHWAY

Individuals engaged in the following types of work, irrespective of the site of the work: asbestos abatement worker, handling of any materials with any foreign matter harmful to skin or clothing, track laborer, cement handlers, chloride handlers, the unloading and loading with steel workers and re-bars, concrete workers wet, tunnel helpers in free air, batch dumpers, mason tenders, kettle and tar men, tank cleaners, plastic installers, scaffold workers, motorized buggies or motorized unit used for wet concrete or handling of building materials, laborers with de-watering systems, sewer workers plus depth, rod and chainmen with technical engineers, rod and chainmen with land surveyors, rod and chainmen with surveyors, vibrator operators, cement silica, clay, fly ash, lime and plasters, handlers (bulk or bag), cofferdam workers plus depth, on concrete paving, placing, cutting and tying of reinforcing, deck hand, dredge hand, and shore laborers, bankmen on floating plant, grade checker, power tools, front end man on chip spreaders, cession workers plus depth, gunnite nozzle men, lead man on sewer work, welders, cutters, burners and torchmen, chainsaw operators, jackhammer and drill operators, layout man and/or drainage tile layer, steel form setter - street and highway, air tamping hammermen, signal man on crane, concrete saw operator, screedman on asphalt pavers, laborers tending masons with hot material or where foreign materials are used, mortar mixer operators, multiple concrete duct - leadsman, lumen, asphalt raker, curb asphalt machine operator, ready mix scalemen (permanent, portable or temporary plant), laborers handling masterplate or similar materials, laser beam operator, concrete burning machine operator, coring machine operator, plaster tender, underpinning and shoring of buildings, pump men, manhole and catch basin, dirt and stone tamper, hose men on concrete pumps, hazardous waste worker, lead base paint abatement worker, lining of pipe, refusing machine, assisting on direct boring machine, the work of laying watermain, fire hydrants, all mechanical joints to watermain work, sewer worker, and tapping water service and forced lift station mechanical worker.

MATERIAL TESTER I: Hand coring and drilling for testing of materials; field inspection of uncured concrete and asphalt.

MATERIAL TESTER II: Field inspection of welds, structural steel, fireproofing, masonry, soil, facade, reinforcing steel, formwork, cured concrete, and concrete and asphalt batch plants; adjusting proportions of bituminous mixtures.

OPERATING ENGINEERS - BUILDING

Class 1. Asphalt Plant; Asphalt Spreader; Autograde; Backhoes with Caisson Attachment; Batch Plant; Benoto (requires Two Engineers);

Boiler and Throttle Valve; Caisson Rigs; Central Redi-Mix Plant; Combination Back Hoe Front End-loader Machine; Compressor and Throttle Valve; Concrete Breaker (Truck Mounted); Concrete Conveyor; Concrete Paver (over 27E cu. ft.): Concrete Paver (27 cu. ft. and under); Concrete Placer; Concrete Pump (Truck Mounted); Concrete Conveyor (Truck Mounted); Concrete Tower; Cranes, All; GCI and similar types (required two operators only); Cranes, Hammerhead; Creter Crane; Crusher, Stone, etc.; Derricks, All; Derricks, Traveling; Formless Curb and Gutter Machine; Grader, Elevating; Grouting Machines; Highlift Shovels or Front Endloader 2-1/4 yd. and over; Hoists, Elevators, outside type rack and pinion and similar machines; Hoists, one, two and three Drum; Hoists, Two Tugger One Floor; Hydraulic Backhoes; Hydraulic Boom Trucks; Locomotives, All; Lubrication Technician; Manipulators; Motor Patrol; Pile Drivers and Skid Rig; Post Hole Digger; Pre-Stress Machine; Pump Cretes Dual Ram; Pump Cretes: Squeeze Cretes - Screw Type Pumps, Gypsum Bulker and Pump; Raised and Blind Hole Drill; Rock Drill (self-propelled); Rock Drill - Truck Mounted; Roto Mill Grinder; Scoops - Tractor Drawn; Slipform Paver; Scrapers Prime Movers; Straddle Buggies; Tie Back Machine; Tractor with Boom and Side Boom; Trenching Machines.

Class 2. Bobcat (over 3/4 cu. yd.); Boilers; Brick Forklift; Broom, All Power Propelled; Bulldozers; Concrete Mixer (Two Bag and Over); Conveyor, Portable; Forklift Trucks; Highlift Shovels or Front Endloaders under 2-1/4 yd.; Hoists, Automatic; Hoists, Sewer Dragging Machine; Hoists, Tugger Single Drum; Rollers, All; Steam Generators; Tractors, All; Tractor Drawn Vibratory Roller; Winch Trucks with "A" Frame.

Class 3. Air Compressor; Asphalt Spreader; Combination - Small Equipment Operator; Generators; Heaters, Mechanical; Hoists, Inside Elevators - (Rheostat Manual Controlled); Hydraulic Power Units (Pile Driving and Extracting); Pumps, Over 3" (1 to 3 not to exceed total of 300 ft.); Pumps, Well Points; Welding Machines (2 through 5); Winches, 4 Small Electric Drill Winches; Bobcat (up to and including 3/4 cu. yd.).

Class 4. Elevator push button with automatic doors; Hoists, Inside; Oilers; Brick Forklift.

Class 5. Assistant Craft Foreman

Class 6. Mechanics

Class 7. Gradall.

OPERATING ENGINEERS - HIGHWAY CONSTRUCTION

Class 1. Asphalt Plant; Asphalt Heater and Planer Combination; Asphalt Heater Scarfire; Asphalt Silo Tender; Asphalt Spreader; Autograder; ABG Paver; Backhoes with Caisson Attachment; Ballast Regulator; Belt Loader; Caisson Rigs; Car Dumper; Central Redi-Mix Plant; Backhoe w/shear attachments; Combination Backhoe Front Endloader Machine, (1 cu. yd. Backhoe Bucket or over or with attachments); Concrete Breaker (Truck Mounted); Concrete Conveyor; Concrete Paver over 27E cu. ft.; Concrete Placer; Concrete Tube Float; Cranes, all attachments; Cranes, Tower of all types; Creter Crane; Crusher, Stone, etc.; Derricks, All; Derrick Boats; Derricks, Traveling; Directional Boring Machine over 12"; Dredges; Formless Curb and Gutter Machine; Grader, Elevating; Grader, Motor Grader, Motor Patrol, Auto Patrol, Form Grader, Pull Grader, Subgrader; Guard Rail Post Driver Mounted; Hoists, One, Two and Three Drum; Hydraulic Backhoes; Lubrication

Technician; Manipulators; Pile Drivers and Skid Rig; Pre-Stress Machine; Pump Cretes Dual Ram; Rock Drill - Crawler or Skid Rig; Rock Drill - Truck Mounted; Rock/Track Tamper; Roto Mill Grinder; Slip-Form Paver; Soil Test Drill Rig (Truck Mounted); Straddle Buggies; GCI Crane; Hydraulic Telescoping Form (Tunnel); Tie Back Machine; Tractor Drawn Belt Loader; Tractor Drawn Belt Loader with attached pusher; Tractor with Boom; Tractaire with Attachments; Traffic Barrier Conveyor Machine; Raised or Blind Hole Drills; Trenching Machine (over 12"); Truck Mounted Concrete Pump with Boom; Truck Mounted Concrete Conveyor; Underground Boring and/or Mining Machines; Wheel Excavator; Widener (APSCO).

Class 2. Batch Plant; Bituminous Mixer; Boiler and Throttle Valve; Bulldozers; Car Loader Trailing Conveyors; Combination Backhoe Front Endloader Machine (less than 1 cu. yd. Backhoe Bucket or over or with attachments); Compressor and Throttle Valve; Compressor, Common Receiver (3); Concrete Breaker or Hydro Hammer; Concrete Grinding Machine; Concrete Mixer or Paver 7S Series to and including 27 cu. ft.; Concrete Spreader; Concrete Curing Machine, Burlap Machine, Belting Machine and Sealing Machine; Conveyor Muck Cars (Haglund or Similar Type); Drills, all; Finishing Machine - Concrete; Highlift Shovels or Front Endloader; Hoist - Sewer Dragging Machine; Hydraulic Boom Trucks (All Attachments); Hydro Blaster; All Locomotives, Dinky; Off-Road Hauling Units (including articulating) / 2 ton capacity or more; Non-Self Loading Ejection Dump; Pump Cretes: Squeeze Cretes - Screw Type Pumps, Gypsum Bulker and Pump; Roller, Asphalt; Rotary Snow Plows; Rototiller, Seaman, etc., self-propelled; Scoops - Tractor Drawn; Self-Propelled Compactor; Spreader - Chip - Stone, etc.; Scraper; Scraper - Prime Mover in Tandem (Regardless of Size); Tank Car Heater; Tractors, Push, Pulling Sheeps Foot, Disc, Compactor, etc.; Tug Boats.

Class 3. Boilers; Brooms, All Power Propelled; Cement Supply Tender; Compressor, Common Receiver (2); Concrete Mixer (Two Bag and Over); Conveyor, Portable; Farm-Type Tractors Used for Mowing, Seeding, etc.; Fireman on Boilers; Forklift Trucks; Grouting Machine; Hoists, Automatic; Hoists, All Elevators; Hoists, Tugger Single Drum; Jeep Diggers; Low Boys; Pipe Jacking Machines; Post-Hole Digger; Power Saw, Concrete Power Driven; Pug Mills; Rollers, other than asphalt; Seed and Straw Blower; Steam Generators; Stump Machine; Winch Trucks with "A" Frame; Work Boats; Tamper - Form - Motor Driven.

Class 4. Air Compressor - Small and Large; Asphalt Spreader, Backend Man; Bobcat (Skid Steer) all; Brick Forklift; Combination - Small Equipment Operator; Directional Boring Machine up to 12"; Generators; Heaters, Mechanical; Hydraulic Power Unit (Pile Driving, Extracting, or Drilling); Hydro-Blaster; Light Plants, All (1 through 5); Pumps, over 3" (1 to 3 not to exceed a total of 300 ft.); Pumps, Well Points; Tractaire; Trencher 12" and under; Welding Machines (2 through 5); Winches, 4 Small Electric Drill Winches.

Class 5. Oilers and Directional Boring Machine Locator.

Class 6. Field Mechanics and Field Welders

Class 7. Gradall and machines of like nature.

TRUCK DRIVER - BUILDING, HEAVY AND HIGHWAY CONSTRUCTION

Class 1. Two or three Axle Trucks. A-frame Truck when used for transportation purposes; Air Compressors and Welding Machines, including those pulled by cars, pick-up trucks and tractors; Ambulances; Batch Gate Lockers; Batch Hopperman; Car and Truck

Washers; Carry-alls; Fork Lifts and Hoisters; Helpers; Mechanics Helpers and Greasers; Oil Distributors 2-man operation; Pavement Breakers; Pole Trailer, up to 40 feet; Power Mower Tractors; Self-propelled Chip Spreader; Skipman; Slurry Trucks, 2-man operation; Slurry Truck Conveyor Operation, 2 or 3 man; TTeamsters Unskilled dumpman; and Truck Drivers hauling warning lights, barricades, and portable toilets on the job site.

Class 2. Four axle trucks; Dump Crets and Adgetors under 7 yards; Dumpsters, Track Trucks, Euclids, Hug Bottom Dump Turnapulls or Turnatrailers when pulling other than self-loading equipment or similar equipment under 16 cubic yards; Mixer Trucks under 7 yards; Ready-mix Plant Hopper Operator, and Winch Trucks, 2 Axles.

Class 3. Five axle trucks; Dump Crets and Adgetors 7 yards and over; Dumpsters, Track Trucks, Euclids, Hug Bottom Dump Turnatrailers or turnapulls when pulling other than self-loading equipment or similar equipment over 16 cubic yards; Explosives and/or Fission Material Trucks; Mixer Trucks 7 yards or over; Mobile Cranes while in transit; Oil Distributors, 1-man operation; Pole Trailer, over 40 feet; Pole and Expandable Trailers hauling material over 50 feet long; Slurry trucks, 1-man operation; Winch trucks, 3 axles or more; Mechanic--Truck Welder and Truck Painter.

Class 4. Six axle trucks; Dual-purpose vehicles, such as mounted crane trucks with hoist and accessories; Foreman; Master Mechanic; Self-loading equipment like P.B. and trucks with scoops on the front.

Other Classifications of Work:

For definitions of classifications not otherwise set out, the Department generally has on file such definitions which are available. If a task to be performed is not subject to one of the classifications of pay set out, the Department will upon being contacted state which neighboring county has such a classification and provide such rate, such rate being deemed to exist by reference in this document. If no neighboring county rate applies to the task, the Department shall undertake a special determination, such special determination being then deemed to have existed under this determination. If a project requires these, or any classification not listed, please contact IDOL at 217-782-1710 for wage rates or clarifications.

LANDSCAPING

Landscaping work falls under the existing classifications for laborer, operating engineer and truck driver. The work performed by landscape plantsman and landscape laborer is covered by the existing classification of laborer. The work performed by landscape operators (regardless of equipment used or its size) is covered by the classifications of operating engineer. The work performed by landscape truck drivers (regardless of size of truck driven) is covered by the classifications of truck driver.