

# SCHEDULE OF QUANTITIES

STATION	DIRECTION	LENGTH (FOOT)	WIDTH (FOOT)	DEPTH (INCH)	44201794
					CLASS D PATCH TYPE III, 12 INCH (SQ YD)
610+44.00	WB	15.0	11.0	12.0	18.3
610+44.00	EB	15.0	11.0	12.0	18.3
627+05.00	WB	20.0	11.0	12.0	24.4
627+05.00	EB	20.0	11.0	12.0	24.4
633+50.00	WB	20.0	11.0	12.0	24.4
633+50.00	EB	20.0	11.0	12.0	24.4
658+81.00	WB	15.0	11.0	12.0	18.3
658+81.00	EB	15.0	11.0	12.0	18.3
670+18.00	EB	15.0	11.0	12.0	18.3
672+70.00	EB	15.0	11.0	12.0	18.3
672+70.00	WB	15.0	11.0	12.0	18.3
678+30.00	WB	15.0	11.0	12.0	18.3
678+30.00	EB	15.0	11.0	12.0	18.3
686+33.00	WB	15.0	11.0	12.0	18.3
686+66.00	EB	15.0	11.0	12.0	18.3
686+83.00	WB	15.0	11.0	12.0	18.3
701+60.00	EB	15.0	11.0	12.0	18.3
703+08.00	EB	20.0	11.0	12.0	24.4
716+37.00	EB	20.0	11.0	12.0	24.4
738+26.00	EB	15.0	11.0	12.0	18.3
738+26.00	WB	15.0	11.0	12.0	18.3
751+22.00	WB	15.0	11.0	12.0	18.3
751+22.00	EB	15.0	11.0	12.0	18.3
789+50.00	WB	15.0	11.0	12.0	18.3
789+51.00	EB	15.0	11.0	12.0	18.3
790+90.00	EB	15.0	11.0	12.0	18.3
841+06.00	EB	15.0	11.0	12.0	18.3
841+52.00	EB	20.0	11.0	12.0	24.4
841+52.00	WB	20.0	11.0	12.0	24.4
865+56.20	BOTH	7.3	22.0	12.0	17.7
TOTAL =					598.3
USE =					599.0

STATION	DIRECTION	LENGTH (FOOT)	WIDTH (FOOT)	DEPTH (INCH)	44201796
					CLASS D PATCH TYPE IV, 12 INCH (SQ YD)
510+24.59	BOTH	15.2	45.0	12.0	76.0
525+50.00	BOTH	27.2	27.6	12.0	83.4
703+08.00	EB	30.0	11.0	12.0	36.7
791+50.00	WB	35.0	11.0	12.0	42.8
857+89.91	BOTH	30.0	21.4	12.0	71.3
865+56.00	WB	30.0	11.0	12.0	36.7
865+56.00	EB	30.0	11.0	12.0	36.7
TOTAL =					383.5
USE =					384.0

### 35600712 HOT-MIX ASPHALT BASE COURSE WIDENING, 9"

SIDE	STATION	TO	STATION	LENGTH (FOOT)	SQ YD
LT/RT	500+90.00	TO	510+00.46	910.5	202.3
LT	510+00.46	TO	510+33.17	32.7	3.6
	510+33.17	TO	511+52.59	119.4	
RT	511+52.59	TO	519+22.11	769.5	85.5
	519+22.11	TO	520+60.51	138.4	
RT	520+60.51	TO	521+81.59	121.1	13.5
STATION EQUATION - 521+81.59 (BK) = 525+30.10 (AH)					
RT	525+30.10	TO	527+04.34	174.24	19.4
LT/RT	527+04.34	TO	563+22.38	3618.0	804.0
LT	563+22.38	TO	565+65.82	243.4	27.1
	565+65.82	TO	566+95.62	129.8	
LT	566+95.62	TO	571+42.10	446.5	49.6
	571+42.10	TO	572+53.06	111.0	
LT	572+53.06	TO	573+36.27	83.2	9.2
STATION EQUATION - 573+36.27 (BK) = 575+56.90 (AH)					
LT/RT	575+56.90	TO	577+36.00	179.1	39.8
LT/RT	577+36.00	TO	585+39.13	803.1	178.5
OMISSION - S.N. 057-0220					
LT/RT	586+49.07	TO	596+54.77	1005.7	223.5
RT	596+54.77	TO	597+23.07	68.3	7.6
LT/RT	597+23.07	TO	623+37.20	2614.1	580.9
LT	623+37.20	TO	623+73.75	36.6	4.1
LT/RT	623+73.75	TO	643+70.48	1996.7	443.7
OMISSION - S.N. 057-0221					
LT/RT	644+99.60	TO	672+75.26	2775.7	616.8
RT	672+75.26	TO	672+88.97	13.7	1.5
	672+88.97	TO	673+38.18	49.2	
RT	673+38.18	TO	673+41.38	3.2	0.4
LT/RT	673+41.38	TO	699+51.96	2610.6	580.1
RT	699+51.96	TO	700+08.91	57.0	6.3
LT/RT	700+08.91	TO	725+95.81	2586.9	574.9
RT	725+95.81	TO	726+50.24	54.4	6.0
LT/RT	726+50.24	TO	752+34.67	2584.4	574.3
LT	752+34.67	TO	752+76.74	42.1	4.7
LT/RT	752+76.74	TO	757+39.01	462.3	102.7
OMISSION - S.N. 057-0222					

### 35600712 HOT-MIX ASPHALT BASE COURSE WIDENING, 9" (CONT.)

SIDE	STATION	TO	STATION	LENGTH (FOOT)	SHLDRS (TON)
LT/RT	759+04.87	TO	762+75.83	371.0	82.4
STATION EQUATION - 762+75.83 (BK) = 762+84+88 (AH)					
LT/RT	762+84.88	TO	794+45.86	3161.0	702.4
RT	794+45.86	TO	795+14.94	69.1	7.7
LT/RT	795+14.94	TO	802+34.97	720.0	160.0
RT	802+34.97	TO	808+70.68	635.7	70.6
RT	811+62.45	TO	812+18.51	56.1	6.2
STATION EQUATION - 812+18.51 (BK) = 813+54.31 (AH)					
RT	813+54.31	TO	815+37.18	182.9	20.3
LT/RT	815+37.18	TO	825+15.97	978.8	217.5
OMISSION - S.N. 057-0110					
LT/RT	828+01.39	TO	831+69.87	368.5	81.9
LT	831+69.87	TO	832+31.96	62.1	6.9
LT/RT	832+31.96	TO	838+29.63	597.7	132.8
LT	838+29.63	TO	839+81.36	151.7	16.9
	839+81.36	TO	841+02.12	120.8	
LT	841+02.12	TO	842+65.78	163.7	18.2
	842+65.78	TO	843+85.37	119.6	
LT	843+85.37	TO	847+59.00	373.6	41.5
STATION EQUATION - 847+59.00 (BK) = 849+88.76 (AH)					
LT	849+88.76	TO	851+50.00	161.2	17.9
LT/RT	851+50.00	TO	871+35.23	1985.2	441.2
LT	871+35.23	TO	871+97.44	62.2	6.9
LT/RT	871+97.44	TO	884+59.46	1262.0	280.4
LT	884+59.46	TO	885+30.90	71.4	7.9
LT/RT	885+30.90	TO	889+13.16	382.3	84.9
LT	889+13.16	TO	889+86.00	72.8	8.1
STATION EQUATION - 889+86.00 (BK) = 878+38.00 (AH)					
LT	878+38.00	TO	878+39.12	1.12	0.1
LT/RT	878+39.12	TO	879+75.72	136.6	30.4
LT	879+75.72	TO	880+16.34	40.6	4.5
LT/RT	880+16.34	TO	886+43.70	627.4	139.4
LT	886+43.70	TO	886+96.76	53.1	5.9
	886+96.76	TO	887+53.70	56.9	
STATION EQUATION - 887+53.70 (BK) = 887+7100 (AH)					
	887+71.00	TO	888+23.21	52.1	
RT	888+23.21	TO	888+36.28	13.1	1.5
LT/RT	888+36.28	TO	896+30.00	793.7	176.4
GRAND TOTAL =					7,930.8
USE =					7,931.0