



Note:
Fiberglass pipe shall conform to ASTM D 2996, with short-time rupture strength hoop tensile stress of 30,000 p.s.i. minimum.

SECTION THRU EXISTING FLOOR DRAIN
Hatched area indicates concrete removal at floor drain replacement and elimination locations. Cost included with Deck Slab Repair (Full Depth)

DRAIN REPLACEMENT DETAIL
Concrete placement details similar at locations of floor drain elimination.

Note: See "Bridge Deck Patching" plan sheets for Floor Drain elimination/replacement locations. See "Total Bill of Materials" for each structure for quantities.

** COST INCLUDED WITH FLOOR DRAINS

FILE NAME = #FILE#	USER NAME = #USER#	DESIGNED - ADR	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	FLOOR DRAIN DETAIL			S.B.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
		DRAWN -	REVISED -		SCALE: N/A	SHEET NO. 8 OF 11 SHEETS	STA.	TO STA.	16	07 BRIDGE REPAIRS 2010-2	SHELBY	16	13
		CHECKED -	REVISED -					CONTRACT NO. 74403					
		DATE -	REVISED -					FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT					