

April 16, 2020

SUBJECT: FAS 1084 (Ideal Road) Section 03-00083-00-BR Carroll County Contract No. 85645 Item 187 April 24, 2020 Letting Addendum (A)

## NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

- 1. Revised the Schedule of Prices
- 2. Revised sheets 3, 8, 13, 110, 121 & 122 of the Plans.
- 3. Revised page 18 of the Special Provisions.

Prime contractors must utilize the enclosed material when preparing their bid and must include any changes to the Schedule of Prices in their bid.

Very truly yours,

SLEG

Jack A. Elston, P.E. Bureau Chief, Design and Environment

and mixed to provide readily workable slurry. The cement content of the grout shall not be less than five (5) bags per cubic yard and the grout shall have a minimum compressive strength of 2,000 pounds per square inch at 28 days.

CONSTRUCTION REQUIREMENTS: Foundation preparation and placing shall be per Articles 281.03 and 281.04 of the Standard Specifications. The riprap shall be a minimum of 18" thick and placed on filter fabric. A bedding layer will not be required. A cement grout shall be placed in such a manner as to form a stable mat between the stone riprap pieces. The estimated quantity of grout is one (1) cubic yard per ten (10) square yards of riprap surface.

BASIS OF PAYMENT (Revised 4/14/2020): Payment for this work shall include excavation, filter fabric, riprap, grout and disposal of waste material. The cost of this work will not be paid separately but considered included in the contract unit price bid per SQUARE YARD of GROUTED RIPRAP.

## SECTION CORNER MARKERS

The Contractor shall monument or re-monument all Section Corners. Quarter Corners with their Reference Monuments, (and any lesser Corners which are in place including those which have been monumented by others and do not conform with the Department's procedures), that will be destroyed. The Section Corners will be monumented according to District 2 Reference Marker Detail No. 63.4. It is required that an Illinois Professional Land Surveyor prepare a Department Monument Record Form which is in compliance with the Land Surveying Monuments Acts (765 ILCS 220/0.01 et seg.) for any designated Section Corner Monument or any Reference Monument that is disturbed. The Contractor shall secure the I.D.O.T. Monument Record Form (with I.D.O.T. logo) from the Department and furnish said form to the Illinois Professional Land Surveyor. Each Monument Record Plat shall note how the Section Corner Monument and all Reference Monuments were set, either flush with the ground, buried 28 inches, (if monuments are buried, four 3.5 foot by 5/8 inch rebars shall be placed around said monuments to make recovery an easier task), or in other cases what was done. A graphic illustration of physical landmarks and their relationship to the Monument Reference Markers shall be shown upon said Monument Record Plat. These Monument Record Plats shall be recorded by the Surveyor. Recorded copies will then be furnished to the Department by the Contractor.

The determination of those Section Corners which are to be re-monumented for this project will be made by said Department.

If any of the before described Section Corners have been previously monumented by Department standards and all Reference Monuments are in place, a signed and sealed letter from the Illinois Professional Land Surveyor shall be sent to this office affirming this fact. In case a Reference Monument has been destroyed, it will be reset and a new Monument Record Plat shall be recorded.

Any questions or deviations from these procedures shall be referred to the Illinois Department of Transportation, District 2 Plats and Plans Unit at 815/284-5370.

This work will be paid for at the contract unit price per Each for SECTION CORNER MARKERS. All work shall be done under the direction of a registered land surveyor of the State of Illinois.

Each item shall include the placement of four reference markers and a land section marker where applicable.