

EARTHWORK SCHEDULE

LOCATION STATION TO STATION	EARTH EXCAVATION	EARTH EXCAVATION ADJUSTED FOR SHRINKAGE	EMBANKMENT	EARTHWORK BALANCE WASTE(+) OR SHORTAGE(-)
IL 13 EAST BOUND	CU YD	CU YD	CU YD	CU YD
400+15 TO 406+63	91	68	203	-135
TOTALS	91			-135

25% SHRINKAGE FOR EARTH EXCAVATION

PAVEMENT MARKING

LOCATION STATION TO STATION	THERMOPLASTIC PAVEMENT MARKING LINE - 4"		THERMOPLASTIC PAVEMENT MARKING LINE - 24"	THERMOPLASTIC PAVEMENT MARKING LETTERS & SYMBOLS
	SOLID YELLOW	SOLID WHITE		
IL 13 EAST BOUND	(FOOT)	(FOOT)	(FOOT)	(SQ FT)
400+85.36 TO 406+63 (OUTSIDE EDGE OF L. T. L.)	578			
403+50 TO 406+55 (INSIDE EDGE OF L. T. L.)		305		
403+64 (ONLY)				11.8
404+21 (ARROW)				8.8
AT GREENBRIAR PATCH			12	
SUBTOTALS	578	305		
TOTALS		883	12	20.6

SEEDING AND EROSION CONTROL

LOCATION STATION TO STATION	SEEDING CLASS 1B	NITROGEN FERTILIZER NUTRIENT	PHOSPHORUS FERTILIZER NUTRIENT	POTASSIUM FERTILIZER NUTRIENT	MULCH METHOD 2	AGRICULTURAL GROUND LIMESTONE	EROSION CONTROL BLANKET	SEEDING CLASS 7	TEMPORARY DITCH CHECKS
IL 13 EAST BOUND	ACRE	POUND	POUND	POUND	ACRE	TON	SQ YD	ACRE	EACH
400+15 TO 406+63	0.25	23	18	18	0.5	0.3	706	0.25	
401+00									1
403+00									1
405+00									1
TOTALS	0.25	23	18	18	0.5	0.3	706	0.25	3

REMOVAL SCHEDULE

LOCATION STATION TO STATION	PAVEMENT REMOVAL	PAVED SHOULDER REMOVAL	PAVEMENT MARKING REMOVAL
IL 13 EAST BOUND	SQ YD	SQ YD	FOOT
400+15 TO 406+63 LT		294	
400+85 TO 404+21 LT			336
404+21 TO 406+63 LT	242		
TOTALS	242	294	336

PAVING SCHEDULE

LOCATION STATION TO STATION	HOT-MIX ASPHALT SHOULDERS 8"	SUB-BASE GRANULAR MATERIAL TYPE A, 4"	PCC BASE COURSE 8"	POLYMERIZED HOT-MIX ASPHALT BINDER COURSE IL-19.0, N105	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE MIX "E", N105	POLYMERIZED BITUMINOUS MATERIALS (PRIME COAT)
IL 13 EAST BOUND	SQ YD	SQ YD	SQ YD	TON	TON	GALLON
400+15 TO 406+63 LT.	289					
400+85.36 TO 406+63 LT.		804	707	89	59	64
TOTALS	289	804	707	89	59	64