

**PAVEMENT SCHEDULE**

STATION	STATION	OFFSET	SUB GRAN MAT A 4	PCC BASE CSE W 10	BIT MATLS PR CT	AGG PR CT	HMA SC "C" N70	HMA SURF REM VAR DP	STRIP REF CR CON TR
			31100300 (SQ YD)	35400500 (SQ YD)	40600100 (GALLON)	40600300 (TON)	40603315 (TON)	44000198 (SQ YD)	44300200 (FOOT)
100+19.01	102+32.48	RT	59	49					227
100+18.49	102+26.82	LT	45	33					217
100+18.01	102+38.41				59	2	86	698	
<b>TOTAL</b>			<b>104</b>	<b>82</b>	<b>59</b>	<b>2</b>	<b>86</b>	<b>698</b>	<b>444</b>

**PAVEMENT NOTES:**

- HMA SURFACE COURSE "C" N70 QUANTITY IS CALCULATED AT A RATE OF 112 LB / SQ YD/INCH.

**SIDEWALK SCHEDULE**

STATION	STATION	OFFSET	PC CONC SIDEWALK 4 (NOTE 1)	DETECTABLE WARNINGS (NOTE 2)	PCC CONC SIDEWALK 6 SP	SIDEWALK REM
			42400100 (SQ FT)	42400800 (SQ FT)	42400440 (SQ FT)	44000600 (SQ FT)
100+19.04	101+78.61	LT	1,221	16	89	1,295
100+19.60	101+78.66	RT	508	20	200	655
101+97.17	102+01.56	RT		8	22	22
102+01.75	102+08.75	LT		8	39	28
<b>TOTAL</b>			<b>1,729</b>	<b>52</b>	<b>350</b>	<b>2,000</b>

**SIDEWALK NOTES:**

- SIDEWALK RAMPS ACCESSIBLE TO THE DISABLED ARE REQUIRED, AND SHALL BE PAID FOR AS PCC CONCRETE SIDEWALK, 6" SPECIAL CURB FOR SIDEWALK RAMPS SHALL BE INCLUDED IN THIS QUANTITY. SEE HIGHWAY STANDARD 424001 FOR SIDEWALK RAMP DETAILS.
- DETECTABLE WARNING MATERIAL SHALL BE RED, PRECAST CONCRETE WITH TRUNCATED DOMES.

**CURB & GUTTER SCHEDULE**

STATION	STATION	OFFSET	CURB REM	CONC CURB TB
			44000300 (FOOT)	60600605 (FOOT)
<b>E. SCHWARZ STREET</b>				
100+18.32	101+79.19	LT	155	177
100+19.01	101+79.16	RT	167	174
101+97.31	102+38.41	RT	39	47
102+02.11	102+38.41	LT	37	44
<b>TOTAL</b>			<b>398</b>	<b>442</b>

**CURB AND GUTTER NOTES:**

- PROPOSED CURB & GUTTER SHALL BE WARPED TO MATCH EXISTING CURBS IN 10' LINEAL FEET (MIN).
- PROPOSED CURB & GUTTER JOINTS AND DETAILS SHALL CONFORM TO HIGHWAY STANDARD 606001.

**ENTRANCE SCHEDULE**

STATION	OFFSET	ENTRANCE TYPE	ENTRANCE WIDTH "W" (NOTE 1)	ENTRANCE DEPTH "D"	EXISTING SURFACE TYPE	AGG BASE CSE A 6	AGG TEMP ACCESS	INCIDENTAL HMA SURF (NOTE 2)	DRIVEWAY PAVEMENT REM (NOTE 3)
(NOTE 1)			(FOOT)	(FOOT)		35100500 (SQ YD)	40201000 (TON)	40800050 (TON)	44000200 (SQ YD)
101+26.27	LT	C.E.	15.3	10.3	ASPHALT	11			11
101+22.47	101+79.19	LT	PARKING LOT	2	ASPHALT	13		3	11
101+88.21	LT	ALLEY	24.1	10.9	ASPHALT	26	9	5	30
101+88.21	RT	ALLEY	21.8	11.7	ASPHALT	22	7	4	25
<b>TOTAL</b>						<b>72</b>	<b>16</b>	<b>12</b>	<b>77</b>

**ENTRANCE NOTES:**

- PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL CONTACT EACH PROPERTY OWNER AND VERIFY THE LOCATION AND WIDTH OF ALL ENTRANCES.
- INCIDENTAL HMA SURFACING QUANTITY IS CALCULATED AT A RATE OF 112 LB / SQ YD/INCH.
- DRIVEWAY PAVEMENT REMOVAL INCLUDES CURB REMOVAL FOR ENTRANCES AT STATION 101+26.77 LT AND STATION 101+88.21 RT AND LT.

**PAVEMENT MARKING SCHEDULE**

STATION	STATION	TEMP PVT MK LINE 4	WORK ZONE PVT MK REM	THPL PVT MK LTRS & SYMB (NOTE 1)	THPL PVT MK LINE 4 (NOTE 1)	THPL PVT MK LINE 6 (NOTE 1)	THPL PVT MK LINE 12 (NOTE 1)	THPL PVT MK LINE 24 (NOTE 1)
		70300220 (FOOT)	70301000 (SQ FT)	78000100 (SQ FT)	78000200 (FOOT)	78000400 (FOOT)	78000600 (FOOT)	78000650 (FOOT)
100+18.45	100+26.95					73		59
100+31.70	102+38.41	534	178	47	530		21	
<b>TOTAL</b>		<b>534</b>	<b>178</b>	<b>47</b>	<b>530</b>	<b>73</b>	<b>21</b>	<b>59</b>

**PAVEMENT MARKING NOTES:**

- SEE HIGHWAY STANDARD 780001 FOR PAVEMENT MARKING DETAILS.

**EARTHWORK SCHEDULE**

STATION	STATION	OFFSET	EARTH EXCAVATION (WIDENING) (NOTE 3)	EARTH EXCAVATION ADJUSTED FOR SHRINKAGE (NOTE 1)	EARTHWORK BALANCE WASTE (+) OR SHORTAGE (-) (NOTE 2)
			20200500 (CU YD)	(CU YD)	(CU YD)
100+19.01	102+38.41	RT	20	15	15
100+18.32	102+38.41	LT	15	12	12
<b>TOTAL</b>			<b>35</b>	<b>27</b>	<b>27</b>

**EARTHWORK NOTES:**

- ESTIMATED SHRINKAGE FACTOR = 25%.
- APPROXIMATE EARTHWORK BALANCE IS SHOWN FOR INFORMATION ONLY.
- EARTH EXCAVATION MAY NOT BE SUITABLE FOR USE AS EMBANKMENT AND SHALL BE REMOVED FROM THE RIGHT-OF-WAY. THE CITY RESERVES THE RIGHT TO EVALUATE EXCAVATED MATERIAL TO DETERMINE IF IT IS SUITABLE FOR EMBANKMENT (SEE SPECIAL PROVISIONS). AN APPROXIMATE EARTHWORK BALANCE AND QUANTITY IS SHOWN FOR INFORMATION ONLY.
- ALL EARTH SURFACES SHALL BE COVERED WITH AT LEAST 4" OF CLEAN EARTH MATERIAL.