

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
*	**	ALEXANDER	65	13
STA.		TO STA.		
FED. ROAD DIST. NO.		ILLINOIS	FED. AID PROJECT	

* FAP 14 (US51/60/62)
 ** 138(N,TS-2,RS-2)

REMOVAL SCHEDULE

LOCATION STATION TO STATION	REMOVING INLETS (EACH)	RAISED REFLECTIVE PAVEMENT MARKER REMOVAL (EACH)	GUTTER REMOVAL (FOOT)	COMBINATION CURB & GUTTER REMOVAL (FOOT)	PAVEMENT REMOVAL (SQ YD)	MEDIAN SURFACE REMOVAL (SQ FT)	REMARKS
US 51							
STA. 3+62.25 TO 56+55.5		86		262		675	
STA. 46+38 TO 47+67			219		485		
STA. 46+48 TO 1+95.5 US 51/60/62					851		
STA. 46+48 TO 50+00 RT US 60/62					523		
STA. 46+48 TO 50+00 LT US 60/63			352				
STA. 46+48 TO 50+00 US 60/62				267			LARGE ISLAND
STA. 47+02 TO 47+96 LT TO 1+08 US 51/60/62				42		93	SMALL ISLAND
STA. 48+00, 33' RT	1						
STA. 48+34 TO 48+48 LT	1						
STA. 48+61.5, 45' LT							
US 60/62				330			
STA. 48+50 TO 50+10							
STA. 48+34 TO 48+49 TO 0+39 US 51/60/62							
STA. 50+00 TO 1+95.5 US 51/60/62			306				
US 51/60/62							
STA. 0+26 TO 1+95.50					818		
TOTALS	2	86	877	901	2677	768	

DETOUR SIGNING

SIGN ID NO.	DESCRIPTION	SIGN SIZE	NUMBER REQUIRED EACH WAY EAST/WEST		TOTAL SIGNS REQUIRED	SIGN PANEL TYPE 1 (0-9) (SQ FT)	SIGN PANEL TYPE 2 (9-24) (SQ FT)
			EAST	WEST			
M6-1	→	21" X 15"	1	4	5	10.94	
M6-1	←	21" X 15"	4	0	4	8.752	
M5-1L	↙	21" X 15"	2	0	2	4.376	
M6-2R	↘	21" X 15"	2	0	2	4.376	
M5-1R	↗	21" X 15"	3	4	7	15.316	
M6-3	↑	21" X 15"	8	7	15	32.82	
M1-4	60	24" X 24"	20	11	31	124	
M1-4	62	24" X 24"	20	11	31	124	
R3-2L	↻	24" X 24"	0	1	1	4	
R3-1R	↻	24" X 24"	1	0	1	4	
M3-2	EAST	24" X 12"	14	0	14	28	
W20-2	DETOUR AHEAD	48" X 48"	4	1	5		80
M4-8	DETOUR	12" X 24"	20	11	31	62	
W20-3	ROAD CLOSED AHEAD	48" X 48"	1	1	2		32
R11-3A	BRIDGE CLOSED 6 MILES AHEAD LOCAL TRAFFIC ONLY	60" X 30"	1	0	1		12.5
N-13	BRIDGE CLOSED	48" X 30"	1	0	1		10
TOTALS						422.58	134.5

PAVING SCHEDULE

LOCATION STATION TO STATION	POLYMERIZED BITUMINOUS MATERIALS, PRIME COAT (GALLON)	AGGREGATE, PRIME COAT (TONS)	HOT-MIX ASPHALT SURFACE REMOVAL 1 1/2" (SQ YD)	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE MIX D, N105 (TONS)	HOT-MIX SHOULDERS 8" (SQ YD)	GUTTERS TO BE CLEANED (FOOT)	PCC PAVEMENT, 10" (JOINTED) (SQ YD)	PROTECTIVE COAT (SQ YD)	SUB-BASE GRANULAR MATERIAL, TYPE A, 4" (SQ YD)	REMARKS
US 51										
3+62.25 TO 7+65						805.5				
3+62.25 TO 7+72.90	213.54	3.56	2372.64	217.12						
3+62.25 TO 46+48						15.8				
7+65 TO 7+72.9						24.4				
7+72.9 TO 7+79						3532				
7+72.29 TO 43+42	1713.17	28.55	19035.2	1706.37						
7+79 TO 16+62						232.05				
16+62 TO 17+39.35 BK										
17+39.35 BK = 17+73.95 AH										
17+73.95 AH TO 34+00						3252.1				STATION EQUATION
34+00 TO 45+09.7						3329.1				
43+42 TO 45+09.7	83.01	1.38	922.35	82.95						
45+09.7 TO 46+48	73.99	1.23	822.1	76.59		414.9				
46+68 TO 47+67							89	89	89	
46+48 TO 50+00 RT US 60/62					313		851	851	889	PAINTED MEDIAN THROUGH AND LEFT LANE
46+48 TO 50+00 LT US 60/62							523	523	523	THROUGH LANE
46+48 TO 1+95.5 US 51/60/62							565	565	565	TURNING RADIUS
US 60/62										
48+49 TO 50+00							305	305	305	PAINTED MEDIAN
50+00.0 TO 52+99.2	83.78	1.40	930.84	94.48		897.6				
52+99.2 TO 56+55.5	104.27	1.74	1158.57	101.18		356.3				
US 51/60/62										
0+26 TO 1+95.5 LT							818	818	818	THROUGHS AND LT RADIUS
TOTALS	2272	38	25242	2279	313	12860	3151	3151	3189	

12/21/2007
 c:\projects\98943\98943.dwg
 50.0000 / IN.
 vanbrakeren