

PAVEMENT MARKING

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
*	**	ALEXANDER	65	14
STA.		TO STA.		
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		

- * FAP 14 (US51/60/62)
- ** I38(N,TS-2,RS-2)

LOCATION STATION TO STATION	THERMOPLASTIC PAVEMENT MARKING									
	LETTERS AND SYMBOLS	4 INCH		12 INCH	PREFORMED PLASTIC PAVEMENT MARKING TYPE B, INLAID 4 INCH	POLYUREA PAVEMENT MARKING LINE 4 INCH		POLYUREA PAVEMENT MARKING LINE 12 INCH		POLYUREA PAVEMENT MARKING LINE 24 INCH
		(WHITE) SQ FT	(YELLOW) FOOT	(YELLOW) FOOT		(WHITE) FOOT	(WHITE) FOOT	(YELLOW) FOOT	(WHITE) FOOT	
3+62.25 TO 7+72.9 26' RT (SOLID)		410.65								
3+62.25 TO 7+72.9 14' RT (SKIP DASH)					102.6					
3+62.25 TO 7+72.9 2' RT (DOUBLE SOLID)			821.3							
3+62.25 TO 7+72.9 2' LT (DOUBLE SOLID)			821.3							
3+62.25 TO 7+72.9 14' LT (SKIP DASH)					102.6					
3+62.25 TO 7+72.9 26' LT (SOLID)		410.65								
7+72.9 TO 17+39.35 26' RT (SOLID)		966.5								
7+72.9 TO 17+39.35 14' RT (SKIP DASH)					241.6					
7+72.9 TO 17+39.35 2' RT (SOLID)			966.5							
7+72.9 TO 17+39.35 2' LT (SOLID)			966.5							
7+72.9 TO 17+39.35 14' LT (SKIP DASH)					241.6					
7+72.9 TO 17+39.35 26' LT (SOLID)		966.5								
STA. EQUATION (17+39.35 BK = 17+73.95 AH)										
17+73.95 TO 43+42 26' RT (SOLID)		2568.1								
17+73.95 TO 43+42 14' RT (SKIP DASH)					642					
17+73.95 TO 43+42 2' RT (SOLID)			2568.1							
17+73.95 TO 43+42 2' LT (SOLID)			2568.1							
17+73.95 TO 43+42 14' LT (SKIP DASH)					642					
17+73.95 TO 43+42 26' LT (SOLID)		2568.1								
43+42 TO 45+09.7 26' RT (SOLID)		167.7								
43+42 TO 45+09.7 14' RT (SKIP DASH)					41.9					
43+42 TO 45+09.7 2' RT (SOLID)			167.7							
43+42 TO 45+09.7 2' LT (SOLID)			167.7							
43+42 TO 45+09.7 14' LT (SKIP DASH)					41.9					
43+42 TO 45+09.7 VAR. 24' TO 27' LT (SOLID)		167.7								
45+09.7 TO 46+48 VAR. RT (SOLID)		138.3								
45+09.7 TO 46+48 VAR. RT (SKIP DASH)					34.6					
45+09.7 TO 46+48 VAR. RT (SOLID)			138.3							
45+09.7 TO 46+48 VAR. LT (SOLID)			138.3							
45+09.7 TO 46+48 VAR. LT (SKIP DASH)					34.6					
45+09.7 TO 46+48 VAR. LT (SOLID)		138.3								
45+89.6 LT TO 48+00.3 LT (SOLID)						470.3				
46+00	92									
46+48 RT TO 50+00 RT (SOLID)						352				
46+48 RT TO 47+51 RT (SKIP DASH)						30				
46+48 TO 47+66.4 (DOUBLE SOLID)							480.4			
48+49 TO 50+00 (DOUBLE SOLID)							614.4			
0+45.5 TO 1+95.4 (DOUBLE SOLID)							300			
45+89.6 LT TO 48+00.3 LT								136		
46+48 TO 47+66.4									57.3	
48+49 TO 50+00									187.5	
0+45.5										14
50+00 TO 53+05 VAR. RT (SOLID)		305								
50+00 TO 53+05 VAR. RT (SOLID)			305							
50+00 TO 53+05 VAR. LT (SOLID)			305							
50+00 TO 53+05 VAR. LT (SOLID)		305								
53+05 TO 54+80				57						
53+05 TO 54+80 VAR. RT (SOLID)		175								
53+05 TO 54+80 VAR. RT (DOUBLE SOLID)			350							
53+05 TO 54+80 VAR. LT (DOUBLE SOLID)			350							
53+05 TO 54+80 VAR. LT (SOLID)		175								
54+80 TO 56+55.5 VAR RT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR RT. (SOLID)			175.5							
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)			175.5							
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								
54+80 TO 56+55.5 VAR LT. (SOLID)										
54+80 TO 56+55.5 VAR LT. (SOLID)		175.5								