

NOTES:

- 1. THE WIDTH OF THE FULL DEPTH PATCH OVER A TRENCH SHALL BE 12 (300) WIDER ON EACH SIDE OF THE TRENCH.
- 2. FOR METHOD OF MEASUREMENT AND BASIS OF PAYMENT, SEE RECURRING SPECIAL PROVISION "PATCHING WITH HOT-MIX ASPHALT OVERLAY REMOVAL".

SEQUENCE OF CONSTRUCTION (PATCHING FIRST)

- 1. REMOVE THE EXISTING HMA MATERIAL OVER THE AREA TO BE PATCHED.
- 2. REMOVE AND REPLACE WITH CLASS C OR D PATCH.
- 3. REPLACE HMA MATERIAL OVER THE AREA TO BE PATCHED.

SEQUENCE OF CONSTRUCTION (MILLING FIRST)

- 1. MILL HMA FIRST IF THERE IS AT LEAST 41/2 INCHES OR MORE OF HMA MATERIAL ON TOP OF THE EXISTING PAVEMENT OR IF THE PAVEMENT IS FULL DEPTH HMA. A MINIMUM OF 2 INCHES OF HMA MATERIAL SHALL BE IN PLACE AFTER MILLING.
- 2. REMOVE AND REPLACE WITH FULL DEPTH CLASS D PATCHES TO TOP OF MILLED SURFACE.

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN,

FILE HAM	ı£ •	USER NAME * pyrzonoxskirb	DESIGNED - R	R. SHAH	REVISED .	A. ABBAS 04-27-98			PAVEMENT PATCHING FOR		F.A.I. RYE.	SECTION	COUNTY	SHEETS	SHEET NO.
c:\p=.xor	ci\pw.work\pwidot\pyrzonowskirb\d0370426	NDI12614-sht-plan.dgn	DRAWN -		REVISED -	R. BORO 01-01-07		HMA SURFACED PAVEMENT		57	(99-2T#S)PP	WILL	18	18A	
1		PLOT SCALE = 100,0000 ' / tn,	CHECKED -		REVISED -	R. BORO 09-04-07	DEPARTMENT OF TRANSPORTATION			BD40	0-04 (BD-22)	CONTRACT	NO. 6	0x55	
1		PLOT DATE = 3/20/2014	DATE - IC	0-25-94	REVISED -	K. ENG 10-27-08		SCALE: NONE	SHEET NO. 1 OF 1 SHEETS STA.	TO STA.	FED. ROAD DIS	t. NO. 1 ILLINOIS FED. A	D PROJECT		