## STAGING GENERAL NOTES

THE CONTRACTOR SHALL COORDINATE MAINTENANCE OF TRAFFIC OF THIS PROJECT WITH OTHER PROJECTS IN ADJACENT SECTIONS. SEE TRAFFIC CONTROL SPECIAL PROVISIONS FOR COORDINATION REQUIREMENTS.

ANY SIGNS THAT ARE TO BE IN PLACE FOR MORE THAN FOUR DAYS SHALL BE POST MOUNTED WHEN FEASIBLE AS DETERMINED BY THE ENGINEER.

ROUGH GROOVED SURFACE AND FRESH OIL SIGNS ARE REQUIRED WHERE APPLICABLE.

PRIOR TO BEGINNING ANY CONSTRUCTION, THE CONTRACTOR SHALL BE REQUIRED TO ATTEND A TRAFFIC CONTROL MEETING TO ASCERTAIN THE EXACT SCHEDULING OF THE TRAFFIC STAGES AND ANY INTERMEDIATE CHANGES NECESSARY. IF AN ALTERNATE TRAFFIC PATTERN IS REQUIRED WITHIN THIS CONTRACT, THE CONTRACTOR SHALL SUBMIT A MAINTENANCE OF TRAFFIC DEVIANCE PLAN FOR APPROVAL BY THE RESIDENT ENGINEER AND THE DISTRICT. FOR ADDITIONAL INFORMATION REGARDING COORDINATION SEE STANDARD SPECIFICATION ARTICLE 701.04.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR ESTABLISHING AND MAINTAINING CONSTRUCTION ACCESS POINTS. THE PROPOSED LOCATIONS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE USE.

UNLESS OTHERWISE APPROVED BY THE ENGINEER, ALL TEMPORARY CONCRETE BARRIER SHALL BE PLACED DURING OFF-PEAK HOURS UNDER TEMPORARY LANE CLOSURES.

TEMPORARY RAMPS SHALL BE 80: 1 MINIMUM RATIO ON I-57/64.

WHEN PAVEMENT DROP-OFF IS TO REMAIN ADJACENT TO A LIVE TRAFFIC LANE, BARRICADES WITH PIPE EXTENSIONS SHALL BE USED TO ACHIEVE THE CORRECT ELEVATION.

ANY SIGNS USED IN TRAFFIC CONTROL & PROTECTION STANDARD 701401 SPECIAL SHALL BE COVERED WHEN NOT IN USE.



FILE NAME =	USER NAME = rollavr	DESIGNED -	REVISED -		STAGING GENERAL NOTES						F.A.I.	SECTION	COUNTY TOTAL SHEET
c:\pw_work\pwidot\rollavr\d0278568\78276	-shtd-stageconstruction.dgn	DRAWN -	REVISED -	STATE OF ILLINOIS	OTAGING GENETIAL NOTES					••	•	JEFFERSON 235 79	
	PLOT SCALE = 100.0000 ' / in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION	,							CONTRACT NO. 78276	
Default	PLOT DATE = 2/28/2014	DATE -	REVISED -		SCALE: SHEET OF SHEETS STA. TO STA.					TO STA.		ILLINOIS FED. AID PROJECT	
	•(41-3-1)RS-1;(41-8)RS-2 ••57/64												