TRAFFIC SIGNAL LEGEND

<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED	ITEM		REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	R			EMERGENCY VEHIC	LE LIGHT DETECTOR	R	\bowtie	~	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE			
RAILROAD CONTROL CABINET		R R	▶ ⋖	CONFIRMATION BE	ACON	R_{\circ}	⊶ (NO. 14 170, ONLESS NOTED OTHERWISE		,	
COMMUNICATIONS CABINET	C C	E C C	СС	HANDHOLE		R N			COAXIAL CABLE		— <u>C</u> —	<u> </u>
MASTER CONTROLLER		EMC	MC	HANDHOLE		D					~	
MASTER MASTER CONTROLLER	D	EMMC	MMC	HEAVY DUTY HAND	DHOLE	Н	Н	H	VENDOR CABLE FOR CAMERA		(v)	<u></u>
NINTERRUPTIBLE POWER SUPPLY	UPS	EUPS	UPS	DOUBLE HANDHOLE		R			COPPER INTERCONNECT CABLE, NO. 18 3 PAIR TWISTED, SHIELDED		-6-	-6-
ERVICE INSTALLATION,	-D-R	-D ^P	- P	JUNCTION BOX		R		•	FIBER OPTIC CABLE		/-	
P) POLE OR (G) GROUND MOUNT ELEPHONE CONNECTION P) POLE OR (G) GROUND MOUNT	R T	P	P	GALVANIZED STEE IN TRENCH (T) OR					NO. 62.5/125, MM12F FIBER OPTIC CABLE		<u></u>	
TEEL MAST ARM ASSEMBLY AND POLE	R	_		TEMPORARY SPAN AND CABLE	WIRE, TETHER WIRE,	_R			NO. 62.5/125, MM12F SM12F		<u> </u>	—24F—
.UMINUM MAST ARM ASSEMBLY AND POLE	O			COMMON TRENCH				СТ	FIBER OPTIC CABLE NO. 62.5/125,		\prec	
TEEL COMBINATION MAST ARM					ALLIC CONDUIT (EMPTY)			CNC	(NUMBER OF FIBERS & TYPE TO BE NOTED ON PLANS)			-
SSEMBLY AND POLE WITH LUMINAIRE	^R O-⊅	O-X	• ×	SYSTEM ITEM			S	S	GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM,		° ∞	^C ı∥ ⊢ •
FEEL COMBINATION MAST ARM SSEMBLY AND POLE WITH PTZ CAMERA		PTZ[1	PTZ	INTERSECTION ITE	EM		I	IΡ	OR (S) SERVICE		'	·
IGNAL POST	R	0	•	REMOVE ITEM		R			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF		
EMPORARY WOOD POLE (CLASS 5 OR	R⊗	\otimes	•	RELOCATE ITEM		RL						
ETTER) 45 FOOT (13.7m) MINIMUM				ABANDON ITEM		А			STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	O-RMF		
JY WIRE	<u></u>	>	<i>></i>	12" (300mm) TRAF	FFIC SIGNAL SECTION		(R)	R	ALUMINUM MAST ARM POLE AND	RMF		
GNAL HEAD	R →>	\rightarrow	-	12" (300mm) RED	WITH 8" (200mm)		R		FOUNDATION TO BE REMOVED	0		
GNAL HEAD CONSTRUCTION STAGES UMBERS INDICATE THE CONSTRUCTION STAGE)			2	YELLOW AND GREE	EN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF O>X		
GNAL HEAD WITH BACKPLATE	+>R	+1>	+-					R	FOUNDATION TO BE REMOVED			
GNAL HEAD OPTICALLY PROGRAMMED	_R —⊠′′P′′		-▶ "P"	SIGNAL FACE				G	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF O		
ASHER INSTALLATION DENOTES SOLAR POWER)	R O-D''F''	O+⊳′′F′′	• "F"				◆ y ◆ G	∢ Y ∢ G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR		[IS]	IS
EDESTRIAN SIGNAL HEAD	R -	-	4				R	R	SAMPLING (SYSTEM) DETECTOR		[s]	S
EDESTRIAN PUSHBUTTON DETECTOR	R (6)		©	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD			(Y)	Y G ◀Y ◀G	EXISTING INTERSECTION LOOP DETECTOR	CTOR	'' [C]	
CCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R APS	⊚APS	APS				(4 y) (4 g)		PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETE	CTOR		
LUMINATED SIGN	R						(P''	"P"	EXISTING PREFORMED INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETE	CTOR	ĮPP.	
NO LEFT TURN"	8		\bigcirc	12" (300mm) PEDE	STRIAN SIGNAL HEAD		[6W]		PREFORMED INTERSECTION AND SAMPLING		Ŷ — Ŷ	•
LUMINATED SIGN	R			WALK/DON'T WALK SYMBOL			W		(SYSTEM) DETECTOR		PIS	PIS
NO RIGHT TURN"				12" (300mm) PEDESTRIAN SIGNAL HEAD International symbol, outlined					PREFORMED SAMPLING (SYSTEM) DETECTOR		[PS]	PS
ETECTOR LOOP, TYPE I												
REFORMED DETECTOR LOOP			Р	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID			Ŕ	*	RAILROAD SYMBOL		OLS	
ICROWAVE VEHICLE SENSOR	R M)	M	M	PEDESTRIAN SIGN. SYMBOL, WITH CO	AL HEAD, INTERNATIONAL UNTDOWN TIMER		(C) C	₽ C ★ D			<u>EXISTING</u>	PROPOSED
DEO DETECTION CAMERA	R [V]1	(V)	\bigcirc	RADIO INTERCONNI	FCT	III. ^R .o	##•		RAILROAD CONTROL CABINET		R R	₽⋖
DEO DETECTION ZONE				RADIO INTERCONNECT		##**	III		RAILROAD CANTILEVER MAST ARM		XOX X	XX
				RADIO REPEATER		RERR	ERR	RR				
AN, TILT, ZOOM CAMERA	PTZ)1	PTZ	PTZ (DENOTES NUMBER OF CONDUCTORS, ELECTRIC			_<	_5_	FLASHING SIGNAL		$\times \oplus \times$	X⊖X
IRELESS DETECTOR SENSOR	RW	W	W		CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED		737		CROSSING GATE		$X \circ X >$	XOX
IRELESS ACCESS POINT	R D			GROUND CABLE IN NO. 6 SOLID COPI			1	1	CROSSBUCK		₹	*
NAME = USER NAME = bauerdl		ESIGNED - DAG/BCK	REVISED -						DISTRICT ONE	F.A.P. RTE.	SECTION	COUNTY TO
w_work\PWIDOT\BAUERDL\d0108315\ts05_dgn PLOT_SCALE = 50.0000 ′/ I		RAWN - BCK HECKED - DAD	REVISED -		STATE DEPARTMENT	OF ILLINOIS	S		STANDARD TRAFFIC SIGNAL DESIGN DETAILS	330	103R-3	COOK 9: