

BEAM 1

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+48.89	-66.00	657.99	657.99
@ EXP. JT.	116+50.97	-66.00	658.01	658.01
@ BRG. S. ABUT.	116+51.89	-66.00	658.02	658.02
A	116+61.89	-66.00	658.11	658.20
B	116+71.89	-66.00	658.17	658.35
C	116+81.89	-66.00	658.22	658.47
D	116+91.89	-66.00	658.26	658.56
E	117+01.89	-66.00	658.28	658.61
F	117+11.89	-66.00	658.28	658.62
G	117+21.89	-66.00	658.27	658.60
H	117+31.89	-66.00	658.24	658.54
I	117+41.89	-66.00	658.19	658.45
J	117+51.89	-66.00	658.13	658.33
K	117+61.89	-66.00	658.06	658.20
L	117+71.89	-66.00	657.96	658.05
M	117+81.89	-66.00	657.85	657.89
@ BRG. PIER	117+95.89	-66.00	657.67	657.67
N	118+05.89	-66.00	657.53	657.52
O	118+15.89	-66.00	657.36	657.36
P	118+25.89	-66.00	657.18	657.20
Q	118+35.89	-66.00	656.99	657.03
R	118+45.89	-66.00	656.78	656.85
S	118+55.89	-66.00	656.55	656.66
T	118+65.89	-66.00	656.31	656.43
U	118+75.89	-66.00	656.05	656.18
V	118+85.89	-66.00	655.77	655.90
W	118+95.89	-66.00	655.48	655.58
X	119+05.89	-66.00	655.17	655.24
@ BRG. N. ABUT.	119+19.89	-66.00	654.71	654.71
@ EXP. JT.	119+20.81	-66.00	654.68	654.68
BK. N. ABUT.	119+22.89	-66.00	654.61	654.61

BEAM 2

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+49.26	-59.00	658.14	658.14
@ EXP. JT.	116+51.34	-59.00	658.16	658.16
@ BRG. S. ABUT.	116+52.26	-59.00	658.17	658.17
A	116+62.26	-59.00	658.25	658.34
B	116+72.26	-59.00	658.31	658.49
C	116+82.26	-59.00	658.37	658.61
D	116+92.26	-59.00	658.40	658.70
E	117+02.26	-59.00	658.42	658.75
F	117+12.26	-59.00	658.42	658.76
G	117+22.26	-59.00	658.41	658.74
H	117+32.26	-59.00	658.38	658.68
I	117+42.26	-59.00	658.33	658.59
J	117+52.26	-59.00	658.27	658.47
K	117+62.26	-59.00	658.19	658.33
L	117+72.26	-59.00	658.10	658.19
M	117+82.26	-59.00	657.99	658.03
@ BRG. PIER	117+96.26	-59.00	657.81	657.81
N	118+06.26	-59.00	657.66	657.65
O	118+16.26	-59.00	657.50	657.49
P	118+26.26	-59.00	657.32	657.33
Q	118+36.26	-59.00	657.12	657.17
R	118+46.26	-59.00	656.91	656.99
S	118+56.26	-59.00	656.68	656.79
T	118+66.26	-59.00	656.44	656.56
U	118+76.26	-59.00	656.18	656.31
V	118+86.26	-59.00	655.90	656.03
W	118+96.26	-59.00	655.61	655.71
X	119+06.26	-59.00	655.30	655.37
@ BRG. N. ABUT.	119+20.26	-59.00	654.84	654.84
@ EXP. JT.	119+21.17	-59.00	654.81	654.81
BK. N. ABUT.	119+23.26	-59.00	654.74	654.74

BEAM 3

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+49.62	-52.00	658.28	658.28
@ EXP. JT.	116+51.71	-52.00	658.30	658.30
@ BRG. S. ABUT.	116+52.62	-52.00	658.31	658.31
A	116+62.62	-52.00	658.39	658.48
B	116+72.62	-52.00	658.46	658.63
C	116+82.62	-52.00	658.51	658.75
D	116+92.62	-52.00	658.54	658.84
E	117+02.62	-52.00	658.56	658.89
F	117+12.62	-52.00	658.56	658.90
G	117+22.62	-52.00	658.55	658.88
H	117+32.62	-52.00	658.52	658.82
I	117+42.62	-52.00	658.47	658.72
J	117+52.62	-52.00	658.41	658.61
K	117+62.62	-52.00	658.33	658.47
L	117+72.62	-52.00	658.24	658.32
M	117+82.62	-52.00	658.13	658.17
@ BRG. PIER	117+96.62	-52.00	657.94	657.94
N	118+06.62	-52.00	657.80	657.79
O	118+16.62	-52.00	657.63	657.63
P	118+26.62	-52.00	657.45	657.47
Q	118+36.62	-52.00	657.25	657.30
R	118+46.62	-52.00	657.04	657.12
S	118+56.62	-52.00	656.81	656.92
T	118+66.62	-52.00	656.57	656.69
U	118+76.62	-52.00	656.31	656.44
V	118+86.62	-52.00	656.03	656.16
W	118+96.62	-52.00	655.74	655.84
X	119+06.62	-52.00	655.43	655.49
@ BRG. N. ABUT.	119+20.62	-52.00	654.97	654.97
@ EXP. JT.	119+21.54	-52.00	654.94	654.94
BK. N. ABUT.	119+23.62	-52.00	654.87	654.87

G:\IDOT\21850_006_CumberlandAve\Drawings\CADD Sheets\0160J14-sh-t-tsl-DkElevTbl1.dgn