

BEAM 4

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+49.99	-45.00	658.42	658.42
@ EXP. JT.	116+52.07	-45.00	658.44	658.44
@ BRG. S. ABUT.	116+52.99	-45.00	658.45	658.45
A	116+62.99	-45.00	658.53	658.63
B	116+72.99	-45.00	658.60	658.78
C	116+82.99	-45.00	658.65	658.90
D	116+92.99	-45.00	658.68	658.98
E	117+02.99	-45.00	658.70	659.03
F	117+12.99	-45.00	658.70	659.04
G	117+22.99	-45.00	658.69	659.02
H	117+32.99	-45.00	658.66	658.96
I	117+42.99	-45.00	658.61	658.86
J	117+52.99	-45.00	658.55	658.74
K	117+62.99	-45.00	658.47	658.61
L	117+72.99	-45.00	658.37	658.46
M	117+82.99	-45.00	658.26	658.30
@ BRG. PIER	117+96.99	-45.00	658.08	658.08
N	118+06.99	-45.00	657.93	657.92
O	118+16.99	-45.00	657.76	657.76
P	118+26.99	-45.00	657.58	657.60
Q	118+36.99	-45.00	657.39	657.43
R	118+46.99	-45.00	657.17	657.25
S	118+56.99	-45.00	656.94	657.05
T	118+66.99	-45.00	656.70	656.82
U	118+76.99	-45.00	656.44	656.57
V	118+86.99	-45.00	656.16	656.29
W	118+96.99	-45.00	655.87	655.97
X	119+06.99	-45.00	655.56	655.62
@ BRG. N. ABUT.	119+20.99	-45.00	655.10	655.10
@ EXP. JT.	119+21.91	-45.00	655.06	655.06
BK. N. ABUT.	119+23.99	-45.00	654.99	654.99

BEAM 5

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+50.36	-38.00	658.57	658.57
@ EXP. JT.	116+52.44	-38.00	658.59	658.59
@ BRG. S. ABUT.	116+53.36	-38.00	658.60	658.60
A	116+63.36	-38.00	658.68	658.77
B	116+73.36	-38.00	658.74	658.92
C	116+83.36	-38.00	658.79	659.04
D	116+93.36	-38.00	658.82	659.12
E	117+03.36	-38.00	658.84	659.17
F	117+13.36	-38.00	658.84	659.18
G	117+23.36	-38.00	658.82	659.15
H	117+33.36	-38.00	658.79	659.09
I	117+43.36	-38.00	658.75	659.00
J	117+53.36	-38.00	658.68	658.88
K	117+63.36	-38.00	658.60	658.74
L	117+73.36	-38.00	658.51	658.59
M	117+83.36	-38.00	658.40	658.44
@ BRG. PIER	117+97.36	-38.00	658.21	658.21
N	118+07.36	-38.00	658.06	658.06
O	118+17.36	-38.00	657.90	657.89
P	118+27.36	-38.00	657.72	657.73
Q	118+37.36	-38.00	657.52	657.56
R	118+47.36	-38.00	657.30	657.38
S	118+57.36	-38.00	657.07	657.18
T	118+67.36	-38.00	656.83	656.96
U	118+77.36	-38.00	656.57	656.70
V	118+87.36	-38.00	656.29	656.41
W	118+97.36	-38.00	655.99	656.10
X	119+07.36	-38.00	655.68	655.75
@ BRG. N. ABUT.	119+21.36	-38.00	655.22	655.22
@ EXP. JT.	119+22.28	-38.00	655.19	655.19
BK. N. ABUT.	119+24.36	-38.00	655.12	655.12

BEAM 6

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+50.73	-31.00	658.71	658.71
@ EXP. JT.	116+52.81	-31.00	658.73	658.73
@ BRG. S. ABUT.	116+53.73	-31.00	658.74	658.74
A	116+63.73	-31.00	658.82	658.91
B	116+73.73	-31.00	658.88	659.06
C	116+83.73	-31.00	658.93	659.18
D	116+93.73	-31.00	658.96	659.26
E	117+03.73	-31.00	658.98	659.31
F	117+13.73	-31.00	658.98	659.32
G	117+23.73	-31.00	658.96	659.29
H	117+33.73	-31.00	658.93	659.23
I	117+43.73	-31.00	658.88	659.14
J	117+53.73	-31.00	658.82	659.02
K	117+63.73	-31.00	658.74	658.88
L	117+73.73	-31.00	658.64	658.73
M	117+83.73	-31.00	658.53	658.57
@ BRG. PIER	117+97.73	-31.00	658.35	658.35
N	118+07.73	-31.00	658.20	658.19
O	118+17.73	-31.00	658.03	658.03
P	118+27.73	-31.00	657.85	657.87
Q	118+37.73	-31.00	657.65	657.70
R	118+47.73	-31.00	657.44	657.51
S	118+57.73	-31.00	657.21	657.31
T	118+67.73	-31.00	656.96	657.09
U	118+77.73	-31.00	656.70	656.83
V	118+87.73	-31.00	656.42	656.54
W	118+97.73	-31.00	656.12	656.23
X	119+07.73	-31.00	655.81	655.88
@ BRG. N. ABUT.	119+21.73	-31.00	655.35	655.35
@ EXP. JT.	119+22.64	-31.00	655.32	655.32
BK. N. ABUT.	119+24.73	-31.00	655.25	655.25

G:\IDOT\21850_006_CumberlandAve\Drawings\CADD Sheets\016014-sh-t-tsl-DkElevTbl.2.dgn