

BEAM 9

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+51.83	-10.00	659.14	659.14
@ EXP. JT.	116+53.91	-10.00	659.16	659.16
@ BRG. S. ABUT.	116+54.83	-10.00	659.17	659.17
A	116+64.83	-10.00	659.25	659.34
B	116+74.83	-10.00	659.31	659.49
C	116+84.83	-10.00	659.36	659.60
D	116+94.83	-10.00	659.39	659.68
E	117+04.83	-10.00	659.40	659.73
F	117+14.83	-10.00	659.40	659.74
G	117+24.83	-10.00	659.38	659.71
H	117+34.83	-10.00	659.35	659.65
I	117+44.83	-10.00	659.30	659.55
J	117+54.83	-10.00	659.23	659.43
K	117+64.83	-10.00	659.15	659.29
L	117+74.83	-10.00	659.05	659.14
M	117+84.83	-10.00	658.94	658.98
@ BRG. PIER	117+98.83	-10.00	658.75	658.75
N	118+08.83	-10.00	658.60	658.59
O	118+18.83	-10.00	658.43	658.43
P	118+28.83	-10.00	658.25	658.26
Q	118+38.83	-10.00	658.05	658.09
R	118+48.83	-10.00	657.83	657.91
S	118+58.83	-10.00	657.60	657.71
T	118+68.83	-10.00	657.35	657.48
U	118+78.83	-10.00	657.09	657.22
V	118+88.83	-10.00	656.81	656.93
W	118+98.83	-10.00	656.51	656.61
X	119+08.83	-10.00	656.20	656.26
@ BRG. N. ABUT.	119+22.83	-10.00	655.73	655.73
@ EXP. JT.	119+23.74	-10.00	655.70	655.70
BK. N. ABUT.	119+25.83	-10.00	655.63	655.63

BEAM 10

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+52.19	-3.00	659.29	659.29
@ EXP. JT.	116+54.28	-3.00	659.30	659.30
@ BRG. S. ABUT.	116+55.19	-3.00	659.31	659.31
A	116+65.19	-3.00	659.39	659.45
B	116+75.19	-3.00	659.45	659.58
C	116+85.19	-3.00	659.50	659.67
D	116+95.19	-3.00	659.53	659.74
E	117+05.19	-3.00	659.54	659.78
F	117+15.19	-3.00	659.54	659.79
G	117+25.19	-3.00	659.52	659.76
H	117+35.19	-3.00	659.49	659.71
I	117+45.19	-3.00	659.44	659.63
J	117+55.19	-3.00	659.37	659.52
K	117+65.19	-3.00	659.29	659.40
L	117+75.19	-3.00	659.19	659.26
M	117+85.19	-3.00	659.07	659.11
@ BRG. PIER	117+99.19	-3.00	658.89	658.89
N	118+09.19	-3.00	658.73	658.73
O	118+19.19	-3.00	658.57	658.56
P	118+29.19	-3.00	658.38	658.39
Q	118+39.19	-3.00	658.18	658.21
R	118+49.19	-3.00	657.96	658.01
S	118+59.19	-3.00	657.73	657.79
T	118+69.19	-3.00	657.48	657.56
U	118+79.19	-3.00	657.22	657.29
V	118+89.19	-3.00	656.94	657.01
W	118+99.19	-3.00	656.64	656.70
X	119+09.19	-3.00	656.33	656.36
@ BRG. N. ABUT.	119+23.19	-3.00	655.86	655.86
@ EXP. JT.	119+24.11	-3.00	655.83	655.83
BK. N. ABUT.	119+26.19	-3.00	655.76	655.76

PROFILE GRADE & @ OPEN JOINT

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+52.35	0.00	659.35	659.35
@ EXP. JT.	116+54.43	0.00	659.37	659.37
@ BRG. S. ABUT.	116+55.35	0.00	659.37	659.37
A	116+65.35	0.00	659.45	659.52
B	116+75.35	0.00	659.51	659.64
C	116+85.35	0.00	659.56	659.73
D	116+95.35	0.00	659.59	659.80
E	117+05.35	0.00	659.60	659.84
F	117+15.35	0.00	659.60	659.85
G	117+25.35	0.00	659.58	659.82
H	117+35.35	0.00	659.55	659.77
I	117+45.35	0.00	659.49	659.69
J	117+55.35	0.00	659.43	659.58
K	117+65.35	0.00	659.35	659.45
L	117+75.35	0.00	659.25	659.31
M	117+85.35	0.00	659.13	659.16
@ BRG. PIER	117+99.35	0.00	658.95	658.95
N	118+09.35	0.00	658.79	658.79
O	118+19.35	0.00	658.62	658.62
P	118+29.35	0.00	658.44	658.45
Q	118+39.35	0.00	658.24	658.26
R	118+49.35	0.00	658.02	658.07
S	118+59.35	0.00	657.79	657.85
T	118+69.35	0.00	657.54	657.61
U	118+79.35	0.00	657.27	657.35
V	118+89.35	0.00	656.99	657.06
W	118+99.35	0.00	656.69	656.75
X	119+09.35	0.00	656.38	656.42
@ BRG. N. ABUT.	119+23.35	0.00	655.92	655.92
@ EXP. JT.	119+24.27	0.00	655.88	655.88
BK. N. ABUT.	119+26.35	0.00	655.81	655.81