

BEAM 11

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+52.51	3.00	659.29	659.29
@ EXP. JT.	116+54.59	3.00	659.31	659.31
@ BRG. S. ABUT.	116+55.51	3.00	659.31	659.31
A	116+65.51	3.00	659.39	659.46
B	116+75.51	3.00	659.45	659.58
C	116+85.51	3.00	659.50	659.67
D	116+95.51	3.00	659.53	659.74
E	117+05.51	3.00	659.54	659.78
F	117+15.51	3.00	659.54	659.79
G	117+25.51	3.00	659.52	659.76
H	117+35.51	3.00	659.48	659.71
I	117+45.51	3.00	659.43	659.62
J	117+55.51	3.00	659.37	659.52
K	117+65.51	3.00	659.28	659.39
L	117+75.51	3.00	659.19	659.25
M	117+85.51	3.00	659.07	659.10
@ BRG. PIER	117+99.51	3.00	658.88	658.88
N	118+09.51	3.00	658.73	658.72
O	118+19.51	3.00	658.56	658.56
P	118+29.51	3.00	658.38	658.38
Q	118+39.51	3.00	658.17	658.20
R	118+49.51	3.00	657.96	658.00
S	118+59.51	3.00	657.72	657.79
T	118+69.51	3.00	657.47	657.55
U	118+79.51	3.00	657.21	657.29
V	118+89.51	3.00	656.93	657.00
W	118+99.51	3.00	656.63	656.69
X	119+09.51	3.00	656.32	656.35
@ BRG. N. ABUT.	119+23.51	3.00	655.85	655.85
@ EXP. JT.	119+24.42	3.00	655.82	655.82
BK. N. ABUT.	119+26.51	3.00	655.75	655.75

BEAM 12

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+52.87	10.00	659.15	659.15
@ EXP. JT.	116+54.96	10.00	659.17	659.17
@ BRG. S. ABUT.	116+55.87	10.00	659.18	659.18
A	116+65.87	10.00	659.25	659.35
B	116+75.87	10.00	659.32	659.49
C	116+85.87	10.00	659.36	659.61
D	116+95.87	10.00	659.39	659.69
E	117+05.87	10.00	659.40	659.73
F	117+15.87	10.00	659.40	659.74
G	117+25.87	10.00	659.38	659.71
H	117+35.87	10.00	659.34	659.64
I	117+45.87	10.00	659.29	659.55
J	117+55.87	10.00	659.22	659.42
K	117+65.87	10.00	659.14	659.28
L	117+75.87	10.00	659.04	659.13
M	117+85.87	10.00	658.93	658.97
@ BRG. PIER	117+99.87	10.00	658.74	658.74
N	118+09.87	10.00	658.58	658.58
O	118+19.87	10.00	658.41	658.41
P	118+29.87	10.00	658.23	658.24
Q	118+39.87	10.00	658.03	658.07
R	118+49.87	10.00	657.81	657.88
S	118+59.87	10.00	657.57	657.68
T	118+69.87	10.00	657.32	657.45
U	118+79.87	10.00	657.06	657.19
V	118+89.87	10.00	656.78	656.90
W	118+99.87	10.00	656.48	656.58
X	119+09.87	10.00	656.16	656.23
@ BRG. N. ABUT.	119+23.87	10.00	655.70	655.70
@ EXP. JT.	119+24.79	10.00	655.67	655.67
BK. N. ABUT.	119+26.87	10.00	655.59	655.59

BEAM 13

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+53.24	17.00	659.01	659.01
@ EXP. JT.	116+55.32	17.00	659.03	659.03
@ BRG. S. ABUT.	116+56.24	17.00	659.04	659.04
A	116+66.24	17.00	659.12	659.21
B	116+76.24	17.00	659.18	659.35
C	116+86.24	17.00	659.22	659.47
D	116+96.24	17.00	659.25	659.55
E	117+06.24	17.00	659.26	659.59
F	117+16.24	17.00	659.26	659.60
G	117+26.24	17.00	659.24	659.57
H	117+36.24	17.00	659.20	659.50
I	117+46.24	17.00	659.15	659.40
J	117+56.24	17.00	659.08	659.28
K	117+66.24	17.00	659.00	659.14
L	117+76.24	17.00	658.90	658.98
M	117+86.24	17.00	658.78	658.82
@ BRG. PIER	118+00.24	17.00	658.59	658.59
N	118+10.24	17.00	658.44	658.43
O	118+20.24	17.00	658.27	658.26
P	118+30.24	17.00	658.08	658.10
Q	118+40.24	17.00	657.88	657.92
R	118+50.24	17.00	657.66	657.74
S	118+60.24	17.00	657.43	657.53
T	118+70.24	17.00	657.17	657.30
U	118+80.24	17.00	656.91	657.04
V	118+90.24	17.00	656.63	656.75
W	119+00.24	17.00	656.33	656.43
X	119+10.24	17.00	656.01	656.08
@ BRG. N. ABUT.	119+24.24	17.00	655.54	655.54
@ EXP. JT.	119+25.16	17.00	655.51	655.51
BK. N. ABUT.	119+27.24	17.00	655.44	655.44

G:\IDOT\21850_006_CumberlandAve\Drawings\CADD Sheets\016014-sh-t-tsl-DkElevTbl.5.dgn