



R4-7

PROP. SIGN REMOVAL AND REPLACEMENT

PROP. MEDIAN SURFACE REMOVAL AND REPLACEMENT (550 SF)

IL. 72 (HIGGINS RD.)

PROP. THERMOPLASTIC PAVEMENT MARKING - LINE 4" WHITE SKIP-DASH, - (TYP.)

PROP. THERMOPLASTIC PAVEMENT MARKING - LETTER AND SYMBOLS (TYP.)

FOREST PRESERVE ENTRANCE

CURB & GUTTER

CONC. MEDIAN CURB & GUTTER

150+00

CONC. MEDIAN

155+00

CURB ONLY

160+00

CONC. MEDIAN

CURB & GUTTER

MATCHLINE STA. 147+00

MATCHLINE STA. 162+00

149+62

150+82

PROP. HOT MIX ASPHALT SURFACE REMOVAL (3") - (TYP.)
 PROP. POLYMERIZED LEVELING BINDER (MM), IL-4.75, N50 (1") - (TYP.)
 PROP. POLY. HOT MIX ASPHALT SURFACE COURSE, MIX "F", N90 (2") - (TYP.)



IL. 72 (HIGGINS RD.)

FOREST PRESERVE ENTRANCE

CURB & GUTTER

CURB & GUTTER

165+00

CONC. MEDIAN

CURB ONLY

170+00

175+00

CURB & GUTTER

CURB & GUTTER

173+63

175+04

175+75

PROP. HOT MIX ASPHALT SURFACE REMOVAL (3") - (TYP.)
 PROP. POLYMERIZED LEVELING BINDER (MM), IL-4.75, N50 (1") - (TYP.)
 PROP. POLY. HOT MIX ASPHALT SURFACE COURSE, MIX "F", N90 (2") - (TYP.)

NOTES:
 LIMIT OF RESURFACING ON SIDE-STREETS THROUGH OUT THE IMPROVEMENT SHALL BE TO THE RADIUS OF RETURN UNLESS OTHERWISE NOTED OR AS DIRECTED BY THE ENGINEER.

ALL FINAL PAVEMENT MARKINGS SHALL BE THERMOPLASTIC (OF THE EXTRUDED TYPE) AND SHOULD BE PLACED IN ACCORDANCE WITH "DISTRICT ONE TYPICAL PAVEMENT MARKINGS" DETAIL, (TC-13).

ALL RAISED REFLECTIVE PAVEMENT MARKINGS SHALL BE PLACED IN ACCORDANCE WITH THE DISTRICT ONE "TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKER DETAIL," (TC-11).

FILE NAME =	USER NAME = chrzesclr	DESIGNED -	REVISED -
es:\pwwork\pwwid\chrzesclr\0245762\0107711-sht-plan.dgn		DRAWN -	REVISED -
	PLOT SCALE = 100.0000' / in.	CHECKED -	REVISED -
	PLOT DATE = 12/20/2012	DATE -	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

ILL. 72 / ILL. 83
 ROADWAY AND PAVEMENT MARKING PLANS

SCALE: SHEET OF SHEETS STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
341	31R-RS-1	COOK	36	10
CONTRACT NO. 60M10			ILLINOIS FED. AID PROJECT	