



**LEGEND**

① EXIST. 4" SUB-BASE GRANULAR MATERIAL	⑮ PROP. STRIP REFLECTIVE CRACK CONTROL TREATMENT
② EXIST. 8" P.C.C. PAVEMENT	⑯ PROP. HOT-MIX ASPHALT SHOULDERS 6 1/2"
③ EXIST. 8" H.M.A. SHOULDER	⑰ PROP. LEVELING BINDER (MACHINE METHOD), N70 1"
④ EXIST. 4" OVERLAY	⑱ PROP. HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70 1 1/2"
⑤ EXIST. COMBINATION CURB AND GUTTER, TYPE B-6.06	⑳ PROP. COMBINATION CONCRETE CURB AND GUTTER, TYPE M-4.24
⑥ PROP. PAVEMENT REMOVAL	㉑ PROP. CONCRETE MEDIAN SURFACE, 4"
⑦ PROP. PAVED SHOULDER REMOVAL	㉒ PROP. CONCRETE MEDIAN, TYPE SM-4.24
⑧ PROP. HOT-MIX ASPHALT SURFACE REMOVAL (VARIABLE DEPTH) *	㉓ PROP. AGGREGATE WEDGE SHOULDER, TYPE B
⑨ PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"	㉔ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 5"
⑩ PROP. COMBINATION CURB AND GUTTER REMOVAL	㉕ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 8"
⑪ PROP. CONCRETE MEDIAN SURFACE REMOVAL	㉖ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B TYPE B - LINE 5"
⑫ PROP. SUBBASE GRANULAR MATERIAL, TYPE B 4"	㉗ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B TYPE B - LINE 6"
⑬ PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8"	
⑭ PROP. HMA BASE COURSE 11" ***	
⑮ PROP. PCC BASE COURSE WIDENING 9"	

**\*\*\* NOTES:**

(A) PROP. HMA SHOULDERS 6 1/2" ARE LOCATED FR. STA. 305+05.47 TO 305+53.78 RT AND STA. 305+16.37 TO 305+48.15 LT.

(B) PROP. CONCRETE MEDIAN BEGINS AT STA. 304+93.00 RT.

\* NOMINAL MILLING DEPTH 1/2" @ C OR pgl  
 \*\*\* WHERE WIDENING IS GREATER THAN 6' OR UNDER NEW TURN LANE