



LEGEND

① EXIST. 4" SUB-BASE GRANULAR MATERIAL	⑩ PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"	⑬ PROP. SUBBASE GRANULAR MATERIAL, TYPE B 4"	⑲ PROP. COMBINATION CONCRETE CURB AND GUTTER, TYPE M-4.24
② EXIST. 8" P.C.C. PAVEMENT	⑪ PROP. CONCRETE MEDIAN SURFACE REMOVAL	⑭ PROP. HMA BASE COURSE 11" ***	⑳ PROP. CONCRETE MEDIAN SURFACE, 4"
③ EXIST. 8" H.M.A. SHOULDER	⑫ PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8"	⑮ PROP. PCC BASE COURSE WIDENING 9"	㉑ PROP. CONCRETE MEDIAN, TYPE SM-4.24
④ EXIST. 4" OVERLAY	⑬ PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8"		㉒ PROP. AGGREGATE WEDGE SHOULDER, TYPE B
⑤ EXIST. COMBINATION CURB AND GUTTER, TYPE B-6.06	⑭ PROP. HMA BASE COURSE 11" ***		㉓ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 5"
⑥ PROP. PAVEMENT REMOVAL	⑮ PROP. PCC BASE COURSE WIDENING 9"		㉔ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 8"
⑦ PROP. PAVED SHOULDER REMOVAL			㉕ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B
⑧ PROP. HOT-MIX ASPHALT SURFACE REMOVAL (VARIABLE DEPTH) *			㉖ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B
⑨ PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"			㉗ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B
⑩ PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"			
⑪ PROP. CONCRETE MEDIAN SURFACE REMOVAL			
⑫ PROP. SUBBASE GRANULAR MATERIAL, TYPE B 4"			
⑬ PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8"			
⑭ PROP. HMA BASE COURSE 11" ***			
⑮ PROP. PCC BASE COURSE WIDENING 9"			
⑯ PROP. COMBINATION CONCRETE CURB AND GUTTER, TYPE M-4.24			
⑰ PROP. CONCRETE MEDIAN SURFACE, 4"			
⑱ PROP. CONCRETE MEDIAN, TYPE SM-4.24			
㉑ PROP. AGGREGATE WEDGE SHOULDER, TYPE B			
㉒ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 5"			
㉓ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 8"			
㉔ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B			
㉕ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B			
㉖ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B			
㉗ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B			

- *** NOTES:**
- (A) PAINTED MEDIAN VAR. FR. 16'-0" TO 0' FR. STA. 307+04.18 TO 310+13.69 LT (WB PAVT).
 - (B) SE TRANSITIONS FROM NORMAL CROWN TO 3.7% FROM STA. 311+21.00 TO 312+66.00
 - (C) PAVED SHLDR REM ENDS AT STA. 312+82.04 LT (WB PAVT).
 - (D) LT TURN LANE WIDTH VAR. FR. 5'-0" TO 13'-0" FR. STA. 307+04.18 TO 308+65.72 LT AND FR. 13'-0" TO 0' FR. STA. 310+13.69 TO 311+90.09 RT.
 - (E) LT TURN LANE WIDTH VAR. FR. 8'-0" TO 0' FR. STA. 307+04.18 TO 309+74.69 LT (WB PAVT).

* NOMINAL MILLING DEPTH 1/2" @ C OR pgl
 *** WHERE WIDENING IS GREATER THAN 6' OR UNDER NEW TURN LANE