



- (A) EXIST. COMBINATION CURB AND GUTTER, TYPE B-6.24
- (B) PROP. COMBINATION CONCRETE CURB AND GUTTER, TYPE M-6.24

LEGEND	
1 EXIST. 4" SUB-BASE GRANULAR MATERIAL	16 PROP. STRIP REFLECTIVE CRACK CONTROL TREATMENT
2 EXIST. 8" P.C.C. PAVEMENT	17 PROP. HOT-MIX ASPHALT SHOULDERS 6 1/2"
3 EXIST. 8" H.M.A. SHOULDER	18 PROP. LEVELING BINDER (MACHINE METHOD), N70 1"
4 EXIST. 4" OVERLAY	19 PROP. HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70 1 1/2"
5 EXIST. COMBINATION CURB AND GUTTER, TYPE B-6.06	20 PROP. COMBINATION CONCRETE CURB AND GUTTER, TYPE M-4.24
6 PROP. PAVEMENT REMOVAL	21 PROP. CONCRETE MEDIAN SURFACE, 4"
7 PROP. PAVED SHOULDER REMOVAL	22 PROP. CONCRETE MEDIAN, TYPE SM-4.24
8 PROP. HOT-MIX ASPHALT SURFACE REMOVAL (VARIABLE DEPTH) *	23 PROP. AGGREGATE WEDGE SHOULDER, TYPE B
9 PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"	24 PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 5"
10 PROP. COMBINATION CURB AND GUTTER REMOVAL	25 PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 8"
11 PROP. CONCRETE MEDIAN SURFACE REMOVAL	26 PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B TYPE B - LINE 5"
12 PROP. SUBBASE GRANULAR MATERIAL, TYPE B 4"	27 PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B TYPE B - LINE 6"
13 PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8"	
14 PROP. HMA BASE COURSE 11" ***	
15 PROP. PCC BASE COURSE WIDENING 9"	

- *** NOTES:
- (A) PROP. HMA SHOULDERS 6 1/2" IS LOCATED STA 338+26.79 TO 338+47.21 LT AND AGG. SHLDR. BEGINS AT STA. 338+47.21 LT.
 - (B) STRIPED SLT TURN LANE WIDTH VAR. FR. 0' TO 4'-3" FR. STA. 338+53.08 TO 339+17.49 LT AND VAR. FR. 12'-0" TO 7'-9" FR. STA. 338+53.08 TO 339+17.49 RT.
 - (C) PAINTED MEDIAN VAR. FR. 0' TO 12'-9" FR. STA. 338+59.48 TO 339+17.49 RT.
 - (D) REFER TO ELEVATION DETAIL SHEETS FOR WIDTHS OF EX. & PROP. PAVTS.

* NOMINAL MILLING DEPTH 1/2" @ C OR pgl
 *** WHERE WIDENING IS GREATER THAN 6' OR UNDER NEW TURN LANE