



**LEGEND**

- |  |   |
|--|---|
| ① EXIST. 4" SUB-BASE GRANULAR MATERIAL                     | ⑩ PROP. STRIP REFLECTIVE CRACK CONTROL TREATMENT            |
| ② EXIST. 8" P.C.C. PAVEMENT                                | ⑪ PROP. HOT-MIX ASPHALT SHOULDERS 6 1/2"                    |
| ③ EXIST. 8" H.M.A. SHOULDER                                | ⑫ PROP. LEVELING BINDER (MACHINE METHOD), N70 1"            |
| ④ EXIST. 4" OVERLAY  | ⑬ PROP. HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70 1 1/2" |
| ⑤ EXIST. COMBINATION CURB AND GUTTER, TYPE B-6.06          | ⑭ PROP. COMBINATION CONCRETE CURB AND GUTTER, TYPE M-4.24   |
| ⑥ PROP. PAVEMENT REMOVAL                                   | ⑮ PROP. CONCRETE MEDIAN SURFACE, 4"                         |
| ⑦ PROP. PAVED SHOULDER REMOVAL                             | ⑯ PROP. CONCRETE MEDIAN, TYPE SM-4.24                       |
| ⑧ PROP. HOT-MIX ASPHALT SURFACE REMOVAL (VARIABLE DEPTH) * | ⑰ PROP. AGGREGATE WEDGE SHOULDER, TYPE B                    |
| ⑨ PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"            | ⑱ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 5"        |
| ⑩ PROP. COMBINATION CURB AND GUTTER REMOVAL                | ⑲ PROP. MODIFIED URETHANE PAVEMENT MARKING - LINE 8"        |
| ⑪ PROP. CONCRETE MEDIAN SURFACE REMOVAL                    | ⑳ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B          |
| ⑫ PROP. SUBBASE GRANULAR MATERIAL, TYPE B 4"               | ㉑ PROP. PREFORMED PLASTIC PAVEMENT MARKING, TYPE B          |
| ⑬ PROP. SUBBASE GRANULAR MATERIAL, TYPE A 8"               |   |
| ⑭ PROP. HMA BASE COURSE 11" ***                            |   |
| ⑮ PROP. PCC BASE COURSE WIDENING 9"                        |   |

**\*\* NOTES:**

- (A) PAINTED MEDIAN WIDTH VAR. FR. 6'-3" TO 0' FR. STA. 341+28.98 TO 342+40.67 LT.
- (B) PAVEMENT STRIPING 6" WHITE (2'DASH/6'SKIP) FR. STA. 342+40.67 TO 344+62.20 LT (SB PAVT).
- (C) LT TURN LANE WIDTH IS 13'-0" FR. STA. 341+28.98 TO 342+40.67 LT AND VAR. FR. 13'-0" TO 1'-0" FR. STA. 342+40.67 TO 344+62.20 LT (SB PAVT).
- (D) PROP. AGG. SHOULDER WIDTH TAPERS FR. 0 TO 3'-0" FR. STA. 343+51.27 TO 344+62.20 LT.

\* NOMINAL MILLING DEPTH 1/2" @ C OR pgl  
 \*\*\* WHERE WIDENING IS GREATER THAN 6' OR UNDER NEW TURN LANE

FILE NAME :	USER NAME : sparkgw	DESIGNED -	REVISED -
c:\pwwork\p\idot\sparkgw\d0259630\0672E31-sh-t-typical.dgn		DRAWN -	REVISED -
		CHECKED -	REVISED -
		DATE -	REVISED -

STATE OF ILLINOIS  
 DEPARTMENT OF TRANSPORTATION

**TYPICAL SECTIONS**

SCALE: NTS SHEET NO. 12 OF 15 SHEETS STA. 341+28.00 TO STA. 344+62.20

* FAP 63 (US 24); FAP 63 (US 24/IL 96); FAP 506 (IL 96)			
F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS
	(11N,TS-2RS-5&7B)RS-3	ADAMS	194
			SHEET NO. 50
			CONTRACT NO. 72E31
ILLINOIS FED. AID PROJECT			