

HIGHWAY STANDARDS

000001-06	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001006	DECIMAL OF AN INCH AND OF A FOOT
280001-07	TEMPORARY EROSION CONTROL SYSTEMS
424001-07	PERPENDICULAR CURB RAMPS FOR SIDEWALKS
542301-03	PRECAST REINFORCED CONCRETE FLARED END SECTION
542401-01	METAL END SECTION FOR PIPE CULVERTS
602701-02	MANHOLE STEPS
604001-03	FRAME AND LIDS TYPE 1
606001-05	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
666001-01	RIGHT OF WAY MARKERS
667101-02	PERMANENT SURVEY MARKERS
701901-02	TRAFFIC CONTROL DEVICES
780001-03	TYPICAL PAVEMENT MARKINGS
781001-03	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

MIX DESIGN

LOCATION(S):	HOT-MIX ASPHALT SURFACE COURSE (NORTH FRONTAGE ROAD, SHARED USE PATH, DRIVEWAYS)
MIXTURE USE(S):	HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N70
AC/PG:	PG64-22
RAP% (MAX):	10
DESIGN AIR VOIDS:	4.0%, 70 GYRATION DESIGN
MIXTURE COMPOSITION:	IL-9.5 mm OR IL-12.5 mm
FRICTION AGGREGATE:	C SURFACE
LOCATION(S):	HOT-MIX ASPHALT BINDER COURSE (NORTH FRONTAGE ROAD)
MIXTURE USE(S):	HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N90
AC/PG:	PG64-22
RAP% (MAX):	10
DESIGN AIR VOIDS:	4.0%, 90 GYRATION DESIGN
MIXTURE COMPOSITION:	IL-19.0
FRICTION AGGREGATE:	NONE