

SURVEY MONUMENT SCHEDULE				PERMANENT SURVEY MARKERS, TYPE 1	SURVEY MARKER VAULT	PROTECTING OR RESETTING SURVEY MARKERS
STATION	O/S	TYPE OF POINT DESCRIPTION				
27+84.40	0	PC	MAG NAIL WITH WASHER	1		
32+98.00	NOT PROVIDED	PI	MAG NAIL WITH WASHER	1		
74+93.75	0	POT	MAG NAIL WITH WASHER	1		
165+60	0	SECTION CORNER	MAG NAIL WITH WASHER		1	1
169+75	0	SECTION CORNER	MAG NAIL WITH WASHER		1	1
240+09.75	0	POT	MAG NAIL	1		
267+63.99	0	POT	MAG NAIL	1		
271+99.24	0	PC	MAG NAIL WITH WASHER	1		
275+49.65	NOT PROVIDED	PI	MAG NAIL WITH WASHER	1		
278+99.24	0	PT	MAG NAIL WITH WASHER	1		
280+81.19	0	PC	MAG NAIL WITH WASHER	1		
290+34.66	0	PT	MAG NAIL WITH WASHER	1		
292+15.72	0	PC	MAG NAIL WITH WASHER	1		
295+66.16	NOT PROVIDED	PI	MAG NAIL WITH WASHER	1		
299+15.71 (BK) = 299+04.02 (AH)	0	PT	MAG NAIL WITH WASHER	1		
305+96.00	0	PI	MAG NAIL WITH WASHER	1		
320+46.00	0	PI	MAG NAIL WITH WASHER	1		
332+45.92	0	PT	MAG NAIL WITH WASHER	1		
TOTALS				16	2	2

NOTE: TIE POINTS NOT PROVIDED FOR ALL SURVEY POINTS. THE RESIDENT ENGINEER NEEDS TO ESTABLISH ANY NECESSARY TIE POINTS BEFORE THE SURVEY POINT IS DISTURBED.

GUARDRAIL SCHEDULE	GUARDRAIL REMOVAL	TRAFFIC BARRIER TERMINAL, TYPE 6B	STEEL PLATE BEAM GUARD RAIL, TYPE A, 9 FOOT POSTS	TRAFFIC BARRIER TERMINAL, TYPE 1 (SPECIAL) TANGENT	TERMINAL MARKERS - DIRECT APPLIED	GUARDRAIL MARKERS, TYPE A
LOCATION	FOOT	EACH	FOOT	EACH	EACH	EACH
S END OF EAST PIER	251.0	1.0	37.5	1.0	1.0	4.0
MIDDLE PIER	82.0	0.0	0.0	0.0	0.0	0.0
N END OF WEST PIER	229.0	1.0	37.5	1.0	1.0	4.0
TOTALS =	562.0	2.0	75.0	2.0	2.0	8.0

PIPE UNDERDRAIN SCHEDULE			PIPE UNDERDRAIN 6"	PIPE UNDERDRAIN 6" (SPECIAL)	UNDERDRAIN CONNECTION TO STRUCTURE	SHOULDER REMOVAL AND REPLACEMENT, 8"	CONCRETE HEADWALL FOR PIPE UNDERDRAINS
FROM STA	TO STATION	LOCATION	FOOT	FOOT	EACH	FOOT	EACH
23+85.00	28+31.00	NB OUTSIDE	446.0	20.0		446.0	1.0
28+31.00	32+30.00	NB OUTSIDE	399.0	20.0		399.0	1.0
32+45.00	35+95.00	NB OUTSIDE	350.0	20.0		350.0	1.0
36+60.00	41+00.00	NB OUTSIDE	440.0	20.0		440.0	1.0
41+00.00	46+00.00	NB OUTSIDE	500.0	20.0		500.0	1.0
46+00.00	50+16.00	NB OUTSIDE	416.0	20.0		416.0	1.0
30+40.00	32+42.00	NB INSIDE	202.0		1.0		
32+42.00	35+95.00	NB INSIDE	353.0		1.0		
36+60.00	39+26.00	NB INSIDE	266.0		1.0		
39+26.00	47+70.00	NB INSIDE	844.0		1.0		
22+85.00	28+31.00	SB OUTSIDE	546.0	20.0		546.0	1.0
31+23.00	35+95.00	SB OUTSIDE	472.0	20.0		472.0	1.0
36+60.00	41+00.00	SB OUTSIDE	440.0	20.0		440.0	1.0
41+00.00	46+00.00	SB OUTSIDE	500.0	20.0		500.0	1.0
46+00.00	50+16.00	SB OUTSIDE	416.0	20.0		416.0	1.0
TOTALS =			6590.0	220.0	4.0	4925.0	11.0