

CULVERT SCHEDULE																																
LOCATION	PIPE CULVERTS, CLASS A										PRECAST REINFORCED CONCRETE								UPSTREAM FLOWLINE	DOWNSTREAM FLOWLINE	TRENCH BACKFILL	CLASS D PATCHES			PIPE CULVERT REMOVAL							
	TYPE 1					TYPE 2					FLARED END SECTIONS											CU YD	CU YD	CU YD		FOOT						
	24"	27"	30"	36"	42"	24"	30"	42"	48"	24"	27"	30"	36"	42"	48"	EQUIVALENT ROUND-SIZE 24"	EQUIVALENT ROUND-SIZE 36"	CU YD									CU YD	CU YD	FOOT			
	FOOT										EACH																					
STA 33+38	48									2								510.7	510.6	10.0	19.6		52									
STA 61+41				46									2					497.4	495.4	14.4	23.6		50									
STA 90+00			40									2						510.6	510.5	6.8	22.2		48									
STA 164+87										2								538.7	537.9				0									
STA 171+50													2					542.1	541.5				0									
STA 209+60					38										2			560.3	560.2	5.1	22.1		54									
STA 212+80										2								559.9	559.2				0									
STA 235+50				124										4				552.6	549.5	62.2		57.4	74									
STA 250+00									112					4				549.4	545.2	67.3		50.9	132									
STA 303+30	42									2						4		551.0	550.5	5.6	21.5		58									
STA 332+50					76													559.5	559.4	8.2		34.3	84									
STA 373+30			42									2						558.8	558.6	7.9	22.2		48									
STA 382+00				58									2					552.5	551.8	13.0		30.8	79									
STA 384+20								60		2								549.5	549.3	19.5	24.6		69									
STA 384+91	50									2								551.4	550.5	10.3	23.9		56									
STA 400+20					40										2			541.2	540.4	7.8	22.1		44									
STA 406+20					40										2			542.1	541.9	6.8	22.4		45									
STA 427+50	42									2								555.0	554.5	6.2	19.6		60									
STA 431+30								68		2								551.6	549.0	22.4	19.6		74									
STA 450+15			62									2						544.2	543.8	21.0		25.6	82									
STA 460+15								78		2								565.6	564.0	29.6	20.2		82									
STA 466+86									98				2					562.2	557.0	67.1		26.7	104									
STA 489+70								66		2								583.0	577.5	20.7	19.9		78									
STA 490+93										2								583.4	582.2				0									
STA 508+95								74				2						579.0	574.0	34.5	22.3		85									
STA 513+45								56		2								577.2	572.5	14.8	19.6		62									
STA 516+60								54				2						573.8	571.0	17.5	23.6		70									
STA 523+05								50				2						577.5	573.8	15.0	22.2		61									
STA 534+25					38										2			585.3	585.1	4.3	22.1		42									
STA 587+50					76										4			597.5	597.3	10.1		34.3	96									
STA 600+90						40										2		595.6	595.3	7.6		25.7	55									
STA 614+60					76										4			592.5	592.4	9.2		34.5	46									
STA 640+05				48									2					582.4	582.2	14.3		25.1	56									
TOTAL	140	42	144	152	124	384	40	328	178	96	112	22	2	12	8	6	4							20	2			539.2	413.3	345.3	1946	
USE	140	42	144	152	124	384	40	328	178	96	112	22	2	12	8	6	4								20	2			539	413	345	1946